



LTE Band 38									
Channel Bandwidth 5MHz				Channel Bandwidth 10MHz					
Channel	Frequency (MHz)	Peak To Average Ratio (dB)			Channal	Frequency	Peak To Average Ratio (dB)		
		QPSK	16QAM	64QAM	Channel	(MHz)	QPSK	16QAM	64QAM
37775	2572.5	7.84	9.80	9.50	37800	2575	7.88	8.82	9.80
38000	2595	7.47	8.89	9.68	38000	2595	7.24	9.20	10.13
38225	2617.5	7.5	9.27	9.45	38200	2615	7.03	10.44	9.42
	Channel Ba	ndwidth 1	5MHz		Channel Bandwidth 20MHz				
Channel	Frequency (MHz)	Peak To	Average F	Ratio (dB)	Channel	Frequency (MHz)	Peak To Average Ratio (dB)		
Chamilei		QPSK	16QAM	64QAM	Chamilei		QPSK	16QAM	64QAM
37825	2577.5	7.61	9.89	8.20	37850	2580	7.71	9.65	8.38
38000	2595	7.21	8.36	8.51	38000	2595	7.56	9.85	8.23
38175	2612.5	6.91	8.42	9.55	38150	2610	7.22	10.45	9.89






LTE CA_38C								
Channal	Eroa (MUz)	Peak to Average Ratio (dB)						
Channel	Freq. (MHz)	Peak	Average	Difference				
38000+38150	2595+2610	14.24	7.86	6.38				






LTE Band 41									
Channel Bandwidth 5MHz				Channel Bandwidth 10MHz					
Observat	Frequency (MHz)	Peak To Average Ratio (dB)			Channal	Frequency	Peak To Average Ratio (dB)		
Channel		QPSK	16QAM	64QAM	Channel	(MHz)	QPSK	16QAM	64QAM
39675	2498.5	10.09	9.74	9.49	39700	2501	12.3	9.13	9.37
40620	2593	7.71	8.36	9.07	50620	2593	7.21	8.84	8.95
41565	2687.5	7.97	9.19	9.38	41540	2685	7.21	9.51	9.14
Channel Bandwidth 15MHz				Channel Bandwidth 20MHz					
Channel	Frequency	Peak To	Average Ratio (dB)		Channel	Frequency	Peak To Average Ratio (dB)		
Chamei	(MHz)	QPSK	16QAM	64QAM	Chamilei	(MHz)	QPSK	16QAM	64QAM
39725	2503.5	7.57	8.36	8.19	39750	2506	7.37	9.56	8.25
40620	2593	7.63	7.83	8.03	40620	2593	7.29	9.12	8.04
41515	2682.5	7.29	9.42	8.28	41490	2680	7.67	9.54	9.80






LTE CA_41C								
Channal	Eroa (MHz)	Peak to Average Ratio (dB)						
Channel	Freq. (MHz)	Peak	Average	Difference				
40620+40692	2593+2600.2	15.49	10.26	5.23				





LTE Band 66										
Channel Bandwidth 1.4MHz				Channel Bandwidth 3MHz						
Channel	Frequency (MHz)	Peak To Average Ratio (dB)			Channal	Frequency	Peak To	Peak To Average Ratio (dB)		
Channel		QPSK	16QAM	64QAM	Channel	(MHz)	QPSK	16QAM	64QAM	
131979	1710.7	4.67	4.85	6.03	131987	1711.5	3.51	4.77	5.93	
132322	1745	4.82	5.72	6.46	132322	1745	3.62	5.61	6.41	
132665	1779.3	4.94	5.71	6.38	132657	1778.5	3.56	5.56	6.35	
	Channel Ba	andwidth 5	MHz			Channel Ba	ndwidth 1	0MHz		
Channel	Frequency (MHz)	Peak To Average Ratio (dB)		01	Frequency	Peak To Average Ratio (dB)				
Channel		QPSK	16QAM	64QAM	Channel	(MHz)	QPSK	16QAM	64QAM	
131997	1712.5	3.54	4.79	5.91	132022	1715	3.47	4.59	5.77	
132322	1745	3.65	5.59	6.44	132322	1745	3.53	5.56	6.44	
132647	1777.5	3.54	5.21	6.19	132622	1775	3.49	4.52	5.69	
	Channel Ba	ndwidth 1	5MHz		Channel Bandwidth 20MHz					
Channal	Frequency (MHz)	Peak To	To Average Ratio (dB)		01 1	Frequency	Peak To Average Ratio (dB)			
Channel		QPSK	16QAM	64QAM	Channel '	(MHz)	QPSK	16QAM	64QAM	
132047	1717.5	3.38	4.47	5.68	132072	1720	3.48	4.50	5.62	
132322	1745	3.49	5.32	6.08	132322	1745	3.5	4.38	5.38	
132597	1772.5	3.45	5.45	6.30	132572	1770	3.49	5.45	6.33	







#### 4.7 Conducted Spurious Emissions

#### 4.7.1 Limits of Conducted Spurious Emissions Measurement

According to FCC 27.53(a)(4) For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands: (i) By a factor of not less than: 43 + 10 log (P) dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than 67 + 10 log (P) dB on all frequencies between 2328 and 2337 MHz; (ii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2296 and 2300 MHz, 61 + 10 log (P) dB on all frequencies between 2288 and 2292 MHz, and 70 + 10 log (P) dB below 2288 MHz; (iii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.

According to FCC 27.53 (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;
- (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;
- (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed:
- (6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

According to FCC 27.53(f) For operations in the 746–758 MHz, 775–788 MHz, and 805–806 MHz bands, emissions in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.


According to FCC 27.53(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least 43 + 10 log (P) dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

According to FCC 27.53(h) AWS emission limits— General protection levels. Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least 43 + 10 log10 (P) dB.

According to FCC 27.53(v)(4) For mobile digital stations, the attenuation factor shall be not less than  $40 + 10 \log (P)$  dB on all frequencies between the channel edge and 5 megahertz from the channel edge,  $43 + 10 \log (P)$  dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and  $55 + 10 \log (P)$  dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that  $43 + 10 \log (P)$  dB on all frequencies between 2490.5 MHz and 2496 MHz and  $55 + 10 \log (P)$  dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.



# 4.7.2 Test Setup



# 4.7.3 Test Procedure

- a. All measurements were done at 3 channels: low, middle and high operational frequency range.
- b. When the spectrum scanned from 9 kHz to the tenth harmonic of the highest fundamental frequency, it shall be connected to the 20dB pad attenuated the carried frequency.



### 4.7.5 Test Results

