

Test of  
Digi Connect Card for i.MX28 with Atheros AR6203  
Wi-Fi Mode  
To: FCC 47 CFR Part 15.247 & IC RSS-210  
Test Report Serial No.: DIGI28-U2B Rev A



# TEST REPORT

FROM



Test of Digi Connect Card for i.MX28 with Atheros AR6203  
Wi-Fi Mode

To FCC 47 CFR Part 15.247 & IC RSS-210

Test Report Serial No.: DIGI28-U2B Rev A

Note: this report contains data with regard to the 2400 to 2483.5 MHz and 5725 to 5850 MHz operational modes of the Digi Connect Card for i.MX28 with Atheros AR6203. Test data for the 5,150 - 5,350 and 5,470 – 5,725 MHz is reported in MiCOM Labs test report DIGI28-U3B

This report supersedes: NONE

Applicant: Digi International  
355 South 520 West, Suite 180  
Lindon  
Utah, 84042 USA

Product Function: 802.11 a/b/g/n Wireless Module

Copy No: pdf Issue Date: 29th March 2013

**This Test Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**

440 Boulder Court, Suite 200

Pleasanton, CA 94566 USA

Phone: +1 (925) 462-0304

Fax: +1 (925) 462-0306

[www.micomlabs.com](http://www.micomlabs.com)



TEST CERTIFICATE #2381.01

**MiCOM Labs is an ISO 17025 Accredited Testing Laboratory**



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 3 of 242

---

This page has been left intentionally blank



## TABLE OF CONTENTS

<b>ACCREDITATION, LISTINGS &amp; RECOGNITION .....</b>	<b>5</b>
TESTING ACCREDITATION .....	5
RECOGNITION .....	6
PRODUCT CERTIFICATION .....	7
<b>1. TEST RESULT CERTIFICATE .....</b>	<b>9</b>
<b>2. REFERENCES AND MEASUREMENT UNCERTAINTY .....</b>	<b>10</b>
2.1. Normative References .....	10
2.2. Test and Uncertainty Procedures .....	11
<b>3. PRODUCT DETAILS AND TEST CONFIGURATIONS .....</b>	<b>12</b>
3.1. Technical Details .....	12
3.2. Scope of Test Program .....	13
3.3. Equipment Model(s) and Serial Number(s) .....	15
3.4. Antenna Details .....	15
3.5. Cabling and I/O Ports .....	15
3.6. Test Configurations .....	16
3.7. Equipment Modifications .....	18
3.8. Deviations from the Test Standard .....	18
<b>4. TEST EQUIPMENT CONFIGURATION(S) .....</b>	<b>19</b>
4.1. Conducted RF Emission Test Set-up .....	19
4.2. Radiated Spurious Emission Test Set-up > 1 GHz .....	20
4.3. Digital Emissions Test Set-up (0.03 – 1 GHz) .....	21
4.4. ac Wireline Emission Test Set-up .....	22
<b>5. TEST SUMMARY .....</b>	<b>23</b>
<b>6. TEST RESULTS .....</b>	<b>25</b>
6.1. Device Characteristics .....	25
6.1.1. <i>Conducted Testing</i> .....	25
6.1.2. <i>Radiated Emission Testing</i> .....	63
6.1.3. <i>AC Wireline Conducted Emissions (150 kHz – 30 MHz)</i> .....	141
<b>7. PHOTOGRAPHS .....</b>	<b>143</b>
7.1. Conducted Test Setup .....	143
7.2. Test Setup - Digital Emissions below 1 GHz .....	144
7.3. Radiated Emissions Test Setup >1 GHz .....	145
<b>8. TEST EQUIPMENT .....</b>	<b>146</b>
<b>APPENDIX .....</b>	<b>147</b>
<b>A. SUPPORTING INFORMATION .....</b>	<b>147</b>
A.1. CONDUCTED TEST PLOTS .....	147
A.1.1. <i>6 dB &amp; 99% Bandwidth</i> .....	148
A.1.2. <i>Peak Output Power</i> .....	168
A.1.3. <i>Power Spectral Density</i> .....	188
A.1.4. <i>Conducted Spurious Emissions</i> .....	208

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## ACCREDITATION, LISTINGS & RECOGNITION

### TESTING ACCREDITATION

MiCOM Labs, Inc. is an accredited Electrical testing laboratory per the international standard EN ISO/IEC 17025. The company is accredited by the American Association for Laboratory Accreditation (A2LA) [www.a2la.org](http://www.a2la.org) test laboratory number 2381.01. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-01.pdf>



The American Association for Laboratory Accreditation

World Class Accreditation

### *Accredited Laboratory*

A2LA has accredited

**MICOM LABS**


*Pleasanton, CA*

for technical competence in the field of

**Electrical Testing**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General Requirements for the Competence of Testing and Calibration Laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Presented this 27<sup>th</sup> day of March 2012.



President & CEO  
For the Accreditation Council  
Certificate Number 2381.01  
Valid to November 30, 2013

*For the tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.*

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 6 of 242

## **RECOGNITION**

MiCOM Labs, Inc has widely recognized Electrical testing capabilities. Our international recognition includes Conformity Assessment Body designation by APEC MRA\*\* countries. Our test reports are widely accepted for global type approvals.

Country	Recognition Body	Status	Phase	Identification No.
USA	Federal Communications Commission (FCC)	TCB	-	US0159 Listing #: 102167
Canada	Industry Canada (IC)	FCB	APEC MRA 2	US0159 Listing #: 4143A-2
Japan	MIC (Ministry of Internal Affairs and Communication)	CAB	APEC MRA 2	RCB 210
	VCCI	--	--	A-0012
Europe	European Commission	NB	EU MRA	NB 2280
Australia	Australian Communications and Media Authority (ACMA)	CAB	APEC MRA 1	US0159
Hong Kong	Office of the Telecommunication Authority (OFTA)	CAB	APEC MRA 1	
Korea	Ministry of Information and Communication Radio Research Laboratory (RRL)	CAB	APEC MRA 1	
Singapore	Infocomm Development Authority (IDA)	CAB	APEC MRA 1	
Taiwan	National Communications Commission (NCC) Bureau of Standards, Metrology and Inspection (BSMI)	CAB	APEC MRA 1	
Vietnam	Ministry of Communication (MIC)	CAB	APEC MRA 1	

\*\*APEC MRA – Asia Pacific Economic Community Mutual Recognition Agreement.

Is a recognition agreement under which test lab is accredited to regulatory standards of the APEC member countries.

Phase I - recognition for product testing

Phase II – recognition for both product testing and certification

N/A – Not Applicable

\*\*EU MRA – European Union Mutual Recognition Agreement.

Is a recognition agreement under which test lab is accredited to regulatory standards of the EU member countries.

\*\*NB – Notified Body

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## **PRODUCT CERTIFICATION**

MiCOM Labs, Inc. is an accredited Product Certification Body per the international standard EN ISO/IEC Guide 65. The company is accredited by the American Association for Laboratory Accreditation (A2LA) [www.a2la.org](http://www.a2la.org) test laboratory number 2381.02. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-02.pdf>



The American Association for Laboratory Accreditation

"World Class Accreditation"

### *Accredited Product Certification Body*

A2LA has accredited

**MICOM LABS**


*Pleasanton, CA*

for technical competence as a

**Product Certification Body**

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC Guide 65:1996 *General requirements for bodies operating product certification systems*. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system.

Presented this 27<sup>th</sup> day of March 2012.



President & CEO  
For the Accreditation Council  
Certificate Number 2381.02  
Valid to November 30, 2013

*For the product certification schemes to which this accreditation applies, please refer to the organization's Product Certification Scope of Accreditation*

### **United States of America – Telecommunication Certification Body (TCB)**

TCB Identifier – US0159

### **Industry Canada – Certification Body**

CAB Identifier – US0159

### **Europe – Notified Body**

Notified Body Identifier - 2280

### **Japan – Recognized Certification Body (RCB)**

RCB Identifier - 210

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 8 of 242

---

## DOCUMENT HISTORY

Document History		
Revision	Date	Comments
Draft		
Rev A	29 <sup>th</sup> March 2013	Initial release.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 9 of 242

## 1. TEST RESULT CERTIFICATE

Manufacturer:	Digi International 355 South 520 West, Suite 180 Lindon Utah, 84042 USA	Tested By:	MiCOM Labs, Inc. 440 Boulder Court Suite 200 Pleasanton California, 94566, USA
EUT:	802.11a/b/g/n AR6203 802.11 a/b/g/n (Operating in Wi-Fi Mode)	Telephone:	+1 925 462 0304
Model:	CCWMX28	Fax:	+1 925 462 0306
S/N's:	5501671-01		
Test Date(s):	26th September to 27th November '12	Website:	www.micomlabs.com

STANDARD(S)	TEST RESULTS
FCC 47 CFR Part 15.247 & IC RSS-210	EQUIPMENT COMPLIES

MiCOM Labs, Inc. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.


### Notes:


1. This document reports conditions under which testing was conducted and the results of testing performed.
2. Details of test methods used have been recorded and kept on file by the laboratory.
3. Test results apply only to the item(s) tested.

Approved & Released for MiCOM Labs, Inc. by:



TEST CERTIFICATE #2381.01

  
\_\_\_\_\_  
Graeme Grieve  
Quality Manager MiCOM Labs,

  
\_\_\_\_\_  
Gordon Hurst  
President & CEO MiCOM Labs, Inc.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## 2. REFERENCES AND MEASUREMENT UNCERTAINTY

### 2.1. Normative References

REF.	PUBLICATION	YEAR	TITLE
i.	FCC 47 CFR Part 15, Subpart C	2012	Title 47: Telecommunication PART 15—RADIO FREQUENCY DEVICES Subpart C—Intentional Radiators
ii.	RSS-210 Annex 8	2010	Radio Standards Specification 210, Issue 8, Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment
iii.	FCC OET KDB 662911	4 <sup>th</sup> April 2011	Emissions Testing of Transmitters with Multiple Outputs in the Same Band
iv.	DA 00-705	2000	FCC DA 00-705 "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems" released March 30, 2000
v.	RSS-GEN	2010	Radio Standards Specification-Gen, Issue 3, General Requirements and Information for the Certification of Radiocommunication Equipment
vi.	FCC 47 CFR Part 15 B	2012	47 CFR Part 15, SubPart B; Unintentional Radiators
vii.	ICES-003	2004	Spectrum Management and Telecommunications Policy Interference-Causing Equipment Standard Digital Apparatus; Issue 4
viii.	ANSI C63.4	2009	American National Standards for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ix.	CISPR 22/ EN 55022	2008 2006+A1:2007	Limits and Methods of Measurements of Radio Disturbance Characteristics of Information Technology Equipment
x.	M 3003	Edition 1 Dec. 1997	Expression of Uncertainty and Confidence in Measurements
xi.	LAB34	Edition 1 Aug 2002	The expression of uncertainty in EMC Testing
xii.	ETSI TR 100 028	2001	Parts 1 and 2 Electromagnetic compatibility and Radio Spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics
xiii.	A2LA	July 2012	Reference to A2LA Accreditation Status – A2LA Advertising Policy

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 11 of 242

---

## **2.2. Test and Uncertainty Procedures**

Conducted and radiated emission measurements were conducted in accordance with American National Standards Institute ANSI C63.4, listed in the Normative References section of this report.

Measurement uncertainty figures are calculated in accordance with ETSI TR 100 028 Parts 1 and 2.

Measurement uncertainties stated are based on a standard uncertainty multiplied by a coverage factor  $k = 2$ , providing a level of confidence of approximately 95 % in accordance with UKAS document M 3003 listed in the Normative References section of this report.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 12 of 242

### 3. PRODUCT DETAILS AND TEST CONFIGURATIONS

#### 3.1. Technical Details

Details	Description
Purpose:	Test of the Digi Connect Card for i.MX28 with Atheros AR6203 to FCC Part 15.247 and Industry Canada RSS-210 regulations.
Applicant:	Digi International 355 South 520 West, Suite 180 Lindon Utah, 84042 USA
Manufacturer:	As applicant.
Laboratory performing the tests:	MiCOM Labs, Inc. 440 Boulder Court, Suite 200 Pleasanton, California 94566 USA
Test report reference number:	DIGI28-U2B Rev A
Date EUT received:	26 <sup>th</sup> September 2012
Standard(s) applied:	FCC 47 CFR Part 15.247 & IC RSS-210
Dates of test (from - to):	26th September to 27th November '12
No of Units Tested:	One
Type of Equipment:	802.11a/b/g/n Wi-Fi Module
Manufacturers Trade Name:	Wi-Fi Module
Model(s):	CCWMX28
Location for use:	Indoor
Declared Frequency Range(s):	2400 - 2483.5 MHz; 5725 - 5850 MHz
Hardware Rev	30013772-04
Software Rev	DEL-5.9 Rev B
Type of Modulation:	Per 802.11 –CCK, BPSK, QPSK, DSSS, OFDM
Declared Nominal Average Output Power:	2400 – 2483.5 MHz 802.11b: +19 dBm; 802.11g: +23 dBm; HT-20 +24 dBm; HT-40 +24 dBm  5725 - 5850 MHz 802.11a:+24 dBm,HT-20 +23 dBm,HT-40 +23 dBm
EUT Modes of Operation:	Legacy 802.11a/b/g, 802.11n HT-20, HT-40
Transmit/Receive Operation:	Time Division Duplex
System Beam Forming:	EUT has no capability for antenna beam forming
Rated Input Voltage and Current:	5 Vdc 0.625 A
Operating Temperature Range:	Declared range -40° to +75°C at 95% humidity non condensing
ITU Emission Designator:	2400 – 2483.5 MHz 802.11b 13M9G1D 2400 – 2483.5 MHz 802.11g 17M6D1D 2400 – 2483.5 MHz 802.11n – HT-20 18M3D1D 2400 – 2483.5 MHz 802.11n – HT-40 36M9D1D 5725 – 5850 MHz 802.11a 16M8D1D 5725 – 5850 MHz 802.11n – HT-20 17M9D1D 5725 – 5850 MHz 802.11n – HT-40 36M6D1D
Equipment Dimensions:	2" (L) x 1.375 (W) x 0.162" (H) inches

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 13 of 242

Weight:	< 0.5 oz
Primary function of equipment:	Wi-Fi Module for transmitting data and voice.

### 3.2. Scope of Test Program

#### Digi Connect Card for i.MX28 with Atheros AR6203 RF Testing

The scope of the test program was to test the Digi Connect Card for i.MX28 with Atheros AR6203 dual port module in the frequency ranges 2400 - 2483.5 MHz and 5725 – 5850 MHz for compliance against FCC 47 CFR Part 15.247 and Industry Canada RSS-210 specifications.

Wi-Fi Dual Port Module: 5501671-01

#### The following operational description of the module was provided by the customer.

The ConnectCard for i.MX28 module set contains a full 802.11 a b g n and Bluetooth radio with a programmable Freescale i.MX28 Processor. The RF section of the part is handled by a Qualcomm Atheros Wi-Fi/BT module with a 5GHz RF front end module. Data is entered into the processor through a variety of interfaces including Ethernet, CAN, UART, SPI, I2C, I2S, USB, SDIO, etc. Data is sent to the Wi-Fi/BT module where it is processed and sent to the RF Antenna(s). Likewise data is received in the Wi-Fi/BT module and converted to baseband data where it is sent to the processor for baseband processing and sent out of the module using one of the interface ports.


The module is comprised of a Freescale i.MX28 processor, a Qualcomm Atheros Wi-Fi/Bluetooth Module, an RFMD 5GHz front end module, Diplex filter, and either a BT-2.4GHz Wi-Fi switch or Diversity antenna switch (if no BT). The ConnectCard for i.MX28 functions in both the 2.4 to 2.5GHz, and 4.9 to 6 GHz ISM bands.

The module uses an efficient architecture in which data streams directly from the processor (at baseband) to the Wi-Fi/BT module through data lines. The processor also controls the transceiver's modes within the 802.11 a, b, g, and n modes. The Wi-Fi module includes LNA's for the receive modes and a power amplifier for the transmit mode within the 2.4GHz band. Further a there are transmit-receive switches within the module for the 2.4GHz bands. The antenna(s) are connected to the module through u.FL connectors. With BT capable modules there is a single u.FL connector for a single antenna. For modules without BT, there is a diversity antenna switch and 2 u.FL antenna connectors. The module is available with different amounts of FLASH, and RAM, as well as various processors within the i.MX28 family for customers to store their programs.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

**Digi Connect Card for i.MX28 with Atheros AR6203 – Dual Port**



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 15 of 242

### 3.3. Equipment Model(s) and Serial Number(s)

Equipment Type	Equipment Description (Including Brand Name)	Mfr	Model No.	Serial No.
EUT	802.11a/b/g/n Module – Dual Port	Digi International	CCWMX28	55001671.01
Support	Laptop PC	IBM	Thinkpad	None

### 3.4. Antenna Details

Antenna Type	Manufacturer	Model Number	Antenna Gain (dBi)	
			2.4 GHz	5 GHz
Patch	Taoglas	PC.11	3.0	4.5
Patch	Taoglas	FXP.830	1.8	4
Dual Band Omni	Antenna Factor	ANT-DB1-xxx	-3.10	4.30
Single Band Omni	Bobbintron Electrical Corp.	SA-006-1	1.8	---

### 3.5. Cabling and I/O Ports

Number and type of I/O ports

1. 1 x DB9 control port on interface card
2. 2 x 2.5 mm DC Power ports on interface card

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



### 3.6. Test Configurations

Testing was performed to determine the highest power level versus bit rate. The variant with the highest power was used to exercise the product.

Operational Mode(s) (802.11a/b/g/n)	Variant	Data Rate with Highest Power	Frequencies (MHz)
b	Legacy	1 MBit/s	2,412
g	Legacy	6 MBit/s	2,437
n	HT-20	6.5 (MCS 0)	2,462
	HT-40	13.5 (MCS 0)	2,422 2,437 2,452
a	Legacy	6 MBit/s	5,745
n	HT-20	6.5 (MCS 0)	5,785
	HT-40	13.5 (MCS 0)	5,825 5,755 5,795

Legacy – data rates for 802.11abg products

Results for the above configurations are provided in this report.





### Antenna Test Configurations for Radiated Emissions

Results for the following configurations are provided in this report.

Modes with the highest spectral density will have the highest spurious emissions, only those modes were tested for this test program.

2,400 – 2483.5 MHz

5,725 – 5850 MHz

15.247	
802.11b	b SE 2412
	b SE 2437
	b SE 2462
	BE b 2390
	BE b 2483.5
802.11g	g SE 2412
	g SE 2437
	g SE 2462
	BE g 2390
	BE g 2483.5
802.11n HT-20	BE n HT-20 2390
	BE n HT-20 2483.5
802.11n HT-40	BE n HT-40 2390
	BE n HT-40 2483.5

15.247	
802.11a	a SE 5745
	a SE 5785
	a SE 5825
	BE a 5490
802.11n HT-20	BE a 5490
802.11n HT-40	BE a 5490

KEY;-

SE – Spurious Emission  
BE – Band-Edge



### 3.7. Equipment Modifications

The following modifications were required to bring the equipment into compliance:

1. Band-Edge and Radiated Spurious Power Reduction

All conducted spurious emission testing was performed with the device set for maximum power at all times. During radiated spurious and band-edge emission testing the output power was reduced in order to comply with the Restricted Band limit criteria.

Dual Port Module		PC.11	FXP.830	ANT-DB1-xxx	SA-006-1*
	Channel (MHz)	Maximum Power Level			
2.4 GHz	b	2412	20	20	20
		2437	20	20	20
		2462	20	19	20
	g	2412	19	17	15
		2437	20	20	20
		2462	20	19	14
	HT-20	2412	18	16	14
		2437	20	20	20
		2462	20	18	13
	HT-40	2422	16	13	10
		2437	19	17	16
		2452	17	16	9
5.8 GHz	a	5745	18	20	13
		5785	16	18	11
		5825	15	13	9
	HT-20	5745	18	20	13
		5785	16	18	11
		5825	15	13	9
	HT-40	5755	18	20	13
		5795	15	13	9

\*Antenna is 2.4 GHz Only

### 3.8. Deviations from the Test Standard

The following deviations from the test standard were required in order to complete the test program:

1. NONE


## 4. TEST EQUIPMENT CONFIGURATION(S)

### 4.1. Conducted RF Emission Test Set-up

The following tests were performed using the conducted test set-up shown in the diagram below.

1. Section 6.1.1.1. 6 dB and 99% Bandwidth
2. Section 6.1.1.2. Peak Output Power
3. Section 6.1.1.3. Power Spectral Density
4. Section 6.1.1.4. Conducted Spurious Emissions

#### Conducted Test Set-Up Pictorial Representation



---


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

#### 4.2. Radiated Spurious Emission Test Set-up > 1 GHz

The following tests were performed using the conducted test set-up shown in the diagram below.

1. Section 6.1.2.2. Dual Band Patch PC.11 - Dual Port Module
2. Section 6.1.2.4. Dual Band Patch FXP.830 - Dual Port Module
3. Section 6.1.2.6. Dual Band Omni ANT-DB1-xxx - Dual Port Module
4. Section 6.1.2.8 Single Band Omni SA-006-1 - Dual Port Module

#### Radiated Emission Measurement Setup – Above 1 GHz




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

#### 4.3. Digital Emissions Test Set-up (0.03 – 1 GHz)

The following tests were performed using the conducted test set-up shown in the diagram below.

1. Section 6.1.2.9. Dual Band OMNI ANT-DB1-xxx

#### Digital Emission Measurement Setup – Below 1 GHz




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

#### 4.4. ac Wireline Emission Test Set-up

The following tests were performed using the conducted test set-up shown in the diagram below.

Refer to MiCOM Labs test report DIGI28-U4.

##### 1. Section 6.1.3 ac Wireline Conducted Emissions



**Measurement Setup for Conducted Emissions Test**



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 23 of 242

## 5. TEST SUMMARY

### List of Measurements

The following table represents the list of measurements required under the **FCC CFR47 Part 15.247** and **Industry Canada RSS-210** and **Industry Canada RSS-Gen**.

Section(s)	Test Items	Description	Condition	Result	Test Report Section
15.247(a)(2) A8.2(1) 4.4	6 dB and 99 % Bandwidths	≥500 kHz	Conducted	Complies	6.1.1
15.247(b)(3) 15.31(e) A8.4(4)	Peak Output Power Voltage Variation	Shall not exceed 1W  Variation of supply voltage 85 % -115 %	Conducted	Complies	6.1.2
15.247(e) A8.2	Peak Power Spectral Density	Shall not be greater than +8 dBm in any 3 kHz band	Conducted	Complies	6.1.3
15.247(i) 5.5	Maximum Permissible Exposure	Exposure to radio frequency energy levels	Conducted	Complies	6.1.4
15.247(d) 15.205 / 15.209 A8.5 2.2 4.7	Spurious Emissions (30MHz - 26 GHz b/g and 30 MHz – 40 GHz a)	The radiated emission in any 100 kHz of out-band shall be at least 20 dB below the highest in-band spectral density	Conducted	Complies	6.1.5

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 24 of 242

### List of Measurements (continued)

The following table represents the list of measurements required under the **FCC CFR47 Part 15.247**, **Industry Canada RSS-210**, and **Industry Canada RSS-Gen**.

Section(s)	Test Items	Description	Condition	Result	Test Report Section
15.247(d) 15.205 / 15.209 A8.5 2.2 2.6 4.7	Radiated Emissions	Restricted Bands	Radiated	Complies	6.1.2.1- 6.1.2.8
	Transmitter Radiated Spurious Emissions	Emissions above 1 GHz		Complies	6.1.2.1- 6.1.2.8
	Radiated Band Edge	Band-edge results Peak Emissions		Complies	6.1.2.1- 6.1.2.8
15.205 / 15.209 2.2	Radiated Spurious Emissions	Emissions <1 GHz (30M-1 GHz)	Radiated	Complies	6.1.2.9
15.207 7.2.2	AC Wireline Conducted Emissions 150 kHz– 30 MHz	Conducted Emissions	Conducted	N/A EUT is DC powered	6.1.3

**Note 1:** Test results reported in this document relate only to the items tested

**Note 2:** The required tests demonstrated compliance as per client declaration of test configuration, monitoring methodology and associated pass/fail criteria

**Note 3:** Section 3.7 Equipment Modifications highlights the equipment modifications that were required to bring the product into compliance with the above test matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 25 of 242

---

## 6. TEST RESULTS

### 6.1. Device Characteristics

#### 6.1.1. Conducted Testing

##### 6.1.1.1. 6 dB and 99 % Bandwidth

Conducted Test Conditions for 6 dB and 99% Bandwidth			
<b>Standard:</b>	FCC CFR 47:15.247	<b>Ambient Temp. (°C):</b>	24.0 - 27.5
<b>Test Heading:</b>	6 dB and 99 % Bandwidth	<b>Rel. Humidity (%):</b>	32 - 45
<b>Standard Section(s):</b>	15.247 (a)(2)	<b>Pressure (mBars):</b>	999 - 1001
<b>Reference Document(s):</b>	KDB 558074 - D01 DTS Measurement Guidance v01: Section 5.1 Emission Bandwidth		

**Test Procedure for 6 dB and 99% Bandwidth Measurement**  
The bandwidth at 6 dB and 99 % was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate centre frequency.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 26 of 242

Dual Port Module:

<b>Equipment Configuration for 6 dB 99%</b>
---

<b>Variant:</b>	802.11b	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6 Mbps	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	CCK	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Measured 6 dB Bandwidth (MHz)				6 dB Bandwidth (MHz)		Limit	Lowest Margin
	Port(s)				Highest	Lowest		
	a	b	c	d				
MHz							MHz	MHz
2412.0	10.261	--	--	--	10.261	10.261	≥ 0.5	-9.76
2437.0	10.180	--	--	--	10.180	10.180	≥ 0.5	-9.68
2462.0	10.261	--	--	--	10.261	10.261	≥ 0.5	-9.76

Test Frequency	Measured 99% Bandwidth (MHz)				Maximum 99% Bandwidth (MHz)		
	Port(s)						
	a	b	c	d			
MHz							
2412.0	14.349	--	--	--	14.349		
2437.0	14.429	--	--	--	14.429		
2462.0	14.589	--	--	--	14.589		

<b>Traceability to Industry Recognized Test Methodologies</b>	
Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 27 of 242

Dual Port Module:

<b>Equipment Configuration for 6 dB 99%</b>
---

<b>Variant:</b>	802.11g	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6 mbps	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency MHz	Measured 6 dB Bandwidth (MHz)				6 dB Bandwidth (MHz)		Limit MHz	Lowest Margin MHz
	Port(s)				Highest	Lowest		
	a	b	c	d				
2412.0	16.353	--	--	--	16.353	16.353	≥ 0.5	-15.85
2437.0	16.353	--	--	--	16.353	16.353	≥ 0.5	-15.85
2462.0	16.353	--	--	--	16.353	16.353	≥ 0.5	-15.85

Test Frequency MHz	Measured 99% Bandwidth (MHz)				Maximum 99% Bandwidth (MHz)		
	Port(s)						
	a	b	c	d			
2412.0	16.754	--	--	--	16.754		
2437.0	17.315	--	--	--	17.315		
2462.0	17.555	--	--	--	17.555		

<b>Traceability to Industry Recognized Test Methodologies</b>	
Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 28 of 242

Dual Port Module:

<b>Equipment Configuration for 6 dB 99%</b>
---

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Measured 6 dB Bandwidth (MHz)				6 dB Bandwidth (MHz)		Limit	Lowest Margin
	Port(s)				Highest	Lowest		
	a	b	c	d				
MHz							MHz	MHz
2412.0	16.994	--	--	--	16.994	16.994	≥ 0.5	-16.49
2437.0	17.395	--	--	--	17.395	17.395	≥ 0.5	-16.90
2462.0	17.395	--	--	--	17.395	17.395	≥ 0.5	-16.90

Test Frequency	Measured 99% Bandwidth (MHz)				Maximum 99% Bandwidth (MHz)		
	Port(s)						
	a	b	c	d			
MHz							
2412.0	18.036	--	--	--	18.036		
2437.0	18.277	--	--	--	18.277		
2462.0	18.517	--	--	--	18.517		

<b>Traceability to Industry Recognized Test Methodologies</b>	
Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 29 of 242

Dual Port Module:

<b>Equipment Configuration for 6 dB 99%</b>
---

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	13.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Measured 6 dB Bandwidth (MHz)				6 dB Bandwidth (MHz)		Limit	Lowest Margin
	Port(s)				Highest	Lowest		
	a	b	c	d				
MHz	a	b	c	d	Highest	Lowest	MHz	MHz
2422.0	36.232	--	--	--	36.232	36.232	≥ 0.5	-35.73
2437.0	36.232	--	--	--	36.232	36.232	≥ 0.5	-35.73
2452.0	36.393	--	--	--	36.393	36.393	≥ 0.5	-35.89

Test Frequency	Measured 99% Bandwidth (MHz)				Maximum 99% Bandwidth (MHz)		
	Port(s)						
	a	b	c	d			
MHz	a	b	c	d			
2422.0	36.713	--	--	--	36.713		
2437.0	36.713	--	--	--	36.713		
2452.0	37.515	--	--	--	37.515		

<b>Traceability to Industry Recognized Test Methodologies</b>	
Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 30 of 242

Dual Port Module:

<b>Equipment Configuration for 6 dB 99%</b>
---

<b>Variant:</b>	802.11a	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6 mbps	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Measured 6 dB Bandwidth (MHz)				6 dB Bandwidth (MHz)		Limit	Lowest Margin
	Port(s)				Highest	Lowest		
	a	b	c	d				
MHz							MHz	MHz
5745.0	15.952	--	--	--	15.952	15.952	≥ 0.5	-15.45
5785.0	15.711	--	--	--	15.711	15.711	≥ 0.5	-15.21
5825.0	15.551	--	--	--	15.551	15.551	≥ 0.5	-15.05

Test Frequency	Measured 99% Bandwidth (MHz)				Maximum 99% Bandwidth (MHz)		
	Port(s)						
	a	b	c	d			
MHz							
5745.0	28.617	--	--	--	28.617		
5785.0	29.579	--	--	--	29.579		
5825.0	29.259	--	--	--	29.259		

<b>Traceability to Industry Recognized Test Methodologies</b>	
Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 31 of 242

Dual Port Module:

<b>Equipment Configuration for 6 dB 99%</b>
---

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Measured 6 dB Bandwidth (MHz)				6 dB Bandwidth (MHz)		Limit	Lowest Margin
	Port(s)				Highest	Lowest		
	a	b	c	d				
MHz							MHz	MHz
5745.0	16.834	--	--	--	16.834	16.834	≥ 0.5	-16.33
5785.0	16.834	--	--	--	16.834	16.834	≥ 0.5	-16.33
5825.0	16.834	--	--	--	16.834	16.834	≥ 0.5	-16.33

Test Frequency	Measured 99% Bandwidth (MHz)				Maximum 99% Bandwidth (MHz)		
	Port(s)						
	a	b	c	d			
MHz							
5745.0	30.220	--	--	--	30.220		
5785.0	30.301	--	--	--	30.301		
5825.0	30.862	--	--	--	30.862		

<b>Traceability to Industry Recognized Test Methodologies</b>	
Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 32 of 242

Dual Port Module:

<b>Equipment Configuration for 6 dB 99%</b>
---

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	13.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency MHz	Measured 6 dB Bandwidth (MHz)				6 dB Bandwidth (MHz)		Limit MHz	Lowest Margin MHz
	Port(s)				Highest	Lowest		
	a	b	c	d				
5755.0	35.271	--	--	--	35.271	35.271	≥ 0.5	-34.77
5795.0	35.431	--	--	--	35.431	35.431	≥ 0.5	-34.93

Test Frequency MHz	Measured 99% Bandwidth (MHz)				Maximum 99% Bandwidth (MHz)		
	Port(s)						
	a	b	c	d			
5755.0	38.156	--	--	--	38.156		
5795.0	48.417	--	--	--	48.417		

<b>Traceability to Industry Recognized Test Methodologies</b>	
Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 33 of 242

---

## Specification

### Limits

#### §15.247 (a)(2) & RSS-210 §A8.2(1)

The minimum 6 dB bandwidth shall be at least 500 kHz.

**§ IC RSS-Gen 4.4.1 Occupied Bandwidth** When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99% emission bandwidth, as calculated or measured.

**§ IC RSS-Gen 4.4.2 6 dB Bandwidth** Where indicated, the 6 dB bandwidth is measured at the points when the spectral density of the signal is 6 dB down from the in-band spectral density of the modulated signal, with the transmitter modulated by a representative signal.

## Traceability

Test Equipment Used
0158, 0287, 0252, 0313, 0314, 0070, 0116, 0117

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 34 of 242

### 6.1.1.2. Peak Output Power

Conducted Test Conditions for Fundamental Emission Output Power			
<b>Standard:</b>	FCC CFR 47:15.247	<b>Ambient Temp. (°C):</b>	24.0 - 27.5
<b>Test Heading:</b>	Emission Output Power	<b>Rel. Humidity (%):</b>	32 - 45
<b>Standard Section(s):</b>	15.247 (a)(2)	<b>Pressure (mBars):</b>	999 - 1004
<b>Reference Document(s):</b>	KDB 558074 - D01 DTS Measurement Guidance v01: Section 5.2 Fundamental Emission Output Power KDB 662911 was implemented for In-band power measurements. The measure and sum technique was implemented in all cases.		

#### Test Procedure for Fundamental Emission Output Power Measurement

The transmitter terminal of EUT was connected to the input of the spectrum analyzer set to measure peak power. The resolution filter bandwidth was set to 6 dB, peak detector selected and the analyzer built-in power function was used to integrate peak power over the 20 dB bandwidth.

#### Supporting Information

Calculated Power = A + G + 10 log (1/x) dBm

A = Total Power [10 Log<sub>10</sub> (10<sup>a/10</sup> + 10<sup>b/10</sup> + 10<sup>c/10</sup> + 10<sup>d/10</sup>)], G = Antenna Gain,

x = Duty Cycle

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 35 of 242

The following Peak Power Matrix(s) was tested using the system maximum power setting dBm = 20, see Section 3.7 Equipment Modifications

Dual Port Module:

<b>Equipment Configuration for peak output power</b>
--

<b>Variant:</b>	802.11b	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6 mbps	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	CCK	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

Test Measurement Results								
Test Frequency	Measured Output Power (dBm)				Calculated Total Power (dBm)	Limit	Margin	EUT Power Setting
	Port(s)							
MHz	a	b	c	d	Σ Port(s)	dBm	dBm	
2412.0	19.15	--	--	--	19.15	30.00	-10.85	20
2437.0	19.31	--	--	--	19.31	30.00	-10.69	20
2462.0	19.47	--	--	--	19.47	30.00	-10.53	20

Traceability to Industry Recognized Test Methodologies	
Work Instruction:	WI-01 MEASURING RF OUTPUT POWER
Measurement Uncertainty:	±1.33 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 36 of 242

Dual Port Module:

**Equipment Configuration for peak output power**

<b>Variant:</b>	802.11g	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6 mbps	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured Output Power (dBm)				Calculated Total Power (dBm)	Limit	Margin	EUT Power Setting
	Port(s)							
MHz	a	b	c	d	Σ Port(s)	dBm	dBm	
2412.0	23.44	--	--	--	23.44	30.00	-6.56	20
2437.0	23.98	--	--	--	23.98	30.00	-6.02	20
2462.0	23.66	--	--	--	23.66	30.00	-6.34	20

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-01 MEASURING RF OUTPUT POWER
Measurement Uncertainty:	±1.33 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 37 of 242

Dual Port Module:

Equipment Configuration for peak output power			
<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

Test Measurement Results								
Test Frequency	Measured Output Power (dBm)				Calculated Total Power (dBm)	Limit	Margin	EUT Power Setting
	Port(s)							
MHz	a	b	c	d	Σ Port(s)	dBm	dBm	
2412.0	23.95	--	--	--	23.95	30.00	-6.05	20
2437.0	24.08	--	--	--	24.08	30.00	-5.92	20
2462.0	23.74	--	--	--	23.74	30.00	-6.26	20

Traceability to Industry Recognized Test Methodologies	
Work Instruction:	WI-01 MEASURING RF OUTPUT POWER
Measurement Uncertainty:	±1.33 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 38 of 242

Dual Port Module:

Equipment Configuration for peak output power			
---	--	--	--

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	13.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

Test Measurement Results								
--------------------------	--	--	--	--	--	--	--	--

Test Frequency	Measured Output Power (dBm)				Calculated Total Power (dBm)	Limit	Margin	EUT Power Setting
	Port(s)							
MHz	a	b	c	d	Σ Port(s)	dBm	dBm	
2422.0	24.53	--	--	--	24.53	30.00	-5.47	20
2437.0	24.65	--	--	--	24.65	30.00	-5.35	20
2452.0	24.64	--	--	--	24.64	30.00	-5.36	20

Traceability to Industry Recognized Test Methodologies	
--	--

Work Instruction:	WI-01 MEASURING RF OUTPUT POWER
Measurement Uncertainty:	±1.33 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 39 of 242

Dual Port Module:

Equipment Configuration for peak output power			
---	--	--	--

<b>Variant:</b>	802.11a	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6 mbps	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

Test Measurement Results								
--------------------------	--	--	--	--	--	--	--	--

Test Frequency	Measured Output Power (dBm)				Calculated Total Power (dBm)	Limit	Margin	EUT Power Setting
	Port(s)							
MHz	a	b	c	d	Σ Port(s)	dBm	dBm	
5745.0	24.34	--	--	--	24.34	30.00	-5.66	20
5785.0	24.60	--	--	--	24.60	30.00	-5.40	20
5825.0	24.11	--	--	--	24.11	30.00	-5.89	20

Traceability to Industry Recognized Test Methodologies	
--	--

Work Instruction:	WI-01 MEASURING RF OUTPUT POWER
Measurement Uncertainty:	±1.33 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 40 of 242

Dual Port Module:

Equipment Configuration for Peak Output Power			
---	--	--	--

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	100%
<b>Data Rate:</b>	6.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

Test Measurement Results								
--------------------------	--	--	--	--	--	--	--	--

Test Frequency	Measured Output Power (dBm)				Calculated Total Power (dBm)	Limit	Margin	EUT Power Setting
	Port(s)							
MHz	a	b	c	d	$\Sigma$ Port(s)	dBm	dBm	
5745.0	22.90	--	--	--	22.90	30.00	-7.10	20.00
5785.0	22.89	--	--	--	22.89	30.00	-7.11	20.00
5825.0	23.84	--	--	--	23.84	30.00	-6.16	20.00

Traceability to Industry Recognized Test Methodologies	
--	--

Work Instruction:	WI-01 MEASURING RF OUTPUT POWER
Measurement Uncertainty:	$\pm 1.33$ dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 41 of 242

Dual Port Module:

<b>Equipment Configuration for peak output power</b>
--

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	13.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Measured Output Power (dBm)				Calculated Total Power (dBm)	Limit	Margin	EUT Power Setting
	Port(s)							
MHz	a	b	c	d	Σ Port(s)	dBm	dBm	
5755.0	21.96	--	--	--	21.96	30.00	-8.04	20
5795.0	23.47	--	--	--	23.47	30.00	-6.53	20

<b>Traceability to Industry Recognized Test Methodologies</b>	
Work Instruction:	WI-01 MEASURING RF OUTPUT POWER
Measurement Uncertainty:	±1.33 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 42 of 242

## Specification

### Limits

**§15.247 (b)** The maximum peak output power of the intentional radiator shall not exceed the following:

**§15.247 (b) (3)** For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands: 1.0 watt.

**15.247 (b) (4)** The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

15.247 (c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

(i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(ii) Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

**§15.31 (e)** For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

**§ RSS-210 A8.4(4)** For systems employing digital modulation techniques operating in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands the maximum peak conducted power shall not exceed 1 watt.

### Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-01 'Measuring RF Output Power'	0158, 0287, 0252, 0313, 0314, 0070, 0116, 0117

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 43 of 242

### 6.1.1.3. Power Spectral Density

Conducted Test Conditions for Power Spectral Density			
<b>Standard:</b>	FCC CFR 47:15.247	<b>Ambient Temp. (°C):</b>	24.0 - 27.5
<b>Test Heading:</b>	Power Spectral Density	<b>Rel. Humidity (%):</b>	32 - 45
<b>Standard Section(s):</b>	15.247 (e)	<b>Pressure (mBars):</b>	999 - 1001
<b>Reference Document(s):</b>	KDB 558074 - D01 DTS Measurement Guidance v01: Section 5.3 Maximum Power Spectral Density Level in the Emission Bandwidth		
<b>Test Procedure for Power Spectral Density</b> The transmitter output was connected to a spectrum analyzer and the maximum level in a 3 kHz bandwidth was measured. A peak value was found over the full emission bandwidth and the frequency span reduced to obtain enhanced resolution. Sweep time $\geq$ span / 3 kHz with video averaging turned off. The Peak Power Spectral Density is the highest level found across the emission in a 3 kHz resolution bandwidth.			
<b>Supporting Information</b> Calculated Power = $A + 10 \log (1/x)$ dBm $A = \text{Total Power Spectral Density } [10 \text{ Log}_{10} (10^{a/10} + 10^{b/10} + 10^{c/10} + 10^{d/10})]$ $x = \text{Duty Cycle}$ Limit Line: KDB 662911 was implemented for In-band power spectral density (PSD) measurements - Option (2) measure and subtract $10 \log (N)$ dB from the limit for devices with multiple RF ports			

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 44 of 242

Dual Port Module:

<b>Equipment Configuration for power density</b>
--

<b>Variant:</b>	802.11b	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6 mbps	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	CCK	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Measured Power Spectral Density (dBm)				Calculated Total Power Spectral Density		Limit	Margin
	Port(s)				dBm			
MHz	a	b	c	d	Σ Port(s)	Conversion to 3 kHz RBW	dBm	dB
2412.0	-7.459	--	--	--	-7.459	N/A	≤8.0	-15.46
2437.0	-7.367	--	--	--	-7.367	N/A	≤8.0	-15.37
2462.0	-7.172	--	--	--	-7.172	N/A	≤8.0	-15.17

<b>Traceability to Industry Recognized Test Methodologies</b>
---

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 45 of 242

Dual Port Module:

<b>Equipment Configuration for power density</b>
--

<b>Variant:</b>	802.11g	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6 mbps	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Measured Power Spectral Density (dBm)				Calculated Total Power Spectral Density		Limit	Margin
	Port(s)				dBm			
MHz	a	b	c	d	Σ Port(s)	Conversion to 3 kHz RBW	dBm	dB
2412.0	-8.337	--	--	--	-8.337	N/A	≤8.0	-16.34
2437.0	-9.185	--	--	--	-9.185	N/A	≤8.0	-17.19
2462.0	-8.427	--	--	--	-8.427	N/A	≤8.0	-16.43

<b>Traceability to Industry Recognized Test Methodologies</b>
---

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 46 of 242

Dual Port Module:

<b>Equipment Configuration for power density</b>
--

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Measured Power Spectral Density (dBm)				Calculated Total Power Spectral Density		Limit	Margin
	Port(s)				dBm			
MHz	a	b	c	d	Σ Port(s)	Conversion to 3 kHz RBW	dBm	dB
2412.0	-8.964	--	--	--	-8.964	N/A	≤8.0	-16.96
2437.0	-9.094	--	--	--	-9.094	N/A	≤8.0	-17.09
2462.0	-9.494	--	--	--	-9.494	N/A	≤8.0	-17.49

<b>Traceability to Industry Recognized Test Methodologies</b>
---

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 47 of 242

Dual Port Module:

<b>Equipment Configuration for power density</b>
--

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	13.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Measured Power Spectral Density (dBm)				Calculated Total Power Spectral Density		Limit	Margin
	Port(s)				dBm			
MHz	a	b	c	d	Σ Port(s)	Conversion to 3 kHz RBW	dBm	dB
2422.0	-12.775	--	--	--	-12.775	N/A	≤8.0	-20.78
2437.0	-12.466	--	--	--	-12.466	N/A	≤8.0	-20.47
2452.0	-10.790	--	--	--	-10.790	N/A	≤8.0	-18.79

<b>Traceability to Industry Recognized Test Methodologies</b>
---

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 48 of 242

Dual Port Module:

<b>Equipment Configuration for power density</b>
--

<b>Variant:</b>	802.11a	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6 mbps	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Measured Power Spectral Density (dBm)				Calculated Total Power Spectral Density		Limit	Margin
	Port(s)				dBm			
MHz	a	b	c	d	Σ Port(s)	Conversion to 3 kHz RBW	dBm	dB
5745.0	-9.153	--	--	--	-9.153	N/A	≤8.0	-17.15
5785.0	-8.978	--	--	--	-8.978	N/A	≤8.0	-16.98
5825.0	-8.227	--	--	--	-8.227	N/A	≤8.0	-16.23

<b>Traceability to Industry Recognized Test Methodologies</b>
---

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 49 of 242

Dual Port Module:

<b>Equipment Configuration for power density</b>
--

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Measured Power Spectral Density (dBm)				Calculated Total Power Spectral Density		Limit	Margin
	Port(s)				dBm			
MHz	a	b	c	d	Σ Port(s)	Conversion to 3 kHz RBW	dBm	dB
5745.0	-8.532	--	--	--	-8.532	N/A	≤8.0	-16.53
5785.0	-7.127	--	--	--	-7.127	N/A	≤8.0	-15.13
5825.0	-6.881	--	--	--	-6.881	N/A	≤8.0	-14.88

<b>Traceability to Industry Recognized Test Methodologies</b>
---

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 50 of 242

Dual Port Module:

**Equipment Configuration for power density**

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	13.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured Power Spectral Density (dBm)				Calculated Total Power Spectral Density		Limit	Margin
	Port(s)				dBm			
MHz	a	b	c	d	Σ Port(s)	Conversion to 3 kHz RBW	dBm	dB
5755.0	-14.691	--	--	--	-14.691	N/A	≤8.0	-22.69
5795.0	-14.725	--	--	--	-14.725	N/A	≤8.0	-22.73

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 51 of 242

---

**Specification**  
**Peak Power Spectral Density Limits**

**§15.247(e)** For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than +8 dBm in any 3 kHz band during any time interval of continuous transmission

**RSS-210 §A8.2(2)** The transmitter power spectral density (into the antenna) shall not be greater than +8 dBm in any 3 kHz band during any time interval of continuous transmission or over 1.0 second if the transmission exceeds 1.0 second duration.

**Traceability**

Method	Test Equipment Used
Measurements were made per work instruction WI-01 'Measuring RF Output Power'	0158, 0287, 0252, 0313, 0314, 0070, 0116, 0117

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 52 of 242

---

#### 6.1.1.4. Conducted Spurious Emissions

Conducted Test Conditions for Transmitter Conducted Spurious and Band-Edge Emissions			
<b>Standard:</b>	FCC CFR 47:15.247	<b>Ambient Temp. (°C):</b>	24.0 - 27.5
<b>Test Heading:</b>	Max Unwanted Emission Levels	<b>Rel. Humidity (%):</b>	32 - 45
<b>Standard Section(s):</b>	15.247 (d)	<b>Pressure (mBars):</b>	999 - 1001
<b>Reference Document(s):</b>	KDB 558074 - D01 DTS Measurement Guidance v01: Section 5.4 Maximum Unwanted Emission Levels		
<b>Test Procedure for Transmitter Conducted Spurious and Band-Edge Emissions Measurement</b> Transmitter Conducted Spurious and Band-Edge emissions were measured at a limit of 20 dB below the highest in-band spectral density measured with a spectrum analyzer connected to the antenna terminal. Measurements were made while EUT was operating in transmit mode of operation at the appropriate centre frequency closest to the band-edge. Emissions were maximized during the measurement and limits derived from the peak spectral power and drawn on each plot.			

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 53 of 242

Dual Port Module:

<b>Equipment Configuration for Transmitter Conducted Spurious and Band-Edge Emissions</b>
---

<b>Variant:</b>	802.11b	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6 mbps	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	CCK	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>									
---------------------------------	--	--	--	--	--	--	--	--	--

Test Frequency	Frequency Range	Transmitter Conducted Spurious Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		SE	Limit	SE	Limit	SE	Limit	SE	Limit
2412.0	30.0 - 26000.0	-44.278	-14.24	--	--	--	--	--	--
2437.0	30.0 - 26000.0	-43.229	-14.07	--	--	--	--	--	--
2462.0	30.0 - 26000.0	-52.295	-13.92	--	--	--	--	--	--

SE - Maximum spurious emission found

Test Frequency	Band-Edge Frequency	Transmitter Conducted Band-Edge Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		BE	Limit	BE	Limit	BE	Limit	BE	Limit
2412.0	2400.0	-41.392	-14.10	--	--	--	--	--	--
2462.0	2483.5	-42.706	-13.90	--	--	--	--	--	--

BE - Maximum band-edge emission found

<b>Traceability to Industry Recognized Test Methodologies</b>	
---	--

Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	= 40 GHz $\pm$ 2.37 dB, > 40 GHz $\pm$ 4.6 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 54 of 242

Dual Port Module:

<b>Equipment Configuration for Transmitter Conducted Spurious and Band-Edge Emissions</b>
---

<b>Variant:</b>	802.11g	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6 mbps	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Frequency Range	Transmitter Conducted Spurious Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		SE	Limit	SE	Limit	SE	Limit	SE	Limit
2412.0	30.0 - 26000.0	-43.585	-15.58	--	--	--	--	--	--
2437.0	30.0 - 26000.0	-43.060	-16.06	--	--	--	--	--	--
2462.0	30.0 - 26000.0	-54.134	-14.35	--	--	--	--	--	--

SE - Maximum spurious emission found

Test Frequency	Band-Edge Frequency	Transmitter Conducted Band-Edge Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		BE	Limit	BE	Limit	BE	Limit	BE	Limit
2412.0	2400.0	-20.484	-14.40	--	--	--	--	--	--
2462.0	2483.5	-28.604	-14.13	--	--	--	--	--	--

BE - Maximum band-edge emission found

<b>Traceability to Industry Recognized Test Methodologies</b>
---

Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	= 40 GHz $\pm$ 2.37 dB, > 40 GHz $\pm$ 4.6 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 55 of 242

Dual Port Module:

<b>Equipment Configuration for Transmitter Conducted Spurious and Band-Edge Emissions</b>
---

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Frequency Range	Transmitter Conducted Spurious Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		SE	Limit	SE	Limit	SE	Limit	SE	Limit
2412.0	30.0 - 26000.0	-43.719	-14.98	--	--	--	--	--	--
2437.0	30.0 - 26000.0	-43.502	-14.46	--	--	--	--	--	--
2462.0	30.0 - 26000.0	-53.754	-14.42	--	--	--	--	--	--

SE - Maximum spurious emission found

Test Frequency	Band-Edge Frequency	Transmitter Conducted Band-Edge Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		BE	Limit	BE	Limit	BE	Limit	BE	Limit
2412.0	2400.0	-19.153	-13.94	--	--	--	--	--	--
2462.0	2483.5	-26.518	-14.14	--	--	--	--	--	--

BE - Maximum band-edge emission found

<b>Traceability to Industry Recognized Test Methodologies</b>
---

Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	= 40 GHz $\pm$ 2.37 dB, > 40 GHz $\pm$ 4.6 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 56 of 242

Dual Port Module:

Equipment Configuration for Transmitter Conducted Spurious and Band-Edge Emissions
--

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	13.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

Test Measurement Results									
--------------------------	--	--	--	--	--	--	--	--	--

Test Frequency	Frequency Range	Transmitter Conducted Spurious Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		SE	Limit	SE	Limit	SE	Limit	SE	Limit
2422.0	30.0 - 26000.0	-44.132	-17.73	--	--	--	--	--	--
2437.0	30.0 - 26000.0	-43.662	-17.55	--	--	--	--	--	--
2452.0	30.0 - 26000.0	-54.167	-17.63	--	--	--	--	--	--

SE - Maximum spurious emission found

Test Frequency	Band-Edge Frequency	Transmitter Conducted Band-Edge Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		BE	Limit	BE	Limit	BE	Limit	BE	Limit
2422.0	2400.0	-19.542	-17.28	--	--	--	--	--	--
2452.0	2483.5	-20.217	-17.31	--	--	--	--	--	--

BE - Maximum band-edge emission found

Traceability to Industry Recognized Test Methodologies	
--	--

Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	= 40 GHz $\pm$ 2.37 dB, > 40 GHz $\pm$ 4.6 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 57 of 242

Dual Port Module:

<b>Equipment Configuration for Transmitter Conducted Spurious and Band-Edge Emissions</b>
---

<b>Variant:</b>	802.11a	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6 mbps	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Frequency Range	Transmitter Conducted Spurious Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		SE	Limit	SE	Limit	SE	Limit	SE	Limit
5745.0	30.0 - 26000.0	-44.062	-14.09	--	--	--	--	--	--
5785.0	30.0 - 26000.0	-39.953	-16.75	--	--	--	--	--	--
5825.0	30.0 - 26000.0	-40.695	-13.31	--	--	--	--	--	--

SE - Maximum spurious emission found

Test Frequency	Band-Edge Frequency	Transmitter Conducted Band-Edge Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		BE	Limit	BE	Limit	BE	Limit	BE	Limit
5745.0	5725.0	-18.270	-12.84	--	--	--	--	--	--
5825.0	5850.0	-24.464	-13.13	--	--	--	--	--	--

BE - Maximum band-edge emission found

<b>Traceability to Industry Recognized Test Methodologies</b>
---

Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	= 40 GHz $\pm$ 2.37 dB, > 40 GHz $\pm$ 4.6 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 58 of 242

Dual Port Module:

Equipment Configuration for Transmitter Conducted Spurious and Band-Edge Emissions
--

<b>Variant:</b>	802.11n HT-20	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

Test Measurement Results									
--------------------------	--	--	--	--	--	--	--	--	--

Test Frequency	Frequency Range	Transmitter Conducted Spurious Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		SE	Limit	SE	Limit	SE	Limit	SE	Limit
5745.0	30.0 - 26000.0	-44.938	-13.94	--	--	--	--	--	--
5785.0	30.0 - 26000.0	-39.825	-16.75	--	--	--	--	--	--
5825.0	30.0 - 26000.0	-40.642	-16.17	--	--	--	--	--	--

SE - Maximum spurious emission found

Test Frequency	Band-Edge Frequency	Transmitter Conducted Band-Edge Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		BE	Limit	BE	Limit	BE	Limit	BE	Limit
5745.0	5725.0	-15.697	-12.46	--	--	--	--	--	--
5825.0	5850.0	-22.151	-12.72	--	--	--	--	--	--

BE - Maximum band-edge emission found

Traceability to Industry Recognized Test Methodologies	
--	--

Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	= 40 GHz $\pm$ 2.37 dB, > 40 GHz $\pm$ 4.6 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 59 of 242

Dual Port Module:

<b>Equipment Configuration for Transmitter Conducted Spurious and Band-Edge Emissions</b>
---

<b>Variant:</b>	802.11n HT-40	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	13.5 MCS	<b>Antenna Gain (dBi):</b>	Not Applicable
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y):</b>	Not Applicable
<b>TPC:</b>	Max Power		
<b>Engineering Test Notes:</b>			

<b>Test Measurement Results</b>
---------------------------------

Test Frequency	Frequency Range	Transmitter Conducted Spurious Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		SE	Limit	SE	Limit	SE	Limit	SE	Limit
5755.0	30.0 - 26000.0	-40.220	-20.45	--	--	--	--	--	--
5795.0	30.0 - 26000.0	-39.844	-18.29	--	--	--	--	--	--

SE - Maximum spurious emission found

Test Frequency	Band-Edge Frequency	Transmitter Conducted Band-Edge Emissions (dBm)							
		Port a		Port b		Port c		Port d	
		BE	Limit	BE	Limit	BE	Limit	BE	Limit
5755.0	5725.0	-24.169	-19.43	--	--	--	--	--	--
5795.0	5850.0	2.226	-17.77	--	--	--	--	--	--

BE - Maximum band-edge emission found

<b>Traceability to Industry Recognized Test Methodologies</b>
---

Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	= 40 GHz $\pm$ 2.37 dB, > 40 GHz $\pm$ 4.6 dB

Note: [click the link in the above results matrix to view the plot](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 60 of 242

## Specification

### Limits Band-Edge

Lower Limit Band-edge	Upper Limit Band-edge	Limit below highest level of desired power
2,400 MHz	2,483.5 MHz	≥ 20 dB
5725 MHz	5850 MHz	

**§15.247(d) and RSS-210 §A8.5** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

#### §15.247(d)

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section §15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(a)).

**RSS-210 §A8.5** If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required. In addition, radiated emissions which fall in the restricted bands of Table 1 must also comply with the radiated emission limits specified in Tables 2 and 3.

#### RSS-Gen §4.7

The search for unwanted emissions shall be from the lowest frequency internally generated or used in the device (local oscillator, intermediate of carrier frequency), or from 30 MHz, whichever is the lowest frequency, to the 5<sup>th</sup> harmonic of the highest frequency generated without exceeding 40 GHz.

### Laboratory Measurement Uncertainty for Conducted Spurious Emissions

Measurement uncertainty	±2.37 dB
-------------------------	----------

### Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-05 'Measurement of Spurious Emissions'	0088, 0158, 0287, 0252, 0313, 0314, 0070, 0116, 0117.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



### 6.1.1.5. Maximum Permissible Exposure

**FCC, Part 15 Subpart C §15.247(i)**  
**Industry Canada RSS-Gen §5.6**

#### Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4\pi d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10^{(G \text{ (dBi)}/10)}$$

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm<sup>2</sup>

Dual Port Module:

Antenna	Freq. Band (GHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm <sup>2</sup> Limit(cm)	Minimum Separation Distance (cm)
PC.11	2.4	3	2	24.65	291.74	6.81	20.0*
	5.8	4.5	3	24.60	288.40	8.04	20.0*
FXP.830	2.4	1.8	2	24.65	291.74	5.93	20.0*
	5.8	4	3	24.60	288.40	7.59	20.0*
ANT-DB1-xxx	2.4	-3.1	0	24.65	291.74	3.37	20.0*
	5.8	4.3	3	24.60	288.40	7.86	20.0*
SA-006-1	2.4	1.8	2	24.65	291.74	5.93	20.0*
	5.8						

\*Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 62 of 242

---

## Specification

### Maximum Permissible Exposure Limits

**§15.247(i)** Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency levels in excess of the Commission's guidelines.

**FCC §1.1310** Limit =  $1\text{mW} / \text{cm}^2$  from 1.310 Table 1

**RSS-Gen §5.6** Category I and Category II equipment shall comply with the applicable requirements of RSS-102.

### Laboratory Measurement Uncertainty for Power Measurements

Measurement uncertainty	±1.33 dB
-------------------------	----------

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 63 of 242

---

## 6.1.2. Radiated Emission Testing

### Transmitter Radiated Spurious Emissions (above 1 GHz); Peak Field Strength Measurements; and Radiated Band Edge Measurements – Restricted Bands

**FCC, Part 15 Subpart C §15.247(d) 15.205; 15.209**  
**Industry Canada RSS-210 §A8.5, §2.2, §2.6**  
**Industry Canada RSS-Gen §4.7**

#### Test Procedure

The worst case highest spectral density radiated emissions above 1 GHz are measured in the anechoic chamber at a 3-meter distance on every azimuth in both horizontal and vertical polarities. The emissions are recorded and maximized as a function of azimuth by rotation through 360° with a spectrum analyzer in peak hold mode. Depending on the frequency band spanned a notch filter and waveguide filter was used to remove the fundamental frequency. The highest emissions relative to the limit are listed for each frequency spanned.

All measurements on any frequency or frequencies over 1 MHz are based on the use of measurement instrumentation employing an average detector function. All measurements above 1 GHz were performed using a minimum resolution bandwidth of 1 MHz.

#### Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

$$FS = R + AF + CORR - FO$$

where: FS = Field Strength

R = Measured Spectrum analyzer Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = CL – AG + NFL

CL = Cable Loss

AG = Amplifier Gain

FO = Distance Falloff Factor

NFL = Notch Filter Loss or Waveguide Loss

For example:

Given receiver input reading of 51.5 dB $\mu$ V; Antenna Factor of 8.5 dB; Cable Loss of 1.3 dB; Falloff Factor of 0 dB, an Amplifier Gain of 26 dB and Notch Filter Loss of 1 dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3 \text{ dB}\mu\text{V/m}$$

Conversion between dB $\mu$ V/m (or dB $\mu$ V) and  $\mu$ V/m (or  $\mu$ V) are done as:

$$\text{Level (dB}\mu\text{V/m)} = 20 * \text{Log (level (\mu\text{V/m}))}$$

$$40 \text{ dB}\mu\text{V/m} = 100 \mu\text{V/m}$$

$$48 \text{ dB}\mu\text{V/m} = 250 \mu\text{V/m}$$

---


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 64 of 242

### 6.1.2.1. Dual Band Patch PC.11 – Dual Port Module

<b>Test Freq.</b>	2412 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11b; 1 Mbs	<b>Temp (°C)</b>	25
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	38
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	PC.11 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port module		
<b>Test Notes 2</b>			



#### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
16092.184	41.4	9.0	0.3	50.7	Peak [Scan]	V	100	0	54.0	-3.3	Pass	Noise
2396.79359	57.8	3.0	11.7	49.1	Peak [Scan]	V						FUND

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 65 of 242

### Band Edge




Date: 6.NOV.2012 12:13:50

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 66 of 242

<b>Test Freq.</b>	2437 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11b; 1 Mbs	<b>Temp (°C)</b>	25
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	38
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	PC.11 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port module		
<b>Test Notes 2</b>			



**Formally measured emission peaks**

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2430.862	60.7	3.0	-11.6	52.1	Peak [Scan]	V						FUND
16058.116	41.3	9.0	0.3	50.6	Peak [Scan]	V	100	0	54.0	-3.5	Pass	Noise
4873.988	55.7	4.5	-9.7	50.5	Peak Max	V	99	360	74	-23.5	Pass	RB
4873.988	52.0	4.5	-9.7	46.8	Average Max	V	99	360	54	-7.2	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 67 of 242

<b>Test Freq.</b>	2462 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11b; 1 Mbs	<b>Temp (°C)</b>	25
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	38
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	PC.11 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port module		
<b>Test Notes 2</b>			



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2464.930	63.4	3.0	-11.5	54.9	Peak [Scan]	V						FUND
15547.094	42.8	8.3	-0.6	50.5	Peak [Scan]	H	150	0	54.0	-3.5	Pass	Noise
4924.048	58.2	4.6	-9.8	53.0	Peak Max	V	107	346	74	-21.0	Pass	RB
4924.048	55.8	4.6	-9.8	50.5	Average Max	V	107	346	54	-3.5	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 68 of 242

### Band Edge

Marker 1 [T1] RBW 1 MHz RF Att 20 dB  
Ref Lvl 48.02 dBμV VBW 1 MHz  
95.7 dBμV 2.48812926 GHz SWT 20 s Unit dBμV




Date: 6.NOV.2012 12:17:36

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 69 of 242

<b>Test Freq.</b>	2412 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11g; 6 Mbs	<b>Temp (°C)</b>	25
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	38
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	PC.11 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port module		
<b>Test Notes 2</b>			



**Formally measured emission peaks**

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2396.794	73.1	3.0	-11.7	64.4	Peak [Scan]	H						FUND
16092.184	42.1	9.0	0.3	51.3	Peak [Scan]	H	150	0	54.0	-2.7	Pass	Noise
4817.873	51.8	4.5	-9.7	46.6	Peak [Scan]	V	98	360	54	-7.4	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 70 of 242

### Band Edge



Date: 6.NOV.2012 12:09:53


Power reduction required in order to bring unit into compliance Power = 19

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 71 of 242

<b>Test Freq.</b>	2437 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11g; 6 Mbs	<b>Temp (°C)</b>	25
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	38
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	PC.11 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port module		
<b>Test Notes 2</b>			



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2430.862	78.3	3.0	-11.6	69.8	Peak [Scan]	H						FUND
16092.184	41.3	9.0	0.3	50.5	Peak [Scan]	H	100	0	54.0	-3.5	Pass	Noise
4875.992	57.0	4.5	-9.7	51.8	Peak Max	V	156	360	74	-22.2	Pass	RB
4875.992	45.2	4.5	-9.7	40.0	Average Max	V	156	360	54	-14.0	Pass	RB
7309.739	42.3	5.4	-5.7	42.0	Average Max	V	98	37	54	-12.0	Pass	RB
7309.739	59.3	5.4	-5.7	59.1	Peak Max	V	98	37	74	-14.9	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 72 of 242

<b>Test Freq.</b>	2462 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11g; 6 Mbs	<b>Temp (°C)</b>	25
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	38
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	PC.11 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port module		
<b>Test Notes 2</b>			



**Formally measured emission peaks**

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2464.930	85.5	3.0	-11.5	77.0	Peak [Scan]	H						FUND
16024.048	41.4	9.0	0.2	50.6	Peak [Scan]	H	150	0	54.0	-3.4	Pass	Noise
7385.251	49.8	5.5	-5.5	49.8	Average Max	V	190	327	54	-4.2	Pass	RB
7385.251	64.7	5.5	-5.5	64.7	Peak Max	V	190	327	74	-9.3	Pass	RB
4924.168	47.7	4.6	-9.8	42.5	Average Max	V	98	2	54	-11.5	Pass	RB
4924.168	59.5	4.6	-9.8	54.2	Peak Max	V	98	2	74	-19.8	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 73 of 242

### Band Edge

Marker 1 [T1] RBW 1 MHz RF Att 20 dB  
Ref Lvl 65.91 dB $\mu$ V VBW 1 MHz  
95.7 dB $\mu$ V 2.48350000 GHz SWT 20 s Unit dB $\mu$ V




Date: 6.NOV.2012 12:21:59

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 74 of 242

Band Edge 802.11n HT20 2412 MHz



Date: 6.NOV.2012 12:09:53


Power reduction required in order to bring unit into compliance Power = 18

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 75 of 242

Band Edge 802.11n HT20 2462 MHz




Date: 6.NOV.2012 12:25:25

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 76 of 242

Band Edge 802.11n HT40 2422 MHz



Date: 6.NOV.2012 11:57:02


Power reduction required in order to bring unit into compliance Power = 16

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 77 of 242

Band Edge 802.11n HT40 2452 MHz



Date: 6.NOV.2012 11:40:52


Power reduction required in order to bring unit into compliance Power = 17

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 78 of 242

<b>Test Freq.</b>	5745 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11a; 6.5 Mbs	<b>Temp (°C)</b>	25
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	38
<b>Power Setting</b>	18	<b>Press. (mBars)</b>	1002
<b>Antenna</b>	PC.11 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>	Power reduced to meet limit		



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5735.471	52.9	4.8	-9.5	48.1	Peak [Scan]	H						FUND
17148.297	40.5	8.6	0.5	49.6	Peak [Scan]	H	150	0	54.0	-4.4	Pass	Noise
11493.255	59.5	6.8	-2.0	64.4	Peak Max	V	133	37	74	-9.6	Pass	RB
11493.255	46.9	6.8	-2.0	51.7	Average Max	V	133	37	54	-2.3	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 79 of 242

### Band Edge

Marker 1 [T1] RBW 1 MHz RF Att 20 dB  
Ref Lvl 49.14 dB $\mu$ V VBW 1 MHz  
98.9 dB $\mu$ V 5.45272545 GHz SWT 20 s Unit dB $\mu$ V




Date: 6.NOV.2012 12:45:46

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 80 of 242

<b>Test Freq.</b>	5785 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11a; 6.5 Mbs	<b>Temp (°C)</b>	25
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	38
<b>Power Setting</b>	18	<b>Press. (mBars)</b>	1002
<b>Antenna</b>	PC.11 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>	Power reduced to meet limit		



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5770.035	50.6	4.8	-9.5	45.9	Peak [Scan]	V						FUND
16092.184	41.2	9.0	0.3	50.4	Peak [Scan]	V	100	0	54.0	-3.6	Pass	Noise
11570.761	61.6	6.8	-2.0	66.4	Peak Max	V	107	23	74	-7.6	Pass	RB
11570.761	48.4	6.8	-2.0	53.2	Average Max	V	107	23	54	-0.8	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 81 of 242

<b>Test Freq.</b>	5825 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11a; 6.5 Mbs	<b>Temp (°C)</b>	25
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	38
<b>Power Setting</b>	15	<b>Press. (mBars)</b>	1002
<b>Antenna</b>	PC.11 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>	Power reduced to meet limit		



**Formally measured emission peaks**

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5821.548	50.7	4.8	-9.3	46.2	Peak [Scan]	V						FUND
16024.048	40.6	9.0	0.2	49.8	Peak [Scan]	H	200	0	54.0	-4.2	Pass	Noise
11646.493	61.4	6.8	-2.3	65.9	Peak Max	V	103	23	74	-8.1	Pass	RB
11646.493	48.2	6.8	-2.3	52.8	Average Max	V	103	23	54	-1.2	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 82 of 242

Band Edge 802.11n HT20 5745 MHz

Marker 1 [T1] RBW 1 MHz RF Att 20 dB  
Ref Lvl 48.82 dBµV VBW 1 MHz  
98.9 dBµV 5.44192385 GHz SWT 20 s Unit dBµV




Date: 6.NOV.2012 12:49:37

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 83 of 242

Band Edge 802.11n HT40 5755 MHz



Date: 6.NOV.2012 12:52:03


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 84 of 242

### 6.1.2.2. Dual Band Patch FXP.830 – Dual Port Module

<b>Test Freq.</b>	2412 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11b; 1 Mbs	<b>Temp (°C)</b>	23
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	33
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1001
<b>Antenna</b>	FXP830 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			




Formally measured emission peaks													
Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments	
2396.797	48.1	3.0	-11.7	39.4	Peak [Scan]	V							FUND
4814.036	50.7	4.5	-9.7	45.5	Peak [Scan]	H	98	360	54.0	-8.5	Pass		RB
16024.048	41.5	9.0	0.2	50.7	Peak [Scan]	V	150	0	54	-3.3	Pass		Noise
Legend:		TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak											

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 85 of 242

### Band Edge




Date: 8.NOV.2012 13:19:07

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 86 of 242

<b>Test Freq.</b>	2437 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11b; 1 Mbs	<b>Temp (°C)</b>	23
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	33
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1001
<b>Antenna</b>	FXP830 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2432.414	48.0	3.0	-11.6	39.4	Peak [Scan]	H						FUND
4856.783	49.2	4.5	-9.7	44.0	Peak [Scan]	H	98	360	54.0	-10.0	Pass	RB
16092.184	41.1	9.0	0.3	50.4	Peak [Scan]	V	100	0	54	-3.7	Pass	Noise


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 87 of 242

<b>Test Freq.</b>	2462 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11b; 1 Mbs	<b>Temp (°C)</b>	23
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	33
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1001
<b>Antenna</b>	FXP830 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



**Formally measured emission peaks**

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2434.769	51.0	3.0	-11.6	42.4	Peak [Scan]	H						FUND
4921.107	48.4	4.6	-9.8	43.2	Peak [Scan]	H	98	98	54.0	-10.8	Pass	RB
16160.321	42.1	9.0	0.2	51.2	Peak [Scan]	V	150	0	54	-2.8	Pass	Noise


Legend:	TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
	RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 88 of 242

### Band Edge



Date: 8.NOV.2012 13:38:15


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 89 of 242

<b>Test Freq.</b>	2412 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11g; 6 Mbs	<b>Temp (°C)</b>	23
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	33
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1001
<b>Antenna</b>	FXP830 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2395.708	47.8	3.0	-11.7	39.1	Peak [Scan]	H						FUND
4818.459	50.6	4.5	-9.7	45.4	Peak [Scan]	H	98	98	54.0	-8.6	Pass	RB
16160.321	41.5	9.0	0.2	50.7	Peak [Scan]	H	100	0	54	-3.4	Pass	Noise
7250.030	62.9	5.4	-5.8	62.5	Peak.	H	106	106	74	-11.5	Pass	RB
7250.030	46.3	5.4	-5.8	45.9	Average.	H	106	106	54	-8.1	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 90 of 242

### Band Edge



Date: 8.NOV.2012 13:22:43


Power reduction required in order to bring unit into compliance Power = 17

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 91 of 242

<b>Test Freq.</b>	2437 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11g; 6 Mbs	<b>Temp (°C)</b>	23
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	33
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1001
<b>Antenna</b>	FXP830 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



**Formally measured emission peaks**

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2431.954	49.3	3.0	-11.6	40.7	Peak [Scan]	H						FUND
4860.764	52.0	4.5	-9.7	46.8	Peak [Scan]	H	98	98	54.0	-7.2	Pass	RB
16092.184	41.3	9.0	0.3	50.5	Peak [Scan]	H	100	0	54	-3.5	Pass	Noise
7307.816	69.3	5.4	-5.7	69.0	Peak Max	H	140	140	74	-5.0	Pass	RB
7307.816	52.7	5.4	-5.7	52.5	Average Max	H	140	140	54	-1.5	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 92 of 242

<b>Test Freq</b>	2462 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11g; 6 Mbs	<b>Temp (°C)</b>	23
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	33
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1001
<b>Antenna</b>	FXP830 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2465.372	51.9	3.0	-11.5	43.4	Peak [Scan]	H						FUND
4916.789	51.7	4.6	-9.8	46.5	Peak [Scan]	H	98	98	54.0	-7.5	Pass	RB
15955.912	40.9	9.0	0.0	49.9	Peak [Scan]	V	150	0	54	-4.2	Pass	Noise
7383.006	62.7	5.5	-5.5	62.7	Peak Max	H	137	137	74	-11.3	Pass	RB
7383.006	45.8	5.5	-5.5	45.7	Average Max	H	137	137	54	-8.3	Pass	RB


**Legend:** TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 93 of 242

### Band Edge



Date: 8.NOV.2012 13:34:37


Power reduction required in order to bring unit into compliance Power = 19

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 94 of 242

### Band Edge 802.11n HT20 2412 MHz



Date: 8.NOV.2012 13:25:09


Power reduction required in order to bring unit into compliance Power = 16

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 95 of 242

Band Edge 802.11n HT20 2462 MHz



Date: 8.NOV.2012 13:32:03


Power reduction required in order to bring unit into compliance Power = 18

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 96 of 242

Band Edge 802.11n HT40 2422 MHz



Date: 8.NOV.2012 12:49:29

Power reduction required in order to bring unit into compliance Power = 13


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 97 of 242

Band Edge 802.11n HT40 2462 MHz



Date: 8.NOV.2012 12:26:03


Power reduction required in order to bring unit into compliance Power = 16

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 98 of 242

<b>Test Freq.</b>	5745 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11a; 6.5 Mbs	<b>Temp (°C)</b>	24
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	32
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1001
<b>Antenna</b>	FXP830 x2	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5735.471	55.4	4.8	-9.5	50.6	Peak [Scan]	H						FUND
17386.774	39.3	8.7	1.4	49.4	Peak [Scan]	H	150	0	54	-4.6	Pass	NRB
11496.553	53.4	6.8	-2.0	58.2	Peak Max	H	98	98	74	-15.8	Pass	RB
11496.553	40.4	6.8	-2.0	45.3	Average Max	H	98	98	54	-8.8	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 99 of 242

**Band Edge**




Date: 8.NOV.2012 12:13:25

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 100 of 242

Band Edge 802.11n HT20 5745 MHz




Date: 8.NOV.2012 12:12:19

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 101 of 242

Band Edge 802.11n HT40 5755 MHz



Date: 8.NOV.2012 12:15:15


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 102 of 242

### 6.1.2.3. Dual Band Omni ANT-DB1-xxx – Dual Port Module

<b>Test Freq.</b>	2412 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11b; 1 Mbs	<b>Temp (°C)</b>	24
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	35
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1008
<b>Antenna</b>	5 dBi Monopole	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Radio		
<b>Test Notes 2</b>			




Formally measured emission peaks													
Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments	
16024.048	42.3	9.0	0.2	51.6	Peak [Scan]	V	150	0	54.0	-2.5	Pass	Noise	
2396.79359	58.2	3.0	11.7	49.5	Peak [Scan]	H						FUND	
Legend:		TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission											
		RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak											

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



### Band Edge




Date: 19.NOV.2012 19:53:30

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 104 of 242

<b>Test Freq.</b>	2437 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11b; 1 Mbs	<b>Temp (°C)</b>	24
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	35
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1008
<b>Antenna</b>	5 dBi Monopole	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Radio		
<b>Test Notes 2</b>			



**Formally measured emission peaks**

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
16058.116	42.2	9.0	0.3	51.5	Peak [Scan]	V	150	0	54.0	-2.5	Pass	Noise
2430.86172	57.7	3.0	-11.6	49.2	Peak [Scan]	V						FUND
4849.094	51.0	4.5	-9.7	45.8	Peak [Scan]	V	98	360	54	-8.2	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 105 of 242

<b>Test Freq.</b>	2462 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11b; 1 Mbs	<b>Temp (°C)</b>	24
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	35
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1008
<b>Antenna</b>	5 dBi Monopole	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Radio		
<b>Test Notes 2</b>			



**Formally measured emission peaks**


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
16058.116	42.0	9.0	0.3	51.3	Peak [Scan]	H	150	0	54.0	-2.7	Pass	Noise
2464.92986	58.7	3.0	-11.5	50.2	Peak [Scan]	V						FUND
4917.520	53.0	4.6	-9.8	47.8	Peak [Scan]	V	98	360	54	-6.2	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



### Band Edge




Date: 19.NOV.2012 18:53:57

Power reduction required in order to bring unit into compliance Power = 19



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 107 of 242

<b>Test Freq.</b>	2412 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11g; 6 Mbs	<b>Temp (°C)</b>	24
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	35
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1008
<b>Antenna</b>	5 dBi Monopole	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Radio Card		
<b>Test Notes 2</b>			



**Formally measured emission peaks**


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
16603.206	42.3	8.8	0.6	51.6	Peak [Scan]	H	100	0	54.0	-2.4	Pass	Noise
2396.79359	59.9	3.0	-11.7	51.2	Peak [Scan]	H						FUND

Legend:	TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
	RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



### Band Edge




Date: 19.NOV.2012 19:47:34

Power reduction required in order to bring unit into compliance Power = 15



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 109 of 242

<b>Test Freq.</b>	2437 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11g; 6 Mbs	<b>Temp (°C)</b>	24
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	35
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1008
<b>Antenna</b>	5 dBi Monopole	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Radio Card		
<b>Test Notes 2</b>			



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
15989.980	42.3	9.0	0.1	51.5	Peak [Scan]	V	100	0	54.0	-2.6	Pass	Noise
2430.86172	58.2	3.0	-11.6	49.6	Peak [Scan]	V						FUND


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 110 of 242

<b>Test Freq.</b>	2462 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11g; 6 Mbs	<b>Temp (°C)</b>	24
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	35
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1008
<b>Antenna</b>	5 dBi Monopole	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Radio Card		
<b>Test Notes 2</b>			



**Formally measured emission peaks**

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
15955.912	42.4	9.0	0.0	51.4	Peak [Scan]	V	150	0	54.0	-2.7	Pass	NOISE
2464.92986	58.5	3.0	-11.5	50.0	Peak [Scan]	V						FUND
4918.228	51.2	4.6	-9.8	46.0	Peak [Scan]	V	98	360	54	-8.0	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 111 of 242

### Band Edge



Date: 19.NOV.2012 18:41:52


Power reduction required in order to bring unit into compliance Power = 14

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 112 of 242

Band Edge 802.11n HT20 2412 MHz



Date: 19.NOV.2012 19:40:38

Power reduction required in order to bring unit into compliance Power = 14


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 113 of 242

Band Edge 802.11n HT20 2462 MHz



Date: 19.NOV.2012 19:04:21


Power reduction required in order to bring unit into compliance Power = 13

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 114 of 242

Band Edge 802.11n HT40 2422 MHz



Date: 19.NOV.2012 19:32:40


Power reduction required in order to bring unit into compliance Power = 10

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 115 of 242

Band Edge 802.11n HT40 2452 MHz



Date: 19.NOV.2012 19:15:12


Power reduction required in order to bring unit into compliance Power = 9

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 116 of 242

<b>Test Freq.</b>	5745 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11a; 6.5 Mbs	<b>Temp (°C)</b>	24
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	39
<b>Power Setting</b>	13 Power Reduced	<b>Press. (mBars)</b>	1003
<b>Antenna</b>	Monopole 5 dBi	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Radio Card		
<b>Test Notes 2</b>			



### Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5735.471	50.4	4.8	-9.5	45.6	Peak [Scan]	V						FUND
11496.057	48.5	6.8	-2.0	53.4	Average	V	98	30	54.0	-0.7	Pass	RB
11496.057	61.0	6.8	-2.0	65.8	Peak.	V	98	30	74	-8.2	Pass	RB
17250.501	38.9	8.6	1.0	48.5	Peak [Scan]	H	100	0	54	-5.5	Pass	Noise

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



### Band Edge




Date: 20.NOV.2012 18:50:29

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 118 of 242

<b>Test Freq.</b>	5785 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11a; 6.5 Mbs	<b>Temp (°C)</b>	24
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	39
<b>Power Setting</b>	11 Pwr reduced	<b>Press. (mBars)</b>	1003
<b>Antenna</b>	Monopole 5 dBi	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Radio Card		
<b>Test Notes 2</b>			



**Formally measured emission peaks**


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5769.539	56.8	4.8	-9.5	52.1	Peak [Scan]	V						FUND
16024.048	41.0	9.0	0.2	50.3	Peak [Scan]	H	100	0	54.0	-3.7	Pass	Noise
3861.723	55.9	3.8	-10.8	49.0	Peak [Scan]	V	100	0	54	-5.0	Pass	RB
11570.260	61.9	6.8	-2.0	66.7	Peak Max	V	98	18	74	-7.3	Pass	RB
11570.260	48.5	6.8	-2.0	53.3	Average Max	V	98	18	54	-0.7	Pass	RB
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 119 of 242

<b>Test Freq.</b>	5825 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11a; 6.5 Mbs	<b>Temp (°C)</b>	24
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	39
<b>Power Setting</b>	9 Pwr reduced	<b>Press. (mBars)</b>	1003
<b>Antenna</b>	Monopole 5 dBi	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Radio Card		
<b>Test Notes 2</b>			



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5701.403	57.7	4.7	-9.6	52.9	Peak [Scan]	V						FUND
11398.317	61.0	6.8	-2.3	65.6	Peak Max	H	106	50	74.0	-8.5	Pass	RB
11398.317	48.9	6.8	-2.3	53.5	Average Max	H	106	50	54	-0.5	Pass	RB
16126.253	40.9	9.0	0.2	50.0	Peak [Scan]	H	100	0	54	-4.0	Pass	Noise


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 120 of 242

Band Edge 802.11n HT20 5745 MHz



Date: 20.NOV.2012 19:04:17


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 121 of 242

Band Edge 802.11n HT40 5755 MHz



Date: 20.NOV.2012 19:09:26


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 122 of 242

#### 6.1.2.4. Single Band Omni SA-006-1 – Dual Port Module

<b>Test Freq.</b>	2412 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11b; 1 Mbs	<b>Temp (°C)</b>	21.5
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	35
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	SA-006 Monopole	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



#### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2396.794	62.4	3.0	-11.7	53.7	Peak [Scan]	H						FUND
16466.934	41.4	8.8	0.3	50.5	Peak [Scan]	V	150	0	54.0	-3.5	Pass	Noise

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 123 of 242

**Band Edge**

	<b>Marker 1 [T1]</b>	RBW	1 MHz	RF Att	20 dB
Ref Lvl	52.38 dB $\mu$ V	VBW	1 MHz		
95.1 dB $\mu$ V	2.38599198 GHz	SWT	20 s	Unit	dB $\mu$ V




Date: 27.NOV.2012 15:59:15

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 124 of 242

<b>Test Freq.</b>	2437 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11b; 1 Mbs	<b>Temp (°C)</b>	21.5
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	35
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	SA-006 Monopole	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



**Formally measured emission peaks**

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2430.862	60.7	3.0	-11.6	52.1	Peak [Scan]	V						FUND
4848.504	52.0	4.5	-9.7	46.8	Peak [Scan]	V	98	360	54.0	-7.2	Pass	RB
16024.048	42.8	9.0	0.2	52.1	Peak [Scan]	H	100	0	54	-1.9	Pass	Noise


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 125 of 242

<b>Test Freq.</b>	2462 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11b; 1 Mbs	<b>Temp (°C)</b>	21.5
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	35
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	SA-006 Monopole	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



**Formally measured emission peaks**

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2464.930	58.9	3.0	-11.5	50.4	Peak [Scan]	V						FUND
15955.912	42.1	9.0	0.0	51.1	Peak [Scan]	V	150	0	54.0	-2.9	Pass	Noise
4924.048	57.1	4.6	-9.8	51.9	Peak Max	V	152	210	74	-22.1	Pass	RB
4924.048	53.5	4.6	-9.8	48.3	Average Max	V	152	210	54	-5.7	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 126 of 242

### Band Edge




Date: 27.NOV.2012 16:35:10

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 127 of 242

<b>Test Freq.</b>	2412 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11g; 6 Mbs	<b>Temp (°C)</b>	21.5
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	35
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	SA-006 2.4 Monopole	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



### Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2396.794	60.3	3.0	-11.7	51.6	Peak [Scan]	V						FUND
16535.07	42.0	8.8	0.4	51.2	Peak [Scan]	H	200	0	54.0	-2.8	Pass	Noise
4819.738	51.8	4.5	-9.7	46.6	Peak [Scan]	V	98	360	54	-7.4	Pass	RB
7233.908	60.0	5.4	-5.8	59.6	Peak Max	V	143	76	74	-14.4	Pass	RB
7233.908	41.3	5.4	-5.8	40.9	Average Max	V	143	76	54	-13.2	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



### Band Edge



Date: 27.NOV.2012 15:52:10

Power reduction required in order to bring unit into compliance Power = 15


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 129 of 242

<b>Test Freq.</b>	2437 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11g; 6 Mbs	<b>Temp (°C)</b>	21.5
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	35
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	SA-006 2.4 Monopole	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2430.862	61.0	3.0	-11.6	52.4	Peak [Scan]	H						FUND
16024.048	41.7	9.0	0.2	50.9	Peak [Scan]	H	100	0	54.0	-3.1	Pass	Noise
4881.681	52.3	4.5	-9.7	47.1	Peak [Scan]	V	98	360	54	-6.9	Pass	RB
7312.305	64.3	5.4	-5.7	64.1	Peak Max	V	160	331	74	-9.9	Pass	RB
7312.305	47.6	5.4	-5.7	47.3	Average Max	V	160	331	54	-6.7	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 130 of 242

<b>Test Freq.</b>	2462 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	802.11g; 6 Mbs	<b>Temp (°C)</b>	21.5
<b>Freq. Range</b>	1000 MHz - 18000 MHz	<b>Rel. Hum.(%)</b>	35
<b>Power Setting</b>	20	<b>Press. (mBars)</b>	1004
<b>Antenna</b>	SA-006 2.4 Monopole	<b>Duty Cycle (%)</b>	100
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



### Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
16058.116	42.0	9.0	0.3	51.2	Peak [Scan]	V	150	0	54.0	-2.8	Pass	Noise
2464.92986	58.8	3.0	-11.5	50.3	Peak [Scan]	V						FUND
4927.214	56.7	4.6	-9.8	51.5	Peak Max	V	137	191	74	-22.5	Pass	RB
4927.214	45.0	4.6	-9.8	39.8	Average Max	V	137	191	54	-14.3	Pass	RB
7383.487	46.6	5.5	-5.5	46.6	Average Max	V	166	245	54	-7.4	Pass	RB
7383.487	63.0	5.5	-5.5	63.0	Peak Max	V	166	245	74	-11.1	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission  
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Band Edge




Date: 27.NOV.2012 16:30:16

Power reduction required in order to bring unit into compliance Power = 14



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 132 of 242

Band Edge 802.11n HT20 2412 MHz



Date: 27.NOV.2012 16:03:42


Power reduction required in order to bring unit into compliance Power = 14

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 133 of 242

Band Edge 802.11n HT20 2462 MHz



Date: 27.NOV.2012 16:24:07


Power reduction required in order to bring unit into compliance Power = 12

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 134 of 242

Band Edge 802.11n HT40 2422 MHz



Date: 27.NOV.2012 16:09:30


Power reduction required in order to bring unit into compliance Power = 10

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 135 of 242

Band Edge 802.11n HT40 2452 MHz



Date: 27.NOV.2012 16:20:53

Power reduction required in order to bring unit into compliance Power = 9

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 136 of 242

## Specification Limits

**FCC §15.247(d) and RSS-210 §A8.5** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### **FCC §15.247(d)**

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section §15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(a)).

**IC RSS-210 §A8.5** If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required. In addition, radiated emissions which fall in the restricted bands of Table 1 must also comply with the radiated emission limits specified in Tables 2 and 3.

### **IC RSS-Gen §4.7**

The search for unwanted emissions shall be from the lowest frequency internally generated or used in the device (local oscillator, intermediate or carrier frequency), or from 30 MHz, whichever is the lowest frequency, to the 5<sup>th</sup> harmonic of the highest frequency generated without exceeding 40 GHz.

**FCC §15.205 (a)** Except as shown in paragraph (d) of 15.205 (a), only spurious emissions are permitted in any of the frequency bands listed.

**FCC §15.205 (a)** Except as shown in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

**FCC §15.209 (a)** Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table.





**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 137 of 242

**§15.209 (a) Limit Matrix**

Frequency(MHz)	Field Strength ( $\mu\text{V/m}$ )	Field Strength ( $\text{dB}\mu\text{V/m}$ )	Measurement Distance (meters)
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

**Laboratory Measurement Uncertainty for Radiated Emissions**

Measurement uncertainty	+5.6/ -4.5 dB
-------------------------	---------------

**Traceability**

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of Radiated Emissions'	0088, 0158, 0134, 0304, 0311, 0315, 0310, 0312

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 138 of 242

---

#### 6.1.2.5. Digital Emissions (0.03-1 GHz)

**FCC, Part 15 Subpart C §15.205/ §15.209**  
**Industry Canada RSS-210 §2.2**

##### Test Procedure

Testing 30M-1 GHz was performed in a 3-meter anechoic chamber using a CISPR compliant receiver. Preliminary radiated emissions were measured on every azimuth and with the receiving antenna in both horizontal and vertical polarizations. To further maximize emissions the receive antenna was varied between 1 and 4 meters. The emissions are recorded with receiver in peak hold mode. Emissions closest to the limits are measured in the quasi-peak mode with the tuned receiver using a bandwidth of 120 kHz. Only the highest emissions relative to the limit are listed. The anechoic chamber test set-up is identified in Section 6 Test Set-Up Photographs.

The EUT had two methods of powering on ac/dc converter and Power over Ethernet (POE). Both modes were tested for emissions below 1GHz.

##### Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. In this test facility, the Antenna Factor, Cable Loss, and Amplifier Gains are loaded into the Rohde & Schwarz Receiver and the corrected field strength can be read directly on the receiver.

$$FS = R + AF + CORR$$

where:

FS = Field Strength  
R = Measured Receiver Input Amplitude  
AF = Antenna Factor  
CORR = Correction Factor = CL – AG + NFL  
CL = Cable Loss  
AG = Amplifier Gain

For example:

Given a Receiver input reading of 51.5dB $\mu$ V; Antenna Factor of 8.5dB; Cable Loss of 1.3dB; Falloff Factor of 0dB, an Amplifier Gain of 26dB and Notch Filter Loss of 1dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3\text{dB}\mu\text{V/m}$$

Conversion between dB $\mu$ V/m (or dB $\mu$ V) and  $\mu$ V/m (or  $\mu$ V) are done as:

$$\text{Level (dB}\mu\text{V/m)} = 20 * \text{Log (level (\mu\text{V/m}))}$$

$$40 \text{ dB}\mu\text{V/m} = 100\mu\text{V/m}$$
$$48 \text{ dB}\mu\text{V/m} = 250\mu\text{V/m}$$


---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 139 of 242

<b>Test Freq.</b>	2437 MHz	<b>Engineer</b>	JMH
<b>Variant</b>	Digital Emissions	<b>Temp (°C)</b>	26
<b>Freq. Range</b>	30 MHz - 1000 MHz	<b>Rel. Hum.(%)</b>	38
<b>Power Setting</b>	NA	<b>Press. (mBars)</b>	1000
<b>Antenna</b>	PC.11		
<b>Test Notes 1</b>	Dual Port Module		
<b>Test Notes 2</b>			



### Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
89.431	55.2	4.0	-24.0	35.2	Peak [Scan]	H	216	0	43.5	-8.3	Pass	
411.025	45.0	5.5	-14.4	36.1	Peak [Scan]	H	98	360	46	-9.9	Pass	
30.939	35.6	3.5	-10.6	28.6	Peak [Scan]	V	98	360	40	-11.4	Pass	
156.378	45.3	4.4	-18.9	30.8	Peak [Scan]	H	98	360	43.5	-12.7	Pass	
199.149	42.8	4.6	-18.4	29.0	Peak [Scan]	V	98	360	43.5	-14.5	Pass	
89.431	46.7	4.0	-24.0	26.7	Quasi Max	H	216	0	43.5	-16.9	Pass	
961.430	36.3	7.3	-7.1	36.5	Peak [Scan]	V	98	360	54	-17.5	Pass	

Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency  
 NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 140 of 242

## Specification

### Limits

**§15.205 (a)** Except as shown in paragraph (d) of 15.205 (a), only spurious emissions are permitted in any of the frequency bands listed.

**§15.205 (a)** Except as shown in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

**§15.209 (a)** Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table.

### §15.209 (a) and RSS-Gen §2.2 Limit Matrix

Frequency(MHz)	Field Strength ( $\mu\text{V}/\text{m}$ )	Field Strength ( $\text{dB}\mu\text{V}/\text{m}$ )	Measurement Distance (meters)
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

### Laboratory Measurement Uncertainty for Radiated Emissions

Measurement uncertainty	+5.6/ -4.5 dB
-------------------------	---------------

### Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of Radiated Emissions'	0088, 0158, 0134, 0304, 0311, 0315, 0310, 0312

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


### 6.1.3. AC Wireline Conducted Emissions (150 kHz – 30 MHz)

**FCC, Part 15 Subpart C §15.207**  
**Industry Canada RSS-Gen §7.2.2**

#### **Test Procedure**

The EUT is configured in accordance with ANSI C63.4. The conducted emissions are measured in a shielded room with a spectrum analyzer in peak hold in the first instance. Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation. The highest emissions relative to the limit are listed.

#### **Test Measurement Set up**



Measurement set up for AC Wireline Conducted Emissions Test

#### **Measurement Results for AC Wireline Conducted Emissions (150 kHz – 30 MHz)**

Ambient conditions.

Temperature: 17 to 23 °C      Relative humidity: 31 to 57 %      Pressure: 999 to 1012 mbar

**Not required - EUT is power by DC only.**



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 142 of 242

## Specification

### Limit

**§15.207 (a)** Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu\Omega$  line impedance stabilization network (LISN), see §15.207 (a) matrix below. Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

### RSS-Gen §7.2.2

The radio frequency voltage that is conducted back into the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in the table below. The tighter limit applies at the frequency range boundaries.

### §15.207 (a) and RSS-Gen §7.2.2 Limit Matrix

The lower limit applies at the boundary between frequency ranges

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency

### Laboratory Measurement Uncertainty for Conducted Emissions

Measurement uncertainty	$\pm 2.64$ dB
-------------------------	---------------

### Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-EMC-01 'Measurement of Conducted Emissions'	0158, 0184, 0287, 0190, 0293, 0307

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## 7. PHOTOGRAPHS

### 7.1. Conducted Test Setup



---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

## 7.2. Test Setup - Digital Emissions below 1 GHz




---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



### 7.3. Radiated Emissions Test Setup >1 GHz



---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 146 of 242

## 8. TEST EQUIPMENT

Asset #	Instrument	Manufacturer	Part #	Serial #	Calibration Due Date
0070	Power Meter	Hewlett Packard	437B	3125U11552	28 <sup>th</sup> Nov 13
0117	Power Sensor	Hewlett Packard	8487D	3318A00371	15 <sup>th</sup> Nov 13
0223	Power Meter	Hewlett Packard	EPM-442A	US37480256	15 <sup>th</sup> Nov 13
0374	Power Sensor	Hewlett Packard	8485A	3318A19694	29 <sup>th</sup> Nov 13
0376	Power Sensor	Agilent	U2000A	MY51440005	8 <sup>th</sup> Dec 13
0158	Barometer /Thermometer	Control Co.	4196	E2846	8 <sup>th</sup> Dec 13
0193	EMI Receiver	Rhode & Schwartz	ESI 7	838496/007	2 <sup>nd</sup> Dec 13
0287	EMI Receiver	Rhode & Schwartz	ESIB40	100201	16 <sup>th</sup> Nov 13
0338	30 - 3000 MHz Antenna	Sunol	JB3	A052907	8 <sup>th</sup> Nov 13
0335	1-18 GHz Horn Antenna	EMCO	3117	00066580	7 <sup>th</sup> Nov 13
0252	SMA Cable	Megaphase	Sucoflex 104	None	N/A
0293	BNC Cable	Megaphase	1689 1GVT4	15F50B001	N/A
0307	BNC Cable	Megaphase	1689 1GVT4	15F50B002	N/A
0310	2m SMA Cable	Micro-Coax	UFA210A-0-0787-3G03G0	209089-001	N/A
0312	3m SMA Cable	Micro-Coax	UFA210A-1-1181-3G0300	209092-001	N/A
0314	30dB N-Type Attenuator	ARRA	N9444-30	1623	N/A
	EMC Test Software	EMISoft	Vasona	5.0051	N/A
	RF Conducted Test Software	National Instruments	Labview	Version 8.2	N/A
	RF Conducted Test Software	MiCOM Labs ATS		Version 1.5	N/A

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 147 of 242

---

## **APPENDIX**

### **A. SUPPORTING INFORMATION**

#### **A.1. CONDUCTED TEST PLOTS**

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**A.1.1. 6 dB & 99% Bandwidth**

Dual Port Module Graphs



6 dB 99%

Variant: 802.11b, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2406.830 MHz : -2.563 dBm M2 : 2413.483 MHz : 5.844 dBm Delta1 : 10.261 MHz : 3.103 dB T1 : 2404.826 MHz : -8.490 dBm T2 : 2419.094 MHz : -8.193 dBm OBW : 14.349 MHz	Measured 6 dB Bandwidth: 10.261 MHz Limit: $\geq 0.5$ MHz Margin: -9.76 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 149 of 242



6 dB 99%

Variant: 802.11b, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2431.910 MHz : -0.540 dBm M2 : 2438.483 MHz : 6.056 dBm Delta1 : 10.180 MHz : 1.552 dB T1 : 2429.826 MHz : -8.016 dBm T2 : 2444.174 MHz : -8.187 dBm OBW : 14.429 MHz	Measured 6 dB Bandwidth: 10.180 MHz Limit: $\geq 0.5$ MHz Margin: -9.68 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 150 of 242



**6 dB 99%**

Variant: 802.11b, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2456.830 MHz : -2.411 dBm M2 : 2463.483 MHz : 6.247 dBm Delta1 : 10.261 MHz : 3.537 dB T1 : 2454.745 MHz : -8.266 dBm T2 : 2469.255 MHz : -8.280 dBm OBW : 14.589 MHz	Measured 6 dB Bandwidth: 10.261 MHz Limit: $\geq 0.5$ MHz Margin: -9.76 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 151 of 242



6 dB 99%

Variant: 802.11g, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2403.784 MHz : -1.911 dBm M2 : 2417.010 MHz : 5.350 dBm Delta1 : 16.353 MHz : 2.284 dB T1 : 2403.623 MHz : -7.192 dBm T2 : 2420.297 MHz : -6.932 dBm OBW : 16.754 MHz	Measured 6 dB Bandwidth: 16.353 MHz Limit: $\geq 0.5$ MHz Margin: -15.85 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 152 of 242



**6 dB 99%**

Variant: 802.11g, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2428.784 MHz : -0.877 dBm M2 : 2442.010 MHz : 6.432 dBm Delta1 : 16.353 MHz : 1.527 dB T1 : 2428.543 MHz : -9.153 dBm T2 : 2445.778 MHz : -11.788 dBm OBW : 17.315 MHz	Measured 6 dB Bandwidth: 16.353 MHz Limit: $\geq 0.5$ MHz Margin: -15.85 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 153 of 242



6 dB 99%

Variant: 802.11g, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2453.784 MHz : -1.431 dBm M2 : 2467.010 MHz : 5.976 dBm Delta1 : 16.353 MHz : 1.771 dB T1 : 2453.383 MHz : -11.929 dBm T2 : 2470.858 MHz : -12.181 dBm OBW : 17.555 MHz	Measured 6 dB Bandwidth: 16.353 MHz Limit: $\geq 0.5$ MHz Margin: -15.85 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 154 of 242



6 dB 99%

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2403.543 MHz : -0.505 dBm M2 : 2417.010 MHz : 6.273 dBm Delta1 : 16.994 MHz : 1.454 dB T1 : 2403.062 MHz : -2.980 dBm T2 : 2421.018 MHz : -8.703 dBm OBW : 18.036 MHz	Measured 6 dB Bandwidth: 16.994 MHz Limit: $\geq 0.5$ MHz Margin: -16.49 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 155 of 242



**6 dB 99%**

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2428.142 MHz : -1.955 dBm M2 : 2442.010 MHz : 6.342 dBm Delta1 : 17.395 MHz : 3.002 dB T1 : 2427.902 MHz : -8.854 dBm T2 : 2446.098 MHz : -8.689 dBm OBW : 18.277 MHz	Measured 6 dB Bandwidth: 17.395 MHz Limit: $\geq 0.5$ MHz Margin: -16.90 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 156 of 242



**6 dB 99%**

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2453.383 MHz : -0.875 dBm M2 : 2467.010 MHz : 5.995 dBm Delta1 : 17.395 MHz : 0.938 dB T1 : 2452.822 MHz : -10.780 dBm T2 : 2471.259 MHz : -11.624 dBm OBW : 18.517 MHz	Measured 6 dB Bandwidth: 17.395 MHz Limit: $\geq 0.5$ MHz Margin: -16.90 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 157 of 242



6 dB 99%

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2403.804 MHz : -4.217 dBm M2 : 2433.303 MHz : 2.684 dBm Delta1 : 36.232 MHz : 1.826 dB T1 : 2403.643 MHz : -6.979 dBm T2 : 2440.196 MHz : -5.559 dBm OBW : 36.713 MHz	Measured 6 dB Bandwidth: 36.232 MHz Limit: $\geq 0.5$ MHz Margin: -35.73 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 158 of 242



6 dB 99%

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2418.804 MHz : -3.521 dBm M2 : 2448.303 MHz : 2.889 dBm Delta1 : 36.232 MHz : 1.295 dB T1 : 2418.643 MHz : -6.702 dBm T2 : 2455.196 MHz : -5.297 dBm OBW : 36.713 MHz	Measured 6 dB Bandwidth: 36.232 MHz Limit: $\geq 0.5$ MHz Margin: -35.73 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 159 of 242



**6 dB 99%**

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2433.643 MHz : -6.653 dBm M2 : 2463.303 MHz : 2.838 dBm Delta1 : 36.393 MHz : 4.708 dB T1 : 2433.483 MHz : -12.179 dBm T2 : 2470.838 MHz : -15.626 dBm OBW : 37.515 MHz	Measured 6 dB Bandwidth: 36.393 MHz Limit: $\geq 0.5$ MHz Margin: -35.89 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 160 of 242



6 dB 99%

Variant: 802.11a, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5737.184 MHz : 0.691 dBm M2 : 5739.990 MHz : 7.319 dBm Delta1 : 15.952 MHz : 0.673 dB T1 : 5730.611 MHz : -11.650 dBm T2 : 5759.148 MHz : -13.422 dBm OBW : 28.617 MHz	Measured 6 dB Bandwidth: 15.952 MHz Limit: $\geq 0.5$ MHz Margin: -15.45 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 161 of 242



6 dB 99%

Variant: 802.11a, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5777.184 MHz : 0.737 dBm M2 : 5779.990 MHz : 7.544 dBm Delta1 : 15.711 MHz : 0.834 dB T1 : 5770.210 MHz : -11.266 dBm T2 : 5799.709 MHz : -11.573 dBm OBW : 29.579 MHz	Measured 6 dB Bandwidth: 15.711 MHz Limit: $\geq 0.5$ MHz Margin: -15.21 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 162 of 242



6 dB 99%

Variant: 802.11a, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5817.184 MHz : 0.243 dBm M2 : 5819.990 MHz : 7.109 dBm Delta1 : 15.551 MHz : 1.204 dB T1 : 5810.210 MHz : -11.662 dBm T2 : 5839.389 MHz : -13.070 dBm OBW : 29.259 MHz	Measured 6 dB Bandwidth: 15.551 MHz Limit: $\geq 0.5$ MHz Margin: -15.05 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 163 of 242



6 dB 99%

Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5736.543 MHz : 1.524 dBm M2 : 5739.990 MHz : 7.552 dBm Delta1 : 16.834 MHz : 0.240 dB T1 : 5729.970 MHz : -9.521 dBm T2 : 5760.110 MHz : -13.645 dBm OBW : 30.220 MHz	Measured 6 dB Bandwidth: 16.834 MHz Limit: $\geq 0.5$ MHz Margin: -16.33 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 164 of 242



6 dB 99%

Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5776.543 MHz : 0.998 dBm M2 : 5779.990 MHz : 7.518 dBm Delta1 : 16.834 MHz : 0.580 dB T1 : 5769.810 MHz : -12.815 dBm T2 : 5800.030 MHz : -10.428 dBm OBW : 30.301 MHz	Measured 6 dB Bandwidth: 16.834 MHz Limit: $\geq 0.5$ MHz Margin: -16.33 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 165 of 242



6 dB 99%

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5816.543 MHz : 1.356 dBm M2 : 5819.990 MHz : 7.573 dBm Delta1 : 16.834 MHz : 0.218 dB T1 : 5809.409 MHz : -11.689 dBm T2 : 5840.190 MHz : -13.448 dBm OBW : 30.862 MHz	Measured 6 dB Bandwidth: 16.834 MHz Limit: $\geq 0.5$ MHz Margin: -16.33 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 166 of 242



6 dB 99%

Variant: 802.11n HT-40, Channel: 5755.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5737.285 MHz : -5.777 dBm M2 : 5758.768 MHz : 0.526 dBm Delta1 : 35.271 MHz : 3.226 dB T1 : 5735.361 MHz : -20.275 dBm T2 : 5773.357 MHz : -16.216 dBm OBW : 38.156 MHz	Measured 6 dB Bandwidth: 35.271 MHz Limit: $\geq 0.5$ MHz Margin: -34.77 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 167 of 242



6 dB 99%

Variant: 802.11n HT-40, Channel: 5795.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5777.124 MHz : -4.461 dBm M2 : 5798.768 MHz : 1.878 dBm Delta1 : 35.431 MHz : 2.973 dB T1 : 5769.749 MHz : -19.972 dBm T2 : 5818.006 MHz : -18.327 dBm OBW : 48.417 MHz	Measured 6 dB Bandwidth: 35.431 MHz Limit: $\geq 0.5$ MHz Margin: -34.93 MHz

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 168 of 242


### A.1.2. Peak Output Power

Dual Port Module:



#### peak output power

Variant: 802.11b, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2403.623 MHz : -9.637 dBm M2 : 2413.002 MHz : 10.562 dBm Delta1 : 16.754 MHz : 0.655 dB	Channel Power: 19.15 dBm Limit: 30.00 dBm Margin: -10.85 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 169 of 242



**peak output power**

Variant: 802.11b, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2428.543 MHz : -9.580 dBm M2 : 2438.082 MHz : 10.737 dBm Delta1 : 16.914 MHz : 0.504 dB	Channel Power: 19.31 dBm Limit: 30.00 dBm Margin: -10.69 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 170 of 242



**peak output power**

Variant: 802.11b, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2453.543 MHz : -9.151 dBm M2 : 2463.082 MHz : 10.884 dBm Delta1 : 16.994 MHz : 0.104 dB	Channel Power: 19.47 dBm Limit: 30.00 dBm Margin: -10.53 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 171 of 242



**peak output power**

Variant: 802.11g, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.176 MHz : -7.107 dBm M2 : 2406.429 MHz : 12.972 dBm Delta1 : 23.006 MHz : 0.329 dB	Channel Power: 23.44 dBm Limit: 30.00 dBm Margin: -6.56 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 172 of 242



**peak output power**

Variant: 802.11g, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.936 MHz : -6.690 dBm M2 : 2442.491 MHz : 13.312 dBm Delta1 : 24.048 MHz : 0.933 dB	Channel Power: 23.98 dBm Limit: 30.00 dBm Margin: -6.02 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 173 of 242



**peak output power**

Variant: 802.11g, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2449.776 MHz : -7.888 dBm M2 : 2467.731 MHz : 12.739 dBm Delta1 : 25.331 MHz : 0.641 dB	Channel Power: 23.66 dBm Limit: 30.00 dBm Margin: -6.34 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 174 of 242



**peak output power**

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2399.535 MHz : -7.286 dBm M2 : 2408.834 MHz : 12.812 dBm Delta1 : 26.052 MHz : 0.956 dB	Channel Power: 23.95 dBm Limit: 30.00 dBm Margin: -6.05 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 175 of 242



**peak output power**

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2423.253 MHz : -7.993 dBm M2 : 2433.754 MHz : 12.846 dBm Delta1 : 27.655 MHz : 1.570 dB	Channel Power: 24.08 dBm Limit: 30.00 dBm Margin: -5.92 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 176 of 242



**peak output power**

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2449.375 MHz : -8.482 dBm M2 : 2464.365 MHz : 12.712 dBm Delta1 : 25.892 MHz : 1.670 dB	Channel Power: 23.74 dBm Limit: 30.00 dBm Margin: -6.26 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 177 of 242



**peak output power**

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2399.956 MHz : -9.027 dBm M2 : 2427.531 MHz : 11.144 dBm Delta1 : 44.088 MHz : 0.350 dB	Channel Power: 24.53 dBm Limit: 30.00 dBm Margin: -5.47 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 178 of 242



**peak output power**

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2412.872 MHz : -9.250 dBm M2 : 2426.018 MHz : 10.876 dBm Delta1 : 47.936 MHz : 0.161 dB	Channel Power: 24.65 dBm Limit: 30.00 dBm Margin: -5.35 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 179 of 242



**peak output power**

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2427.872 MHz : -9.012 dBm M2 : 2457.531 MHz : 11.138 dBm Delta1 : 48.257 MHz : 0.447 dB	Channel Power: 24.64 dBm Limit: 30.00 dBm Margin: -5.36 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 180 of 242



**peak output power**

Variant: 802.11a, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5726.523 MHz : -6.411 dBm M2 : 5748.086 MHz : 13.668 dBm Delta1 : 38.076 MHz : 0.079 dB	Channel Power: 24.34 dBm Limit: 30.00 dBm Margin: -5.66 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 181 of 242



**peak output power**

Variant: 802.11a, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5766.202 MHz : -6.285 dBm M2 : 5788.006 MHz : 13.768 dBm Delta1 : 38.637 MHz : 0.628 dB	Channel Power: 24.60 dBm Limit: 30.00 dBm Margin: -5.40 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 182 of 242



**peak output power**

Variant: 802.11a, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5806.122 MHz : -6.838 dBm M2 : 5827.846 MHz : 13.269 dBm Delta1 : 38.477 MHz : 0.836 dB	Channel Power: 24.11 dBm Limit: 30.00 dBm Margin: -5.89 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 183 of 242



### PEAK OUTPUT POWER

Variant: 802.11a, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 5 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5722.575 MHz : -8.307 dBm M2 : 5738.687 MHz : 11.699 dBm Delta1 : 43.888 MHz : 0.600 dB	Channel Power: 22.90 dBm Limit: 30.00 dBm Margin: -7.10 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 184 of 242



### PEAK OUTPUT POWER

Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 5 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5762.575 MHz : -9.635 dBm M2 : 5781.814 MHz : 11.693 dBm Delta1 : 5806.46 MHz : -8.307 dBm	Channel Power: 22.89 dBm Limit: 30.00 dBm Margin: -7.11 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 185 of 242



### PEAK OUTPUT POWER

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 5 Vdc



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5802.455 MHz : -8.787 dBm M2 : 5821.453 MHz : 12.702 dBm Delta1 : 44.008 MHz : 2.337 dB	Channel Power: 23.84 dBm Limit: 30.00 dBm Margin: -6.16 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 186 of 242



**peak output power**

Variant: 802.11n HT-40, Channel: 5755.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5730.391 MHz : -12.016 dBm M2 : 5752.515 MHz : 8.458 dBm Delta1 : 46.814 MHz : 0.946 dB	Channel Power: 21.96 dBm Limit: 30.00 dBm Margin: -8.04 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 187 of 242



**peak output power**

Variant: 802.11n HT-40, Channel: 5795.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5761.413 MHz : -10.102 dBm M2 : 5787.866 MHz : 10.070 dBm Delta1 : 63.808 MHz : 0.712 dB	Channel Power: 23.47 dBm Limit: 30.00 dBm Margin: -6.53 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 188 of 242

### A.1.3. Power Spectral Density



#### power density

Variant: 802.11b, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2412.909 MHz : -7.459 dBm	Limit: $\leq 8.00$ dBm Margin: -15.46 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 189 of 242



**power density**

Variant: 802.11b, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2437.909 MHz : -7.367 dBm	Limit: ≤8.00 dBm Margin: -15.37 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 190 of 242



**power density**

Variant: 802.11b, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2462.909 MHz : -7.172 dBm	Limit: ≤8.00 dBm Margin: -15.17 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 191 of 242



**power density**

Variant: 802.11g, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2414.507 MHz : -8.337 dBm	Limit: ≤8.00 dBm Margin: -16.34 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 192 of 242



**power density**

Variant: 802.11g, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2440.384 MHz : -9.185 dBm	Limit: ≤8.00 dBm Margin: -17.19 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 193 of 242



**power density**

Variant: 802.11g, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2464.507 MHz : -8.427 dBm	Limit: ≤8.00 dBm Margin: -16.43 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 194 of 242



**power density**

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2408.580 MHz : -8.964 dBm	Limit: ≤8.00 dBm Margin: -16.96 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 195 of 242



**power density**

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2433.582 MHz : -9.094 dBm	Limit: ≤8.00 dBm Margin: -17.09 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 196 of 242



**power density**

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2458.857 MHz : -9.494 dBm	Limit: ≤8.00 dBm Margin: -17.49 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 197 of 242



**power density**

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2415.402 MHz : -12.775 dBm	Limit: ≤8.00 dBm Margin: -20.77 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 198 of 242



**power density**

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2444.524 MHz : -12.466 dBm	Limit: ≤8.00 dBm Margin: -20.47 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 199 of 242



**power density**

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2443.791 MHz : -10.790 dBm	Limit: ≤8.00 dBm Margin: -18.79 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 200 of 242



**power density**

Variant: 802.11a, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5747.730 MHz : -9.153 dBm	Limit: ≤8.00 dBm Margin: -17.15 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 201 of 242



**power density**

Variant: 802.11a, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5788.420 MHz : -8.978 dBm	Limit: ≤8.00 dBm Margin: -16.98 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 202 of 242



**power density**

Variant: 802.11a, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5819.955 MHz : -8.227 dBm	Limit: ≤8.00 dBm Margin: -16.23 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 203 of 242



**power density**

Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5741.576 MHz : -8.532 dBm	Limit: ≤8.00 dBm Margin: -16.53 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 204 of 242



**power density**

Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5779.977 MHz : -7.127 dBm	Limit: ≤8.00 dBm Margin: -15.13 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 205 of 242



**power density**

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5819.979 MHz : -6.881 dBm	Limit: ≤8.00 dBm Margin: -14.88 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 206 of 242



**power density**

Variant: 802.11n HT-40, Channel: 5755.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5741.254 MHz : -14.691 dBm	Limit: ≤8.00 dBm Margin: -22.69 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 207 of 242



**power density**

Variant: 802.11n HT-40, Channel: 5795.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5797.153 MHz : -14.725 dBm	Limit: ≤8.00 dBm Margin: -22.73 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 208 of 242


#### A.1.4. Conducted Spurious Emissions

Dual Port Module:



band-edge

Variant: 802.11b, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -41.392 dBm M2 : 2403.820 MHz : -15.239 dBm M3 : 2413.631 MHz : 5.896 dBm	Limit: -14.10 dBm Margin: -27.29 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 209 of 242



**band-edge**

Variant: 802.11b, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2463.399 MHz : 6.102 dBm M2 : 2470.325 MHz : -14.600 dBm M3 : 2483.500 MHz : -42.706 dBm	Limit: -13.90 dBm Margin: -28.81 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 210 of 242



**spurious**

Variant: 802.11b, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 5.756 dBm M2 : 22.097 GHz : -44.278 dBm	Limit: -14.24 dBm Margin: -30.04 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 211 of 242



**spurious**

Variant: 802.11b, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 5.931 dBm M2 : 6639.599 MHz : -43.229 dBm	Limit: -14.07 dBm Margin: -29.16 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 212 of 242



**spurious**

Variant: 802.11b, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 6.079 dBm M2 : 4922.144 MHz : -52.295 dBm	Limit: -13.92 dBm Margin: -38.38 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 213 of 242



**band-edge**

Variant: 802.11g, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -20.484 dBm M2 : 2403.098 MHz : -14.773 dBm M3 : 2417.094 MHz : 5.605 dBm	Limit: -14.40 dBm Margin: -6.08 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 214 of 242



**band-edge**

Variant: 802.11g, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2467.006 MHz : 5.870 dBm M2 : 2471.912 MHz : -16.050 dBm M3 : 2483.500 MHz : -28.604 dBm	Limit: -14.13 dBm Margin: -14.47 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 215 of 242



spurious

Variant: 802.11g, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 4.420 dBm M2 : 6639.599 MHz : -43.585 dBm	Limit: -15.58 dBm Margin: -28.01 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 216 of 242



**spurious**

Variant: 802.11g, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 3.942 dBm M2 : 22.097 GHz : -43.060 dBm	Limit: -16.06 dBm Margin: -27.00 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 217 of 242



**spurious**

Variant: 802.11g, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 5.646 dBm M2 : 22.097 GHz : -54.134 dBm	Limit: -14.35 dBm Margin: -39.78 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 218 of 242



**band-edge**

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -19.153 dBm M2 : 2402.521 MHz : -14.199 dBm M3 : 2417.094 MHz : 6.061 dBm	Limit: -13.94 dBm Margin: -5.21 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 219 of 242



**band-edge**

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2467.006 MHz : 5.864 dBm M2 : 2471.912 MHz : -15.657 dBm M3 : 2483.500 MHz : -26.518 dBm	Limit: -14.14 dBm Margin: -12.38 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 220 of 242



**spurious**

Variant: 802.11n HT-20, Channel: 2412.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 5.020 dBm M2 : 22.617 GHz : -43.719 dBm	Limit: -14.98 dBm Margin: -28.74 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 221 of 242



**spurious**

Variant: 802.11n HT-20, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 5.540 dBm M2 : 6691.643 MHz : -43.502 dBm	Limit: -14.46 dBm Margin: -29.04 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 222 of 242



**spurious**

Variant: 802.11n HT-20, Channel: 2462.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 5.579 dBm M2 : 22.097 GHz : -53.754 dBm	Limit: -14.42 dBm Margin: -39.33 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 223 of 242



**band-edge**

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -19.542 dBm M2 : 2402.621 MHz : -17.854 dBm M3 : 2433.283 MHz : 2.724 dBm	Limit: -17.28 dBm Margin: -2.26 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 224 of 242



**band-edge**

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2455.747 MHz : 2.695 dBm M2 : 2471.980 MHz : -18.112 dBm M3 : 2483.500 MHz : -20.217 dBm	Limit: -17.31 dBm Margin: -2.91 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 225 of 242



**spurious**

Variant: 802.11n HT-40, Channel: 2422.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.268 dBm M2 : 6795.731 MHz : -44.132 dBm	Limit: -17.73 dBm Margin: -26.40 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 226 of 242



**spurious**

Variant: 802.11n HT-40, Channel: 2437.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.453 dBm M2 : 6587.555 MHz : -43.662 dBm	Limit: -17.55 dBm Margin: -26.11 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 227 of 242



**spurious**

Variant: 802.11n HT-40, Channel: 2452.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 2424.028 MHz : 2.374 dBm M2 : 22.461 GHz : -54.167 dBm	Limit: -17.63 dBm Margin: -36.54 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 228 of 242



**band-edge**

Variant: 802.11a, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5725.000 MHz : -18.270 dBm M2 : 5729.749 MHz : -14.495 dBm M3 : 5739.994 MHz : 7.158 dBm	Limit: -12.84 dBm Margin: -5.43 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 229 of 242



**band-edge**

Variant: 802.11a, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5819.906 MHz : 6.874 dBm M2 : 5841.982 MHz : -15.127 dBm M3 : 5850.000 MHz : -24.464 dBm	Limit: -13.13 dBm Margin: -11.33 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 230 of 242



spurious

Variant: 802.11a, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 5754.850 MHz : 5.910 dBm M2 : 17.257 GHz : -44.062 dBm	Limit: -14.09 dBm Margin: -29.97 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 231 of 242



spurious

Variant: 802.11a, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5754.850 MHz : 3.254 dBm M2 : 6743.687 MHz : -39.953 dBm	Limit: -16.75 dBm Margin: -23.20 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 232 of 242



**spurious**

Variant: 802.11a, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5806.894 MHz : 6.687 dBm M2 : 5442.585 MHz : -40.695 dBm	Limit: -13.31 dBm Margin: -27.38 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 233 of 242



**band-edge**

Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5725.000 MHz : -15.697 dBm M2 : 5728.018 MHz : -15.475 dBm M3 : 5739.994 MHz : 7.545 dBm	Limit: -12.46 dBm Margin: -3.24 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 234 of 242



**band-edge**

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5819.906 MHz : 7.285 dBm M2 : 5840.972 MHz : -13.290 dBm M3 : 5850.000 MHz : -22.151 dBm	Limit: -12.72 dBm Margin: -9.43 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 235 of 242



spurious

Variant: 802.11n HT-20, Channel: 5745.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 10 Trace Mode = VIEW	M1 : 5754.850 MHz : 6.056 dBm M2 : 17.257 GHz : -44.938 dBm	Limit: -13.94 dBm Margin: -31.00 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 236 of 242



spurious

Variant: 802.11n HT-20, Channel: 5785.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5754.850 MHz : 3.252 dBm M2 : 6795.731 MHz : -39.825 dBm	Limit: -16.75 dBm Margin: -23.08 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 237 of 242



spurious

Variant: 802.11n HT-20, Channel: 5825.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5806.894 MHz : 3.830 dBm M2 : 6639.599 MHz : -40.642 dBm	Limit: -16.17 dBm Margin: -24.47 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 238 of 242



**band-edge**

Variant: 802.11n HT-40, Channel: 5755.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5725.000 MHz : -24.169 dBm M2 : 5735.621 MHz : -19.646 dBm M3 : 5758.768 MHz : 0.567 dBm	Limit: -19.43 dBm Margin: -4.74 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 239 of 242



**band-edge**

Variant: 802.11n HT-40, Channel: 5795.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5798.747 MHz : 2.226 dBm M2 : 5827.906 MHz : -21.817 dBm M3 : 5850.000 MHz : -35.958 dBm	Limit: -17.77 dBm Margin: 20.00 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 240 of 242



spurious

Variant: 802.11n HT-40, Channel: 5755.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5754.850 MHz : -0.450 dBm M2 : 6743.687 MHz : -40.220 dBm	Limit: -20.45 dBm Margin: -19.77 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.






**Title:** Digi Connect Card for i.MX28 with Atheros AR6203  
**To:** FCC 47 CFR Part 15.247 & IC RSS-210  
**Serial #:** DIGI28-U2B Rev A  
**Issue Date:** 29th March 2013  
**Page:** 241 of 242



spurious

Variant: 802.11n HT-40, Channel: 5795.00 MHz, Chain a, Temp: Ambient, Voltage: 5.00V



Analyser Setup	Marker : Frequency : Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 5754.850 MHz : 1.715 dBm M2 : 6795.731 MHz : -39.844 dBm	Limit: -18.29 dBm Margin: -21.55 dB

[Back to the Matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



440 Boulder Court, Suite 200  
Pleasanton, CA 94566, USA  
Tel: 1.925.462.0304  
Fax: 1.925.462.0306  
[www.micomlabs.com](http://www.micomlabs.com)