

Test of Digi International XBPS3B

To: FCC 47 CFR Part15.247 & IC RSS-210

Test Report Serial No.: DIGI22-U1 Rev B



TEST REPORT

FROM



Test of Digi International XBPS3B

To FCC 47 CFR Part15.247 & IC RSS-210

Test Report Serial No.: DIGI22-U1 Rev B

This report supersedes: DIGI22-U1 Rev A

Manufacturer: Digi International
355 South 520 West, Suite 180
Lindon Utah 84042
USA

Product Function: General Data and Control Radio

Copy No: pdf **Issue Date:** 17th November 2011

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
440 Boulder Court, Suite 200
Pleasanton, CA 94566 USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



CERTIFICATE #2381.01

MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 3 of 92

This page has been left intentionally blank

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



TABLE OF CONTENTS

ACCREDITATION & LISTINGS.....	5
RECOGNITION.....	6
PRODUCT CERTIFICATION.....	7
1. TEST RESULT CERTIFICATE	9
2. REFERENCES AND MEASUREMENT UNCERTAINTY	10
2.1. Normative References	10
2.2. Test and Uncertainty Procedures	10
3. PRODUCT DETAILS AND TEST CONFIGURATIONS	11
3.1. Technical Details	11
3.2. Scope of Test Program.....	12
3.3. Equipment Model(s) and Serial Number(s)	14
3.4. Antenna Details	14
3.5. Cabling and I/O Ports	14
3.6. Test Configurations.....	15
3.7. Equipment Modifications.....	15
3.8. Deviations from the Test Standard	15
3.9. Subcontracted Testing or Third Party Data	15
4. TEST SUMMARY	16
5. TEST RESULTS.....	18
5.1. Device Characteristics	18
5.1.1. 20 dB Bandwidth.....	18
5.1.2. Transmitter Channels - Channel Spacing.....	24
5.1.3. Transmitter Channels.....	27
5.1.4. Output Power	33
5.1.5. Maximum Permissible Exposure.....	36
5.1.6. Conducted Spurious Emissions Transmitter.....	37
5.1.7. Conducted Receiver Spurious Emissions.....	45
5.1.8. Radiated Emissions	53
5.1.9. AC Wireline Conducted Emissions (150 kHz – 30 MHz)	82
6. PHOTOGRAPHS.....	84
6.1. General Measurement Test Set-Up	84
6.2. Radiated Emissions >1 GHz.....	86
6.3. Radiated Emissions <1 GHz.....	88
7. TEST EQUIPMENT DETAILS.....	91

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

ACCREDITATION & LISTINGS

MiCOM Labs, Inc. an accredited laboratory complies with the international standard BS EN ISO/IEC 17025. The company is accredited by the American Association for Laboratory Accreditation (A2LA) www.a2la.org test laboratory number 2381.01. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-01.pdf>



The American Association for Laboratory Accreditation

World Class Accreditation

Accredited Laboratory

A2LA has accredited

MICOM LABS


Pleasanton, CA

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General Requirements for the Competence of Testing and Calibration Laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Presented this 14th day of April 2010.



President & CEO
For the Accreditation Council
Certificate Number 2381.01
Valid to November 30, 2011

For the tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 6 of 92

RECOGNITION

MiCOM Labs, Inc has widely recognized Electrical testing capabilities. Our international recognition includes Conformity Assessment Body designation by APEC MRA** countries. Our test reports are widely accepted for global type approvals.

Country	Recognition Body	Status	Phase	Identification No.
USA	Federal Communications Commission (FCC)	TCB	-	Listing #: 102167
Canada	Industry Canada (IC)	FCB	APEC MRA 2	Listing #: 4143A
Japan	MIC	CAB	APEC MRA 2	210
	VCCI	--	--	No. 2959
Europe	European Commission	NB	EU MRA	NB 2280
Australia	Australian Communications and Media Authority (ACMA)	CAB	APEC MRA 1	US0159
Hong Kong	Office of the Telecommunication Authority (OFTA)	CAB	APEC MRA 1	
Korea	Ministry of Information and Communication Radio Research Laboratory (RRL)	CAB	APEC MRA 1	
Singapore	Infocomm Development Authority (IDA)	CAB	APEC MRA 1	
Taiwan	National Communications Commission (NCC) Bureau of Standards, Metrology and Inspection (BSMI)	CAB	APEC MRA 1	
Vietnam	Ministry of Communication (MIC)	CAB	APEC MRA 1	

**APEC MRA – Asia Pacific Economic Community Mutual Recognition Agreement.

Is a recognition agreement under which test lab is accredited to regulatory standards of the APEC member countries.

Phase I - recognition for product testing

Phase II – recognition for both product testing and certification

N/A – Not Applicable

**EU MRA – European Union Mutual Recognition Agreement.

Is a recognition agreement under which test lab is accredited to regulatory standards of the EU member countries.

**NB – Notified Body

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 7 of 92

PRODUCT CERTIFICATION

MiCOM Labs, Inc. is an accredited Product Certification Body per the international standard EN ISO/IEC Guide 65. The company is accredited by the American Association for Laboratory Accreditation (A2LA) www.a2la.org test laboratory number 2381.02. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-02.pdf>



The American Association for Laboratory Accreditation

World Class Accreditation

Accredited Product Certification Body

A2LA has accredited

MICOM LABS

Pleasanton, CA

for technical competence as a

Product Certification Body

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC Guide 65:1996 *General requirements for bodies operating product certification systems*. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system for a Telecommunications Certification Body (TCB) meeting FCC (U.S.), and IC (Canada) requirements.



Presented this 24th day of June 2010.

Peter Almyer

President & CEO
For the Accreditation Council
Certificate Number 2381.02
Valid to November 30, 2011

For the product certification schemes to which this accreditation applies, please refer to the organization's Product Certification Scope of Accreditation.

United States of America – Telecommunication Certification Body (TCB)

TCB Identifier – US0159

Industry Canada – Certification Body

CAB Identifier – US0159

Europe – Notified Body

Notified Body Identifier - 2280

Japan – Recognized Certification Body (RCB)

RCB Identifier - 210

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 8 of 92

DOCUMENT HISTORY

Document History		
Revision	Date	Comments
Draft		
Rev A	31 st October 2011	Initial Release
Rev B	17 th November 2011	Updated Section 5.1.1 20 dB BW with new spectrum plot

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 9 of 92

1. TEST RESULT CERTIFICATE

Manufacturer:	Digi International 355 South 520 West, Suite 180 Lindon Utah 84042 USA	Tested By:	MiCOM Labs, Inc. 440 Boulder Court Suite 200 Pleasanton California, 94566, USA
EUT:	General Data and Control Radio	Telephone:	+1 925 462 0304
Model:	XBPS3B	Fax:	+1 925 462 0306
S/N:	Not Available		
Test Date(s):	15 - 22nd September 2011	Website:	www.micomlabs.com

STANDARD(S)	TEST RESULTS
FCC 47 CFR Part15.247 & IC RSS-210	EQUIPMENT COMPLIES

MiCOM Labs, Inc. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

Notes:

1. This document reports conditions under which testing was conducted and the results of testing performed.
2. Details of test methods used have been recorded and kept on file by the laboratory.
3. Test results apply only to the item(s) tested.

Approved & Released for MiCOM Labs, Inc. by:



TEST CERTIFICATE #2381.01



Graeme Grieve
Quality Manager MiCOM Labs,



Gordon Hurst
President & CEO MiCOM Labs, Inc.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

2. REFERENCES AND MEASUREMENT UNCERTAINTY

2.1. Normative References

Ref.	Publication	Year	Title
(i)	FCC 47 CFR Part 15.247	2007	Code of Federal Regulations
(ii)	Industry Canada RSS-210	Issue 7 June 2007	Low Power License-Exempt Radiocommunication Devices (All Frequency Bands)
(iii)	Industry Canada RSS-Gen	Issue 2 June 2007	General Requirements and Information for the Certification of Radiocommunication Equipment.
(iv)	ANSI C63.4	2003	American National Standards for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
(v)	CISPR 22/ EN 55022	1997 1998	Limits and Methods of Measurements of Radio Disturbance Characteristics of Information Technology Equipment
(vi)	M 3003	Edition 1 Dec. 1997	Expression of Uncertainty and Confidence in Measurements
(vii)	LAB34	Edition 1 Aug 2002	The expression of uncertainty in EMC Testing
(viii)	ETSI TR 100 028	2001	Parts 1 and 2 Electromagnetic compatibility and Radio Spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics
(ix)	A2LA	14 th September 2005	Reference to A2LA Accreditation Status – A2LA Advertising Policy

2.2. Test and Uncertainty Procedures

Conducted and radiated emission measurements were conducted in accordance with American National Standards Institute ANSI C63.4, listed in the Normative References section of this report.

Measurement uncertainty figures are calculated in accordance with ETSI TR 100 028 Parts 1 and 2.

Measurement uncertainties stated are based on a standard uncertainty multiplied by a coverage factor $k = 2$, providing a level of confidence of approximately 95 % in accordance with UKAS document M 3003 listed in the Normative References section of this report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 11 of 92

3. PRODUCT DETAILS AND TEST CONFIGURATIONS

3.1. Technical Details

Details	Description
Purpose:	Test of the Digi International XBPS3B to FCC Part 15.247 and Industry Canada RSS-210 regulations for Frequency Hopping operation.
Applicant:	Digi International 355 South 520 West, Suite 180 Lindon, Utah 84042 USA
Manufacturer:	Digi International 355 South 520 West, Suite 180 Lindon Utah 84042 USA
Laboratory performing the tests:	MiCOM Labs, Inc. 440 Boulder Court, Suite 200 Pleasanton, California 94566 USA
Test report reference number:	DIGI22-U1 Rev B
Standard(s) applied:	FCC 47 CFR Part15.247 & IC RSS-210
Date EUT received:	1 st September 2011
Dates of test (from - to):	15 - 22nd September 2011
No of Units Tested:	One
Type of Equipment:	915 MHz Frequency Hopping
Manufacturers Trade Name:	XBee Pro XSC
Model:	XBee Pro S3B
Location for use:	Indoor and Outdoor
Declared Frequency Range(s):	902 - 928 MHz
Type of Modulation:	FSK
Declared Nominal Output Power:	Max: +24 dBm Min: -17 dBm
EUT Modes of Operation:	FHSS
Transmit/Receive Operation:	Transceiver Half Duplex
Rated Input Voltage and Current:	Nom: 3.3 Vdc, Min: 2.4 Vdc Max: 3.6 Vdc
Operating Temperature Range:	-40°C to +85°C (client declared range)
ITU Emission Designator:	300KF7D
Long Term Frequency Stability:	±3ppm/year
EUT Dimensions (L x W x H):	33 x 22 x 4mm or with Reverse SMA 33 x 22 x 8mm
EUT Weight :	6 grams
Primary function of equipment:	General data and control radio

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

3.2. Scope of Test Program


The scope of the test program was to testing on the Digi International XBPS3B in the frequency ranges 902 - 928 MHz against FCC 47 CFR Part 15.247 and Industry Canada RSS-210 specifications for radiated and conducted emissions for intentional radiators. The intentional radiator was tested in a simulated typical installation to demonstrate compliance with the stated standards.

Device is a frequency hopper which utilizes 84 hopping channels.

Digi International XBee Pro S3B Top



Digi International XBee Pro S3B Reverse



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 14 of 92

3.3. Equipment Model(s) and Serial Number(s)

Type (EUT/Support)	Equipment Description (Including Brand Name)	Mfr	Model No.	Serial No.
EUT	915 MHz	Digi International	XBPS3B	None Available
Support	Cable Assembly + pcb	Digi International	N/A	N/A

3.4. Antenna Details

The following is a description of the EUT antennas.

Manufacturer	Model	Type	Gain (dBi)	Frequency Band (MHz)
Digi International	A09-Y15	Yagi Directional	15.1	900 - 950
Digi International	A09-F8	Omni	8.1	900 - 950

3.5. Cabling and I/O Ports

Number and type of I/O ports

1. RF Port (915 MHz)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



3.6. Test Configurations

Test configurations

Operating Channel	Frequencies (MHz)
0	902.4
42	915.00
83	927.5

3.7. Equipment Modifications

The following modifications were required to bring the equipment into compliance:

1. NONE

3.8. Deviations from the Test Standard

The following deviations from the test standard were required in order to complete the test program:

1. NONE

3.9. Subcontracted Testing or Third Party Data

The following tests were performed by a MiCOM Labs approved test facility:-

1. NONE



4. TEST SUMMARY

List of Measurements

The following table represents the list of measurements required under the **FCC CFR47 Part 15.247**, **Industry Canada RSS-210** and **Industry Canada RSS-Gen**.

Section(s)	Test Items	Description	Condition	Result	Test Report Section
15.247(a)(1) A8.1	20 dB BW	20 dB BW	Conducted	Complies	5.1.1
15.247(a)(1) A8.1	Transmitter Channels	Channel Spacing	Conducted	Complies	5.1.2
15.247(a)(1) A8.1	Transmitter Channels	Number of Channels	Conducted	Complies	5.1.3.1
		Channel Occupancy	Conducted	Complies	5.1.3.2
15.247(b)(2) A8.4	Output Power	Transmit Power	Conducted	Complies	5.1.4
15.247(i) 5.5	Maximum Permissible Exposure	Exposure to radio frequency energy levels	Conducted	Complies	5.1.5
15.247(d) A8.5	Conducted Spurious Emissions	Band Edge	Conducted	Complies	5.1.6
		Spurious Emissions Transmitter (1 to 10 GHz)	Conducted	Complies	
§7.2.3		Standby	Conducted	Complies	5.1.7

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 17 of 92

List of Measurements

The following table represents the list of measurements required under the **FCC CFR47 Part 15.247**, **Industry Canada RSS-210** and **Industry Canada RSS-Gen**.

Section(s)	Test Items	Description	Condition	Result	Test Report Section
15.247(d) 15.205 15.209 A8.5 2.2 2.6 4.9	Radiated Emissions above 1 GHz	Transmitter	Radiated	Complies	5.1.8.1
4.10		Receiver	Radiated	Complies	5.1.8.2
15.247(d) 15.205 15.209 A8.5 2.2 2.6	Radiated Emissions below 1 GHz		Radiated	Complies	5.1.9
15.207 7.2.2	Conducted	AC Wireline Conducted Emissions	Conducted	Complies	5.1.10

Note 1: Test results reported in this document relate only to the items tested

Note 2: The required tests demonstrated compliance as per client declaration of test configuration, monitoring methodology and associated pass/fail criteria

Note 3: Section 3.7 - Equipment Modifications highlights the equipment modifications that were required to bring the product into compliance with the above test matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5. TEST RESULTS

5.1. Device Characteristics


5.1.1. 20 dB Bandwidth

FCC, Part 15 Subpart C §15.247(a)(1)
Industry Canada RSS-210 §A8.1

Test Procedure

The 20 dB bandwidth is measured with a spectrum analyzer connected to the antenna terminal, while the EUT is operating in transmission mode at the appropriate center frequency and modulation.

Test Measurement Set up



Measurement set up for 20 dB bandwidth test



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 19 of 92

Test Results for 20 dB Bandwidth

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar


TABLE OF RESULTS

Channel #	Center Frequency (MHz)	20 dB Bandwidth (kHz)	Specification (kHz)
0	902.4	260.521	<500
42	915.0	272.545	
83	927.5	282.565	

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



CH 0 902.4 MHz 20 dB Bandwidth




Date: 15.SEP.2011 11:27:20

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



CH 42 915.0 MHz 20 dB Bandwidth




Date: 15.SEP.2011 11:29:47

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



CH 83 927.5 MHz 20 dB Bandwidth



Date: 5.DEC.2011 10:34:08

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 23 of 92

Specification

Limits

FCC §15.247 (a)(1)
Industry Canada RSS-210 §8.1

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

Laboratory Measurement Uncertainty for Spectrum Measurement

Measurement uncertainty	±2.81 dB
-------------------------	----------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of RF Spectrum Mask'	0158, 0193, 0252, 0313, 0314, 0070, 0116, 0117

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5.1.2. Transmitter Channels - Channel Spacing

FCC, Part 15 Subpart C §15.247(a)(1)
Industry Canada RSS-210 §8.1(2)

Test Procedure

The channel spacing is measured with a spectrum analyzer connected to the antenna terminal, while the EUT is operating in transmission mode at the appropriate center frequency and modulation.

Test Measurement Set up



Measurement set up for Channel Spacing Test




Ambient conditions.
Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

TABLE OF RESULTS

Channel(s)	Channel Spacing (KHz)	Specification
25-26	300.902	Greater than maximum 20 dB Bandwidth

Maximum 20 dB bandwidth = 52.6052 kHz



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 26 of 92

Specification for Channel Spacing

Limits

FCC §15.247 (a)(1)
Industry Canada RSS-210 §A8.1(2)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Laboratory Uncertainty for Frequency Measurements

Measurement uncertainty	$\pm 0.86\text{ppm}$
-------------------------	----------------------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-02 'Frequency Measurement'	0078, 0134, 0158, 0184, 0193, 0250, 0252 0310, 0312.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5.1.3. Transmitter Channels

5.1.3.1. **Number of Channels** **FCC, Part 15 Subpart C §15.247(a)(1)** **Industry Canada RSS-210 §A8.1**

Test Procedure

The number of channels and channel occupancy is measured with a spectrum analyzer connected to the antenna terminal, while the EUT is operating in transmission mode at the appropriate center frequency and modulation.

Test Measurement Set up



Test set up to measure the number of channels and channel occupancy



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 28 of 92


Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

TABLE OF RESULTS

Number of Channels	Specification
84	At least 25 hopping channels

Number of Transmission Channels – Lower Band




Date: 15.SEP.2011 13:45:00

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Number of Transmission Channels – Upper Band



Date: 15.SEP.2011 13:41:04

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




5.1.3.2. Channel Occupancy
FCC, Part 15 Subpart C §15.247(a)(1)
Industry Canada RSS-210 §A8.1

Ambient conditions.
 Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

Channel Dwell Time

TABLE OF RESULTS

Channel #	Center Frequency (MHz)	Channel Dwell Time (single channel) (mSecs)
0	902.4	98.997



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Channel Occupancy

TABLE OF RESULTS

Channel #	Center Frequency (MHz)	Channel Occupancy within 10 Second Period (Seconds)
0	902.4	5.01

Channel Occupancy 927.5 MHz



Date: 15.SEP.2011 13:50:05

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 32 of 92

Specification for Number of Channels and Channel Occupancy

Limits

FCC, Part 15 Subpart C §15.247(a)(1)
Industry Canada RSS-210 §A8.1

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

Laboratory Uncertainty for Frequency Measurements

Measurement uncertainty	±0.86ppm
-------------------------	----------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-02 'Frequency Measurement'	0078, 0134, 0158, 0184, 0193, 0250, 0252 0310, 0312.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5.1.4. Output Power

FCC, Part 15 Subpart C §15.247(b)(2)
Industry Canada RSS-210 §A8.4

Test Procedure

The transmitter terminal of EUT was set for CW (continuous wave) operation and connected to the input of the power meter which was calibrated to measure power. The value of measured power including antenna cable loss was reported.

Test Measurement Set up



Measurement set up for Transmitter Output Power



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 34 of 92

Measurement Results for Output Power

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

TABLE OF RESULTS

Channel #	Center Frequency (MHz)	Power (dBm)
0	902.4	+23.63
42	915.0	+23.59
83	927.5	+23.69

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 35 of 92

Specification

Limits

FCC, Part 15 Subpart C §15.247 (b)(2) The maximum output power of the intentional radiator shall not exceed the following:

(2) For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

Industry Canada RSS-210 §A8.4

For frequency hopping systems operating in the 902 - 928 MHz band, the maximum peak conducted power output power is not to exceed 1.0 W if the hopset uses 50 or more hopping channels and 0.25 W if the hopset uses less than 50 hopping channels.

Laboratory Measurement Uncertainty for Power Measurements

Measurement uncertainty

±1.33 dB

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-01 'Measuring RF Output Power'	0158, 0193, 0252, 0313, 0314, 0070, 0116, 0117

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



5.1.5. Maximum Permissible Exposure

FCC, Part 15 Subpart C §15.247(i)
Industry Canada RSS-Gen §5.5

Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4\pi d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10 ^ (G \text{ (dBi)}/10)$$

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm²

Antenna Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm ² Limit(cm)	Minimum Separation Distance (cm)
0	1	+23.69	233.9	4.31	20*
8.1	6.46	+23.69	233.9	8.92	20*
15.1	32.36	+20.90	123.03	17.8	20*

***Note:** for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification

Maximum Permissible Exposure Limits

§15.247(i) Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency levels in excess of the Commission's guidelines.

FCC §1.1310 Limit = 1mW / cm² from 1.310 Table 1

RSS-Gen §5.5 Before equipment certification is granted, the applicable requirements of RSS-102 shall be met.

Laboratory Measurement Uncertainty for Power Measurements

Measurement uncertainty

±1.33 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5.1.6. Conducted Spurious Emissions Transmitter

FCC, Part 15 Subpart C §15.247(d)
Industry Canada RSS-210 §A8.5

Test Procedure

Conducted emissions were measured at a limit of 20 dB below the highest in-band spectral density measured with a spectrum analyzer connected to the antenna terminal. Emissions at the band edge were measured and recorded. Measurements were made while EUT was operating in transmit mode of operation at the appropriate center frequency.

Test Measurement Set up



Band-edge measurement test configuration

Measurement Results of Conducted Spurious Emissions

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar




Conducted Band-Edge Results

TABLE OF RESULTS – 802.11b

Channel #	Center Frequency (MHz)	Band-edge Frequency (MHz)	Limit (dBm)	Amplitude @ Band-edge (dBm)	Margin (dB)
0	902.4	902.0	+3.34	-5.71	-9.05
83	927.5	928.0	+3.11	-11.18	-14.29

Conducted Spurious Emissions at the 902 MHz Lower Band Edge




Date: 15.SEP.2011 11:37:39

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Conducted Spurious Emissions at the 928 MHz Upper Band Edge



Date: 15.SEP.2011 11:39:32

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Spurious Emissions (1-10 GHz)

Conducted spurious emissions (1-10 GHz) are provided indicated by the following matrix. Measurements were performed with the transmitter tuned to the channel closest to the band-edge being measured. All emissions were maximized during measurement. Limits which were derived from the band-edge measurements provided below are drawn on each plot.

TABLE OF RESULTS

Channel Centre Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Maximum Emission Observed (dBm)	Limit (dBm)	Margin (dB)
902.4	30	10,000	-8.58	+3.02	-11.6

The emission breaking the limit line is the carrier.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 41 of 92

Conducted Transmitter Spurious Emissions

Channel 902.4 MHz - 30 MHz to 10,000 MHz



Date: 15.SEP.2011 11:11:33

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Channel Centre Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Maximum Emission Observed (dBm)	Limit (dBm)	Margin (dB)
915.0	30	10,000	-8.95	+3.02	-11.97

The emission breaking the limit line is the carrier.

Conducted Transmitter Spurious Emissions

Channel 915.0 MHz - 30 MHz to 10,000 MHz



Date: 15.SEP.2011 11:09:09

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 43 of 92

Channel Centre Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Maximum Emission Observed (dBm)	Limit (dBm)	Margin (dB)
927.5	30	10,000	-9.50	+3.02	-12.52

The emission breaking the limit line is the carrier.

Conducted Transmitter Spurious Emissions

Channel 927.5 MHz - 30 MHz to 10,000 MHz



Date: 15.SEP.2011 11:07:15

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 44 of 92

Specification

Limits Band-Edge

Lower Limit Band-edge	Upper Limit Band-edge	Limit below highest level of desired power
902 MHz	928 MHz	≥ 20 dB

FCC, Part 15 Subpart C §15.247(d)

Industry Canada RSS-210 §A.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Laboratory Measurement Uncertainty for Conducted Spurious Emissions

Measurement uncertainty	±2.37 dB
-------------------------	----------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-05 'Measurement of Spurious Emissions'	0287, 0158, 0193, 0252, 0313, 0314, 0070, 0116, 0117.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


5.1.7. Conducted Receiver Spurious Emissions

Industry Canada RSS-Gen §7.2.3

Test Procedure

Conducted Stand-By emissions were measured on the device on the mid channel. The EUT was placed in Stand-By mode and emissions were measured 30 MHz – 7 GHz.

Test Measurement Set up



Stand-By spurious emissions test configuration

Measurement Results of Stand –By Spurious Emissions


Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar



Receiver Conducted Spurious Emissions 0.03 – 10 GHz

902.4 MHz Receiver Conducted Emissions 30 MHz – 1 GHz




No emissions were observed breaking the limit.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 47 of 92

902.4 MHz Receiver Conducted Emissions 1 – 10 GHz



Date: 15.SEP.2011 14:02:33


No emissions were observed breaking the limit.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 48 of 92

915 MHz Receiver Conducted Emissions 30 MHz – 1 GHz



Date: 15.SEP.2011 13:57:31


No emissions were observed breaking the limit.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 49 of 92

915 MHz Receiver Conducted Emissions 1 – 10 GHz



Date: 15.SEP.2011 14:01:33


No emissions were observed breaking the limit.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 50 of 92

927.5 MHz Receiver Conducted Emissions 30 MHz – 1 GHz




Date: 15.SEP.2011 13:58:12

No emissions were observed breaking the limit.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



927.5 MHz Receiver Conducted Emissions 1 – 10 GHz



Date: 15.SEP.2011 14:01:59

No emissions were observed breaking the limit.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 52 of 92

Specification

Antenna Conducted Measurement

Industry Canada RSS-Gen §7.2.3

If the device has a detachable antenna of known antenna impedance, then the antenna conducted method is permitted in lieu of a radiated measurement.

Receiver spurious emissions at any discrete frequency shall not exceed 2 nanowatts (-57 dBm) in the band 30-1000 MHz, or 5 nanowatts (-53 dBm) above 1 GHz.

Laboratory Measurement Uncertainty for Conducted Spurious Emissions

Measurement uncertainty	±2.37 dB
-------------------------	----------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-05 'Measurement of Spurious Emissions'	0287, 0158, 0193, 0252, 0313, 0314, 0070, 0116, 0117.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 53 of 92

5.1.8. Radiated Emissions

FCC, Part 15 Subpart C §15.247(d) 15.205; 15.209
Industry Canada RSS-210 §A8.5, §2.2, §2.6
Industry Canada RSS-Gen §4.7

Test Procedure

Radiated emissions above 1 GHz are measured in the anechoic chamber at a 3-meter distance on every azimuth in both horizontal and vertical polarities. The emissions are recorded and maximized as a function of azimuth by rotation through 360° with a spectrum analyzer in peak hold mode. Depending on the frequency band spanned a notch filter and waveguide filter was used to remove the fundamental frequency. The highest emissions relative to the limit are listed for each frequency spanned.

All measurements on any frequency or frequencies over 1 MHz are based on the use of measurement instrumentation employing an average detector function. All measurements above 1 GHz were performed using a minimum resolution bandwidth of 1 MHz.

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

$$FS = R + AF + CORR - FO$$

where: FS = Field Strength

R = Measured Spectrum analyzer Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = CL – AG + NFL

CL = Cable Loss

AG = Amplifier Gain

FO = Distance Falloff Factor

NFL = Notch Filter Loss or Waveguide Loss

For example:

Given receiver input reading of 51.5 dB μ V; Antenna Factor of 8.5 dB; Cable Loss of 1.3 dB; Falloff Factor of 0 dB, an Amplifier Gain of 26 dB and Notch Filter Loss of 1 dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3 \text{ dB}\mu\text{V/m}$$

Conversion between dB μ V/m (or dB μ V) and μ V/m (or μ V) are done as:


$$\text{Level (dB}\mu\text{V/m)} = 20 * \text{Log (level (\mu\text{V/m}))}$$

$$40 \text{ dB}\mu\text{V/m} = 100 \mu\text{V/m}$$

$$48 \text{ dB}\mu\text{V/m} = 250 \mu\text{V/m}$$


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Radiated Emission Measurement Setup – Above 1 GHz



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Radiated Emission Measurement Setup – Below 1 GHz



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 56 of 92

5.1.8.1. Antenna Yagi Directional - Transmitter Peak and Radiated Spurious Emissions

Radiated Peak Emissions – Yagi 15.1 dBi

Test Freq.	902.4 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	Maximum	Press. (mBars)	1000
Antenna	13 Element Welded Yagi 15.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
902.405	89.8	17.3	22.8	129.8	Peak [Scan]	H	100	0				
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 57 of 92

Test Freq.	915 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	Maximum	Press. (mBars)	1000
Antenna	13 Element Welded Yagi 15.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
915.030	90.5	17.4	22.9	130.8	Peak [Scan]	H	100	0				


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 58 of 92

Test Freq.	927.5 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	Maximum	Press. (mBars)	1000
Antenna	13 Element Welded Yagi 15.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
927.655	90.2	17.4	23.0	130.6	Peak [Scan]	H	100	0				

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 59 of 92

Radiated Spurious Emissions

Test Freq.	902.4 MHz	Engineer	SB
Variant	Digital Emissions	Temp (°C)	28
Freq. Range	30 MHz - 1000 MHz	Rel. Hum.(%)	30
Power Setting	Maximum	Press. (mBars)	100
Antenna	13 Element Welded Yagi 15.1 dBi		
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
902.806	53.6	7.3	-7.2	53.8	Peak [Scan]	H	100	0				FUND
850.321	44.4	7.2	-7.8	43.8	Peak [Scan]	H	100	0	109.8	-66.0	Pass	NRB

Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency
 NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band


NRB Limit = Pk Emission – 20 dB = 129.8 – 20 = 109.8 dB μ V

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 60 of 92

Test Freq.	902.4 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	24 dBm	Press. (mBars)	1000
Antenna	13 Element Welded Yagi 15.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
3609.735	56.1	3.7	-11.3	48.5	Peak Max	H	138	183	74.0	-25.5	Pass	RB
3609.735	49.8	3.7	-11.3	42.2	Average Max	H	138	183	54.0	-11.9	Pass	RB
1783.567	88.0	2.6	-13.3	77.3	Peak [Scan]	H	100	0	109.8	-32.5	Pass	NRB
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak												


NRB Limit = Pk Emission – 20 dB = 129.8 – 20 = 109.8 dBuV

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 61 of 92

Test Freq.	915.0 MHz	Engineer	SB
Variant	Digital Emissions	Temp (°C)	28
Freq. Range	1000 MHz - 6000 MHz	Rel. Hum.(%)	33
Power Setting	Maximum	Press. (mBars)	1000
Antenna	13 Element Welded Yagi 15.1 dBi		
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
863.928	44.8	7.2	-7.7	44.4	Peak [Scan]	H	100	0	110.8	-66.4	Pass	NRB

Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency
 NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band


NRB Limit = Pk Emission – 20 dB = 130.8 – 20 = 110.8 dBµV

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 62 of 92

Test Freq.	915 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	24 dBm	Press. (mBars)	1000
Antenna	13 Element Welded Yagi 15.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
3659.699	62.9	3.7	-11.3	55.3	Peak Max	H	200	169	74.0	-18.7	Pass	RB
3659.699	57.6	3.7	-11.3	50.0	Average Max	H	200	169	54.0	-4.0	Pass	RB
1817.635	88.0	2.6	-13.0	77.6	Peak [Scan]	H	150	0	110.8	-33.2	Pass	NRB
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak												


NRB Limit = Pk Emission – 20 dB = 130.8 – 20 = 110.8 dBµV

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 63 of 92

Test Freq.	927.5 MHz	Engineer	SB
Variant	Digital Emissions	Temp (°C)	28
Freq. Range	30 MHz - 1000 MHz	Rel. Hum.(%)	30
Power Setting	Maximum	Press. (mBars)	100
Antenna	13 Element Welded Yagi 15.1 dBi		
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
953.511	46.5	7.5	-6.5	47.6	Quasi Max	H	98	15	110.6	-63.0	Pass	NRB
857.090	39.6	7.2	-7.8	39.0	Quasi Max	H	107	19	110.6	-71.6	Pass	NRB
928.076	75.3	7.4	-6.9	75.8	Peak [Scan]	H	100	0				FUND

Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency
 NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band


NRB Limit = Pk Emission – 20 dB = 130.6 – 20 = 110.6 dBμV

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 64 of 92

Test Freq.	928 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	24 dBm	Press. (mBars)	1000
Antenna	13 Element Welded Yagi 15.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
3710.591	57.4	3.7	-11.1	50.1	Peak Max	H	149	172	74.0	-23.9	Pass	RB
3710.591	50.9	3.7	-11.1	43.5	Average Max	H	149	172	54.0	-10.5	Pass	RB
1851.703	88.0	2.7	-12.8	77.9	Peak [Scan]	H	200	0	110.6	-32.7	Pass	NRB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

NRB Limit = Pk Emission – 20 dB = 130.6 – 20 = 110.6 dBµV

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 65 of 92

5.1.8.2. Antenna Omni Directional - Transmitter Peak and Radiated Spurious Emissions

Radiated Peak Emissions – Antenna Omni Directional 8.1 dBi

Test Freq.	902 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	24 dBm	Press. (mBars)	1000
Antenna	A09-F8TM 8.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
902.345	85.3	17.3	22.8	125.3	Peak [Scan]	V	150	0				
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 66 of 92

Test Freq.	915 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	24 dBm	Press. (mBars)	1000
Antenna	A09-F8TM 8.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
914.970	85.0	17.4	22.9	125.3	Peak [Scan]	V	150	0				


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 67 of 92

Test Freq.	928 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	24 dBm	Press. (mBars)	1000
Antenna	A09-F8TM 8.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
927.655	85.5	17.4	23.0	125.9	Peak [Scan]	V	150	0				


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Radiated Spurious Emissions

Test Freq.	902.4 MHz	Engineer	SB
Variant	Digital Emissions	Temp (°C)	28
Freq. Range	30 MHz - 1000 MHz	Rel. Hum.(%)	30
Power Setting	24 dBm	Press. (mBars)	100
Antenna	A09-F8TM 8.1 dBi		
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
902.806	59.6	7.3	-7.2	59.7	Peak [Scan]	V						FUND
877.535	41.8	7.3	-7.6	41.5	Peak [Scan]	V	100	0	105.3	-63.8	Pass	NRB
825.050	42.2	7.2	-7.9	41.5	Peak [Scan]	V	100	0	105.3	-63.8	Pass	NRB

Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency
 NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band


NRB Limit = Pk Emission – 20 dB = 125.3 – 20 = 105.3 dB μ V

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 69 of 92

Test Freq.	902.4 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	24 dBm	Press. (mBars)	1000
Antenna	A09-F8TM 8.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
1783.567	87.9	2.6	-13.3	77.3	Peak [Scan]	V	200	0	105.3	-28.0	Pass	NRB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak


$$\text{NRB Limit} = \text{Pk Emission} - 20 \text{ dB} = 125.3 - 20 = 105.3 \text{ dB}\mu\text{V}$$

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 70 of 92

Test Freq.	915 MHz	Engineer	SB
Variant	Digital Emissions	Temp (°C)	28
Freq. Range	30 MHz - 1000 MHz	Rel. Hum.(%)	33
Power Setting	24 dBm	Press. (mBars)	1000
Antenna	A09-F8TM 8.1 dBi		
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
863.928	41.2	7.2	-7.7	40.8	Peak [Scan]	V	100	0	105.3	-64.5	Pass	NRB

Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency
 NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band


NRB Limit = Pk Emission – 20 dB = 125.3 – 20 = 105.3 dBμV

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 71 of 92

Test Freq.	915 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	24 dBm	Press. (mBars)	1000
Antenna	A09-F8TM 8.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
3660.050	56.3	3.7	-11.3	48.7	Peak Max	V	104	0	74.0	-25.3	Pass	RB
3660.05	50.0	3.7	-11.3	42.4	Average Max	V	104	0	54.0	-11.6	Pass	RB
1817.635	87.7	2.6	-13.0	77.4	Peak [Scan]	V	200	0	105.3	-27.9	Pass	NRB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak


NRB Limit = Pk Emission – 20 dB = 125.3 – 20 = 105.3 dBμV

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 72 of 92

Test Freq.	927.5 MHz	Engineer	SB
Variant	Digital Emissions	Temp (°C)	28
Freq. Range	30 MHz - 1000 MHz	Rel. Hum.(%)	30
Power Setting	24 dBm	Press. (mBars)	100
Antenna	A09-F8TM 8.1 dBi		
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
928.076	58.3	7.4	-6.9	58.8	Peak [Scan]	V	100	0				FUND
875.591	43.4	7.2	-7.6	43.0	Peak [Scan]	V	100	0	105.9	-62.9	Pass	NRB
850.321	42.8	7.2	-7.8	42.2	Peak [Scan]	V	100	0	105.9	-63.7	Pass	NRB

Legend: DIG = Digital Device Emission; TX = Transmitter Emission; FUND = Fundamental Frequency
 NRB = Non-Restricted Band, Limit is 20 dB below Fundamental; RB = Restricted Band


NRB Limit = Pk Emission – 20 dB = 125.9 – 20 = 105.9 dBμV

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 73 of 92

Test Freq.	927.5 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	24 dBm	Press. (mBars)	1000
Antenna	A09-F8TM 8.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
1851.703	87.9	2.7	-12.8	77.8	Peak [Scan]	V	200	0	125.9	-48.1	Pass	NRB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak

NRB Limit = Pk Emission – 20 dB = 125.9 – 20 = 105.9 dBμV

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Specification

Limits

§15.205 (a) Except as shown in paragraph (d) of 15.205 (a), only spurious emissions are permitted in any of the frequency bands listed.

§15.205 (a) Except as shown in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.109 (b) The field strength of radiated emissions from a Class A digital device, as determined at a distance of 3 meters, shall not exceed the following:

§15.109 (b) Limit Matrix Class A digital device

Frequency(MHz)	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Measurement Distance (meters)
30-88	100	49.5	3
88-216	150	54.0	3
216-960	200	57.0	3
Above 960	500	60.0	3

Laboratory Measurement Uncertainty for Radiated Emissions

Measurement uncertainty	+5.6/ -4.5 dB
-------------------------	---------------

Traceability

Method	Test Equipment Used
Measurements were made per work instruction WI-03 'Measurement of Radiated Emissions'	0287, 0335, 0338, 0158, 0134, 0304, 0311, 0315, 0310, 0312, 0341

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



5.1.8.3. Receiver Radiated Spurious Emissions (above 1 GHz)

Industry Canada RSS-Gen §4.10, §6

Test Procedure

Radiated emissions above 1 GHz are measured in the anechoic chamber at a 3-meter distance on every azimuth in both horizontal and vertical polarities. The emissions are recorded and maximized as a function of azimuth by rotation through 360° with a spectrum analyzer in peak hold mode. Depending on the frequency band spanned a notch filter and waveguide filter was used to remove the fundamental frequency. The highest emissions relative to the limit are listed for each frequency spanned.

All measurements on any frequency or frequencies over 1 MHz are based on the use of measurement instrumentation employing an average detector function. All measurements above 1 GHz were performed using a minimum resolution bandwidth of 1 MHz.

All Sectors of the EUT were tested simultaneously

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

$$FS = R + AF + CORR - FO$$

where: FS = Field Strength

R = Measured Spectrum analyzer Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = CL – AG + NFL

CL = Cable Loss

AG = Amplifier Gain

FO = Distance Falloff Factor

NFL = Notch Filter Loss or Waveguide Loss

For example:

Given receiver input reading of 51.5 dB μ V; Antenna Factor of 8.5 dB; Cable Loss of 1.3 dB; Falloff Factor of 0 dB, an Amplifier Gain of 26 dB and Notch Filter Loss of 1 dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3 \text{ dB}\mu\text{V/m}$$


Conversion between dB μ V/m (or dB μ V) and μ V/m (or μ V) are done as:

$$\text{Level (dB}\mu\text{V/m)} = 20 * \text{Log (level (\mu\text{V/m}))}$$

$$40 \text{ dB}\mu\text{V/m} = 100 \mu\text{V/m}$$


$$48 \text{ dB}\mu\text{V/m} = 250 \mu\text{V/m}$$

Radiated Emission Measurement Setup – Above 1 GHz



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Radiated Emission Measurement Setup – Below 1 GHz




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 78 of 92

Yagi Receiver Spurious Emissions

Test Freq.	915 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	30 MHz - 1000 MHz	Rel. Hum.(%)	30
Power Setting	Not Applicable Receiver Emissions	Press. (mBars)	1000
Antenna	13 Element Welded Yagi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 79 of 92

Test Freq.	915 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	30
Power Setting	Not Applicable Receiver Emissions	Press. (mBars)	1000
Antenna	13 Element Welded Yagi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak												


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 80 of 92

Omni Receiver Spurious Emissions

Test Freq.	915 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	30 MHz - 1000 MHz	Rel. Hum.(%)	30
Power Setting	Not Applicable Receiver Emissions	Press. (mBars)	1000
Antenna	A09-F8TM 8.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 81 of 92

Test Freq.	915 MHz	Engineer	SB
Variant	N/A	Temp (°C)	28.5
Freq. Range	1000 MHz -18000 MHz	Rel. Hum.(%)	30
Power Setting	Not Applicable Receiver Emissions	Press. (mBars)	1000
Antenna	A09-F8TM 8.1 dBi	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission RB = Restricted Band (15.209 Limits); NRB = Non Restricted Band, Limit is 20dB below fundamental peak												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

5.1.9. AC Wireline Conducted Emissions (150 kHz – 30 MHz)


FCC, Part 15 Subpart C §15.207
Industry Canada RSS-Gen §7.2.2

ac Wireline Emissions Not Applicable as the device under test is a wireless module energized with dc power

Test Procedure

The EUT is configured in accordance with ANSI C63.4. The conducted emissions are measured in a shielded room with a spectrum analyzer in peak hold in the first instance. Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation. The highest emissions relative to the limit are listed.

Test Measurement Set up



Measurement set up for AC Wireline Conducted Emissions Test

Measurement Results for AC Wireline Conducted Emissions (150 kHz – 30 MHz)

Ambient conditions.

Temperature: 17 to 23 °C Relative humidity: 31 to 57 % Pressure: 999 to 1012 mbar

Radio Parameters:

Transmitting on Channel 26. 915.25 MHz

Transmit Power +30 dBm

Active antenna port was terminated in a 50Ω termination



Specification

Limit

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 $\mu\Omega$ line impedance stabilization network (LISN), see §15.207 (a) matrix below. Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

RSS-Gen §7.2.2

The radio frequency voltage that is conducted back into the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in the table below. The tighter limit applies at the frequency range boundaries.

§15.207 (a) and **RSS-Gen §7.2.2** Limit Matrix

The lower limit applies at the boundary between frequency ranges

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency

Laboratory Measurement Uncertainty for Conducted Emissions

Measurement uncertainty	± 2.64 dB
-------------------------	---------------


Traceability

Method	Test Equipment Used
Measurements were made per Sanmina work instruction	0190, 0193



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

6. PHOTOGRAPHS

6.1. General Measurement Test Set-Up




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



6.2. Radiated Emissions >1 GHz

Omni Directional Antenna



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Yagi Directional Antenna



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.


6.3. Radiated Emissions <1 GHz

Omni Directional Antenna



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Yagi Directional Antenna



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.

Yagi Directional Antenna



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Digi International XBPS3B
To: FCC 47 CFR Part15.247 & IC RSS-210
Serial #: DIGI22-U1 Rev B
Issue Date: 17th November 2011
Page: 91 of 92

7. TEST EQUIPMENT DETAILS

Asset #	Instrument	Manufacturer	Part #	Serial #
0070	Power Meter	Hewlett Packard	437B	3125U11552
0116	Power Sensor	Hewlett Packard	8485A	3318A19694
0117	Power Sensor	Hewlett Packard	8487D	3318A00371
0158	Barometer /Thermometer	Control Co.	4196	E2844
0184	Pulse Limiter	Rhode & Schwarz	ESH3Z2	357.8810.52
0190	LISN	Rhode & Schwarz	ESH3Z5	836679/006
0223	Power Meter	Hewlett Packard	HP EPM-442A	US37480256
0251	K-Cable	Megaphase	Sucoflex 104	Unknown
0252	K-Cable	Megaphase	Sucoflex 104	Unknown
0253	K-Cable	Megaphase	Sucoflex 104	Unknown
0256	K-Cable	Megaphase	Sucoflex 104	Unknown
0271	Amplifier	1 to 26.5 GHz	MiCOM	--
0287	EMI Receiver	Rhode & Schwarz	ESIB 40	100201
0293	BNC Cable	Megaphase	1689 1GVT4	15F50B001
0307	BNC Cable	Megaphase	1689 1GVT4	15F50B002
0310	2m SMA Cable	Micro-Coax	UFA210A-0-0787- 3G03G0	209089-001
0312	3m SMA Cable	Micro-Coax	UFA210A-1-1181- 3G0300	209092-001
0313	Coupler	Hewlett Packard	86205A	3140A01285
0314	30 dB N-Type Attenuator	ARRA	N944-30	1623
0335	Horn Antenna	The Electro-Mechanics Company	3117	00066580
0337	Amplifier	30 MHz – 3 GHz	MiCOM	--
0338	Antenna (30M-3GHz)	Sunol Sciences	JB3	A052907
0341	902-928 MHz Notch Filter	EWT	EWT-14-0199	H1
0363	Switch	MiCOM Labs	--	--

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



440 Boulder Court, Suite 200
Pleasanton, CA 94566, USA
Tel: 1.925.462.0304
Fax: 1.925.462.0306
www.micomlabs.com