

**Input-Output Inc.**  
**2888Transceiver**

**FCC ID: MCV-FSU101**

**Model No.: FSU101**

**FCC Rule Parts: 2, 90**

**General Overview**

A description of the theory of operation and product configuration is found in an attachment to this application and report.

**SPECIFICATIONS**

Transmitter

TX operating frequency: 217.0125 MHz (ch.1) – 219.9875 MHz (ch.16)

TX output power: 2 watts nominal, 1.42 watts measured

Modulation: FSK

Power requirements: Modulation is internally generated and limited  
7.2 VDC, approx. 2 A maximum current draw

Antenna connector: TNC- type

Frequency Tolerance .0001, ±219 Hz  
-30 to +50 C

85%-115% supply voltage at 25C

**Test Dates:** 8,9, 15 August 2006

**Test Site**

All tests reported here were performed at Compliance Certification Services.  
Conducted and radiated emissions were performed using test equipment with calibration  
traceable to NIST, and following test procedures accepted by the industry.



THOMAS N. COKENIAS  
Consultant, EMC&Radio Type Approvals  
Agent for Input-Output Inc.

## FCC CERTIFICATION INFORMATION

The following information is in accordance with FCC Rules, 47CFR Part 2.

**2.1033(c)2** FCC ID: MCV-FSU101

## 2.1033(c)4,5 Emission type and Frequency range

### Modulation: FSK from internal source

## 2.1033(c) 6 Range of Operating Power

2 watts peak (33.0 dBm)

## 2.1033(c) 7 Maximum Power Rating

31.52 dBm measured = 1.42 watts

Maximum allowed per 90.259(a): 2 watts

### 2.1033(c) 13 Description of Modulation System

4000 bps FSK digital, from internal source.

## 2.1033(c) 14 Test Data per 2.1046 – 2.1057


TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	Cal Due
EMI Receiver, 9 kHz ~ 2.9 GHz	Agilent / HP	8542E	3942A00286	2/4/07
RF Filter Section	Agilent / HP	85420E	3705A00256	2/4/07
Antenna, Bilog 30 MHz ~ 2 Ghz	Sunol Sciences	JB1	A121003	9/3/06
Spectrum analyzer	HP	8593EM	CCS T32	7/26/08
Digital Multimeter (voltmeter)	Fluke	26III	CCS3	1/3/07

### 2.1046 RF Output Power Measurements

Requirement/Limit: 90.259(a)5

#### Test set-up:

Figure 1




#### Test Procedures

1. Set the transmitter to produce maximum modulated power at the desired frequency
2. Set analyzer RBW and VBW to 300 kHz, much greater than 99% BW
3. Read PEAK output power

#### Test Results


Maximum output power 31.52 dBm = 1.42 watts. Refer to spectrum analyzer plots below.

### Channel 1 Output Power



### Channel 11 Output Power

### Channel 16 Output Power



## Section 2.1047 Modulation Characteristics

### Requirement/Limit: 90.210(c)

(c) *Emission Mask C*. For transmitters that are not equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier output power (P) as follows:

- (1) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 5 kHz, but not more than 10 kHz: At least  $83 \log (f_d/5)$  dB;
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 10 kHz, but not more than 250 percent of the authorized bandwidth: At least  $29 \log (f_d^2/11)$  dB or 50 dB, whichever is the lesser attenuation;
- (3) On any frequency removed from the center of the authorized bandwidth by more than 250 percent of the authorized bandwidth: At least  $43 + 10 \log (P)$  dB.

**Test set-up:** Figure 1

### Test Procedures


- a. Set the transmitter to produce maximum modulated power at the desired frequency
- b. Set RBW and VBW to required values and record emission masks.

### Test Results


**PASS.** Refer to attached spectrum analyzer charts.

Emissions are shown with mask lines superimposed on spectrum analyzer charts.

## Channel 1 Emissions Mask



## Channel 16 Emissions Mask



**Section 2.1049 Occupied Bandwidth**  
**Requirement/Limit: 90.209(a)5**

(5) Unless specified elsewhere, channel spacings and bandwidths that will be authorized in the following frequency bands are given in the following table.

Standard Channel Spacing/Bandwidth

Frequency band (MHz)	Channel spacing (kHz)	Authorized bandwidth (kHz)
216-2205.....	6.25	20/11.25/6 \5\

**Test set-up:** Figure 1

**Test Procedures and Results:**

-20 dBc occupied bandwidth was measured manually.


**Test Results**

Refer to spectrum analyzer plots below

## Occupied Bandwidth, Channel 1



## Occupied Bandwidth, Channel 16



**Section 2.1051 Spurious and Harmonic Emissions at Antenna Terminals**  
**Requirement/Limit: 90.210(c)3**

(3) On any frequency removed from the center of the authorized bandwidth by more than 250 percent of the authorized bandwidth: At least  $43 + 10 \log (P)$  dB.

**Test set-up:**

Refer to Figure 3 above


**Test Procedures**

1. Record transmitter output spectrum from 1 MHz to 10<sup>th</sup> harmonic of TX output frequency
2. Plot spectrum analyzer output traces.

**Test Results**

**PASS.** Refer to data plots below.


Channel 1 Spurious emissions, antenna port



Test Item: All

Description: Demo

Channel 16 Spurious emissions, antenna port



Description: Demo



### Section 2.1053 Field Strength of Spurious and Harmonic Radiation

#### Requirement/Limit: 90.210(c)3

(3) On any frequency removed from the center of the authorized bandwidth by more than 250 percent of the authorized bandwidth: At least  $43 + 10 \log (P)$  dB.

#### Test Set-Up

**Figure 2**



### **Minimum Requirement**

-13 dBm ERP beyond 250% of authorized bandwidth

### **Test Method**

The antenna output port of the EUT was terminated with a 50-ohm load. With the transmitter operating at full power, the EUT was rotated 360° and the search antenna was raised and lowered in both polarities, all in an attempt to maximize the levels of the received emission for each harmonic and spurious emission up to 10 fo.

The EUT was removed and was replaced by a substitution antenna connected via coax to a signal generator. The generator output was set to each emission frequency detected, the search antenna was raised and lowered, the turntable was rotated, and until the maximum emission level was obtained. The signal generator output level was adjusted to match the radiated emission level from the EUT. After correcting for substitution antenna factor and generator cable loss, output power level is compared to the limit.


### **Test Results**

**Pass.** All emissions detected were at least 21.9 dB below limits. Refer to worst-case data below.

**High Frequency Substitution Measurement**  
Compliance Certification Services, Morgan Hill 5m Chamber Site

Company: Input-output  
Project #: 06U10476  
Date: 08/08/2006  
Test Engineer: Gordon Andrews  
Configuration: EUT and laptop  
Mode: Tx  
Model Number: FSU 217-220 MHz Part 90 C Transceiver

**Test Equipment:**



f GHz	SA reading (dBuV/m)	Ant. Pol. (H/V)	SG reading (dBm)	CL (dB)	Gain (dBi)	Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)
<b>Channel 1</b>									
1.085	70.8	V	-48.0	1.4	5.1	2.9	-46.4	-13.0	-33.4
1.300	81.7	V	-37.1	1.5	5.8	3.7	-34.9	-13.0	-21.9
1.520	60.2	V	-58.6	1.5	6.6	4.5	-55.7	-13.0	-42.7
1.740	73.5	V	-45.4	1.6	7.4	5.2	-41.8	-13.0	-28.8
1.960	71.9	V	-47.0	1.7	8.2	6.0	-42.7	-13.0	-29.7
2.090	54.4	V	-64.4	1.8	8.5	6.4	-59.8	-13.0	-46.8
2.180	65.6	V	-53.2	1.8	8.7	6.6	-48.4	-13.0	-35.4
1.087	68.0	H	-50.1	1.4	5.1	2.9	-48.5	-13.0	-35.5
1.300	71.6	H	-46.5	1.5	5.8	3.7	-44.3	-13.0	-31.3
1.520	58.0	H	-60.1	1.5	6.6	4.5	-57.2	-13.0	-44.2
1.740	70.1	H	-48.1	1.6	7.4	5.2	-44.5	-13.0	-31.5
1.960	67.3	H	-50.9	1.7	8.2	6.0	-46.6	-13.0	-33.6
2.090	51.7	H	-66.9	1.8	8.5	6.4	-62.3	-13.0	-49.3
2.180	61.2	H	-57.4	1.8	8.7	6.6	-52.6	-13.0	-39.6
<b>Channel 16</b>									
1.100	71.1	V	-47.7	1.4	5.1	3.0	-46.1	-13.0	-33.1
1.324	79.2	V	-39.6	1.5	5.9	3.8	-37.3	-13.0	-24.3
1.770	68.7	V	-50.2	1.6	7.5	5.3	-46.5	-13.0	-33.5
1.990	66.1	V	-52.8	1.7	8.3	6.1	-48.4	-13.0	-35.4
1.100	70.9	H	-47.2	1.4	5.1	3.0	-45.5	-13.0	-32.5
1.324	75.3	H	-42.8	1.5	5.9	3.8	-40.5	-13.0	-27.5
1.770	69.4	H	-48.8	1.6	7.5	5.3	-45.1	-13.0	-32.1
1.990	65.8	H	-52.4	1.7	8.3	6.1	-48.0	-13.0	-35.0

Rev. 5.1.6

**2.1055 Frequency Stability**

**Requirement/Limit: 90.213(a)**


(a) Unless noted elsewhere, transmitters used in the services governed by this part must have a minimum frequency stability as specified following table.

Minimum Frequency Stability  
[Parts per million (ppm)]

Frequency range (MHz)	Fixed base stations	Mobile stations		
		Over 2 watts	2 watts or less	output power
216-220.....	1.0	-----	1.0	
Frequency Tolerance :		.0001% (1 part per million)		
		= $\pm 217$ Hz at 217.1250MHz		
		= $\pm 219$ Hz at 219.9875 MHz		
Temperature Range:		-30C to +50 C		
Supply Voltage Range:		85% - 115% nominal 13.6 VDC (11.6 - 15.6 VDC)		

## Test Setup

Figure 3



## Test Procedures

1. Spectrum analyzer center frequency was set to channel 1 operating frequency. Frequency was measured at +25C using spectrum analyzer marker function.
2. The transmitter was allowed to stabilize at every 10 degrees C from -30C to +50C and measurements were recorded at each temperature.


## Test Results

<u>Temp, °C</u>	<u>Frequency</u>	<u>Delta, Hz</u>
25	217.012501	+1
50	217.012409	-91
40	217.012533	-67
30	217.012509	+9
20	217.012512	+12
10	217.012535	+35
0	217.012481	-19
-10	217.012522	+22
-20	217.012514	+14
-30	217.012500	0

## Operating Voltage v Frequency

### Test Setup

Figure 4



### Test Procedures

At 25C the power supply voltage was varied between 85% and 115% nominal.

### Test Results

<u>Supply Voltage, DC</u>	<u>Frequency</u>	<u>Delta</u>
7.2 (Nominal)	217.012481	-19
8.28 (115%)	217.012478	-22
6.12 ( 85%)	217.012478	-22

### **15.109 Unintentional radiated**

Receiver radiated emissions tests were performed concurrently with TX radiated emissions tests. No emissions were detected from receiver portion of the EUT.

Emissions from the digital portion of the EUT were tested to class A limits as the EUT is not sold or used in residences.

### Test Set-up

Figure 2.

## **Test Procedures**

The EUT was placed on a turntable located in a 5m anechoic chamber. The EUT was tested twice, once with the transmitter ON, the second time with the transmitter off but with the rest of the circuitry active (digital board, GPS receiver, and Bluetooth module).

EUT emissions were maximized by raising the search antenna 1-4 m in both horizontal and vertical polarities, and by rotating the turntable through a full 360 degrees.

## **Test Results**


Test plots and tabulated data are presented below for both test conditions, transmitter ON and transmitter OFF. The EUT meets class a limits for both conditions of operation.

Transmitter ON (Vertical)



561F Monterey Road  
Morgan Hill, CA 95037  
Tel: (408) 463-0888  
Fax: (408) 463-0885

Data#: 6 File#: Input-output FSU.emi Date: 08-08-2006 Time: 12:05:19



(Audix ATC)

Trace: 5

Ref Trace:

Condition: FCC CLASS-A VERTICAL  
Test Operator: : Gordon Andrews  
Company: : Input-Output  
Project #: : 06U10476  
Configuration: : EUT with laptop on floor  
Mode of Operation: Tx  
: FSU 217-220 MHz Transceiver

Page: 1


Freq	Read		Limit	Over	Remark	
	Level	Factor				
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	88.200	23.18	8.56	31.74	43.50	-11.76 Peak
2	121.180	21.83	15.16	36.99	43.50	-6.51 Peak
3	361.740	20.76	17.20	37.96	46.40	-8.44 Peak
4	482.990	24.87	19.89	44.76	46.40	-1.64 Peak
5	643.040	17.32	22.23	39.55	46.40	-6.85 Peak
6	803.090	13.77	24.59	38.36	46.40	-8.04 Peak

Transmitter ON (Horizontal)



561F Monterey Road  
Morgan Hill, CA 95037  
Tel: (408) 463-0888  
Fax: (408) 463-0885

Data#: 4 File#: Input-output FSU.emi Date: 08-08-2006 Time: 11:48:19



Ref Trace:

Condition: FCC CLASS-A VERTICAL  
Test Operator: : Gordon Andrews  
Company: : Input-Output  
Project #: : 06U10476  
Configuration: : EUT with laptop on floor  
Mode of Operation: TX  
: FSU 217-220 MHz Transceiver

Page: 1


Freq MHz	Read		Limit Line	Over Limit	Remark
	Level dBuV	Factor			
	MHz	dBuV	dB	dBuV/m	dBuV/m
1	33.880	17.45	19.05	36.50	39.00 -2.50 Peak
2	121.180	20.09	15.16	35.25	43.50 -8.25 Peak
3	441.280	23.16	19.02	42.18	46.40 -4.22 Peak
4	482.990	20.35	19.89	40.24	46.40 -6.16 Peak
5	643.040	14.56	22.23	36.79	46.40 -9.61 Peak
6	803.090	12.95	24.59	37.54	46.40 -8.86 Peak

Transmitter OFF, worst case (Vertical)



561F Monterey Road  
Morgan Hill, CA 95037  
Tel: (408) 463-0888  
Fax: (408) 463-0885

Data#: 11 File#: Input-output FSU.emi Date: 08-24-2006 Time: 16:49:16



(Audix ATC)

Trace: 7

Ref Trace:


Condition: FCC CLASS-A VERTICAL  
Test Operator: : Gordon Andrews  
Company: : Input-Output  
Project #: : 06U10476  
Configuration: : EUT with laptop on floor  
Mode of Operation: Rx  
: FSU 217-220 MHz Transceiver

Page: 1


Freq	Read		Limit	Over	Remark
	Level	Factor			
MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	121.180	15.01	15.16	30.17	43.50 -13.33 Peak
2	189.080	13.77	12.93	26.70	43.50 -16.80 Peak
3	482.990	18.37	19.89	38.26	46.40 -8.14 Peak
4	643.040	6.20	22.23	28.43	46.40 -17.97 Peak
5	722.580	3.96	23.50	27.46	46.40 -18.94 Peak
6	963.140	3.18	26.61	29.79	49.50 -19.71 Peak

## **Test Set-up Photographs**

Antenna port conducted emissions



Radiated emissions



**Frequency Stability Test (Frequency v Temperature)**



**Frequency Stability (Frequency v Operating Voltage)**

