

RF Exposure Evaluation declaration

Product Name	802.11n, 2.4G 1T1R Wireless LAN USB Module
Model No.	WN4608R
FCC ID	MDZLTRT5370-WL

Applicant	Amtran Technology Co Ltd
Address	17F, No. 268, Lien Chen Rd. Chung Ho City, Taipei County, Taiwan 235

Date of Receipt	Nov. 03, 2011
Date of Declaration	Nov. 14, 2011
Report No.	11B163R-RFUSP32V01-A

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product : 802.11n, 2.4G 1T1R Wireless LAN USB Module
 Test Item : RF Exposure Evaluation
 Test Site : No.3 OATS

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.97 dBi in logarithm scale.

802.11b (1Mbps) Output Power Into Antenna & RF Exposure Evaluation Distance (3.97 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412.00	83.7529	0.041565
6	2437.00	85.1138	0.042241
11	2462.00	84.1395	0.041757

The RF exposure at 20 cm is below limit.

802.11g (6Mbps) Output Power Into Antenna & RF Exposure Evaluation Distance (3.97 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412.00	259.4179	0.128745
6	2437.00	267.3006	0.132657
11	2462.00	272.8978	0.135435

The RF exposure at 20 cm is below limit.

802.11n-20MHz_7.2Mbps - 2.4G Band**Output Power Into Antenna & RF Exposure Evaluation Distance (3.97 dBi):**

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
01	2412.00	246.6039	0.122386
06	2437.00	252.3481	0.125236
11	2462.00	246.6039	0.122386

The RF exposure at 20 cm is below limit.

802.11n-40MHz_15Mbps - 2.4G Band**Output Power Into Antenna & RF Exposure Evaluation Distance (3.97 dBi):**

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
01	2422.00	118.3042	0.058712
04	2437.00	127.9381	0.063494
07	2452.00	120.5036	0.059804

The RF exposure at 20 cm is below limit.