

MPE Report

Test Report Number	GLS-21090842-L-FCC-MPE
FCC ID	MG3-59007000007
Applicant	Universal Electronic Inc.
Applicant Address	201 East Sandpointe Ave., 7th Floor, Santa Ana, CA 92707
Product Name	UE61 Module
Model (s)	UE61V
Date of Receipt	09/08/2021
Date of Test	11/24/2021- 12/07/2021
Report Issue Date	12/28/2022
Test Standards	47 CFR §1.1307(b), 47 CFR §1.1310 RSS-102 Issue 5: Feb 2021
Test Result	PASS
	<p>Issued by:</p> <p>Vista Compliance Laboratories 1261 Puerta Del Sol, San Clemente, CA 92673 USA www.vista-compliance.com</p>
 <hr/> <p>Devin Tai (Test Engineer)</p>	 <hr/> <p>David Zhang (Technical Manager)</p>
<p>This report is for the exclusive use of the applicant. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Note that the results contained in this report pertain only to the test samples identified herein, and the results relate only to the items tested and the results that were obtained in the period between the date of initial receipt of samples and the date of issue of the report. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested and the results thereof based upon the information provided to us. The applicant has 60 days from date of issuance of this report to notify us of any material error or omission. Failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies. This report is not to be reproduced by any means except in full and in any case not without the written approval of Vista Laboratories.</p>	

REVISION HISTORY

Report Number	Version	Description	Issued Date
GLS-21090842-L-FCC-MPE	01	Initial report	12/28/2022

TABLE OF CONTENTS

1 GENERAL INFORMATION.....4

1.1 Applicant.....4

1.2 Product information.....4

1.3 Test standard and method5

2 TEST SITE INFORMATION.....5

3 RF EXPOSURE6

3.1 Limits for Maximum Permissible Exposure (MPE).....6

3.2 MPE Calculation Formula6

3.3 Classification6

3.4 Antenna Gain6

4 TEST RESULTS.....7

1 General Information

1.1 Applicant

Applicant	UNIVERSAL ELECTRONICS INC
Applicant address	201 E. Sandpointe Ave., 7th Floor Santa Ana CA 92707
Manufacturer	UNIVERSAL ELECTRONICS INC
Manufacturer Address	201 E. Sandpointe Ave., 7th Floor Santa Ana CA 92707

1.2 Product information

Product Name	UE61 Module
Product Description	UE61V
Model Number	N/A
Family Models	N/A
Serial Number	N/A
Frequency Band	BLE: 2402-2480MHz WLAN: 2412-2462MHz
Type of modulation	BLE: GFSK WLAN_2.4G: CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Equipment Class	DTS
Antenna Information	PCB Antenna Antenna Gain: 1.5dBi ±0.5dB
Clock Frequencies	N/A
Input Power	DC 3.0V
Power Adapter Manufacturer/Model	N/A
Power Adapter SN	N/A
Hardware version	N/A
Software version	N/A
Additional Info	N/A

1.3 Test standard and method

Test standard	47 CFR §1.1307(b), 47 CFR §1.1310 47 CFR §2.1093
Test method	47 CFR §1.1307(b), 47 CFR §1.1310 47 CFR §2.1093

2 Test Site Information

Lab performing tests	Vista Laboratories, Inc.
Lab Address	1261 Puerta Del Sol, San Clemente, CA 92673 USA
Phone Number	+1 (949) 393-1123
Website	www.vista-compliance.com

Test Condition	Temperature	Humidity	Atmospheric Pressure
RF Testing	23.2°C	57.5%	996 mbar
Radiated Emission Testing	23.2°C	57.5%	996 mbar

3 RF Exposure

3.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

3.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * pi * r^2)$$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

3.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

3.4 Antenna Gain

The antenna type is PCB trace antenna with 1.5 ± 0.5 dBi gain.

4 Test Results

Mode	Max Power (dBm)	Max Power (mW)	Turn-Up Tolerance	Max Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
BLE	7.956	6.25	±1dB	2.0	20	0.00248	1
WLAN	16.28	42.46	±1dB	2.0	20	0.01686	1

Conclusion:

The worst-case ratio = 0.01686 < 1

The above results show that the device complies with the MPE requirement.

---END---