

FCC PART 15, SUBPART B and C
TEST REPORT

for

AT&T RC82V GEO REMOTE CONTROL 2018

Model: R35602BA00-00004

Prepared for

UNIVERSAL ELECTRONICS, INC.
201 EAST SANDPOINTE AVENUE, 8TH FLOOR
SANTA ANA, CALIFORNIA 92707

Prepared by: 

JAMES ROSS

Approved by: 

KYLE FUJIMOTO

COMPATIBLE ELECTRONICS INC.
114 OLINDA DRIVE
BREA, CALIFORNIA 92823
(714) 579-0500

DATE: NOVEMBER 9, 2018

	REPORT BODY	APPENDICES					TOTAL
		A	B	C	D	E	
PAGES	20	2	2	2	13	44	83

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.



TABLE OF CONTENTS

Section / Title	PAGE
GENERAL REPORT SUMMARY	4
SUMMARY OF TEST RESULTS	5
1. PURPOSE	6
2. ADMINISTRATIVE DATA	7
2.1 Location of Testing	7
2.2 Traceability Statement	7
2.3 Cognizant Personnel	7
2.4 Date Test Sample was Received	7
2.5 Disposition of the Test Sample	7
2.6 Abbreviations and Acronyms	7
3. APPLICABLE DOCUMENTS	8
4. DESCRIPTION OF TEST CONFIGURATION	9
4.1.1 Cable Construction and Termination	9
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT	10
5.1 EUT and Accessory List	10
6. TEST SITE DESCRIPTION	12
6.1 Test Facility Description	12
6.2 EUT Mounting, Bonding and Grounding	12
6.3 Measurement Uncertainty	12
7. CHARACTERISTICS OF THE TRANSMITTER	13
7.1 Channel Number and Frequencies	13
7.2 Antenna	13
8. TEST PROCEDURES	14
8.1 RF Emissions	14
8.1.1 Conducted Emissions Test	14
8.1.2 Radiated Emissions Test	15
8.1.3 RF Emissions Test Results	16
8.2 DTS Bandwidth	17
8.3 Peak Output Power	17
8.4 Emissions in Non-restricted Frequency Bands	18
8.5 RF Band Edges	18
8.6 Spectral Density Test	19
9. CONCLUSIONS	20

LIST OF APPENDICES

APPENDIX	TITLE
A	Laboratory Accreditations and Recognitions
B	Modifications to the EUT
C	Additional Models Covered Under This Report
D	Diagrams and Charts <ul style="list-style-type: none">• Test Setup Diagrams• Antenna and Effective Gain Factors
E	Data Sheets

LIST OF FIGURES

FIGURE	TITLE
1	Conducted Emissions Test Setup
2	Layout of the Semi-Anechoic Test Chamber

LIST OF TABLES

TABLE	TITLE
1.0	Radiated Emission Results

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced without the written permission of Compatible Electronics, unless done so in full.

This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the federal government.

Device Tested: AT&T RC82V Geo Remote Control 2018
Model: R35602BA00-00004
S/N: N/A

Product Description: The EUT is a universal remote control that allows users to operate devices using radio frequency (RF) signals and/or infrared (IR) signals.

Modifications: The EUT was not modified in order to meet the specifications.

Customer: Universal Electronics, Inc.
201 East Sandpointe Avenue, 8th Floor
Santa Ana, California 92707

Test Dates: October 26, 27 and 29, 2018

Test Specification covered by accreditation:



Test Specifications: Emissions requirements
CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.207, 15.209,
and 15.247

Test Procedures: ANSI C63.4: 2013, ANSI C63.10: 2014

Test Deviations: The test procedure was not deviated from during the testing.

SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS
1	Conducted RF Emissions, 150 kHz - 30 MHz	This test was not performed because the EUT is battery powered only.
2	Radiated RF Emissions, 9 kHz – 25000 MHz	Complies with the Class B limits of CFR Title 47, Part 15, Subpart B; and the limits of CFR Title 47, Part 15 Subpart C, 15.205, 15.209 and 15.247 (d) Highest reading in relation to spec limit 50.08 (Avg) dBuV/m @ 2370.00 MHz (*U = 3.67 dB)
3	DTS Bandwidth	Complies with the relevant requirements of CFR Title 47, Part 15, Subpart C, section 15.247 (a)(2)
4	Peak Output Power	Complies with the relevant requirements of FCC Title 47, Part 15, Subpart C, section 15.247 (b)(3)
5	RF Band Edges	Complies with the relevant requirements of FCC Title 47, Part 15, Subpart C, section 15.247 (d)
6	Spectral Density	Complies with the relevant requirements of FCC Title 47, Part 15, Subpart C, section 15.247 (e)

1. PURPOSE

This document is a qualification test report based on the emissions tests performed on the AT&T RC82V Geo Remote Control 2018, Model: R35602BA00-00004. The emissions measurements were performed according to the measurement procedure described in ANSI C63.4 and ANSI C63.10. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the Class B specification limits defined by CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.207, 15.209, and 15.247.



2. ADMINISTRATIVE DATA

2.1 Location of Testing

The emissions tests described herein were performed at the test facility of Compatible Electronics, 114 Olinda Drive, Brea, California 92823.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Universal Electronics, Inc.

Jesse Mendez Staff Engineer, Electrical

Compatible Electronics Inc.

Tom Szynal Test Technician

James Ross Test Engineer

Kyle Fujimoto Test Engineer

2.4 Date Test Sample was Received

The test sample was received prior to the initial date of testing.

2.5 Disposition of the Test Sample

The test sample has not been returned to Universal Electronics, Inc. as of the date of this test report.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
ITE	Information Technology Equipment
DoC	Declaration of Conformity
N/A	Not Applicable
Tx	Transmit
Rx	Receive
Inc.	Incorporated
RF	Radio Frequency
IR	Infrared
AT&T	American Telephone & Telegraph

3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this emissions Test Report.

SPEC	TITLE
FCC Title 47, Part 15 Subpart C	FCC Rules – Radio frequency devices (including digital devices) – Intentional Radiators
FCC Title 47, Part 15 Subpart B	FCC Rules – Radio frequency devices (including digital devices) – Unintentional Radiators
558074 D01 DTS Meas Guidance v05	Guidance for Performing Compliance Measurements on Digital Transmissions Systems (DTS) Operating Under Section 15.247
EN 50147-2: 1997	Anechoic chambers. Alternative test site suitability with respect to site attenuation
ANSI C63.4 2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10 2013	American National Standard for Testing Unlicensed Wireless Devices

4. DESCRIPTION OF TEST CONFIGURATION

The AT&T RC82V Geo Remote Control 2018, Model: R35602BA00-00004 (EUT) was setup in a stand-alone configuration. The EUT was investigated in all three orthogonal axis (X, Y, & Z) at its low, middle, and high channels (2402 MHz, 2442 MHz, and 2480 MHz), respectively. During the testing, the EUT was continuously transmitting in its RF mode, as well as in its Voice and IR mode.

Fresh batteries were installed inside the EUT prior to the testing. The EUT was programmed via the Radio Control Console v4.0.3 firmware.

The firmware is stored in one of the network drives in the company's server.

The final radiated emissions data for the EUT was taken in the Y-axis (worse case). Please see Appendix E for the data sheets.

4.1.1 Cable Construction and Termination

The EUT had no external cables.

5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT**5.1 EUT and Accessory List**

EQUIPMENT	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	FCC ID
AT&T RC82V GEO REMOTE CONTROL 2018 (EUT)	UNIVERSAL ELECTRONICS, INC.	R35602BA00-00004	N/A	MG3-R35602
LAPTOP*	HEWLETT PACKARD	HSTNN-C82C	N/A	N/A
AC ADAPTER FOR LAPTOP*	HEWLETT PACKARD	HSTNN-DA40	N/A	DoC
PROGRAM BOARD*	UNIVERSAL ELECTRONICS, INC.	RMF-TX300C	N/A	N/A
FIRMWARE*	UNIVERSAL ELECTRONICS, INC.	RADIO CONTROL CONSOLE	v4.0.3	N/A

*Used to program the EUT only and was removed prior to the testing

5.2 Emissions Test Equipment

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
RF RADIATED EMISSIONS TEST EQUIPMENT					
TDK TestLab	TDK RF Solutions, Inc.	9.22	700145	N/A	N/A
EMI Receiver, 20 Hz – 26.5 GHz	Keysight Technologies	N9038A	MY51210150	July 26, 2018	1 Year
System Controller	Sunol Sciences Corporation	SC110V	112213-1	N/A	N/A
Turntable	Sunol Sciences Corporation	2011VS	N/A	N/A	N/A
Antenna-Mast	Sunol Sciences Corporation	TWR95-4	112213-3	N/A	N/A
Loop Antenna	Com-Power	AL-130R	121090	February 9, 2017	2 Year
CombiLog Antenna	Com-Power	AC-220	61060	July 27, 2017	2 Year
Horn Antenna	Com-Power	AH-118	071175	February 22, 2018	2 Year
Horn Antenna	Com-Power	AH-826	71957	N/A	N/A
Preamplifier	Com-Power	PAM-118A	551024	May 10, 2018	1 Year
Preamplifier	Com-Power	PA-840	711013	May 10, 2018	1 Year
Computer	Hewlett Packard	p6716f	MXX1030PX0	N/A	N/A
LCD Monitor	Hewlett Packard	52031a	3CQ046N3MG	N/A	N/A

6. TEST SITE DESCRIPTION

6.1 Test Facility Description

Please refer to section 2.1 and 7.1 of this report for emissions test location.

6.2 EUT Mounting, Bonding and Grounding

For frequencies 1 GHz and below: The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 0.8 meters above the ground plane.

For frequencies above 1 GHz: The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 1.5 meters above the ground plane.

The EUT was not grounded.

6.3 Measurement Uncertainty

The uncertainty values are in the table below.

The uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level, using a coverage factor of $k=2$

MEASUREMENT TYPE	PARTICULAR CONFIGURATION	UNCERTAINTY VALUES
RADIATED EMISSIONS	3-METER CHAMBER, COMBILOG ANTENNA	3.26 dB (Vertical) 3.19 dB (Horizontal)
RADIATED EMISSIONS	3-METER CHAMBER, HORN ANTENNA	3.67 dB

7. CHARACTERISTICS OF THE TRANSMITTER

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

7.1 Channel Number and Frequencies

The EUT uses a total of 40 channels which are spaced 2 MHz apart.

The low channel (channel 0) is 2402 MHz
The high channel (channel 39) is 2480 MHz

7.2 Antenna

The EUT has a 2 dBi gain trace antenna.



8. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

8.1 RF Emissions

8.1.1 Conducted Emissions Test

The EMI Receiver was used as a measuring meter. A quasi-peak and/or average reading was taken only where indicated in the data sheets. A transient limiter was used for the protection of the EMI Receiver input stage, and the offset was adjusted accordingly to read the actual data measured. The LISN output was measured using the EMI Receiver. The output of the second LISN was terminated by a 50-ohm termination. The effective measurement bandwidth used for this test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding, and grounding of the EUT. The EUT was powered through the LISN, which was bonded to the ground plane. The LISN power was filtered and the filter was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI 63:4. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The conducted emissions from the EUT were maximized for operating mode as well as cable placement. The final data was collected under program control by computer software. The final qualification data is located in Appendix E.

The EUT was tested at 120 VAC. The six highest emissions are listed in Table 1.0.

Test Results:

This test was not performed because the EUT operates on battery power only and cannot be connected to the AC public mains.

8.1.2 Radiated Emissions Test

The EMI Receiver was used as the measuring meter. Preamplifiers were used to increase the sensitivity of the instrument. The EMI Receiver was initially used with the Analyzer mode feature activated. In this mode, the EMI receiver can then record the actual frequency to be measured. This final reading is then taken accurately in the EMI Receiver mode, which takes into account the cable loss, amplifier gain and antenna factors, so that a true reading is compared to the true limit. The effective measurement bandwidth used for the radiated emissions test was according to the frequency measured.

The frequencies below 1 GHz were quasi-peaked using the quasi-peak detector of the EMI Receiver.

The frequencies above 1 GHz were averaged using the RMS detector average function on the EMI Receiver.

The EMI test chamber of Compatible Electronics, Inc. was used for radiated emissions testing. This test site is in full compliance with ANSI C63.4. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength). The gunsight method was used when measuring with the horn antenna in order to ensure accurate results.

The EUT was tested at a 3-meter test distance. The six highest emissions are listed in Table 1.0.

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE	EFFECTIVE MEASUREMENT BANDWIDTH	TRANSDUCER
9 kHz to 150 kHz	200 Hz	Loop Antenna
150 kHz to 30 MHz	9 kHz	Loop Antenna
30 MHz to 1 GHz	120 kHz	CombiLog Antenna
1 GHz to 25 GHz	1 MHz	Horn Antenna

Test Results:

The EUT complies with the **Class B** limits of **CFR** Title 47, Part 15, Subpart B; and Subpart C sections 15.205, 15.209, and 15.247 (d) for radiated emissions.

8.1.3 RF Emissions Test Results

Table 1.0 RADIATED EMISSION RESULTS
AT&T RC82V Geo Remote Control 2018
Model: R35602BA00-00004

Frequency (MHz)	Average EMI Reading (dBuV/m)	Average Specification Limit (dBuV/m)	Delta (Cor. Reading – Spec. Limit) (dB)
2370.00 (H) (X-Axis)	50.08	53.97	-3.89
2369.80 (V) (Y-Axis)	50.07	53.97	-3.90
7440.00 (H) (X-Axis)	47.58	53.97	-6.39
7326.00 (H) (X-Axis)	47.01	53.97	-6.96
7440.00 (H) (Z-Axis)	46.97	53.97	-7.00
7326.00 (H) (Z-Axis)	45.94	53.97	-8.03

Notes:

- * The complete emissions data is given in Appendix E of this report.
- (V) Vertical
- (H) Horizontal

8.2 DTS Bandwidth

The DTS Bandwidth was measured using the EMI Receiver. The following steps were performed for measuring the DTS Bandwidth.

1. Set RBW = 100 kHz
2. Set the video bandwidth (VBW) to equal or greater than 3 times the RBW
3. Detector = Peak
4. Trace Mode = Max Hold
5. Sweep = Auto Couple
6. Allow the trace to stabilize
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Results:

The EUT complies with the relevant requirements of FCC Title 47, Part 15, Subpart C section 15.247 (a)(2).

8.3 Peak Output Power

The Peak Output Power was measured using radiated emissions method described in section 8.1.2 of this test report. The peak power was calculated by the following equation:

$$P = [(E \cdot D)^2] / (30 G)$$

P = Power in Watts for which you are solving

E = the measured maximum field strength in V/m utilizing the widest available RBW.

G = the numeric gain of the transmitting antenna over an isotropic radiator.

Test Results:

The EUT complies with the relevant requirements of FCC Title 47, Part 15, Subpart C section 15.247 (b)(3). The maximum peak output power is less than 1 Watt. Please see the data sheets located in Appendix E.

8.4 Emissions in Non-restricted Frequency Bands

The procedure described in section 8.1.2 of this test report was used to maximize the emissions. The procedure of section 11.11.2 of ANSI C63.10 was then used to determine that the highest reference level was the middle channel, which was 104.46 dBuV/m.

Test Results:

The EUT complies with the relevant requirements of FCC Title 47, Part 15, Subpart C section 15.247 (d). The emissions in the non-restricted frequency bands are at least attenuated by 20 dB below the highest reference level established by section 11.11.2 of ANSI C63.10. Please see the data sheets located in Appendix E.

8.5 RF Band Edges

The RF band edges were taken at 2390 MHz when the EUT was on the low channel and 2483.5 MHz when the EUT was on the high channel using the EMI Receiver. A preamplifier was used to boost the signal level, with the plots being taken at a 3 meter test distance. The radiated emissions test procedure as describe in section 8.1.2 of this test report was used to maximize the emission.

Test Results:

The EUT complies with the relevant requirements of FCC Title 47, Part 15, Subpart C section 15.247 (d). The RF power at the restricted bands closest to the band edges at 2390 MHz and 2483.5 MHz also meet the limits of section 15.209. Please see the data sheets located in Appendix E.

8.6 Spectral Density Test

The spectrum density output was measured using radiated emissions method described in section 8.1.2 of this test report. The spectral density was calculated by the following equation.

$$P = [(E \cdot D)^2] / (30 G)$$

P = Power in Watts for which you are solving

E = the measured maximum field strength in V/m utilizing the an RBW of 3 kHz.

G = the numeric gain of the transmitting antenna over an isotropic radiator.

The EMI Receiver was setup as follows:

1. Set analyzer center frequency to DTS channel center frequency
2. Set the span to at least 1.5 times the OBW.
3. Set the RBW to 3 kHz
4. Set the VBW $\geq 3 \times$ RBW
5. Detector = Peak
6. Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW
7. Sweep time = auto couple
8. Use the peak marker function to determine the maximum amplitude level

Test Results:

The EUT complies with the relevant requirements of FCC Title 47, Part 15, Subpart C section 15.247 (e).

9. CONCLUSIONS

The AT&T RC82V Geo Remote Control 2018, Model: R35602BA00-00004 (EUT), as tested, meets all of the specification limits defined in FCC Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.207, 15.209, and 15.247.




APPENDIX A***LABORATORY ACCREDITATIONS AND RECOGNITIONS***

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044

LABORATORY ACCREDITATIONS AND RECOGNITIONS



For US, Canada, Australia/New Zealand, Japan, Taiwan, Korea, and the European Union, Compatible Electronics is currently accredited by NVLAP to ISO/IEC 17025.

For the most up-to-date version of our scopes and certificates please visit <http://celectronics.com/quality/scope/>

Quote from ISO-ILAC-IAF Communiqué on 17025:

"A laboratory's fulfilment of the requirements of ISO/IEC 17025:2005 means the laboratory meets both the technical competence requirements and management system requirements that are necessary for it to consistently deliver technically valid test results and calibrations. The management system requirements in ISO/IEC 17025:2005 (Section 4) are written in language relevant to laboratory operations and meet the principles of ISO 9001:2008 Quality Management Systems — Requirements."





APPENDIX B

MODIFICATIONS TO THE EUT

MODIFICATIONS TO THE EUT

The modifications listed below were made to the EUT to pass FCC Subpart B and FCC 15.247 specifications.

All the rework described below was implemented during the test in a method that could be reproduced in all the units by the manufacturer.

No modifications were made to the EUT during the testing.





APPENDIX C

***ADDITIONAL MODELS COVERED
UNDER THIS REPORT***

ADDITIONAL MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

AT&T RC82V Geo Remote Control 2018
Models: R35602BA00-00004
S/N: N/A

There are no additional models covered under this report.



APPENDIX D

DIAGRAMS AND CHARTS

FIGURE 1: CONDUCTED EMISSIONS TEST SETUP





FIGURE 2: LAYOUT OF THE SEMI MI-ANECHOIC TEST CHAMBER



COM-POWER AL-130R**LOOP ANTENNA**

S/N: 121090

CALIBRATION DATE: FEBRUARY 9, 2017

FREQUENCY (MHz)	MAGNETIC (dB/m)	ELECTRIC (dB/m)
0.009	-36.17	15.33
0.01	-35.86	15.64
0.02	-37.30	14.20
0.03	-36.58	14.92
0.04	-36.99	14.51
0.05	-37.66	13.84
0.06	-37.53	13.97
0.07	-37.64	13.86
0.08	-37.52	13.98
0.09	-37.62	13.88
0.1	-37.59	13.91
0.2	-37.79	13.71
0.3	-37.80	13.70
0.4	-37.70	13.80
0.5	-37.79	13.71
0.6	-37.79	13.71
0.7	-37.69	13.81
0.8	-37.49	14.01
0.9	-37.39	14.11
1	-37.39	14.11
2	-37.09	14.41
3	-37.09	14.41
4	-37.19	14.31
5	-36.98	14.52
6	-37.17	14.33
7	-37.05	14.45
8	-36.85	14.65
9	-36.84	14.66
10	-36.75	14.75
15	-37.16	14.34
20	-36.44	15.06
25	-37.88	13.62
30	-39.14	12.36

COM-POWER AC-220**COMBILOG ANTENNA****S/N: 61060****CALIBRATION DATE: JULY 27, 2017**

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	23.80	200	14.10
35	24.00	250	15.30
40	24.70	300	17.70
45	22.90	350	17.70
50	22.10	400	19.00
60	17.60	450	21.30
70	12.70	500	21.00
80	11.20	550	22.30
90	13.10	600	23.40
100	14.40	650	22.90
120	15.30	700	24.60
125	15.00	750	24.50
140	12.80	800	25.40
150	16.50	850	26.40
160	12.90	900	27.20
175	14.30	950	27.80
180	14.50	1000	26.80

COM POWER AH-118**HORN ANTENNA**

S/N: 071175

CALIBRATION DATE: FEBRUARY 22, 2018

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	23.71	10.0	40.08
1.5	25.46	10.5	40.75
2.0	29.26	11.0	41.78
2.5	27.95	11.5	41.02
3.0	29.03	12.0	40.32
3.5	29.70	12.5	40.96
4.0	30.71	13.0	40.29
4.5	31.62	13.5	39.48
5.0	33.23	14.0	39.89
5.5	35.07	14.5	42.75
6.0	34.43	15.0	40.98
6.5	34.98	15.5	38.54
7.0	36.75	16.0	39.40
7.5	37.10	16.5	39.40
8.0	37.66	17.0	41.74
8.5	39.29	17.5	42.58
9.0	37.75	18.0	44.68
9.5	38.23		

COM-POWER PAM-118A
PREAMPLIFIER

S/N: 551024

CALIBRATION DATE: MAY 10, 2018

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	40.99	6.0	39.01
1.1	39.77	6.5	39.00
1.2	39.02	7.0	39.69
1.3	39.44	7.5	38.96
1.4	39.64	8.0	38.57
1.5	40.23	8.5	39.17
1.6	40.17	9.0	38.82
1.7	40.23	9.5	39.30
1.8	39.48	10.0	38.90
1.9	39.85	11.0	38.86
2.0	39.99	12.0	39.87
2.5	40.38	13.0	39.55
3.0	40.64	14.0	38.92
3.5	40.68	15.0	39.33
4.0	40.87	16.0	39.60
4.5	40.04	17.0	40.28
5.0	39.54	18.0	39.58
5.5	39.58		

COM-POWER AH-826**HORN ANTENNA**

S/N: 71957

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
18.0	33.5	22.5	35.5
18.5	33.5	23.0	35.9
19.0	34.0	23.5	35.7
19.5	34.0	24.0	35.6
20.0	34.3	24.5	36.0
20.5	34.9	25.0	36.2
21.0	34.7	25.5	36.1
21.5	35.0	26.0	36.2
22.0	35.0	26.5	35.7

COM-POWER PA-840**MICROWAVE PREAMPLIFIER**

S/N: 711013

CALIBRATION DATE: MAY 10, 2018


FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
18.0	26.90	31.0	24.56
19.0	24.65	31.5	25.84
20.0	25.74	32.0	26.93
21.0	24.78	32.5	27.76
22.0	24.83	33.0	25.76
23.0	24.81	33.5	26.76
24.0	25.52	34.0	26.51
25.0	24.90	34.5	27.49
26.0	25.92	35.0	27.64
26.5	26.53	35.5	27.45
27.0	26.41	36.0	25.08
27.5	24.78	36.5	25.61
28.0	25.13	37.0	24.69
28.5	29.29	37.5	24.10
29.0	28.44	38.0	24.83
29.5	27.51	38.5	24.41
30.0	27.12	39.0	24.44
30.5	26.42	39.5	22.96
		40.0	22.29



FRONT VIEW

UNIVERSAL ELECTRONICS, INC.
AT&T RC82V Geo Remote Control 2018
MODEL: R35602BA00-00004
FCC SUBPART B AND C – RADIATED EMISSIONS – BELOW 1 GHz


**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



REAR VIEW

UNIVERSAL ELECTRONICS, INC.
AT&T RC82V Geo Remote Control 2018
MODEL: R35602BA00-00004
FCC SUBPART B AND C – RADIATED EMISSIONS – BELOW 1 GHz


**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



FRONT VIEW

UNIVERSAL ELECTRONICS, INC.
AT&T RC82V Geo Remote Control 2018
MODEL: R35602BA00-00004
FCC SUBPART B AND C – RADIATED EMISSIONS – ABOVE 1 GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



REAR VIEW

UNIVERSAL ELECTRONICS, INC.
AT&T RC82V Geo Remote Control 2018
MODEL: R35602BA00-00004
FCC SUBPART B AND C – RADIATED EMISSIONS – ABOVE 1 GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**

APPENDIX E

DATA SHEETS



***RADIATED EMISSIONS
DATA SHEETS***

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

Harmonics - Low Channel
 Transmit Mode - X-Axis

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4804.00	46.10	V	73.97	-27.87	Peak	3.25	111.44	
4804.00	38.49	V	53.97	-15.48	Avg	3.25	111.44	
7206.00	45.78	V	84.46	-38.68	Peak	280.75	111.32	Not in Restricted Band
9608.00	50.47	V	84.46	-33.99	Peak	131.75	127.26	Not in Restricted Band
12010.00								No Emission Detected
14412.00								No Emission Detected
16814.00								No Emission Detected
19216.00								No Emission Detected
21618.00								No Emission Detected
24020.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - Low Channel
 Transmit Mode - Y-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4804.00	47.05	V	73.97	-26.92	Peak	62.00	127.08	
4804.00	40.38	V	53.97	-13.59	Avg	62.00	127.08	
7206.00	50.26	V	84.46	-34.20	Peak	81.75	159.08	Not in Restricted Band
9608.00	52.25	V	84.46	-32.21	Peak	332.75	127.20	Not in Restricted Band
12010.00								No Emission Detected
14412.00								No Emission Detected
16814.00								No Emission Detected
19216.00								No Emission Detected
21618.00								No Emission Detected
24020.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

Harmonics - Low Channel
 Transmit Mode - Z-Axis

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4804.00	46.78	V	73.97	-27.19	Peak	346.75	127.20	
4804.00	40.25	V	53.97	-13.72	Avg	346.75	127.20	
7206.00	52.26	V	84.46	-32.20	Peak	160.50	159.08	Not in Restricted Band
9608.00	52.77	V	84.46	-31.69	Peak	111.25	111.38	Not in Restricted Band
12010.00								No Emission Detected
14412.00								No Emission Detected
16814.00								No Emission Detected
19216.00								No Emission Detected
21618.00								No Emission Detected
24020.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - Low Channel
 Transmit Mode - X-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4804.00	49.12	H	73.97	-24.85	Peak	100.75	100.67	
4804.00	43.00	H	53.97	-10.97	Avg	100.75	100.67	
7206.00	51.07	H	84.46	-33.39	Peak	88.25	174.91	Not in Restricted Band
9608.00	51.66	H	84.46	-32.80	Peak	51.75	159.08	Not in Restricted Band
12010.00								No Emission Detected
14412.00								No Emission Detected
16814.00								No Emission Detected
19216.00								No Emission Detected
21618.00								No Emission Detected
24020.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

 Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

 Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - Low Channel
Transmit Mode - Y-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4804.00	42.58	H	73.97	-31.39	Peak	86.50	190.79	
4804.00	31.72	H	53.97	-22.25	Avg	86.50	190.79	
7206.00	48.33	H	84.46	-36.13	Peak	51.25	111.14	Not in Restricted Band
9608.00	50.88	H	84.46	-33.58	Peak	216.75	174.91	Not in Restricted Band
12010.00								No Emission Detected
14412.00								No Emission Detected
16814.00								No Emission Detected
19216.00								No Emission Detected
21618.00								No Emission Detected
24020.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - Low Channel
 Transmit Mode - Z-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4804.00	41.34	H	73.97	-32.63	Peak	90.25	190.73	
4804.00	30.76	H	53.97	-23.21	Avg	90.25	190.73	
7206.00	47.86	H	84.46	-36.60	Peak	51.25	111.32	Not in Restricted Band
9608.00	50.34	H	84.46	-34.12	Peak	211.50	249.97	Not in Restricted Band
12010.00								No Emission Detected
14412.00								No Emission Detected
16814.00								No Emission Detected
19216.00								No Emission Detected
21618.00								No Emission Detected
24020.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - Middle Channel
 Transmit Mode - X-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4884.00	42.49	V	73.97	-31.48	Peak	166.75	111.32	
4884.00	30.33	V	53.97	-23.64	Avg	166.75	111.32	
7326.00	44.08	V	73.97	-29.89	Peak	104.50	127.20	
7326.00	33.02	V	53.97	-20.95	Avg	104.50	127.20	
9768.00	50.52	V	84.46	-33.94	Peak	211.75	127.38	Not in Restricted Band
12210.00								No Emission Detected
14652.00								No Emission Detected
17094.00								No Emission Detected
19536.00								No Emission Detected
21978.00								No Emission Detected
24420.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - Middle Channel
 Transmit Mode - Y-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4884.00	47.53	V	73.97	-26.44	Peak	70.00	143.26	
4884.00	40.50	V	53.97	-13.47	Avg	70.00	143.26	
7326.00	50.91	V	73.97	-23.06	Peak	54.75	111.32	
7326.00	44.29	V	53.97	-9.68	Avg	54.75	111.32	
9768.00	51.16	V	84.46	-33.30	Peak	154.25	127.08	Not in Restricted Band
12210.00								No Emission Detected
14652.00								No Emission Detected
17094.00								No Emission Detected
19536.00								No Emission Detected
21978.00								No Emission Detected
24420.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

Harmonics - Middle Channel
 Transmit Mode - Z-Axis

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4884.00	46.71	V	73.97	-27.26	Peak	158.75	238.79	
4884.00	40.12	V	53.97	-13.85	Avg	158.75	238.79	
7326.00	43.76	V	73.97	-30.21	Peak	316.00	191.02	
7326.00	33.06	V	53.97	-20.91	Avg	316.00	191.02	
9768.00	52.26	V	84.46	-32.20	Peak	267.25	127.14	Not in Restricted Band
12210.00								No Emission Detected
12210.00								Detected
14652.00								No Emission Detected
14652.00								Detected
17094.00								No Emission Detected
17094.00								Detected
19536.00								No Emission Detected
19536.00								Detected
21978.00								No Emission Detected
21978.00								Detected
24420.00								No Emission Detected
24420.00								Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - Middle Channel
 Transmit Mode - X-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4884.00	48.09	H	73.97	-25.88	Peak	109.25	158.85	
4884.00	41.84	H	53.97	-12.13	Avg	109.25	158.85	
7326.00	52.54	H	73.97	-21.43	Peak	86.50	110.91	
7326.00	47.01	H	53.97	-6.96	Avg	86.50	110.91	
9768.00	50.15	H	84.46	-34.31	Peak	316.25	127.08	Not in Restricted Band
12210.00								No Emission Detected
14652.00								No Emission Detected
17094.00								No Emission Detected
19536.00								No Emission Detected
21978.00								No Emission Detected
24420.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - Middle Channel
 Transmit Mode - Y-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4884.00	42.71	H	73.97	-31.26	Peak	61.50	190.91	
4884.00	33.15	H	53.97	-20.82	Avg	61.50	190.91	
7326.00	47.89	H	73.97	-26.08	Peak	355.50	111.38	
7326.00	39.33	H	53.97	-14.64	Avg	355.50	111.38	
9768.00	52.05	H	84.46	-32.41	Peak	221.25	190.91	Not in Restricted Band
12210.00								No Emission Detected
12210.00								Detected
14652.00								No Emission Detected
14652.00								Detected
17094.00								No Emission Detected
17094.00								Detected
19536.00								No Emission Detected
19536.00								Detected
21978.00								No Emission Detected
21978.00								Detected
24420.00								No Emission Detected
24420.00								Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - Middle Channel
 Transmit Mode - Z-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4884.00	43.31	H	73.97	-30.66	Peak	87.50	127.02	
4884.00	34.45	H	53.97	-19.52	Avg	87.50	127.02	
7326.00	52.51	H	73.97	-21.46	Peak	220.25	111.26	
7326.00	45.94	H	53.97	-8.03	Avg	220.25	111.26	
9768.00	51.97	H	84.46	-32.49	Peak	205.00	111.38	Not in Restricted Band
12210.00								No Emission Detected
14652.00								No Emission Detected
17094.00								No Emission Detected
19536.00								No Emission Detected
21978.00								No Emission Detected
24420.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - High Channel
 Transmit Mode - X-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4960.00	44.14	V	73.97	-29.84	Peak	182.50	108.16	
4960.00	36.07	V	53.97	-17.90	Avg	182.50	108.16	
7440.00								No Emission Detected
7440.00								
9920.00	46.98	V	84.46	-37.48	Peak	83.00	144.94	Not in Restricted Band
12400.00								No Emission Detected
12400.00								
14880.00								No Emission Detected
14880.00								
17360.00								No Emission Detected
17360.00								
19840.00								No Emission Detected
19840.00								
22320.00								No Emission Detected
22320.00								
24800.00								No Emission Detected
24800.00								

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

Harmonics - High Channel
 Transmit Mode - Y-Axis

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4960.00	46.34	V	73.97	-27.63	Peak	88.00	110.79	
4960.00	39.69	V	53.97	-14.28	Avg	88.00	110.79	
7440.00	50.85	V	73.97	-23.12	Peak	54.00	223.26	
7440.00	43.96	V	53.97	-10.01	Avg	54.00	223.26	
9920.00	44.38	V	84.46	-40.08	Peak	318.00	158.85	Not in Restricted Band
12400.00								No Emission Detected
12400.00								Detected
14880.00								No Emission Detected
14880.00								Detected
17360.00								No Emission Detected
17360.00								Detected
19840.00								No Emission Detected
19840.00								Detected
22320.00								No Emission Detected
22320.00								Detected
24800.00								No Emission Detected
24800.00								Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - High Channel
 Transmit Mode - Z-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4960.00	42.37	V	73.97	-31.61	Peak	350.00	186.67	
4960.00	33.35	V	53.97	-20.62	Avg	350.00	186.67	
7440.00	50.86	V	73.97	-23.11	Peak	352.75	235.68	
7440.00	43.43	V	53.97	-10.54	Avg	352.75	235.68	
9920.00	50.06	V	84.46	-34.40	Peak	58.00	158.43	Not in Restricted Band
12400.00								No Emission Detected
14880.00								No Emission Detected
17360.00								No Emission Detected
19840.00								No Emission Detected
22320.00								No Emission Detected
24800.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - High Channel
 Transmit Mode - X-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4960.00	48.00	H	73.97	-25.97	Peak	285.00	127.32	
4960.00	41.64	H	53.97	-12.33	Avg	285.00	127.32	
7440.00	52.96	H	73.97	-21.01	Peak	218.75	127.30	
7440.00	47.58	H	53.97	-6.39	Avg	218.75	127.30	
9920.00	51.27	H	84.46	-33.19	Peak	129.25	127.32	Not in Restricted Band
12400.00								No Emission Detected
14880.00								No Emission Detected
17360.00								No Emission Detected
19840.00								No Emission Detected
22320.00								No Emission Detected
24800.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

**Harmonics - High Channel
 Transmit Mode - Y-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4960.00	42.09	H	73.97	-31.88	Peak	3.00	191.08	
4960.00	32.22	H	53.97	-21.75	Avg	3.00	191.08	
7440.00								No Emission Detected
7440.00								
9920.00	52.45	H	84.46	-32.01	Peak	224.00	158.91	Not in Restricted Band
12400.00								No Emission Detected
12400.00								
14880.00								No Emission Detected
14880.00								
17360.00								No Emission Detected
17360.00								
19840.00								No Emission Detected
19840.00								
22320.00								No Emission Detected
22320.00								
24800.00								No Emission Detected
24800.00								

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto


**Harmonics - High Channel
 Transmit Mode - Z-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
4960.00	45.10	H	73.97	-28.87	Peak	205.50	111.50	
4960.00	37.48	H	53.97	-16.49	Avg	205.50	111.50	
7440.00	52.95	H	73.97	-21.02	Peak	223.50	127.14	
7440.00	46.97	H	53.97	-7.00	Avg	223.50	127.14	
9920.00	50.47	H	84.46	-33.99	Peak	253.50	238.73	Not in Restricted Band
12400.00								No Emission Detected
14880.00								No Emission Detected
17360.00								No Emission Detected
19840.00								No Emission Detected
22320.00								No Emission Detected
24800.00								No Emission Detected

*The Limit at the 4th Harmonic is 20 dB Below the Maximum Fundamental of 104.46 dBuV/m per section 11.11.2 of ANSI C63.10: 2013

Title: Pre-Scan - FCC Class B
File: Agilent - RF Pre-Scan - FCC Class B - 30 MHz to 1000 MHz.set
Operator: Kyle Fujimoto
EUT Type: AT&T RC82V Geo Remote Control 2018
EUT Condition: EUT is continuously transmitting at the low channel RF frequency - Y-Axis Worst Case
Comments: Company: Universal Electronics, Inc.
Model: R35602BA00-00004
S/N: N/A

10/29/2018 8:30:31 AM
Sequence: Preliminary Scan



Title: Radiated Final - FCC Class B
 File: Aqilent - RF Final Scan - FCC Class B - 30 MHz to 1000 MHz.set
 Operator: Kyle Fujimoto
 EUT Type: AT&T RC82V Geo Remote Control 2018
 EUT Condition: EUT is continuously transmitting at the low channel RF frequency - Y-Axis Worst Case
 Comments: Company: Universal Electronics, Inc.
 Model: R35602BA00-00004
 S/N: N/A

10/29/2018 8:40:56 AM
 Sequence: Final Measurements


FCC Class B

Freq (MHz)	Pol	(PEAK) EMI (dBµV/m)	(QP) EMI (dBµV/m)	(PEAK) Margin (dB)	(QP) Margin (dB)	Limit (dBµV/m)	Transducer (dB)	Cable (dB)	Ttbl Aql (deq)	Twr Ht (cm)
35.40	H	31.42	26.39	-8.58	-13.61	40.00	24.08	0.86	309.50	334.73
36.70	H	32.03	26.42	-7.97	-13.58	40.00	24.22	0.87	213.75	127.50
40.70	H	33.42	26.57	-6.58	-13.43	40.00	24.40	0.90	64.75	143.02
41.20	H	31.88	26.86	-8.12	-13.14	40.00	24.24	0.90	316.50	255.32
45.40	H	30.19	24.93	-9.81	-15.07	40.00	22.81	0.90	198.00	366.73
48.30	H	30.01	24.23	-9.99	-15.77	40.00	22.36	0.90	146.50	207.20



Title: Pre-Scan - FCC Class B
 File: Agilent - IR Pre-Scan - FCC Class B - 30 MHz to 1000 MHz.set
 Operator: Kyle Fujimoto
 EUT Type: AT&T RC82V Geo Remote Control 2018
 EUT Condition: EUT is continuously transmitting an IR code - Y-Axis Worst Case
 Comments: Company: Universal Electronics, Inc.
 Model: R35602BA00-00004
 S/N: N/A

10/29/2018 8:57:22 AM
 Sequence: Preliminary Scan



Title: Radiated Final - FCC Class B
 File: Agilent - IR Final Scan - FCC Class B - 30 MHz to 1000 MHz.set
 Operator: Kyle Fujimoto
 EUT Type: AT&T RC82V Geo Remote Control 2018
 EUT Condition: EUT is continuously transmitting an IR code - Y-Axis Worst Case
 Comments: Company: Universal Electronics, Inc.
 Model: R35602BA00-00004
 S/N: N/A

10/29/2018 9:06:01 AM
 Sequence: Final Measurements


FCC Class B

Freq (MHz)	Pol	(PEAK) EMI (dBµV/m)	(QP) EMI (dBµV/m)	(PEAK) Margin (dB)	(QP) Margin (dB)	Limit (dBµV/m)	Transducer (dB)	Cable (dB)	Ttbl Aql (deg)	Twr Ht (cm)
32.00	V	31.42	26.24	-8.58	-13.76	40.00	23.88	0.82	82.25	207.26
33.50	H	31.17	26.31	-8.83	-13.69	40.00	23.94	0.84	245.50	207.14
34.30	H	31.77	26.29	-8.23	-13.71	40.00	23.98	0.85	221.25	270.19
39.80	H	32.20	26.88	-7.80	-13.12	40.00	24.69	0.90	289.50	239.02
40.50	H	32.30	27.28	-7.70	-12.72	40.00	24.47	0.90	165.75	271.02
40.70	H	33.03	26.72	-6.97	-13.28	40.00	24.44	0.90	270.50	255.14



Title: Pre-Scan - FCC Class B
File: Agilent - RF Voice Pre-Scan - FCC Class B - 30 MHz to 1000 MHz.set
Operator: Kyle Fujimoto
EUT Type: AT&T RC82V Geo Remote Control 2018
EUT Condition: EUT is continuously transmitting RF in Voice Mode - Y-Axis Worst Case
Comments: Company: Universal Electronics, Inc.
Model: R35602BA00-00004
S/N: N/A

10/29/2018 9:23:05 AM
Sequence: Preliminary Scan



Title: Radiated Final - FCC Class B

File: Agilent - RF Voice Final Scan - FCC Class B - 30 MHz to 1000 MHz.set

Operator: Kyle Fujimoto

EUT Type: AT&T RC82V Geo Remote Control 2018

EUT Condition: EUT is continuously transmitting RF in Voice Mode - Y-Axis Worst Case

Comments: Company: Universal Electronics, Inc.

Model: R35602BA00-00004

S/N: N/A

10/29/2018 9:31:40 AM

Sequence: Final Measurements

FCC Class B

Freq (MHz)	Pol	(PEAK) EMI (dB μ V/m)	(QP) EMI (dB μ V/m)	(PEAK) Margin (dB)	(QP) Margin (dB)	Limit (dB μ V/m)	Transducer (dB)	Cable (dB)	Ttbl Agl (deq)	Twr Ht (cm)
30.40	H	31.71	26.28	-8.29	-13.72	40.00	23.82	0.80	196.50	367.02
32.60	H	31.70	26.36	-8.30	-13.64	40.00	23.91	0.83	61.25	127.26
38.90	H	31.88	26.90	-8.12	-13.10	40.00	24.56	0.89	124.50	383.08
39.80	V	31.94	27.02	-8.06	-12.98	40.00	24.69	0.90	270.50	398.01
40.30	H	32.63	26.94	-7.37	-13.06	40.00	24.60	0.90	68.25	111.50
41.80	H	31.83	26.09	-8.17	-13.91	40.00	23.96	0.90	270.00	255.20





***BAND EDGES
DATA SHEETS***


FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004


Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

Band Edges


Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
2402.00	103.63	H	--	--	Peak	318.75	166.61	Fundamental - Low Ch.
2402.00	102.78	H	--	--	Avg	318.75	166.61	X-Axis - Worst Case
2370.00	54.66	H	73.97	-19.31	Peak	318.75	166.61	Band Edge
2370.00	50.08	H	53.97	-3.89	Avg	318.75	166.61	X-Axis - Worst Case
2390.00	48.56	H	73.97	-25.41	Peak	318.75	166.61	Band Edge
2390.00	37.14	H	53.97	-16.83	Avg	318.75	166.61	X-Axis - Worst Case
2402.00	104.46	V	--	--	Peak	254.75	148.82	Fundamental - Low Ch.
2402.00	103.54	V	--	--	Avg	254.75	148.82	Y-Axis - Worst Case
2369.80	55.52	V	73.97	-18.45	Peak	254.75	148.82	Band Edge
2369.80	50.07	V	53.97	-3.90	Avg	254.75	148.82	Y-Axis - Worst Case
2390.00	47.42	V	73.97	-26.55	Peak	254.75	148.82	Band Edge
2390.00	38.35	V	53.97	-15.62	Avg	254.75	148.82	Y-Axis - Worst Case




BE - 2402 MHz - Horizontal - X-Axis Worst Case at 2390 MHz




BE - 2402 MHz - Horizontal - X-Axis Worst Case at 2400 MHz




BE - 2402 MHz - Vertical - Y-Axis Worst Case at 2390 MHz



BE - 2402 MHz - Vertical - Y-Axis Worst Case at 2400 MHz




BE - 2480 MHz - Horizontal - X-Axis Worst Case at 2483.50 MHz




BE - 2480 MHz - Vertical - Y-Axis Worst Cast at 2483.50 MHz




***DTS BANDWIDTH
DATA SHEETS***



Bandwidth 6 dB - 2402 MHz



Bandwidth 6 dB - 2442 MHz



Bandwidth 6 dB - 2480 MHz



***PEAK OUTPUT POWER
DATA SHEETS***

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

Peak Output Power

Freq. (MHz)	Level (dBuV/m)	Level (V/m)	Antenna Gain (dBi)	Numeric Gain	Power Output (Watts)	Power Output (mW)	Power Output (dBm)	Limit (dBm)	Margin (dB)	Comments
2402.00	94.76	0.054701596	2	1.584893	0.00056640	0.56640	-2.47	30.00	-32.47	Vert. X-Axis
2442.00	95.04	0.056493697	2	1.584893	0.00060412	0.60412	-2.19	30.00	-32.19	Vert. X-Axis
2480.00	95.54	0.05984116	2	1.584893	0.00067783	0.67783	-1.69	30.00	-31.69	Vert. X-Axis
2402.00	104.43	0.166532883	2	1.584893	0.00524954	5.24954	7.20	30.00	-22.80	Vert. Y-Axis
2442.00	105.05	0.178854553	2	1.584893	0.00605510	6.05510	7.82	30.00	-22.18	Vert. Y-Axis
2480.00	102.58	0.134566035	2	1.584893	0.00342864	3.42864	5.35	30.00	-24.65	Vert. Y-Axis
2402.00	100.32	0.103752842	2	1.584893	0.00203761	2.03761	3.09	30.00	-26.91	Vert. Z-Axis
2442.00	100.30	0.103514217	2	1.584893	0.00202825	2.02825	3.07	30.00	-26.93	Vert. Z-Axis
2480.00	100.54	0.106414302	2	1.584893	0.00214349	2.14349	3.31	30.00	-26.69	Vert. Z-Axis
2402.00	103.83	0.155417529	2	1.584893	0.00457216	4.57216	6.60	30.00	-23.40	Horiz. X-Axis
2442.00	105.22	0.18238957	2	1.584893	0.00629682	6.29682	7.99	30.00	-22.01	Horiz. X-Axis
2480.00	104.27	0.163493315	2	1.584893	0.00505966	5.05966	7.04	30.00	-22.96	Horiz. X-Axis
2402.00	90.24	0.03250873	2	1.584893	0.00020004	0.20004	-6.99	30.00	-36.99	Horiz. Y-Axis
2442.00	92.01	0.039856577	2	1.584893	0.00030069	0.30069	-5.22	30.00	-35.22	Horiz. Y-Axis
2480.00	94.18	0.051168184	2	1.584893	0.00049559	0.49559	-3.05	30.00	-33.05	Horiz. Y-Axis
2402.00	103.55	0.150487352	2	1.584893	0.00428668	4.28668	6.32	30.00	-23.68	Horiz. Z-Axis
2442.00	105.21	0.182179707	2	1.584893	0.00628234	6.28234	7.98	30.00	-22.02	Horiz. Z-Axis
2480.00	103.47	0.149107676	2	1.584893	0.00420844	4.20844	6.24	30.00	-23.76	Horiz. Z-Axis

RBW = 8 MHz, VBW = 50 MHz, Sweep Time = Auto

$$P = [(E \cdot D)^2 / (30 \cdot G)]$$

P = Power in Watts

E = The Measured Maximum Field Strength in V/m

D = Test Distance in Meters

G = The Numeric Gain of the Transmitting Antenna over an Isotropic Radiator



***SPECTRAL DENSITY OUTPUT
DATA SHEETS***

FCC 15.247

Universal Electronics, Inc.
 AT&T RC82V Geo Remote Control 2018
 Model: R35602BA00-00004

Date: 10/26/2018
 Lab: D
 Tested By: Kyle Fujimoto

Spectral Density Output

Freq. (MHz)	Level (dBuV/m)	Level (V/m)	Antenna Gain (dBi)	Numeric Gain	PPSD Output (Watts)	PPSD Output (mW)	PPSD Output (dBm)	Limit (dBm)	Margin (dB)	Comments
2402.00	80.59	0.010702864	2	1.584893	0.00002168	0.02168	-16.64	8.00	-24.64	Vert. X-Axis
2442.00	80.91	0.011104525	2	1.584893	0.00002334	0.02334	-16.32	8.00	-24.32	Vert. X-Axis
2480.00	82.47	0.013287706	2	1.584893	0.00003342	0.03342	-14.76	8.00	-22.76	Vert. X-Axis
2402.00	91.85	0.039147136	2	1.584893	0.00029008	0.29008	-5.37	8.00	-13.37	Vert. Y-Axis
2442.00	92.96	0.044437539	2	1.584893	0.00037378	0.37378	-4.27	8.00	-12.27	Vert. Y-Axis
2480.00	89.95	0.031444884	2	1.584893	0.00018716	0.18716	-7.28	8.00	-15.28	Vert. Y-Axis
2402.00	87.33	0.023248771	2	1.584893	0.00010231	0.10231	-9.90	8.00	-17.90	Vert. Z-Axis
2442.00	86.29	0.020637163	2	1.584893	0.00008062	0.08062	-10.94	8.00	-18.94	Vert. Z-Axis
2480.00	88.43	0.026393683	2	1.584893	0.00013186	0.13186	-8.80	8.00	-16.80	Vert. Z-Axis
2402.00	90.62	0.033954708	2	1.584893	0.00021823	0.21823	-6.61	8.00	-14.61	Horiz. X-Axis
2442.00	92.63	0.042785834	2	1.584893	0.00034651	0.34651	-4.60	8.00	-12.60	Horiz. X-Axis
2480.00	91.90	0.039368603	2	1.584893	0.00029337	0.29337	-5.33	8.00	-13.33	Horiz. X-Axis
				1						
2402.00	76.94	0.007032342	2	1.584893	0.00000936	0.00936	-20.29	8.00	-28.29	Horiz. Y-Axis
2442.00	78.88	0.008785167	2	1.584893	0.00001461	0.01461	-18.35	8.00	-26.35	Horiz. Y-Axis
2480.00	86.20	0.02041973	2	1.584893	0.00007893	0.07893	-11.03	8.00	-19.03	Horiz. Y-Axis
2402.00	90.27	0.032602432	2	1.584893	0.00020120	0.20120	-6.96	8.00	-14.96	Horiz. Z-Axis
2442.00	89.93	0.031379788	2	1.584893	0.00018639	0.18639	-7.30	8.00	-15.30	Horiz. Z-Axis
2480.00	91.60	0.038023317	2	1.584893	0.00027367	0.27367	-5.63	8.00	-13.63	Horiz. Z-Axis

RBW = 3 kHz, VBW = 10 kHz, Sweep Time = 100 Seconds

$P = [(E \cdot D)^2 / (30 \cdot G)]$

P = Power In Watts

E = The Measured Maximum Field Strength In V/m

D = Test Distance In Meters

G = The Numeric Gain of the Transmitting Antenna over an Isotropic Radiator

Limit = +8 dBm