



5473A Clouds Rest Road : Mariposa, CA 95338 : Phone 209-966-5420 : Fax 209-742-6133

Maximum Permissible Exposure Calculations

Date of Report: Jan 08, 2003

Calculations prepared for:

IP Mobile Net
11909 East Telegraph Road
Santa Fe Springs, CA 90670

Calculations prepared by:

Eddie Wong
110 N. Olinda Place
Brea, CA 9283

Model Number: IP4HPV-GPS
FCC Identification: MI7-IPMNIP4H

Fundamental Operating Frequency: 509-512MHz
Maximum Rated Output Power: 40.00 Watts
Measured Output Power: 34.00 Watts
Typical Antenna gain: 3dBi

In accordance with 47CFR2.1093(d)(2), source based time averaging is allowed for this type of device:
Source Based Time Averaging = $20\text{LOG}(\text{ON time}/\text{TOTAL time})$
= $20\text{LOG}(389\text{mS}/(389+310 = 699\text{mS}))$
= -5.09dB

Therefore the Output = 46.02dBm (40.00W) - 5.09dB + 3dBi = **43.93dBm (24.717W EIRP)**

MPE Limit in accordance with 1.1310(b): Limits for general population/uncontrolled exposure

MPE Limit for 509 MHz = $509/1500 = 0.3393 \text{ mW/cm}^2$ (3.339W/M^2)
MPE Limit for 512 MHz = $512/1500 = 0.3413 \text{ mW/cm}^2$

Power Output (Watts EIRP)	Power Density Limit (mW/cm ²)	Minimum Distance (Meters)
24.717	0.3393	0.7616

Power Density (W/M^2) = (EIRP) / ($d^2 * 4 * \pi$)

The typical vehicle used by police was measured, and a separation distance of 1 meter was found to be an appropriate distance. Under normal operating conditions, the antenna will maintain a separation of 1 meter from all persons. As can be seen from the MPE results, this device passes the limits specified in 1.1310 at a distance of **0.7616** Meters at the rated power of 40W.