

## **Exhibit 12 – Measurement Techniques**

### **Motorola Head-end Transceiver (HUB)**

FCC ID: MIJMILHUB-USA-01

Millitech Part No. 9031291001

## **12.0 Measurement Techniques**

### **12.1 Radiated Spurious and Harmonic Emissions**

#### **12.1.1 Definition**

Radiated spurious and harmonic emissions from the equipment at a frequency and/or frequencies which are outside an occupied band sufficient to insure transmission of information of required quality for the class of communication desired. The reduction in the level of these spurious emissions will not effect the quality of information being transmitted.

#### **12.1.2 Minimum Standard**

For the HUB data transmitter, the mean power of radiated spurious and harmonic emissions shall be attenuated as per 101.12(a)(2)(ii). The frequency offset attenuation is based on an authorized bandwidth of 850 MHz and mean output power of +18 dBm. For frequencies removed greater than 50% to less than or equal to 250% of the authorized bandwidth and measured in a 1 MHz bandwidth, the attenuation requirement is as follows:

$$\text{Attenuation (dBc)} = 12 + 0.4 * (\text{Percent}-50) + 10 * \text{Log}_{10}(\text{Bandwidth})$$

Note: Attenuation of greater than 56 dBc is not required.

For frequencies removed greater than 250% of the authorized bandwidth and measured in a 4 kHz bandwidth, the attenuation requirement is as follows:

$$\text{Attenuation (dBc)} = 43 + 10 * \text{Log}_{10}(\text{mean output power})$$

Note: Attenuation of greater than 80 dBc is not required.

For the HUB pilot transmitter, the mean power of radiated spurious and harmonic emissions shall be attenuated as per 101.12(a)(1). The frequency offset attenuation is based on an authorized bandwidth of 850 MHz and mean output power of +18 dBm. For frequencies removed greater than 50% to less than or equal to 100% of the authorized bandwidth and measured in a 1 MHz bandwidth, the attenuation requirement is as follows:

$$\text{Attenuation (dBc)} = 25 \text{ dBc}$$

For frequencies removed greater than 100% to less than or equal to 250% of the authorized bandwidth and measured in a 1 MHz bandwidth, the attenuation requirement is as follows:

$$\text{Attenuation (dBc)} = 35 \text{ dBc}$$

For frequencies removed greater than 250% of the authorized bandwidth and measured in a 4 kHz bandwidth, the attenuation requirement is as follows:

$$\text{Attenuation (dBc)} = 43 + 10 * \text{Log}_{10}(\text{mean output power})$$

Note: Attenuation of greater than 80 dBc is not required.

### 12.1.3 Method of Measurement

#### **Facility Description:**

All final testing reported herein was performed at the Motorola SSG semi-anechoic chamber, located at 8201 E. McDowell Rd., Scottsdale, AZ. 85252. The facility has also been issued a Certificate of Accreditation through the National Voluntary Laboratory Accreditation Program (NVLAP) by NIST. This is under NVLAP Code: 100405-0 and is effective through September 30, 1999.

#### **Measurement Description:**

Spurious and harmonic emissions were measured as radiated emissions in an anechoic chamber (20ft x 24ft x 16ft). The HUB equipment does not require a CPE to operate. The CPE requires the HUB's Pilot tone to enable it to transmit. Therefore, when the HUB was tested only the HUB was in the test chamber and when the CPE was tested with both the HUB and the CPE in the chamber. The DOCSIS modulation was provided by a HPE4430B Signal Generator.

Radiated emissions were measured from 30 MHz to 100 GHz. For all emissions with the exception of the transmitter's fundamental frequency and its harmonics, measurements were made at a distance of 3 meters. All four sides of the EUT and both vertical and horizontal polarization's were tested for maximum radiated levels. All emissions detected were greater than 20 dB below the emission limitations of 47 CFR 101.111 (see paragraph 12.1.2 of this Exhibit). Therefore, no Open Area Test Site (OATS) measurements were made.

Testing of the transmitter's fundamental frequency and its harmonics were performed in the main beam of the transmit antenna. The receive antenna was positioned at a distance to maximize the received signal. Spurious and harmonic levels were then compared to the radiated level of the fundamental signal. The attenuation requirement was based on 47 CFR 101.111 (see paragraph 12.1.2 of this Exhibit).

## 12.2 Frequency Stability

### 12.2.1 Definition

The carrier frequency stability is the ability of the transmitter to maintain an assigned carrier frequency

### 12.2.2 Minimum Standard

The minimum frequency stability shall be  $\pm 0.001\%$  at any time during normal operation.

### 12.2.3 Method of Measurement

The crystal oscillator manufacturer made frequency measurements on twenty samples at the extremes of the temperature range -40 to +65 degrees C (See Table 12.2-1).

Sample No.	Error PPM at -40° C	Error PPM at +65° C
1	+.1119	-.0666
2	+.1337	-.0975
3	+.1035	-.0818
4	+.2094	-.1268
5	+.1231	-.080
6	+.1222	-.0708
7	+.1658	-.1056
8	+.1199	-.0607
9	+.167	-.1206
10	+.153	-.1563
11	+.1208	-.0734
12	+.218	-.1427
13	+.0991	-.0745
14	+.1188	-.0826
15	+.1276	-.0941
16	+.0442	-.0374
17	+.1927	-.1284
18	+.1764	-.1058
19	+.1699	-.1024
20	+.1464	-.0884