



Test Requirements Document

GSM3208MG000TRD

Wireless Portfolio Test and Upgrade Procedure

WARNING: Information in this document is proprietary and confidential to Enfora LP. Do not copy or distribute without prior written consent of Enfora LP.

Revision History

Date	Rev	Author	Description
02.27.04	A	CSpillers	Initial Release



- Verify IMEI using “AT+GSN”
- Verify AREG is set to 1.
- Verify VSELECT is set to 1.
- Verify AT%V contains the string “Calypso C035”
- AT&V should display the following:

```
E1 Q0 V1 X0 &C1 &D0 S0:000 S3:013 S4:010 S5:008 +CBST: 7,0,1 +FCLASS:0
+CRLP: 61,61,48,6 +CR:0 +CRC:0 +CMGF:1 +CSCS:"PCCP437" +CNMI:1,1,0,0,0
+ILRR:0 +IPR:115200 +CMEE:0 +CSMS:0,1,1,1 +CFUN:1 +CREG:0 +CGREG:0
+CLIP:0,2 +CAOC:1 +COPS:0,0 +CSNS:0 +CSSN:0,0 +CSDH:0 +CMUT:0
+COLP:0 +CPBS:"AD" +CGAUTO:3 +CGSMS:3 +CGEREP:0,0 +CGCLASS:"B"
+CSVM:0,"",129 +CGQREQ +CGQMIN
+CMOD:0 +IFC:2,2 +ICF:3 %CGAATT:0,1 %CGPPP:3 $AREG:1 $HOSTIF:0
$VGR: 22 $VGT: 7 $VLVL: 4 $VST: 0 $VSELECT: 1
$PADBLK: 512 $PADBS: 08 $PADCMD: 001b $PADDST: "000.000.000.000", 0
$PADFWD: 0d $PADSRC: 0 $PADTO: 50 $UDPAPI: "199.245.180.013", 1720
$ACTIVE: 1 $CONNTO: 60 $IDLETO: 120 $GATEWAY:000.000.000.000
$MSCLS: 8 %SLEEP: 2 %CPI: 0 %CGREG: 0 %ACKTM: 0, 0, 0
$MDMID: ""
$EVTIM1: 0, $EVTIM2: 0, $EVTIM3: 0, $EVTIM4: 0
$WAKEUP: 0, 0 $NETMON: 0, 0, 0
$IOCFG: 00100010, $IOGPA: 10000101
$EVENT: evgp evtyp evcat p1 p2
```

4.4 Record Keeping

Save all parametric data for each completed unit in a common database.