


85L232SI120S REV 2A

ECN



1.375 X 8


12/18/00




Luxline
 ELECTRONIC INSTANT START BALLAST
 • POWER FACTOR ABOVE 90% • SOUND RATED A
 MINIMUM STARTING TEMPERATURE: 0°F
 INSTALL IN ACCORDANCE WITH NATIONAL
 AND LOCAL ELECTRICAL CODES

2 LAMP
 CAT. NO. L232SI120S
 NO PCB'S
 CLASS P



120 VOLTS
 60 HZ
 0.49 AMPS
 FCC ID: MKGLUXLINE
 LISTED BALLAST
 TYPE 1 OUTDOOR



FOR USE WITH (2) P8278 OR (2) P8279 LAMPS.
 04L232SI120S REV 2A

 EL PASO, TX USA
 1-800-655-7290
 ASSEMBLED IN MEXICO



Luxline
 ELECTRONIC INSTANT START BALLAST
 • POWER FACTOR ABOVE 90% • SOUND RATED A
 MINIMUM STARTING TEMPERATURE: 0°F
 INSTALL IN ACCORDANCE WITH NATIONAL
 AND LOCAL ELECTRICAL CODES

2 LAMP
 CAT. NO. L232SI120S
 NO PCB'S
 CLASS P

120 VOLTS
 60 HZ
 0.49 AMPS
 FCC ID: MKGLUXLINE
 LISTED BALLAST
 TYPE 1 OUTDOOR


FOR USE WITH (2) P8278 OR (2) P8279 LAMPS.
 04L232SI120S REV 2A

 EL PASO, TX USA
 1-800-655-7290
 ASSEMBLED IN MEXICO