User manual

Introduction

Congratulations on receiving your 25010-11N. As part of our Green Initiative, we do not include printed user documentation with our product packaging. This policy saves paper, lowers shipping costs, reduces carbon emissions and results in a cleaner environment.

Documentation

All product and accessory documentation can be found at the GLI Support Centre: <u>http://www.gl-inet.com/docs</u> On this site you will gain access to GLI technical resources and information about GLI products. To use your new GLI Mini Router you will need to follow the simple steps which you can see from


http://www.gl-inet.com/docs/wiki/#!mini/index.md

Default System Settings

Product	LAN Default IP Address	LAN Fall-back IP Address
25010-11N	DHCP	192.168.8.1

Initial Set-up

Interfaces described as followed:



Power to the GLI Mini Router is provided by connect the power lead (supplied) to the power adaptor (buy separately) and then to the power interface on the GLI Mini Router.

Once power is provided to the GLI Mini Router the LED's will provide status on its operation based on the

following:		
LED	Indicator	Description
LED 1 (Power)	Green solid	Power is applied
LED 2 (Customized)	Customized	This is customized LED.
LED 3 (WiFi connection)	Red	Indicates WiFi signal (solid) and
		data transfer (flashing).

Button Definition



- Press the Reset button to toggle the WiFi signal ON or OFF.
- Press and hold the Reset button for at least 8 seconds, then release your finger to reset the router to factory default state. Wait until the router reboots, which could take about 3 minutes.
- The function of "switch" is configurable by user.

FCC Warning

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions

(1) this device may not cause harmful interference, and

(2) this device must accept any interference received, including interference that may cause undesired operation. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note 1: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-Reorient or relocate the receiving antenna.

-Increase the separation between the equipment and receiver.

-Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

--Consult the dealer or an experienced radio/TV technician for help. Note 2: 1. Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

WARNNING: The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.