



RADIO TEST REPORT

Report No: STS2211125H02

Issued for

Orbit Irrigation Products Inc

845N. Overland Road, North Salt Lake, Utah 84054 USA

Product Name:	CMS Control Unit
Brand:	Hydro-Rain
Model Number:	CMS-CU
Series Model(s):	N/A
FCC ID:	ML6CMSCU
Test Standard:	FCC 47CFR §2.1091

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.





Test Report Certification

Applicant's Name..... : Orbit Irrigation Products Inc
 Address : 845N. Overland Road, North Salt Lake, Utah 84054 USA
Manufacturer's Name : GARDENA Inc.
 Address : 845N. Overland Road, North Salt Lake, Utah 84054 USA

Product Description

Product Name..... : CMS Control Unit
 Brand : Hydro-Rain
 Model Number..... : CMS-CU
 Series Model(s) : N/A

Standards..... : FCC 47CFR §2.1091
 447498 D04 Interim General RF Exposure Guidance v01

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test..... :
 Date of receipt of test item : 08 Feb. 2023
 Date (s) of performance of tests..... : 08 Feb. 2023 ~ 10 Apr. 2023
 Date of Issue..... : 10 Apr. 2023
 Test Result..... : **Pass**

Testing Engineer : *Chris Chen*

 (Chris Chen)

Technical Manager : *Sean She*

 (Sean she)

Authorized Signatory : *Bovey Yang*

 (Bovey Yang)





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	5
2. FCC 47CFR §2.1091 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 TEST RESULT	9





Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	10 Apr. 2023	STS2211125H02	ALL	Initial Issue





1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	CMS Control Unit								
Brand	Hydro-Rain								
Model Number	CMS-CU								
Series Model(s)	N/A								
Model Difference	N/A								
Product Description	<p>The EUT is CMS Control Unit.</p> <table border="1"><tr><td>Operation Frequency:</td><td>BLE: 2402-2480 MHz Other SRD: 125KHz: 903.9-914.9 MHz 500KHz: 903-916.2 MHz 923.3-926.9 MHz</td></tr><tr><td>Modulation Type:</td><td>BLE: GFSK Other SRD: LoRa</td></tr><tr><td>Antenna gain:</td><td>BLE: 0.5dBi Other SRD: 0.2dBi</td></tr><tr><td>Antenna Designation:</td><td>BLE: Ceramic Antenna Other SRD: FPC Antenna</td></tr></table>	Operation Frequency:	BLE: 2402-2480 MHz Other SRD: 125KHz: 903.9-914.9 MHz 500KHz: 903-916.2 MHz 923.3-926.9 MHz	Modulation Type:	BLE: GFSK Other SRD: LoRa	Antenna gain:	BLE: 0.5dBi Other SRD: 0.2dBi	Antenna Designation:	BLE: Ceramic Antenna Other SRD: FPC Antenna
Operation Frequency:	BLE: 2402-2480 MHz Other SRD: 125KHz: 903.9-914.9 MHz 500KHz: 903-916.2 MHz 923.3-926.9 MHz								
Modulation Type:	BLE: GFSK Other SRD: LoRa								
Antenna gain:	BLE: 0.5dBi Other SRD: 0.2dBi								
Antenna Designation:	BLE: Ceramic Antenna Other SRD: FPC Antenna								
Rating	Input: 3.3-6V DC, or Battery: 6 Alkaline AA batteries								
Hardware version number	008								
Software version number	1.0								

1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

Follow the maximum permissible exposure (MPE) limits specified in 447498 D04 Interim General Radio Frequency Exposure Guidelines v01. The gain of the antenna used in the product was extracted from the supplied antenna data sheet and the maximum total power input to the antenna was also measured. Calculate the distance from the product to the MPE limit by the formula.

2.2 LIMIT

For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);



(C) Or using below table and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.



For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those is paragraph (b)(3)(i)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of Part 1.1307 for Pth, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of Part 1.1307 for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

Pi = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

Pth,i = the exemption threshold power (Pth) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERPj = the ERP of fixed, mobile, or portable RF source j.

ERPth,j = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of Part 1.1307.

Evaluatedk = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limitk = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310.



2.3 TEST RESULT

Turn up

Mode	Detector	Turn up Power
BLE	AV	2±1dBm

Mode	Field Strength	EIRP
SRD 903.9-914.9 MHz	89.20 dBuV/m	-6dBm (+/- 1dBm)
SRD 903-916.2 MHz	88.92 dBuV/m	-6dBm (+/- 1dBm)
SRD 923.3-926.9 MHz	92.36 dBuV/m	-3dBm (+/- 1dBm)

Remark: dBm= dBuV/m-95.2

Protocol	Fre. (GHz)	Separation distance (cm)	Max Turn up power (dBm)	ANT Gain (dBi)	Max EIRP (dBm)	Max EIRP (mW)	Limit (mW)	Ratio	Result
BLE	2.480	20	3	0.5	3.5	2.2387	3060	0.0007	Pass
SRD 903.9-914.9 MHz	0.9149	20	-5	0.2	-4.8	0.3162	1866	0.0002	Pass
SRD 903-916.2 MHz	0.9162	20	-5	0.2	-4.8	0.3162	1869	0.0002	Pass
SRD 923.3-926.9 MHz	0.9269	20	-2	0.2	-1.8	0.6607	1891	0.0003	Pass

Note: The Maximum power is less than the limit, complies with the exemption requirements.

*****END OF THE REPORT*****