

Alignment instructions

WARNING

Any repairs or adjustments should be made under the supervision of a Qualified radiotelephone technician.

TRANSMITTER

1. Power Supply Voltage

The Power supply voltage should be set for 4.5 VDC measured at the radio
During transmit. Periodically check the power supply voltage during the alignment procedure.

2. Frequency Setting

- A. Connect a frequency counter or Communications Service Monitor to the Antenna connector through an RF power attenuator (5 watt minimum rating, 20 dB minimum attenuation).
- B. Depress the PTT switch.
- C. Adjust the CTX1 trimmer capacitor such that The output frequency is equal to the channel frequency with a maximum error of +/- 200 Hz.
- D. Release the PTT switch.

3. Output Power Alignment.

- A. Set the power supply voltage for 4.5 VDC.
- B. Connect a Communications Service Monitor or a wattmeter and dummy load To the antenna connector.
- C. Depress the PTT switch.
- D. To be convinced for 1 Watt(50 ohm load) output power with a maximum error of +/- 0.15 Watts.
- E. Release the PTT switch.

4. Deviation Adjustment.

- A. Connect an audio generator .
The audio frequency should be set at 1 KHz.
- B. Connect an FM deviation meter or Communications Service Monitor to the antenna connector through an RF power attenuator (5 watt minimum rating, 20 dB minimum attenuation). Set the monitor to read peak deviation.
- C. Depress the PTT switch.
- D. Adjust RV201 for +/- 4.0KHz maximum deviation.
- E. Release the PTT switch.