



# RADIO TEST REPORT

**Test Report No. : 11062791H-R1**

**Applicant** : TOKAI RIKA CO., LTD.  
**Type of Equipment** : Immobilizer  
**Model No.** : RI-57BTY  
**Test regulation** : FCC Part 15 Subpart C: 2015  
**FCC ID** : MOZRI-57BTY  
**Test Result** : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
6. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
7. This report is a revised version of 11062791H. 11062791H is replaced with this report.

**Date of test:** December 17, 2015

**Representative test engineer:**

Ken Fujita  
Engineer

Consumer Technology Division

**Approved by:**

Motoya Imura  
Engineer

Consumer Technology Division



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.  
\*As for the range of Accreditation in NVLAP, you may refer to the WEB address,  
[http://japan.ul.com/resources/emc\\_accredited/](http://japan.ul.com/resources/emc_accredited/)

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

13-EM-F0429



<b>CONTENTS</b>	<b>PAGE</b>
<b>SECTION 1: Customer information .....</b>	<b>4</b>
<b>SECTION 2: Equipment under test (E.U.T.).....</b>	<b>4</b>
<b>SECTION 3: Test specification, procedures &amp; results .....</b>	<b>5</b>
<b>SECTION 4: Operation of E.U.T. during testing .....</b>	<b>8</b>
<b>SECTION 5: Radiated emission (Fundamental and Spurious Emission) .....</b>	<b>9</b>
<b>SECTION 6: -26dB Bandwidth.....</b>	<b>12</b>
<b>SECTION 7: 99% Occupied Bandwidth.....</b>	<b>12</b>
<b>APPENDIX 1: Test data .....</b>	<b>13</b>
<b>Radiated Emission below 30 MHz (Fundamental and Spurious Emission) .....</b>	<b>13</b>
<b>Radiated Emission above 30 MHz (Spurious Emission).....</b>	<b>14</b>
<b>-26 dB Bandwidth.....</b>	<b>15</b>
<b>99 % Occupied Bandwidth.....</b>	<b>16</b>
<b>APPENDIX 2: Test instruments .....</b>	<b>17</b>
<b>APPENDIX 3: Photographs of test setup .....</b>	<b>18</b>
<b>Radiated Emission.....</b>	<b>18</b>
<b>Worst Case Position .....</b>	<b>19</b>

---

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## **SECTION 1: Customer information**

Company Name : TOKAI RIKA CO., LTD  
Address : 3-260 Toyota, Oguchi-cho, Niwa-gun, Aichi 480-0195, Japan  
Telephone Number : +81-587-95-0093  
Facsimile Number : +81-587-95-5471  
Contact Person : Hiroki Unno

## **SECTION 2: Equipment under test (E.U.T.)**

### **2.1 Identification of E.U.T.**

Type of Equipment : Immobilizer  
Model No. : RI-57BTY  
Serial No. : Refer to Clause 4.2  
Rating : DC 12 V  
Receipt Date of Sample : November 25, 2015  
Condition of EUT : Engineering prototype  
(Not for Sale: This sample is equivalent to mass-produced items.)  
Modification of EUT : No Modification by the test lab

### **2.2 Product Description**

#### **Radio Specification**

[Transmitter]  
Frequency of operation : 134.2 kHz  
Modulation Type : ASK  
Operating Voltage Range : 8 V to 16 V  
Operating Temperature Range : -40 to +85 deg.C

[Receiver]  
Frequency of operation : 134.2 kHz

---

## **UL Japan, Inc.**

### **Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## **SECTION 3: Test specification, procedures & results**

### **3.1 Test Specification**

Test Specification : FCC Part 15 Subpart C: 2015, final revised on November 23, 2015  
\*Some parts are effective on and after December 17, 2015 or December 23, 2015.  
The revision does not affect the test specification applied to the EUT.

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators  
Section 15.207 Conducted Emission  
Section 15.209 Radiated emission limits, general requirements

### **3.2 Procedures and results**

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	Conducted Emission	<FCC> ANSI C63.4:2009 7. AC powerline conducted emission measurements	<FCC> Section 15.207	-	N/A *1)	N/A	N/A
2	Electric Field Strength of Fundamental Emission	<FCC> ANSI C63.4:2009 13. Measurement of intentional radiators	<FCC> Section 15.209	Radiated	N/A	33.4 dB 0.13420 MHz 0 deg. AV (PK with Duty factor)	Complied
3	Electric Field Strength of Spurious Emission	<FCC> ANSI C63.4:2009 13. Measurement of intentional radiators	<FCC> Section 15.209	Radiated	N/A	6.1 dB 59.218 MHz, Vertical, QP	Complied
4	-26dB Bandwidth	<FCC> ANSI C63.4:2009 13. Measurement of intentional radiators	<FCC> Reference data	Radiated	N/A	N/A	N/A

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.

\*1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line.

#### **FCC Part 15.31 (e)**

The test was performed with the New Battery (DC 12.0 V) and the EUT constantly provides the stable voltage to RF part through the regulator regardless of input voltage from New Battery. Therefore, this EUT complies with the requirement.

#### **FCC Part 15.203 Antenna requirement**

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the vehicle. Therefore, the equipment complies with the antenna requirement of Section 15.203.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### 3.3 Addition to standard

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	99 % Occupied Band Width	RSS-Gen 6.6	-	Radiated	N/A	N/A	N/A

Other than above, no addition, exclusion nor deviation has been made from the standard.

### 3.4 Uncertainty

#### EMI

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor  $k = 2$ .

Polarity	Radiated emission (Below 1GHz)			
	(3 m*)(+dB)		(10 m*)(+dB)	
	30 – 300 MHz	300 – 1000MHz	30 – 300 MHz	300 – 1000MHz
Horizontal	4.8 dB	5.2 dB	4.8 dB	5.0 dB
Vertical	4.5 dB	5.9 dB	4.8 dB	5.1 dB

Radiated emission				
(3 m*)(+dB)		(1 m*)(+dB)	(0.5 m*)(+dB)	(10 m*)(+dB)
1 – 6GHz	6 – 18GHz	10 – 26.5 GHz	26.5 – 40GHz	1 -18 GHz
5.1 dB	5.3 dB	5.1 dB	5.1 dB	5.3 dB

#### Radiated emission test(3 m and 10 m)

The data listed in this test report has enough margin, more than the site margin.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### 3.5 Test Location

UL Japan, Inc. Ise EMC Lab. \*NVLAP Lab. code: 200572-0  
 4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN  
 Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	4.0 x 4.5 x 2.7m	4.0 x 4.5 m	-
No.6 measurement room	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	8.0 x 4.6 x 2.8m	2.4 x 2.4m	-
No.11 measurement room	-	6.2 x 4.7 x 3.0m	4.8 x 4.6m	-

\* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

### 3.6 Test data, Test instruments, and Test set up

Refer to APPENDIX.

## UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN  
 Telephone : +81 596 24 8999  
 Facsimile : +81 596 24 8124


## **SECTION 4: Operation of E.U.T. during testing**

### **4.1 Operating Modes**

Test mode	Remarks
Continuous Transmitting mode	-

Justification : The system was configured in typical fashion (as a user would normally use it) for testing.

### **4.2 Configuration and peripherals**



\* Cabling and setup were taken into consideration and test data was taken under worse case conditions.

### **Description of EUT and Support equipment**

No.	Item	Model number	Serial number	Manufacturer	Remark
A	ECU	RI-57BTY	001	TOKAI RIKA CO., LTD.	EUT
B	Coil Antenna	-	-	TOKAI RIKA CO., LTD.	EUT
C	Key Cylinder	-	-	-	-
D	Key	-	-	-	-
E	LED PCB	-	-	-	-

### **List of cables used**

No.	Name	Length (m)	Shield		Remark
			Cable	Connector	
1	DC Cable	2.0	Unshielded	Unshielded	-
2	DC Cable	0.5	Unshielded	Unshielded	-
3	Signal Cable	0.2	Unshielded	Unshielded	-
4	Signal Cable	1.6	Unshielded	Unshielded	-

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124



## **SECTION 5: Radiated emission (Fundamental and Spurious Emission)**

### **Test Procedure**

EUT was placed on a urethane platform of nominal size, 0.5 m by 1.0 m, raised 0.8m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

Frequency : From 9 kHz to 30 MHz

The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for vertical polarization (antenna angle: 0 deg., 45 deg., 90 deg., and 135 deg.) and horizontal polarization.

\*Refer to Figure 1 about Direction of the Loop Antenna.

Frequency: From 30 MHz to 1 GHz

The measuring antenna height varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization.

The test was made with the detector (RBW / VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

### **Test Antennas are used as below;**

Frequency	Below 30 MHz	30 MHz to 300 MHz	300 MHz to 1 GHz	Above 1 GHz
Antenna Type	Loop	Biconical	Logperiodic	Horn

Frequency	From 9 kHz to 90 kHz and From 110 kHz to 150 kHz	From 90 kHz to 110 kHz	From 150 kHz to 490 kHz	From 490 kHz to 30 MHz	From 30 MHz to 1 GHz	Above 1 GHz	
Instrument used	Test Receiver					Spectrum Analyzer	
Detector	PK / AV	QP	PK / AV	QP	QP	PK	AV
IF Bandwidth	200 Hz	200 Hz	9 kHz	9 kHz	120 kHz	RBW: 1 MHz VBW: 3 MHz	RBW: 1 MHz VBW: 10 Hz
Test Distance	3 m *1)	3 m *1)	3 m *1)	3 m *2)	3 m	3 m	3 m

\*1) Distance Factor:  $40 \times \log(3 \text{ m} / 300 \text{ m}) = -80 \text{ dB}$

\*2) Distance Factor:  $40 \times \log(3 \text{ m} / 30 \text{ m}) = -40 \text{ dB}$

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open field test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 937606.

These tests were performed in semi anechoic chamber. Therefore the measured level of emissions may be higher than if measurements were made without a ground plane.

However test results were confirmed to pass against standard limit.

- This EUT has two modes which a mechanical key is inserted or not. The worst case was confirmed with and without a mechanical key, as a result, the test without mechanical key was the worst case. Therefore the test without a mechanical key was only performed.

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

## **UL Japan, Inc.**

### **Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

**Measurement range** : 9 kHz - 1 GHz  
**Test data** : APPENDIX 1  
**Test result** : Pass

Date: December 17, 2015

Test engineer: Ken Fujita

---

**UL Japan, Inc.**

**Ise EMC Lab.**


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999


Facsimile : +81 596 24 8124

**Figure 1: Direction of the Loop Antenna**

*Side View (Vertical)*




.....  
*Top View (Horizontal)*



Antenna was not rotated.

.....  
*Top View (Vertical)*



Front side: 0 deg.  
Forward direction: clockwise

## **SECTION 6: -26dB Bandwidth**

### **Test Procedure**

The test was measured with a spectrum analyzer using a test fixture.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
-26 dB Bandwidth	100 kHz	1 kHz	3 kHz	Auto	Peak	Max Hold	Spectrum Analyzer

Test data : APPENDIX 1  
Test result : Pass

## **SECTION 7: 99% Occupied Bandwidth**

### **Test Procedure**

The test was measured with a spectrum analyzer using a test fixture.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
99 % Occupied Bandwidth	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak *1)	Max Hold *1)	Spectrum Analyzer

\*1) The measurement was performed with Peak detector, Max Hold since the duty cycle was not 100 %.  
Peak hold was applied as Worst-case measurement.

Test data : APPENDIX 1  
Test result : Pass

## APPENDIX 1: Test data

### Radiated Emission below 30 MHz (Fundamental and Spurious Emission)

Test place : Ise EMC Lab. No.4 Semi Anechoic Chamber  
Order No. : 11062791H  
Date : 12/17/2015  
Temperature / Humidity : 24 deg. C / 41 % RH  
Engineer : Ken Fujita  
Mode : Tx 134.2 kHz

#### PK or QP

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit dBuV/m	Margin [dB]	Remark
0	0.1342	PK	78.0	19.6	-73.9	32.1	-	-8.4	45.0	53.4	Fundamental
0	0.1342	PK	67.7	19.6	-73.9	32.1	-	-18.7	45.0	63.7	Loop:Horizontal
0	0.2684	PK	45.2	19.6	-73.8	32.1	-	-41.1	39.0	80.1	
0	0.4026	PK	42.8	19.6	-73.8	32.1	-	-43.5	35.5	79.0	
0	0.5368	QP	32.8	19.5	-33.8	32.1	-	-13.6	33.0	46.6	
0	0.6710	QP	32.2	19.5	-33.8	32.1	-	-14.2	31.1	45.3	
0	0.8052	QP	31.8	19.5	-33.8	32.1	-	-14.6	29.5	44.1	
0	0.9394	QP	31.7	19.5	-33.8	32.1	-	-14.7	28.1	42.8	
0	1.0736	QP	31.3	19.5	-33.7	32.1	-	-15.0	26.9	41.9	
0	1.2078	QP	31.2	19.5	-33.7	32.1	-	-15.1	25.9	41.0	
0	1.3420	QP	31.0	19.5	-33.7	32.1	-	-15.3	25.0	40.3	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier)

#### PK with Duty factor

Ant Deg [deg]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit dBuV/m	Margin [dB]	Remark
0	0.1342	AV	78.0	19.6	-73.9	32.1	0.0	-8.4	25.0	33.4	Fundamental
0	0.1342	AV	67.7	19.6	-73.9	32.1	0.0	-18.7	25.0	43.7	Loop:Horizontal
0	0.2684	AV	45.2	19.6	-73.8	32.1	0.0	-41.1	19.0	60.1	
0	0.4026	AV	42.8	19.6	-73.8	32.1	0.0	-43.5	15.5	59.0	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier) + Duty factor \*

\* Since the peak emission result satisfied the average limit, duty factor was omitted.

### Result of the fundamental emission at 3m without Distance factor

#### PK or QP

Ant Deg [deg]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0	0.13420	PK	78.0	19.6	6.0	32.1	-	71.5	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter) - Gain(Amplifier)

\* All spurious emissions lower than this result.

\*The test result is rounded off to one or two decimal places, so some differences might be observed.

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

## Radiated Emission above 30 MHz (Spurious Emission)


### DATA OF RADIATED EMISSION TEST

UL Japan, Inc. Ise EMC Lab. No. 4 Semi Anechoic Chamber  
 Date : 2015/12/17

Report No. : 11062791H  
 Temp./Humi. : 24deg. C / 41% RH  
 Engineer : Ken Fujita

Mode / Remarks : Tx 134.2kHz, Coil Antenna, Worst-axis(Ant H:X V:Z, ECU H:X V:X)

LIMIT : FCC15.209 3m, below 1GHz:QP, above 1GHz:PK  
 All other spurious emissions were less than 20dB for the limit.



Frequency [MHz]	Reading [dBuV]	DET	Antenna		Level [dBuV/m]	Angle [Deg]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]	Comment
			Factor [dB/m]	Loss& Gain [dB]							
59.218	50.2	QP	8.1	-24.4	33.9	98	100	Vert.	40.0	6.1	
59.759	37.4	QP	8.0	-24.4	21.0	125	378	Hori.	40.0	19.0	
79.780	36.5	QP	6.1	-24.1	18.5	11	400	Hori.	40.0	21.5	
79.780	50.8	QP	6.1	-24.1	32.8	289	100	Vert.	40.0	7.2	
87.005	43.2	QP	7.4	-24.1	26.5	156	100	Vert.	40.0	13.5	
128.477	47.5	QP	13.7	-23.6	37.6	355	100	Vert.	43.5	5.9	
128.477	43.4	QP	13.7	-23.6	33.5	277	400	Hori.	43.5	10.0	
160.401	42.9	QP	15.2	-23.1	35.0	124	100	Vert.	43.5	8.5	
160.401	38.8	QP	15.2	-23.1	30.9	112	400	Hori.	43.5	12.6	
176.583	35.5	QP	15.9	-23.0	28.4	89	400	Hori.	43.5	15.1	
208.595	39.8	QP	16.8	-22.6	34.0	178	100	Vert.	43.5	9.5	
208.604	38.4	QP	16.8	-22.6	32.6	234	400	Hori.	43.5	10.9	

CHART:WITH FACTOR ANT TYPE: -30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz--HORN  
 CALCULATION : RESULT = READING + ANT FACTOR + LOSS & GAIN(CABLE - GAIN(AMP))

\*The test result is rounded off to one or two decimal places, so some differences might be observed.


**UL Japan, Inc.**  
**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN  
 Telephone : +81 596 24 8999  
 Facsimile : +81 596 24 8124

### -26 dB Bandwidth

Report No. 11062791H  
Test place Ise EMC Lab.  
Semi Anechoic Chamber No.4  
Date 12/17/2015  
Temperature / Humidity 24 deg. C / 41 % RH  
Engineer Ken Fujita  
Mode Tx 134.2 kHz

-26 dB Bandwidth
[kHz]
18.671



**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

### 99 % Occupied Bandwidth

Report No.	11062791H
Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.4
Date	12/17/2015
Temperature / Humidity	24 deg. C / 41 % RH
Engineer	Ken Fujita
Mode	Tx 134.2 kHz

99 % Occupied Bandwidth
[kHz]
19.4411





## **APPENDIX 2: Test instruments**

### **EMI test equipment**

<b>Control No.</b>	<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Serial No</b>	<b>Test Item</b>	<b>Calibration Date * Interval(month)</b>
MAEC-04	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	RE	2015/10/02 * 12
MOS-15	Thermo-Hygrometer	Custom	CTH-180	1501	RE	2015/01/13 * 12
MJM-26	Measure	KOMELON	KMC-36	-	RE	-
COTS-MEMI	EMI measurement program	TSJ	TEPTO-DV	-	RE	-
MTR-01	Test Receiver	Rohde & Schwarz	ESI40	100084	RE	2015/11/28 * 12
MLPA-01	Loop Antenna	Rohde & Schwarz	HFH2-Z2	100017	RE	2015/10/24 * 12
MCC-113	Coaxial cable	Fujikura/Suhner/TSJ	5D-2W(10m)/ SFM141(5m)/ 421-010(1m)/ suoform141-PE(1m)/ RFM-E121(Switcher)	-/04178	RE	2015/07/02 * 12
MCC-143	Coaxial Cable	UL Japan	-	-	RE	2015/06/24 * 12
MPA-14	Pre Amplifier	SONOMA INSTRUMENT	310	260833	RE	2015/03/09 * 12
MAT-68	Attenuator	Anritsu	MP721B	6200961025	RE	2015/11/12 * 12
MMM-10	DIGITAL HiTESTER	Hioki	3805	051201148	RE	2015/01/16 * 12
MBA-05	Biconical Antenna	Schwarzbeck	BBA9106	1302	RE	2015/11/02 * 12
MLA-08	Logperiodic Antenna	Schwarzbeck	UKLP9140-A	N/A	RE	2015/11/03 * 12
MCC-50	Coaxial Cable	UL Japan	-	-	RE	2015/06/19 * 12

**The expiration date of the calibration is the end of the expired month.**

**All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.**

**As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.**

**Test Item:**

**RE: Spurious emission**

**UL Japan, Inc.**

**Ise EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124