

RF Exposure Evaluation declaration

Product Name : 802.11b+g Wireless AP(2.4GHz)

Model No.: AP900

FCC ID: MQ4-AP900

Applicant : Abocom Systems , Inc.

Address : No.77 , Yu-Yih Rd. , Chu-Nan Chen , Miao-Lih Hsian 350 ,
Taiwan , R.O.C.

Date of Receipt : Sep. 29, 2003

Date of Declaration : Oct. 07, 2003

Report No. : 03AL007FI

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b) LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product : 802.11b+g Wireless AP(2.4GHz)
 Test Item : RF Exposure Evaluation
 Test Site : No.3 OATS

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.8dBi in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance (1.8dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2411.90	49.5450	0.0149
6	2436.90	66.5273	0.0200
11	2461.90	64.8634	0.0195

Output Power Into Antenna & RF Exposure Evaluation Distance (1.8dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2411.90	67.4528	0.0203
6	2436.90	70.1455	0.0211
11	2461.90	66.9885	0.0202

The distance r (4th column) calculated from the Friis transmission formula is far shorter than 20 cm separation requirement.