



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Abocom Systems, Inc
Applicant Address	No.77, Yu-Yih Rd., Chu-Nan, Miao-Lih County 35059, Taiwan R.O.C.
FCC ID	MQ4-PLW5Z
Manufacturer's company	Abocom Systems, Inc
Manufacturer Address	No.77, Yu-Yih Rd., Chu-Nan, Miao-Lih County 35059, Taiwan R.O.C.

Product Name	500Mbps Powerline Wireless-N Extender
Brand Name	AboCom
Model No.	PLW5Z
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Oct. 01, 2013
Final Test Date	Jan. 11, 2014
Submission Type	Original Equipment

Statement

Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03r01 and KDB 662911 D01 v02.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	5
3.5. Table for Test Modes.....	6
3.6. Table for Testing Locations.....	7
3.7. Table for Supporting Units	7
3.8. Table for Parameters of Test Software Setting	8
3.9. EUT Operation during Test	8
3.10. Duty Cycle.....	9
3.11. Test Configurations	11
4. TEST RESULT	14
4.1. AC Power Line Conducted Emissions Measurement.....	14
4.2. Maximum Conducted Output Power Measurement.....	18
4.3. Power Spectral Density Measurement	21
4.4. 6dB Spectrum Bandwidth Measurement	28
4.5. Radiated Emissions Measurement	33
4.6. Emissions Measurement	52
4.7. Antenna Requirements	70
5. LIST OF MEASURING EQUIPMENTS	71
6. MEASUREMENT UNCERTAINTY.....	73
APPENDIX A. TEST PHOTOS	A1 ~ A5
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B3



History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR320545-02	Rev. 01	Initial issue of report	Mar. 06, 2014



1. CERTIFICATE OF COMPLIANCE

Product Name : 500Mbps Powerline Wireless-N Extender
Brand Name : AboCom
Model No. : PLW5Z
Applicant : Abocom Systems, Inc
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Oct. 01, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Sam Chen'.

Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	6.45 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	5.48 dB
4.3	15.247(e)	Power Spectral Density	Complies	8.53 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.04 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.04 dB
4.7	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From internal power supply
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS0 (20MHz): 22.96 MHz ; MCS0 (40MHz): 36.48 MHz
Maximum Conducted Output Power	MCS0 (20MHz): 24.52 dBm ; MCS0 (40MHz): 18.77 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11b/g

Items	Description
Product Type	WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From internal power supply
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 14.72 MHz ; 11g: 19.60 MHz
Maximum Conducted Output Power	11b: 22.45 dBm ; 11g: 22.23 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna and Band width

Antenna	Single (TX)		Two (TX)	
	20 MHz	40 MHz	20 MHz	40 MHz
Band width Mode				
IEEE 802.11b	V	X	X	X
IEEE 802.11g	V	X	X	X
IEEE 802.11n	X	X	V	V

IEEE 11n Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	2	MCS 0-15
802.11n (HT40)	2	MCS 0-15

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).
Then EUT support HT20 and HT40.

Note 2: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n

3.2. Accessories

N/A

3.3. Table for Filed Antenna

Ant.	Brand Holder	Model Name	Antenna Type	Connector	Gain (dBi)	Remark
1	Unictron	H2U262GKBA0100	Chip Antenna	N/A	3.1	TX/RX
2	Unictron	H2U262GKBA0100	Chip Antenna	N/A	3.1	TX/RX

Note: The EUT has two antennas.


For IEEE 802.11b/g Mode: (1TX, 1RX)

Only Ant. 1 can be used as transmitting/receiving antenna.

For IEEE 802.11n Mode: (2TX, 2RX)

Both Ant. 1 and Ant. 2 can be used as transmitting/receiving antenna.

Ant. 1 and Ant. 2 could both transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	802.11n 20MHz	MCS0	1/6/11	1+2
	802.11n 40MHz	MCS0	3/6/9	1+2
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Power Spectral Density	802.11n 20MHz	MCS0	1/6/11	1+2
	802.11n 40MHz	MCS0	3/6/9	1+2
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
6dB Spectrum Bandwidth	802.11n 20MHz	MCS0	1/6/11	1+2
	802.11n 40MHz	MCS0	3/6/9	1+2
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-
Radiated Emissions 1GHz~10 th Harmonic	802.11n 20MHz	MCS0	1/6/11	1+2
	802.11n 40MHz	MCS0	3/6/9	1+2
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Band Edge Emissions	802.11n 20MHz	MCS0	1/6/11	1+2
	802.11n 40MHz	MCS0	3/6/9	1+2
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1. Normal Link

For Radiated Emission below 1GHz test:

Mode 1. Stand of EUT

Mode 2. Laying of EUT

Mode 2 is the worst case, so it was selected to record in this test report.

For Radiated Emission above 1GHz test:

Mode 1. Place EUT in X axis

Mode 2. Place EUT in Y axis

Mode 3. Place EUT in Z axis

Mode 3 is the worst case, so it was selected to record in this test report.

3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Supporting Units
For Test Site No: 03CH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6220	DoC
Notebook	DELL	E6430	DoC
Notebook	Apple	Mac Book	DoC
500Mbps Powerline Wireless-N Extender (Device)	AboCom	PLW5Z	MQ4-PLW5Z

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6430	DoC
Notebook	DELL	E6430	DoC
Notebook	DELL	E6430	DoC
500Mbps Powerline Wireless-N Extender (Device)	AboCom	PLW5Z	MQ4-PLW5Z

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6220	D2A62L1989V5

3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11n

Test Software Version	ART-GUI verison 2.3		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 20MHz	15.5	25	20
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 40MHz	13	17.5	16.5

Power Parameters of IEEE 802.11b/g


Test Software Version	ART-GUI verison 2.3		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	23.5	23.5	23
IEEE 802.11g	19	25	22

3.9. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


3.10. Duty Cycle

IEEE 802.11n MCS0 20MHz




Date: 11.JAN.2014 16:45:25

IEEE 802.11n MCS0 40MHz




Date: 11.JAN.2014 17:04:10

IEEE 802.11b



Date: 11.JAN.2014 16:04:29


IEEE 802.11g



Date: 11.JAN.2014 16:21:45

3.11. Test Configurations


3.11.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shield	Length	Remark
1	RJ-45 cable	No	3m	-
2	RJ-45 cable	No	3m	LOAD
3	RJ-45 cable	No	10m	-


3.11.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz



Item	Connection	Shield	Length	Remark
1	RJ-45 cable	No	1.5m	Load
2	RJ-45 cable	No	10m	-
3	RJ-45 cable	No	1.5m	-

Test Configuration: above 1GHz



Item	Connection	Shield	Length	Remark
1	RJ-45 cable	No	10m	-

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	53%
Test Engineer	Justin Chiu	Phase	Line
Configuration	Normal Link	Test Mode	Mode 1



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.16677	58.08	-7.04	65.12	57.76	0.16	0.16	LINE	QP
2	0.16677	42.18	-12.94	55.12	41.86	0.16	0.16	LINE	AVERAGE
3	0.20289	53.49	-10.01	63.49	53.17	0.15	0.17	LINE	QP
4	0.20289	39.50	-14.00	53.49	39.18	0.15	0.17	LINE	AVERAGE
5	0.23910	50.11	-12.02	62.13	49.79	0.15	0.17	LINE	QP
6	0.23910	37.59	-14.54	52.13	37.27	0.15	0.17	LINE	AVERAGE
7	0.26724	47.06	-14.14	61.20	46.74	0.15	0.17	LINE	QP
8	0.26724	32.41	-18.79	51.20	32.09	0.15	0.17	LINE	AVERAGE
9	0.64058	32.75	-23.25	56.00	32.40	0.16	0.19	LINE	QP
10	0.64058	26.88	-19.12	46.00	26.53	0.16	0.19	LINE	AVERAGE
11	2.554	27.61	-28.39	56.00	27.14	0.20	0.27	LINE	QP
12	2.554	19.32	-26.68	46.00	18.85	0.20	0.27	LINE	AVERAGE
13	10.905	31.53	-28.47	60.00	30.79	0.35	0.39	LINE	QP
14	10.905	27.02	-22.98	50.00	26.28	0.35	0.39	LINE	AVERAGE

Temperature	24°C	Humidity	53%
Test Engineer	Justin Chiu	Phase	Neutral
Configuration	Normal Link	Test Mode	Mode 1



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.17399	58.32	-6.45	64.77	58.08	0.08	0.16	NEUTRAL	QP
2	0.17399	44.43	-10.34	54.77	44.19	0.08	0.16	NEUTRAL	AVERAGE
3	0.20289	51.80	-11.70	63.49	51.55	0.08	0.17	NEUTRAL	QP
4	0.20289	37.50	-16.00	53.49	37.25	0.08	0.17	NEUTRAL	AVERAGE
5	0.23285	49.82	-12.53	62.35	49.57	0.08	0.17	NEUTRAL	QP
6	0.23285	34.95	-17.40	52.35	34.70	0.08	0.17	NEUTRAL	AVERAGE
7	0.26724	45.67	-15.53	61.20	45.42	0.08	0.17	NEUTRAL	QP
8	0.26724	30.93	-20.27	51.20	30.68	0.08	0.17	NEUTRAL	AVERAGE
9	0.70468	32.69	-23.31	56.00	32.41	0.09	0.19	NEUTRAL	QP
10	0.70468	32.22	-13.78	46.00	31.94	0.09	0.19	NEUTRAL	AVERAGE
11	2.358	31.33	-24.67	56.00	30.96	0.11	0.26	NEUTRAL	QP
12	2.358	22.57	-23.43	46.00	22.20	0.11	0.26	NEUTRAL	AVERAGE
13	10.072	31.24	-28.76	60.00	30.61	0.24	0.38	NEUTRAL	QP
14	10.072	24.78	-25.22	50.00	24.15	0.24	0.38	NEUTRAL	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r01 section 9.2.2 Measurement using a power meter (PM).
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	21°C	Humidity	56%
Test Engineer	YC Chen	Configurations	IEEE 802.11n
Test Date	Jan. 11, 2014		

Configuration IEEE 802.11n MCS0 20MHz

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	14.97	15.85	18.44	30.00	Complies
6	2437 MHz	21.33	21.69	24.52	30.00	Complies
11	2462 MHz	17.11	17.65	20.40	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
3	2422 MHz	12.03	12.57	15.32	30.00	Complies
6	2437 MHz	15.41	16.09	18.77	30.00	Complies
9	2452 MHz	13.69	14.25	16.99	30.00	Complies

Temperature	21°C	Humidity	56%
Test Engineer	YC Chen	Configurations	IEEE 802.11b/g
Test Date	Jan. 11, 2014		

Configuration IEEE 802.11b / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	22.45	30.00	Complies
6	2437 MHz	21.76	30.00	Complies
11	2462 MHz	21.01	30.00	Complies

Configuration IEEE 802.11g / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	18.52	30.00	Complies
6	2437 MHz	22.23	30.00	Complies
11	2462 MHz	19.67	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r01 section 10.2 Method PKPSD (peak PSD) and KDB 662911 D01 v02 section In-Band Power Spectral Density (PSD) Measurements option (b) Measure and sum spectral maximal across the outputs.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	21°C	Humidity	56%
Test Engineer	YC Chen	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 20MHz

Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	-8.68	-10.07	-6.31	8.00	Complies
6	2437 MHz	-3.23	-3.88	-0.53	8.00	Complies
11	2462 MHz	-7.16	-7.22	-4.18	8.00	Complies

Configuration IEEE 802.11n MCS0 40MHz

Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Total		
3	2422 MHz	-9.35	-12.59	-7.66	8.00	Complies
6	2437 MHz	-10.37	-11.46	-7.87	8.00	Complies
9	2452 MHz	-9.40	-14.28	-8.18	8.00	Complies

Temperature	21°C	Humidity	56%
Test Engineer	YC Chen	Configurations	IEEE 802.11b/g

Configuration IEEE 802.11b / Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
1	2412 MHz	-1.41	8.00	Complies
6	2437 MHz	-2.24	8.00	Complies
11	2462 MHz	-3.01	8.00	Complies


Configuration IEEE 802.11g / Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
1	2412 MHz	-6.66	8.00	Complies
6	2437 MHz	-3.17	8.00	Complies
11	2462 MHz	-2.95	8.00	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / 2437 MHz / Ant. 1




Date: 11.JAN.2014 16:52:27

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / 2437 MHz / Ant. 2




Date: 11.JAN.2014 16:54:26

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / 2422 MHz / Ant. 1




Date: 11.JAN.2014 17:18:39

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / 2422 MHz / Ant. 2




Date: 11.JAN.2014 17:19:56

Power Density Plot on Configuration IEEE 802.11b / 2412 MHz / Ant. 1



Date: 11.JAN.2014 16:09:04

Power Density Plot on Configuration IEEE 802.11g / 2462 MHz / Ant. 1



Date: 11.JAN.2014 16:42:59

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03r01 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.0 DTS 6-dB signal bandwidth option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	21°C	Humidity	56%
Test Engineer	YC Chen	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.60	17.92	500	Complies
6	2437 MHz	17.28	22.96	500	Complies
11	2462 MHz	17.04	17.76	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	35.68	36.48	500	Complies
6	2437 MHz	35.36	36.32	500	Complies
9	2452 MHz	35.20	36.32	500	Complies

Temperature	21°C	Humidity	56%
Test Engineer	YC Chen	Configurations	IEEE 802.11b/g

Configuration IEEE 802.11b / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.00	14.72	500	Complies
6	2437 MHz	9.52	14.16	500	Complies
11	2462 MHz	9.60	14.00	500	Complies


Configuration IEEE 802.11g / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.32	16.64	500	Complies
6	2437 MHz	16.00	19.60	500	Complies
11	2462 MHz	16.32	16.72	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / 2462 MHz / Ant. 1 + Ant. 2




Date: 11.JAN.2014 18:31:03

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / 2452 MHz / Ant. 1 + Ant. 2




Date: 11.JAN.2014 18:42:49

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz / Ant. 1



Date: 11.JAN.2014 18:08:28

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz / Ant. 1



Date: 11.JAN.2014 18:16:05

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	Normal Link
Test Date	Oct. 07, 2013	Test Mode	Mode 2

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	Normal Link
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	36.79	27.97	40.00	-12.03	39.40	0.95	28.00	15.62	Peak	0	400	HORIZONTAL
2	199.75	37.70	43.50	-5.80	52.46	2.09	27.25	10.40	Peak	0	400	HORIZONTAL
3	312.27	35.68	46.00	-10.32	45.80	2.58	26.88	14.18	Peak	0	400	HORIZONTAL
4	399.57	32.54	46.00	-13.46	40.51	2.99	27.46	16.50	Peak	0	400	HORIZONTAL
5	600.36	35.79	46.00	-10.21	40.36	3.73	27.60	19.30	Peak	0	400	HORIZONTAL
6	900.09	35.60	46.00	-10.40	36.33	4.60	26.83	21.50	Peak	0	400	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	55.22	32.23	40.00	-7.77	51.20	1.13	27.90	7.80	QP	305	100	VERTICAL
2	66.86	35.11	40.00	-4.89	55.00	1.23	27.95	6.83	QP	9	100	VERTICAL
3	77.53	35.79	40.00	-4.21	55.07	1.32	27.91	7.31	Peak	0	100	VERTICAL
4	169.68	36.61	43.50	-6.89	51.78	1.94	27.41	10.30	Peak	0	100	VERTICAL
5	600.36	38.37	46.00	-7.63	42.94	3.73	27.60	19.30	Peak	0	100	VERTICAL
6	900.09	36.94	46.00	-9.06	37.67	4.60	26.83	21.50	Peak	0	100	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 1 / Ant. 1 + Ant. 2
Test Date	Dec. 06, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2288.00	48.52	54.00	-5.48	51.66	4.02	27.80	34.96	Average	168	312	HORIZONTAL
2	2288.02	54.03	74.00	-19.97	57.17	4.02	27.80	34.96	Peak	168	312	HORIZONTAL
3	4816.50	36.02	54.00	-17.98	32.01	5.85	33.36	35.20	Average	143	336	HORIZONTAL
4	4822.10	49.23	74.00	-24.77	45.17	5.87	33.39	35.20	Peak	143	336	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2288.03	53.52	54.00	-0.48	56.66	4.02	27.80	34.96	Average	104	316	VERTICAL
2	2288.06	58.47	74.00	-15.53	61.61	4.02	27.80	34.96	Peak	104	316	VERTICAL
3	4823.70	46.90	74.00	-27.10	42.84	5.87	33.39	35.20	Peak	146	50	VERTICAL
4	4824.00	33.70	54.00	-20.30	29.64	5.87	33.39	35.20	Average	146	50	VERTICAL



Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 6 / Ant. 1 + Ant. 2
Test Date	Dec. 06, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2287.86	53.90	74.00	-20.10	57.04	4.02	27.80	34.96	Peak	139	306	HORIZONTAL
2	2288.00	46.87	54.00	-7.13	50.01	4.02	27.80	34.96	Average	139	306	HORIZONTAL
3	4864.84	65.53	74.00	-8.47	61.38	5.90	33.45	35.20	Peak	137	330	HORIZONTAL
4	4868.80	48.09	54.00	-5.91	43.92	5.92	33.45	35.20	Average	137	330	HORIZONTAL
5	7307.32	73.62	74.00	-0.38	65.44	7.13	36.48	35.43	Peak	137	254	HORIZONTAL
6	7313.96	46.56	54.00	-7.44	38.35	7.13	36.51	35.43	Average	137	254	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2288.02	50.39	54.00	-3.61	53.53	4.02	27.80	34.96	Average	103	275	VERTICAL
2	2288.05	56.61	74.00	-17.39	59.75	4.02	27.80	34.96	Peak	103	275	VERTICAL
3	4871.72	62.10	74.00	-11.90	57.90	5.92	33.48	35.20	Peak	148	51	VERTICAL
4	4872.96	45.20	54.00	-8.80	41.00	5.92	33.48	35.20	Average	148	51	VERTICAL
5	7307.80	73.39	74.00	-0.61	65.18	7.13	36.51	35.43	Peak	180	174	VERTICAL
6	7316.24	49.69	54.00	-4.31	41.47	7.14	36.51	35.43	Average	180	174	VERTICAL

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 11 / Ant. 1 + Ant. 2
Test Date	Dec. 06, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	2287.88	54.95	74.00	-19.05	58.09	4.02	27.80	34.96	Peak	170	304	HORIZONTAL
2	2288.06	49.34	54.00	-4.66	52.48	4.02	27.80	34.96	Average	170	304	HORIZONTAL
3	4916.80	54.34	74.00	-19.66	50.05	5.95	33.54	35.20	Peak	136	4	HORIZONTAL
4	4917.80	41.35	54.00	-12.65	37.06	5.95	33.54	35.20	Average	136	4	HORIZONTAL
5	7381.96	57.02	74.00	-16.98	48.70	7.16	36.61	35.45	Peak	131	283	HORIZONTAL
6	7386.00	41.09	54.00	-12.91	32.77	7.17	36.61	35.46	Average	131	283	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	2288.04	53.26	54.00	-0.74	56.40	4.02	27.80	34.96	Average	104	339	VERTICAL
2	2288.12	58.50	74.00	-15.50	61.64	4.02	27.80	34.96	Peak	104	339	VERTICAL
3	4923.24	53.85	74.00	-20.15	49.50	5.97	33.58	35.20	Peak	126	34	VERTICAL
4	4924.26	39.80	54.00	-14.20	35.45	5.97	33.58	35.20	Average	126	34	VERTICAL
5	7382.08	61.50	74.00	-12.50	53.18	7.16	36.61	35.45	Peak	177	174	VERTICAL
6	7383.40	43.98	54.00	-10.02	35.67	7.16	36.61	35.46	Average	177	174	VERTICAL

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz CH 3 / Ant. 1 + Ant. 2
Test Date	Dec. 06, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2287.85	54.37	74.00	-19.63	57.51	4.02	27.80	34.96	Peak	170	282	HORIZONTAL
2	2288.04	49.98	54.00	-4.02	53.12	4.02	27.80	34.96	Average	170	282	HORIZONTAL
3	4834.64	32.51	54.00	-21.49	28.44	5.88	33.39	35.20	Average	100	238	HORIZONTAL
4	4854.00	45.68	74.00	-28.32	41.53	5.90	33.45	35.20	Peak	100	238	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2287.97	59.28	74.00	-14.72	62.42	4.02	27.80	34.96	Peak	103	339	VERTICAL
2	2288.03	53.96	54.00	-0.04	57.10	4.02	27.80	34.96	Average	103	339	VERTICAL
3	4844.00	32.62	54.00	-21.38	28.52	5.88	33.42	35.20	Average	100	119	VERTICAL
4	4848.40	45.34	74.00	-28.66	41.24	5.88	33.42	35.20	Peak	100	119	VERTICAL

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz CH 6 / Ant. 1 + Ant. 2
Test Date	Dec. 06, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	2288.02	54.64	74.00	-19.36	57.78	4.02	27.80	34.96	Peak	171	301	HORIZONTAL
2	2288.06	49.37	54.00	-4.63	52.51	4.02	27.80	34.96	Average	171	301	HORIZONTAL
3	4872.52	34.02	54.00	-19.98	29.82	5.92	33.48	35.20	Average	100	260	HORIZONTAL
4	4873.66	46.51	74.00	-27.49	42.31	5.92	33.48	35.20	Peak	100	260	HORIZONTAL
5	7306.92	36.45	54.00	-17.55	28.27	7.13	36.48	35.43	Average	100	83	HORIZONTAL
6	7308.54	49.99	74.00	-24.01	41.78	7.13	36.51	35.43	Peak	100	83	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	2287.98	58.06	74.00	-15.94	61.20	4.02	27.80	34.96	Peak	104	340	VERTICAL
2	2288.03	53.05	54.00	-0.95	56.19	4.02	27.80	34.96	Average	104	340	VERTICAL
3	4872.24	46.25	74.00	-27.75	42.05	5.92	33.48	35.20	Peak	100	313	VERTICAL
4	4875.74	32.54	54.00	-21.46	28.34	5.92	33.48	35.20	Average	100	313	VERTICAL
5	7308.28	54.15	74.00	-19.85	45.94	7.13	36.51	35.43	Peak	100	185	VERTICAL
6	7314.58	37.18	54.00	-16.82	28.97	7.13	36.51	35.43	Average	100	185	VERTICAL

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz CH 9 / Ant. 1 + Ant. 2
Test Date	Dec. 06, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2287.96	55.37	74.00	-18.63	58.51	4.02	27.80	34.96	Peak	169	302	HORIZONTAL
2	2288.04	49.63	54.00	-4.37	52.77	4.02	27.80	34.96	Average	169	302	HORIZONTAL
3	4902.40	45.84	74.00	-28.16	41.58	5.95	33.51	35.20	Peak	100	82	HORIZONTAL
4	4904.54	32.45	54.00	-21.55	28.19	5.95	33.51	35.20	Average	100	82	HORIZONTAL
5	7351.96	50.48	74.00	-23.52	42.20	7.16	36.56	35.44	Peak	100	186	HORIZONTAL
6	7356.64	37.21	54.00	-16.79	28.93	7.16	36.56	35.44	Average	100	186	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2288.04	58.70	74.00	-15.30	61.84	4.02	27.80	34.96	Peak	103	338	VERTICAL
2	2288.06	53.62	54.00	-0.38	56.76	4.02	27.80	34.96	Average	103	338	VERTICAL
3	4904.18	32.11	54.00	-21.89	27.85	5.95	33.51	35.20	Average	100	70	VERTICAL
4	4906.12	45.34	74.00	-28.66	41.05	5.95	33.54	35.20	Peak	100	70	VERTICAL
5	7351.30	37.37	54.00	-16.63	29.09	7.16	36.56	35.44	Average	100	355	VERTICAL
6	7351.74	51.37	74.00	-22.63	43.09	7.16	36.56	35.44	Peak	100	355	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11b CH 1 / Ant. 1
Test Date	Dec. 03, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4824.01	50.53	54.00	-3.47	49.19	3.31	33.06	35.03	Average	174	262	HORIZONTAL
2	4824.07	52.91	74.00	-21.09	51.57	3.31	33.06	35.03	Peak	174	262	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.95	52.99	74.00	-21.01	51.65	3.31	33.06	35.03	Peak	116	291	VERTICAL
2	4823.98	50.57	54.00	-3.43	49.23	3.31	33.06	35.03	Average	116	291	VERTICAL

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11b CH 6 / Ant. 1
Test Date	Dec. 03, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.89	47.77	74.00	-26.23	46.31	3.33	33.16	35.03	Peak	100	223	HORIZONTAL
2	4873.95	43.15	54.00	-10.85	41.69	3.33	33.16	35.03	Average	100	223	HORIZONTAL
3	7311.14	61.68	74.00	-12.32	57.06	4.06	35.96	35.40	Peak	122	294	HORIZONTAL
4	7311.77	48.74	54.00	-5.26	44.12	4.06	35.96	35.40	Average	122	294	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.01	50.28	54.00	-3.72	48.82	3.33	33.16	35.03	Average	115	291	VERTICAL
2	4874.07	53.88	74.00	-20.12	52.42	3.33	33.16	35.03	Peak	115	291	VERTICAL
3	7311.03	66.20	74.00	-7.80	61.58	4.06	35.96	35.40	Peak	103	351	VERTICAL
4	7311.75	53.54	54.00	-0.46	48.92	4.06	35.96	35.40	Average	103	351	VERTICAL

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11b CH 11 / Ant. 1
Test Date	Dec. 03, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.98	47.56	54.00	-6.44	43.21	5.97	33.58	35.20	Average	140	108	HORIZONTAL
2	4924.37	52.98	74.00	-21.02	48.63	5.97	33.58	35.20	Peak	140	108	HORIZONTAL
3	7386.12	61.33	74.00	-12.67	53.01	7.17	36.61	35.46	Peak	150	94	HORIZONTAL
4	7386.75	50.05	54.00	-3.95	41.73	7.17	36.61	35.46	Average	150	94	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4924.00	57.38	74.00	-16.62	53.03	5.97	33.58	35.20	Peak	162	79	VERTICAL
2	4924.02	53.89	54.00	-0.11	49.54	5.97	33.58	35.20	Average	162	79	VERTICAL
3	7385.26	53.75	54.00	-0.25	45.43	7.17	36.61	35.46	Average	152	360	VERTICAL
4	7389.73	68.42	74.00	-5.58	60.10	7.17	36.61	35.46	Peak	152	360	VERTICAL

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11g CH 1 / Ant. 1
Test Date	Dec. 06, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4829.48	45.03	74.00	-28.97	40.97	5.87	33.39	35.20	Peak	100	13	HORIZONTAL
2	4833.80	32.23	54.00	-21.77	28.16	5.88	33.39	35.20	Average	100	13	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4814.20	32.21	54.00	-21.79	28.20	5.85	33.36	35.20	Average	100	261	VERTICAL
2	4833.32	45.69	74.00	-28.31	41.63	5.87	33.39	35.20	Peak	100	261	VERTICAL

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11g CH 6 / Ant. 1
Test Date	Dec. 06, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4872.32	56.10	74.00	-17.90	51.90	5.92	33.48	35.20	Peak	159	235	HORIZONTAL
2	4873.52	40.58	54.00	-13.42	36.38	5.92	33.48	35.20	Average	159	235	HORIZONTAL
3	7311.08	56.10	74.00	-17.90	47.89	7.13	36.51	35.43	Peak	100	46	HORIZONTAL
4	7311.84	41.46	54.00	-12.54	33.25	7.13	36.51	35.43	Average	100	46	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4871.44	56.08	74.00	-17.92	51.88	5.92	33.48	35.20	Peak	166	267	VERTICAL
2	4873.68	39.59	54.00	-14.41	35.39	5.92	33.48	35.20	Average	166	267	VERTICAL
3	7310.04	48.67	54.00	-5.33	40.46	7.13	36.51	35.43	Average	108	185	VERTICAL
4	7314.84	67.38	74.00	-6.62	59.17	7.13	36.51	35.43	Peak	108	185	VERTICAL

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11g CH 11 / Ant. 1
Test Date	Dec. 06, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4925.88	33.22	54.00	-20.78	28.87	5.97	33.58	35.20	Average	100	22	HORIZONTAL
2	4926.16	46.20	74.00	-27.80	41.85	5.97	33.58	35.20	Peak	100	22	HORIZONTAL
3	7382.20	57.18	74.00	-16.82	48.86	7.16	36.61	35.45	Peak	138	278	HORIZONTAL
4	7386.64	43.63	54.00	-10.37	35.31	7.17	36.61	35.46	Average	138	278	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.36	36.55	54.00	-17.45	32.20	5.97	33.58	35.20	Average	138	242	VERTICAL
2	4925.16	49.66	74.00	-24.34	45.31	5.97	33.58	35.20	Peak	138	242	VERTICAL
3	7386.92	46.90	54.00	-7.10	38.58	7.17	36.61	35.46	Average	148	186	VERTICAL
4	7393.40	62.09	74.00	-11.91	53.74	7.17	36.64	35.46	Peak	148	186	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Radiated Out of Band Emission Measurement:

1. Test was performed in accordance with KDB 558074 D01 v03r01 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.
2. The radiated emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.
Only worst data of each operating mode is presented.

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 1, 6, 11 / Ant. 1 + Ant. 2
Test Date	Dec. 06, 2013		

Channel 1

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	53.96	54.00	-0.04	21.82	4.09	28.05	0.00	Average	100	4	VERTICAL
2	2390.00	73.25	74.00	-0.75	41.11	4.09	28.05	0.00	Peak	100	4	VERTICAL
3	2412.80	110.50			78.30	4.11	28.09	0.00	Peak	100	4	VERTICAL
4	2413.40	98.77			66.57	4.11	28.09	0.00	Average	100	4	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2357.60	66.62	74.00	-7.38	34.58	4.07	27.97	0.00	Peak	100	332	VERTICAL
2	2359.60	53.39	54.00	-0.61	21.35	4.07	27.97	0.00	Average	100	332	VERTICAL
3	2438.20	116.81			84.50	4.13	28.18	0.00	Peak	100	332	VERTICAL
4	2438.60	105.02			72.71	4.13	28.18	0.00	Average	100	332	VERTICAL
5	2483.50	48.43	54.00	-5.57	16.01	4.16	28.26	0.00	Average	100	332	VERTICAL
6	2483.90	62.73	74.00	-11.27	30.31	4.16	28.26	0.00	Peak	100	332	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2463.60	98.74			66.38	4.14	28.22	0.00	Average	228	304	HORIZONTAL
2	2463.80	110.89			78.53	4.14	28.22	0.00	Peak	228	304	HORIZONTAL
3	2483.50	53.79	54.00	-0.21	21.37	4.16	28.26	0.00	Average	228	304	HORIZONTAL
4	2483.90	73.30	74.00	-0.70	40.88	4.16	28.26	0.00	Peak	228	304	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz CH 3, 6, 9 / Ant. 1 + Ant. 2
Test Date	Dec. 06, 2013		

Channel 3

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	52.73	54.00	-1.27	20.59	4.09	28.05	0.00	Average	100	334	VERTICAL
2	2390.00	73.62	74.00	-0.38	41.48	4.09	28.05	0.00	Peak	100	334	VERTICAL
3	2410.80	92.14			59.94	4.11	28.09	0.00	Average	100	334	VERTICAL
4	2410.80	105.04			72.84	4.11	28.09	0.00	Peak	100	334	VERTICAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.20	52.88	54.00	-1.12	20.74	4.09	28.05	0.00	Average	100	334	VERTICAL
2	2390.00	71.00	74.00	-3.00	38.86	4.09	28.05	0.00	Peak	100	334	VERTICAL
3	2428.20	95.36			63.11	4.12	28.13	0.00	Average	100	334	VERTICAL
4	2429.00	108.07			75.82	4.12	28.13	0.00	Peak	100	334	VERTICAL
5	2483.50	47.24	54.00	-6.76	14.82	4.16	28.26	0.00	Average	100	334	VERTICAL
6	2483.50	64.17	74.00	-9.83	31.75	4.16	28.26	0.00	Peak	100	334	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 9

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2435.20	93.89			61.59	4.12	28.18	0.00	Average	100	333	VERTICAL
2	2436.40	107.07			74.77	4.12	28.18	0.00	Peak	100	333	VERTICAL
3	2483.50	48.84	54.00	-5.16	16.42	4.16	28.26	0.00	Average	100	333	VERTICAL
4	2483.50	73.67	74.00	-0.33	41.25	4.16	28.26	0.00	Peak	100	333	VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. 1
Test Date	Dec. 03, 2013		

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2383.75	60.30	74.00	-13.70	29.92	2.21	28.17	0.00	Peak	100	215 VERTICAL
2	2385.99	50.42	54.00	-3.58	20.04	2.21	28.17	0.00	Average	100	215 VERTICAL
3	2410.24	104.56			74.13	2.22	28.21	0.00	Average	100	215 VERTICAL
4	2411.04	108.21			77.78	2.22	28.21	0.00	Peak	100	215 VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2355.06	59.52	74.00	-14.48	29.23	2.19	28.10	0.00	Peak	101	190 VERTICAL
2	2358.59	49.64	54.00	-4.36	19.35	2.19	28.10	0.00	Average	101	190 VERTICAL
3	2437.96	105.57			75.05	2.23	28.29	0.00	Peak	101	190 VERTICAL
4	2438.92	101.99			71.47	2.23	28.29	0.00	Average	101	190 VERTICAL
5	2483.50	46.47	54.00	-7.53	15.84	2.26	28.37	0.00	Average	101	190 VERTICAL
6	2491.83	59.02	74.00	-14.98	28.34	2.27	28.41	0.00	Peak	101	190 VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2461.20	104.93			72.57	4.14	28.22	0.00	Average	100	152 VERTICAL
2	2463.60	109.77			77.41	4.14	28.22	0.00	Peak	100	152 VERTICAL
3	2483.82	50.04	54.00	-3.96	17.62	4.16	28.26	0.00	Average	100	152 VERTICAL
4	2484.78	65.14	74.00	-8.86	32.72	4.16	28.26	0.00	Peak	100	152 VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	25°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 1
Test Date	Dec. 03, 2013 ~ Dec. 06, 2013		

Channel 1

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.42	51.23	54.00	-2.77	20.85	2.21	28.17	0.00	Average	187	300	HORIZONTAL
2	2389.71	72.50	74.00	-1.50	42.12	2.21	28.17	0.00	Peak	187	300	HORIZONTAL
3	2405.63	95.03			64.60	2.22	28.21	0.00	Average	187	300	HORIZONTAL
4	2407.66	106.15			75.72	2.22	28.21	0.00	Peak	187	300	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	46.69	54.00	-7.31	16.30	2.22	28.17	0.00	Average	101	293	VERTICAL
2	2390.00	64.64	74.00	-9.36	34.25	2.22	28.17	0.00	Peak	101	293	VERTICAL
3	2441.05	100.34			69.81	2.24	28.29	0.00	Average	101	293	VERTICAL
4	2441.34	112.73			82.20	2.24	28.29	0.00	Peak	101	293	VERTICAL
5	2483.50	47.32	54.00	-6.68	16.69	2.26	28.37	0.00	Average	101	293	VERTICAL
6	2483.50	63.12	74.00	-10.88	32.49	2.26	28.37	0.00	Peak	101	293	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2456.00	96.07			63.71	4.14	28.22	0.00	Average	100	27	VERTICAL
2	2466.40	108.01			75.65	4.14	28.22	0.00	Peak	100	27	VERTICAL
3	2483.50	53.08	54.00	-0.92	20.66	4.16	28.26	0.00	Average	100	27	VERTICAL
4	2484.30	71.89	74.00	-2.11	39.47	4.16	28.26	0.00	Peak	100	27	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level




Date: 6.DEC.2013 22:13:12

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 6.DEC.2013 22:14:01

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 6.DEC.2013 22:14:47

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 6.DEC.2013 22:15:43

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 6.DEC.2013 22:15:24

Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level




Date: 6.DEC.2013 22:07:51

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 6.DEC.2013 22:08:48

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 6.DEC.2013 22:09:47

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 / 30MHz~2400MHz (down 30dBc)




Date: 6.DEC.2013 22:10:47

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 / 2500MHz~26500MHz (down 30dBc)




Date: 6.DEC.2013 22:10:26

Plot on Configuration IEEE 802.11b / Reference Level




Date: 6.DEC.2013 22:22:34

Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 6.DEC.2013 22:23:26

Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 6.DEC.2013 22:23:58

Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 6.DEC.2013 22:25:01

Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 6.DEC.2013 22:24:45

Plot on Configuration IEEE 802.11g / Reference Level




Date: 6.DEC.2013 22:19:15

Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 6.DEC.2013 22:19:55

Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)



Date: 6.DEC.2013 22:20:26

Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)



Date: 6.DEC.2013 22:21:20

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9 kHz ~ 2.75 GHz	Apr. 12, 2013	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150 kHz ~ 100 MHz	Nov. 23, 2013	Conduction (CO01-CB)
Artificial Mains Network	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Nov. 23, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150 kHz ~ 30 MHz	Dec. 04, 2013	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	-	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Apr. 16, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 01, 2013	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-507	15GHz ~ 40GHz	Jan. 14, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02097	1GHz ~ 26.5GHz	Dec. 02, 2013	Radiation (03CH01-CB)
Spectrum analyzer	Agilent	N9010A	MY52220557	9KHz~44GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100019	9kHz~40GHz	Dec. 02, 2013	Radiation (03CH01-CB)
EMI Test Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8GHz	Nov. 26, 2012	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

Note: "*" Calibration Interval of instruments listed above is two years.

Note: N.C.R. means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	0.026	dB	normal(k=2)	0.013
Cable loss	0.002	dB	normal(k=2)	0.001
AMN/LISN specification	1.200	dB	normal(k=2)	0.600
Mismatch Receiver VSWR 1= AMN/LISN VSWR 2=	-0.080	dB	U-shaped	0.060
Combined standard uncertainty $U_c(y)$				1.2
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				2.4

Uncertainty of Radiated Emission Measurement (30MHz ~ 1,000MHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	± 0.173	dB	K=1	0.086
Cable loss	± 0.174	dB	K=2	0.087
Antenna gain	± 0.169	dB	K=2	0.084
Site imperfection	± 0.433	dB	Triangular	0.214
Pre-amplifier gain	± 0.366	dB	K=2	0.183
Transmitter antenna	± 1.200	dB	Rectangular	0.600
Signal generator	± 0.461	dB	Rectangular	0.231
Mismatch	± 0.080	dB	U-shape	0.040
Spectrum analyzer	± 0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.778
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.555

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	±0.191	dB	K=1	0.095
Cable loss	±0.169	dB	K=2	0.084
Antenna gain	±0.191	dB	K=2	0.096
Site imperfection	±0.582	dB	Triangular	0.291
Pre-amplifier gain	±0.304	dB	K=2	0.152
Transmitter antenna	±1.200	dB	Rectangular	0.600
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.839
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.678

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	±0.186	dB	K=1	0.093
Cable loss	±0.167	dB	K=2	0.083
Antenna gain	±0.190	dB	K=2	0.095
Site imperfection	±0.488	dB	Triangular	0.244
Pre-amplifier gain	±0.269	dB	K=2	0.134
Transmitter antenna	±1.200	dB	Rectangular	0.600
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.771
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.541

Uncertainty of Conducted Emission Measurement

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Cable loss	±0.038	dB	K=2	0.019
Attenuator	±0.047	dB	K=2	0.024
Power Meter specification	±0.300	dB	Triangular	0.150
Power Sensor specification	±0.300	dB	Rectangular	0.150
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				0.863
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				1.726