

# FCC Test Report

**EQUIPMENT** : 60GHz WirelessHD Source Module  
**BRAND NAME** : Abocom  
**MODEL NO.** : VM311T  
**FCC ID** : MQ4-VM311T01  
**STANDARD** : 47 CFR FCC Part 15.255  
**APPLICANT** : Abocom Systems, Inc  
No.77, Yu-Yih Rd., Chu-Nan, Miao-Lih County  
35059, Taiwan R.O.C.  
**MANUFACTURER** : Abocom Systems, Inc

The product sample received on Nov. 30, 2010 and completely tested on Dec. 03, 2010. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

*Jordan Hsiao 2010-12-7*  
Reviewed by: Jordan Hsiao





# TABLE OF CONTENTS

**TABLE OF CONTENTS** .....2

**SUMMARY OF TEST RESULT** .....3

**REVISION HISTORY**.....4

**1 GENERAL DESCRIPTION** .....5

1.1 Information.....5

1.2 Additional Information Provided by the Submitter .....8

1.3 Ancillary and/or Support Equipment.....9

1.4 EUT Setups .....9

1.5 Testing Applied Standards .....13

1.6 Testing Location .....13

1.7 Abbreviations Used for the Test Report .....13

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST** .....14

2.1 Test Channel Frequencies .....14

2.2 Conformance Tests and Related Test Frequencies .....14

**3 TRANSMITTER TEST RESULT** .....15

3.1 AC Power Conducted Emissions .....15

3.2 Occupied Bandwidth .....19

3.3 EIRP Power and Power Density.....25

3.4 Peak Conducted Power.....33

3.5 Transmitter Spurious Emissions.....36

3.6 Frequency Stability .....43

3.7 Publicly-accessible Coordination Channel .....46

3.8 Operation Restriction and Group Installation .....49

3.9 Transmitter Identification .....50

3.10 Maximum Permissible Exposure .....51

**4 LIST OF MEASURING EQUIPMENTS**.....53

**5 CERTIFICATION OF TAF ACCREDITATION**.....55

**APPENDIX A. TEST PHOTOS** .....56

**APPENDIX B. PHOTOGRAPHS OF EUT** .....59



### SUMMARY OF TEST RESULT

FCC Standard Requirements and Conformance Test Specifications				
Report Clause	Ref. Std. Clause	Description	Result	Remark
3.1	15.207	AC Power Conducted Emissions	Complied	-
3.2	15.255(e)	Occupied Bandwidth	Complied	-
3.3	15.255(b)(1)	EIRP Power and Power Density	Complied	-
3.4	15.255(e)	Peak Conducted Power	Complied	-
3.5	15.255(c)	Transmitter Spurious Emissions	Complied	-
3.6	15.255(f)	Frequency Stability	Complied	-
3.7	15.255(d)	Publicly-accessible Coordination Channel	Complied	-
3.8	15.255(a),(h)	Operation Restriction and Group Installation	Complied	-
3.9	15.255(i)	Transmitter Identification	Complied	-
3.10	15.255(g)	Maximum Permissible Exposure	Complied	-



# 1 General Description

## 1.1 Information

### 1.1.1 The Channel Plan(s)

The Channel Plan(s)	
Low-rate PHY (LRP) Band	60.32 – 60.64 GHz/ 62.48-62.80GHz
LRP Channel List:	60.32 +n x 0.16 (n=0, 1, 2) GHz / 62.48 +n x 0.16 (n=0, 1, 2) GHz
High rate PHY (HRP) Band	60.48 GHz / 62.64GHz

### 1.1.2 Transmit Operating Modes

The Different Transmit Operating Modes	
<input checked="" type="checkbox"/>	Operating mode 1: Smart Antenna Systems - with beam forming
<input type="checkbox"/>	Operating mode 2: Smart Antenna Systems - without beam forming
<input type="checkbox"/>	Operating mode 3: Single Antenna Equipment

### 1.1.3 Smart Antenna Systems

In Case of Smart Antenna Systems	
The number of Receive chains:	4
The number of Transmit chains:	31
Equal power distribution among the transmit chains:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
<input checked="" type="checkbox"/> In case of beam forming, the maximum beam forming gain:	22 dB

### 1.1.4 Antenna Information

Antenna Information	
<input type="checkbox"/>	Equipment placed on the market without antennas
<input checked="" type="checkbox"/>	Integral antenna
Integral antenna gain:	16.00 dBi for LRP      22.00 dBi for HRP
(Beam forming gain)	<input type="checkbox"/> Temporary RF connector provided
	<input checked="" type="checkbox"/> No temporary RF connector provided
<input type="checkbox"/>	External antenna (dedicated antennas)
	<input type="checkbox"/> Single power level with corresponding antenna(s)
	<input type="checkbox"/> Multiple power settings and corresponding antenna(s)



1.1.5 Type of Equipment

Type of Equipment	
<input checked="" type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined Equipment (The radio part is fully integrated within another type of equipment)
<input type="checkbox"/>	Plug-in radio device (Equipment intended for a variety of host systems)
<input type="checkbox"/>	Other:

1.1.6 Power Levels

(a) Worst Power Levels for LRP (Integrated Antenna)				
Applicable power levels:		<input type="checkbox"/> Conducted	<input checked="" type="checkbox"/> EIRP	
Integral antenna gain:		16.00 dBi		
Frequency (GHz)	Highest setting ( $P_{high}$ ): (dBm)			
	Modulation	Data Rate (Mb/s)	AV Power	Peak Power
62.80	BPSK	20.337	12.09	28.13

(b) Worst Power Levels for HRP (Integrated Antenna)				
Applicable power levels:		<input type="checkbox"/> Conducted	<input checked="" type="checkbox"/> EIRP	
Integral antenna gain:		22.00 dBi		
Frequency (GHz)	Highest setting ( $P_{high}$ ): (dBm)			
	Modulation	Data Rate (Gb/s)	AV Power	Peak Power
60.48	QPSK	0.952	34.36	40.89



1.1.7 Extreme Operating

The Extreme Operating Temperature Range that Apply to the Equipment	
<input type="checkbox"/>	-20 °C to +50 °C
<input checked="" type="checkbox"/>	0 °C to +40 °C
<input type="checkbox"/>	Other:
The nominal voltages of the stand-alone radio equipment or the nominal voltages of the combined (host) equipment or test jig in case of plug-in devices.	
Details provided are for the:	<input checked="" type="checkbox"/> stand-alone equipment
	<input type="checkbox"/> combined (or host) equipment
	<input type="checkbox"/> test jig
Supply Voltage	<input type="checkbox"/> AC mains      State AC voltage      V
Supply Voltage	<input checked="" type="checkbox"/> DC                      State DC voltage    5      V
In case of DC, indicate the type of power source:	
<input type="checkbox"/>	Internal Power Supply
<input checked="" type="checkbox"/>	External Power Supply or AC/DC adapter
<input type="checkbox"/> Battery	<input type="checkbox"/> Nickel Cadmium
	<input type="checkbox"/> Alkaline
	<input type="checkbox"/> Nickel-Metal Hydride
	<input type="checkbox"/> Lithium-Ion
	<input type="checkbox"/> Lead acid (Vehicle regulated)
	<input type="checkbox"/> Other:

1.1.8 Equipment Use Condition

Equipment Use Condition
<input type="checkbox"/> Fixed field disturbance sensors at 61-61.5GHz
<input type="checkbox"/> Except fixed field disturbance sensors at 61-61.5GHz
<input checked="" type="checkbox"/> Except fixed field disturbance sensors

## 1.2 Additional Information Provided by the Submitter

### 1.2.1 Modulation

Modulation	
ITU Class of emission	G1D (BPSK, QPSK), OFDM LRP – BPSK at 20.337 Mb/s (FEC 1/3) HRP – QPSK at 0.952 Gb/s (Quarter Rate), QPSK at 1.904 Gb/s (Half Rate) D1D (16QAM), OFDM HRP – 16-QAM at 3.807 Gb/s (Full Rate)
Can the transmitter operate un-modulated:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No

### 1.2.2 Duty Cycle

Duty Cycle	
The transmitter is intended for:	<input checked="" type="checkbox"/> Continuous Duty    100    %
	<input type="checkbox"/> Intermittent Duty:                    %
	<input type="checkbox"/> Continuous operation possible for testing purposes

### 1.2.3 About the EUT

About the EUT	
<input checked="" type="checkbox"/>	The equipment submitted are representative production models.
<input type="checkbox"/>	If not, the equipment submitted are pre-production models
<input type="checkbox"/>	If pre-production equipment is submitted, the final production equipment will be identical in all respects with the equipment tested.
<input type="checkbox"/>	If not, supply full details:

### 1.2.4 Table for Existing Change

This product is an extension of original one reported under Sporton project number: FR081919

Below is the table for the change of the product with respect to the original one.

Modifications	Description	Performance Checking
HDMI circuit	The difference between original project and new project is the HDMI circuit of EUT.	-Conducted Emissions Test -Radiated Emissions Test Below 1GHz




### 1.3 Ancillary and/or Support Equipment


<b>Ancillary Equipment (AE)</b>				
<b>Item</b>	<b>Equipment</b>	<b>Brand Name</b>	<b>Model Name</b>	<b>Serial No.</b>
AE01	AC Power Adapter	DVE	DSA-12PFA-05 FUS	-


<b>Support Equipment (SE)</b>				
<b>Item</b>	<b>Equipment</b>	<b>Brand Name</b>	<b>Model Name</b>	<b>Serial No.</b>
SE01	LCD Monitor	DELL	2709wb	LM-D
SE02	BD-PLAYER	SONY	BDP-BX1	BD-A
SE03	DVD Player	Pioneer	DV-600AV-S	DP-B
SE04	Receiver	Abocom	VM311R	N/A

### 1.4 EUT Setups

High Definition Audio / Video in the 1080p format was sent from the TX device to the receiver via the wireless link. A Blu-Ray player furnished HD A/V to the TX device. The receiver furnished HD A/V to the television. The television was placed outside the chamber. A laptop computer with test software was utilized to vary the radio configuration and antenna beam orientation for testing purposes. This computer was not connected during measurements. For Extreme environmental tests, an external Variable DC power supply was utilized in place of the AC/DC adapter to furnish power to the EUT.





Setup No.	Combination of EUT with AE or SE	Description
Setup_02	EUT + AE01 + SE01 + SE02 + SE04	Setup for AC power conducted emission
 <p style="text-align: center;">1. POWER CABLE , 150 CM, NON-SHIELDED 2. HDMI CABLE , 115 CM, SHIELDED 3. POWER CABLE , 180 CM, NON-SHIELDED</p>		

### 1.5 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15.255
- ♦ ANSI C63.10-2009

### 1.6 Testing Location

<b>Testing Location</b>			
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456      FAX : 886-3-318-0055	
<input type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065      FAX : 886-3-656-9085	
<b>Testing Site No.</b>			
05CH01-HY	03CH03-HY	-	-

### 1.7 Abbreviations Used for the Test Report

- ♦ Test Channel: B (Bottom channel), M (Middle channel), and T (Top channel).
- ♦ EUT: Equipment under Test.
- ♦ AE: EUT's Ancillary Equipment
- ♦ SE: Testing Support Equipment
- ♦ LRP: Low-rate PHY
- ♦ HRP: High rate PHY

## 2 Test Configuration of Equipment under Test

### 2.1 Test Channel Frequencies

Nominal Channel Bandwidth 1				
Frequency Band	Channel Plan	B (Bottom channel)	M (Middle channel)	T (Top channel)
60.32 – 60.64 GHz	1 (LRP)	60.32 GHz (F1)	60.48 GHz (F2)	60.64 GHz (F3)
60.48 GHz	2 (HRP)	-	60.48 GHz (F4)	-
62.48 – 62.80 GHz	3 (LRP)	62.48 GHz (F1)	62.64 GHz (F2)	62.80 GHz (F3)
62.64 GHz	4 (HRP)	-	62.64 GHz (F4)	-

### 2.2 Conformance Tests and Related Test Frequencies

Test	Test frequencies (MHz)	
	LRP – Channel Plan 1&3 ( 60.32 GHz to 60.64 GHz)/ (62.48GHz to 62.80GHz)	HRP – Channel Plan 2&4 ( 60.48 GHz)/(62.64GHz)
AC Power Conducted Emissions	-	F4
Occupied Bandwidth	F1, F2, F3	F4
Power Density	F1, F2, F3	F4
Peak Conducted Power	F1, F2, F3	F4
Transmitter Spurious Emissions	-	F4
Frequency Stability	-	F4

F1: The centre frequency of the lowest declared channel for every declared nominal bandwidth within this band.

F2, F4: The centre frequency of the middle declared channel for every declared nominal bandwidth within this band.

F3: The centre frequency of the highest declared channel for every declared nominal bandwidth within this band.

### 3 Transmitter Test Result

#### 3.1 AC Power Conducted Emissions

##### 3.1.1 Limit of AC Power Conducted Emissions

AC Power Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note: \* Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

Refer a measuring instruments list in this test report.

##### 3.1.3 Test Procedures

Method of measurement: Refer as ANSI C63.10-2009, clause 6.2.

##### 3.1.4 Test Setup



<b>AC Power Conducted Emissions</b>	
1.	Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see ANSI C63.10, clause 6.2.3.1).
2.	I/O cables that are not connected to an accessory shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m (see ANSI C63.10, clause 6.2.2).
3.	EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 ohm loads. LISN can be placed on top of, or immediately beneath, reference ground plane (see ANSI C63.10, clauses 6.2.2 and 6.2.3). <ul style="list-style-type: none"> <li>3.1. All other equipment powered from additional LISN(s).</li> <li>3.2. A multiple-outlet strip can be used for multiple power cords of non-EUT equipment.</li> <li>3.3. LISN at least 80 cm from nearest part of EUT chassis.</li> </ul>
4.	Non-EUT components of EUT system being tested.
5.	Rear of EUT, including peripherals, shall all be aligned and flush with edge of tabletop (see ANSI C63.10, clause 6.2.3.1).
6.	Edge of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane (see ANSI C63.10, clause 6.2.2 for options).
7.	Antenna may be integral or detachable. If detachable, the antenna shall be attached for this test.


**3.1.5 Test Result of AC Power Conducted Emissions**

<b>Test Conditions:</b>	see ANSI C63.10, clause 5.11
<b>Test Setup:</b>	see ANSI C63.10, clause 6.2.3
<b>Test Frequency Band:</b>	60.48 GHz (HRP) Band
<p>NOTE 1: If equipment having different channel plan and nominal channel bandwidth modes (see test report clause 1.1.1), the measurements are uninfluenced by different channel plan and nominal channel bandwidth modes, may not need to be repeated for all modes. If equipment having different transmit operating modes (see test report clause 1.1.2), the measurements are uninfluenced by different transmit operating modes, may not need to be repeated for all the operating modes. Similar, if the equipment supports different modulations and/or data rates, the measurements described in ANSI C63.10, clause 5.12 may not need to be repeated for all these modulations and data rates. Simple comparison of engineering test across all operating modes, modulations and data rates may need to be performed to define the worse case combination to be used for the conformance testing.</p> <p>NOTE 2: "&gt;20dB" means the tables in this clause should only list values of spurious emissions that exceed the level of 20 dB below the applicable limit, see ANSI C63.4, clause 10.1.8.1.</p>	





Temp:	23 °C	Humidity:	54%
Test Engineer:	Beck Wu	Phase:	Neutral
Configuration	Normal Link		




	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.16155	44.93	-20.46	65.38	44.63	0.10	0.20	QP
2	0.16155	30.45	-24.94	55.38	30.15	0.10	0.20	AVERAGE
3	0.20614	40.62	-22.74	63.36	40.34	0.08	0.20	QP
4	0.20614	26.94	-26.42	53.36	26.66	0.08	0.20	AVERAGE
5	0.25078	30.02	-21.71	51.73	29.74	0.08	0.20	AVERAGE
6	0.25078	38.31	-23.42	61.73	38.03	0.08	0.20	QP
7	0.41927	27.45	-30.01	57.46	27.18	0.07	0.20	QP
8	0.41927	18.78	-28.68	47.46	18.51	0.07	0.20	AVERAGE
9	0.75094	26.56	-29.44	56.00	26.29	0.07	0.20	QP
10	0.75094	18.17	-27.83	46.00	17.90	0.07	0.20	AVERAGE
11	8.683	29.02	-20.98	50.00	28.37	0.35	0.30	AVERAGE
12	8.683	34.77	-25.23	60.00	34.12	0.35	0.30	QP

Measurement uncertainty: ±2.26 dB



Temp:	23 °C	Humidity:	54%
Test Engineer:	Beck Wu	Phase:	Line
Configuration	Normal Link		



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.15650	55.41	-10.24	65.65	55.14	0.07	0.20	QP
2	0.15650	30.77	-24.88	55.65	30.50	0.07	0.20	AVERAGE
3	0.17866	44.60	-19.95	64.55	44.34	0.06	0.20	QP
4	0.17866	28.22	-26.33	54.55	27.96	0.06	0.20	AVERAGE
5	0.20723	27.84	-25.48	53.32	27.59	0.05	0.20	AVERAGE
6	0.20723	50.72	-12.60	63.32	50.47	0.05	0.20	QP
7	0.23040	22.90	-29.54	52.44	22.65	0.05	0.20	AVERAGE
8	0.23040	46.81	-15.63	62.44	46.56	0.05	0.20	QP
9	0.24682	52.12	-9.74	61.86	51.88	0.04	0.20	QP
10	0.24682	27.77	-24.09	51.86	27.53	0.04	0.20	AVERAGE
11	0.26442	23.30	-27.99	51.29	23.06	0.04	0.20	AVERAGE
12	0.26442	50.51	-10.78	61.29	50.27	0.04	0.20	QP
13	0.30028	24.04	-26.20	50.24	23.80	0.04	0.20	AVERAGE
14	0.30028	38.16	-22.08	60.24	37.92	0.04	0.20	QP
15	0.35201	18.08	-30.83	48.91	17.85	0.03	0.20	AVERAGE
16	0.35201	33.23	-25.68	58.91	33.00	0.03	0.20	QP
17	2.900	11.78	-34.22	46.00	11.50	0.08	0.20	AVERAGE
18	2.900	23.50	-32.50	56.00	23.22	0.08	0.20	QP
19	3.943	14.78	-31.22	46.00	14.38	0.10	0.30	AVERAGE
20	3.943	28.08	-27.92	56.00	27.68	0.10	0.30	QP

Measurement uncertainty: ±2.26 dB

### 3.2 Occupied Bandwidth

#### 3.2.1 Limit of Occupied Bandwidth

<b>6dBc Bandwidth</b> (see Note 1)	None
<b>26dBc Bandwidth</b>	None
<b>99% Occupied Bandwidth</b> (see Note 2)	None

NOTE 1: Refer as FCC 15.255(e). The 6dBc bandwidth is the frequency bandwidth of the signal power at the -6 dBc points when measured with a 100 kHz resolution bandwidth. These measurements shall also be performed at normal test conditions.

NOTE 2: The 99% occupied bandwidth is the frequency bandwidth of the signal power at the 99% channel power of occupied bandwidth when resolution bandwidth should be approximately 1 % to 5 % of the occupied bandwidth (OBW). These measurements shall also be performed at normal test conditions.


#### 3.2.2 Measuring Instruments

Refer a measuring instruments list in this test report.

#### 3.2.3 Test Procedures

Method of measurement: Refer as ANSI C63.10-2009, clauses 6.9.1 and 7.8.5.

#### 3.2.4 Test Setup






**3.2.5 Test Result of Occupied Bandwidth**

<b>Test Conditions:</b>	see ANSI C63.10, clause 5.11
<b>Test Setup:</b>	see ANSI C63.10, clause 7.8.5
<b>Test Frequency Band:</b>	60.32 – 60.64 GHz /62.48 – 62.80(LRP) Band 60.48 GHz / 62.64GHz (HRP) Band
<p>NOTE: If equipment having different transmit operating modes (see test report clause 1.1.2), the measurements are uninfluenced by different transmit operating modes, may not need to be repeated for all the operating modes. Similar, if the equipment supports different modulations and/or data rates, the measurements described in ANSI C63.10, clause 5.12 may not need to be repeated for all these modulations and data rates. Simple comparison of engineering test across all operating modes, modulations and data rates may need to be performed to define the worse case combination to be used for the conformance testing. Refer as ANSI C63.10, clause 6.9.1, observe and record with plotted graphs or photographs the worst-case (i.e., widest) occupied bandwidth produced by these different modulation sources.</p>	

<b>Test Conditions:</b>	see ANSI C63.10, clause 5.12	<b>Rel. Humidity:</b>	65 %		
<b>Test Engineer:</b>	Sam Chen	<b>Ambient Temp.:</b>	25°C		
<b>Test results</b>					
<b>Test Frequency:</b>	<b>6 dBc Bandwidth (MHz)</b>	<b>Occupied Bandwidth (MHz)</b>	<b>26 dBc Bandwidth (MHz)</b>	<b>Limit (MHz)</b>	<b>Margin (MHz)</b>
<b>F1 60.32 GHz</b>	91.8	256.2	-	N/A	N/A
<b>F2 60.48 GHz</b>	90.0	244.8	-	N/A	N/A
<b>F3 60.64 GHz</b>	91.2	252.6	-	N/A	N/A
<b>F4 60.48 GHz</b>	1760.0	2736.0	4716.0	N/A	N/A
<b>F1 62.48 GHz</b>	91.8	252.0	-	N/A	N/A
<b>F2 62.64 GHz</b>	90.0	244.2	-	N/A	N/A
<b>F3 62.80 GHz</b>	90.6	259.8	-	N/A	N/A
<b>F4 62.64 GHz</b>	1700.0	2748.0	4308.0	N/A	N/A
<b>Measurement uncertainty:</b>		$\pm 8.5 \times 10^{-8}$ Hz			




3.2.5.1 Bandwidth Plots for 60.32 – 60.64 GHz (LRP) Band






### 3.2.5.2 Bandwidth Plots for 60.48 GHz (HRP) Band






3.2.5.3 Bandwidth Plots for 62.48 – 62.80 GHz (LRP) Band





### 3.2.5.4 Bandwidth Plots for 62.64 GHz (HRP) Band





### 3.3 EIRP Power and Power Density

#### 3.3.1 Limit of EIRP Power and Power Density

Power Density Limit		
Use Condition	EIRP Average Power Density	EIRP Peak Power Density
Fixed field disturbance sensors at 61-61.5GHz	9 nW/cm <sup>2</sup> equivalent 10.2 mW (10.08 dBm)	18 nW/cm <sup>2</sup> equivalent 10.2 mW (13.09 dBm)
Except fixed field disturbance sensors at 61-61.5GHz	N/A	9 nW/cm <sup>2</sup> equivalent 10.2 mW (10.08 dBm)
Except fixed field disturbance sensors	9 μW/cm <sup>2</sup> equivalent 10.2 mW (40.08 dBm)	18 μW/cm <sup>2</sup> equivalent 10.2 mW (43.08 dBm)

NOTE: For the applicable limit, see FCC 15.255 (b)


#### 3.3.2 Measuring Instruments

Refer a measuring instruments list in this test report.

#### 3.3.3 Test Procedures

Method of measurement: Refer as ANSI C63.10-2009, clauses 7.8.3 and 7.8.6.

#### 3.3.4 Test Setup





### 3.3.5 Test Result of EIRP Power and Power Density

<b>Test Conditions:</b>	see ANSI C63.10, clause 5.11
<b>Test Setup:</b>	see ANSI C63.10, clause 7.8.6
<b>Test Frequency Band:</b>	60.32 – 60.64 GHz /62.48 – 62.80(LRP) Band 60.48 GHz / 62.64GHz (HRP) Band
NOTE: If the equipment supports different modulations and/or data rates, the measurements described in ANSI C63.10, clause 5.12 may not need to be repeated for all these modulations and data rates. Simple comparison of engineering test across all operating modes, modulations and data rates may need to be performed to define the worse case combination to be used for the conformance testing.	



3.3.5.1 Test Result of EIRP Power

<b>Maximum Antenna Gain:</b>		16	dBi for 60.32 – 60.64 GHz /62.48 – 62.80(LRP) Band							
<b>Maximum Antenna Gain:</b>		22	dBi for 60.48 GHz / 62.64GHz (HRP) Band							
<b>Equipment Use Condition:</b>		<input type="checkbox"/> Fixed field disturbance sensors at 61-61.5GHz <input type="checkbox"/> Except fixed field disturbance sensors at 61-61.5GHz <input checked="" type="checkbox"/> Except fixed field disturbance sensors								
<b>Test Conditions:</b>		0.5 m			<b>Rel. Humidity:</b>		65 %			
<b>Test Engineer:</b>		Sam Chen			<b>Ambient Temp.:</b>		25°C			
Test results										
Test Frequency:		Measured Power (dBm)		EIRP (dBm)		EIRP Limit (dBm) (note 2)		Margin (dB)		
		AV	Peak	AV	Peak	AV	Peak	AV	Peak	
<b>F1</b>	<b>60.32 GHz</b>	-27.49	-11.93	11.54	27.10	40.08	43.08	28.54	15.98	
<b>F2</b>	<b>60.48 GHz</b>	-27.03	-11.68	12.02	27.37	40.08	43.08	28.06	15.71	
<b>F3</b>	<b>60.64 GHz</b>	-27.8	-11.72	11.28	27.36	40.08	43.08	28.80	15.72	
<b>F4</b>	<b>60.48 GHz</b>	-4.69	1.84	34.36	40.89	40.08	43.08	5.72	2.19	
<b>F1</b>	<b>62.48 GHz</b>	-27.73	-11.82	11.61	27.52	40.08	43.08	28.47	15.56	
<b>F2</b>	<b>62.64 GHz</b>	-27.62	-11.54	11.74	27.82	40.08	43.08	28.34	15.26	
<b>F3</b>	<b>62.80 GHz</b>	-27.29	-11.25	12.09	28.13	40.08	43.08	27.99	14.95	
<b>F4</b>	<b>62.64 GHz</b>	-4.07	1.3	35.29	40.66	40.08	43.08	4.79	2.42	
<b>Measurement uncertainty:</b>		±2.7 dB								
<p>The measured power level is converted to EIRP using the Friis equation:  <math display="block">EIRP = P_T * G_T = (P_R / G_R) * (4 * \pi * D / \lambda)^2</math> <math display="block">P_R = \text{measured channel power}</math> <math display="block">G_R = 23 \text{ dBi, The gain of the receive measurement antenna}</math> <math display="block">D = 0.5 \text{ m, The measurement distance}</math> <math display="block">\lambda = \text{The wavelength.}</math> </p> <p>NOTE 2: For the applicable limit, see FCC 15.255(b)          NOTE 3: AV is average EIRP power.</p>										





3.3.5.2 Test Result of EIRP Power Density

<b>Maximum Antenna Gain:</b>		16	dBi for 60.32 – 60.64 GHz /62.48 – 62.80(LRP) Band							
<b>Maximum Antenna Gain:</b>		22	dBi for 60.48 GHz / 62.64GHz (HRP) Band							
<b>Equipment Use Condition:</b>		<input type="checkbox"/> Fixed field disturbance sensors at 61-61.5GHz <input type="checkbox"/> Except fixed field disturbance sensors at 61-61.5GHz <input checked="" type="checkbox"/> Except fixed field disturbance sensors								
<b>Test Conditions:</b>		0.5 m			<b>Rel. Humidity:</b>		65 %			
<b>Test Engineer:</b>		Sam Chen			<b>Ambient Temp.:</b>		25°C			
Test results										
Test Frequency:	EIRP Power (dBm) (note 1)		EIRP Power Density (μW/cm <sup>2</sup> )		EIRP Power Density Limit (μW/cm <sup>2</sup> )		Margin (μW/cm <sup>2</sup> )			
	AV	Peak	AV	Peak	AV	Peak	AV	Peak	AV	Peak
<b>F1 60.32 GHz</b>	11.57	27.10	0.013	0.454	9	18	8.987	17.546		
<b>F2 60.48 GHz</b>	12.02	27.37	0.014	0.483	9	18	8.986	17.517		
<b>F3 60.64 GHz</b>	11.28	27.36	0.012	0.481	9	18	8.988	17.519		
<b>F4 60.48 GHz</b>	34.36	40.89	2.415	10.861	9	18	6.585	7.139		
<b>F1 62.48 GHz</b>	11.61	27.52	0.013	0.499	9	18	8.987	17.501		
<b>F2 62.64 GHz</b>	11.74	27.82	0.013	0.535	9	18	8.987	17.465		
<b>F3 62.80 GHz</b>	12.09	28.13	0.014	0.575	9	18	8.986	17.425		
<b>F4 62.64 GHz</b>	35.29	40.66	2.988	10.289	9	18	6.012	7.711		
<b>Measurement uncertainty:</b>		±2.7 dB								
<p>NOTE 1: The EIRP is converted to Power Density using the equation:  <math>PD = EIRP / (4 * \pi * D_s^2)</math>  <math>D_s = 3m</math>, the specification distance</p> <p>NOTE 2: For the applicable limit, see FCC 15.255(b)</p> <p>NOTE 3: AV is average power density.</p>										




3.3.5.3 Measured Power Plots for 60.32 – 60.64 GHz (LRP) Band & 60.48 GHz (HRP) Band








### 3.3.5.4 Measured Power Plots for 62.48 – 60.80 GHz (LRP) Band & 62.64 GHz (HRP) Band







### 3.4 Peak Conducted Power

#### 3.4.1 Limit of Peak Conducted Power

Peak Conducted Power Limit	
6dBc Bandwidth	Peak Conducted Power (note 1)
> 100MHz	500mW
≤ 100MHz	500mW x (B/100) (see note 2)

NOTE 1: For the applicable limit, see FCC 15.255(e)  
 NOTE 2: B= 6dB bandwidth (measured at RBW 100kHz)


#### 3.4.2 Measuring Instruments

Refer a measuring instruments list in this test report.

#### 3.4.3 Test Procedures

Method of measurement: Refer as ANSI C63.10-2009, clauses 7.8.3 and 7.8.6.

#### 3.4.4 Test Setup





### 3.4.5 Test Result of Peak Conducted Power

<b>Test Conditions:</b>	see ANSI C63.10, clause 5.11
<b>Test Setup:</b>	see ANSI C63.10, clause 7.8.6
<b>Test Frequency Band:</b>	60.32 – 60.64 GHz /62.48 – 62.80(LRP) Band 60.48 GHz / 62.64GHz (HRP) Band
NOTE: If the equipment supports different modulations and/or data rates, the measurements described in ANSI C63.10, clause 5.12 may not need to be repeated for all these modulations and data rates. Simple comparison of engineering test across all operating modes, modulations and data rates may need to be performed to define the worse case combination to be used for the conformance testing.	



3.4.5.1 Peak Conducted Power

<b>Test Conditions:</b> 0.5 m				<b>Rel. Humidity:</b> 65 %			
<b>Test Engineer:</b> Sam Chen				<b>Ambient Temp.:</b> 25°C			
Test results							
Test Frequency:	EIRP (dBm)	Max. Ant. Gain	Peak Power (dBm) (note 1)	Peak Power (mW)	6dBc BW (MHz) (note 2)	Peak Power Limit (mW) (note 3)	Margin (mW)
F1 60.32 GHz	27.10	16	11.10	12.884	91.80	459.00	446.116
F2 60.48 GHz	27.37	16	11.37	13.720	90.00	450.00	436.280
F3 60.64 GHz	27.36	16	11.36	13.666	91.20	456.00	442.334
F4 60.48 GHz	40.89	22	18.89	77.507	1,760.00	500.00	422.493
F1 62.48 GHz	27.52	16	11.52	14.177	91.80	459.00	444.823
F2 62.64 GHz	27.82	16	11.82	15.199	90.00	450.00	434.801
F3 62.80 GHz	28.13	16	12.13	16.332	90.60	453.00	436.668
F4 62.64 GHz	40.66	22	18.66	73.421	1,700.00	500.00	426.579
<b>Measurement uncertainty:</b> ±2.7 dB							
NOTE 1: Because EUT used for the integral antenna without temporary RF connector provided. Therefore peak conducted power is equal to EIRP power subtract the antenna gain.							
NOTE 2: For the 6dBc bandwidth, see test report clause 3.2.5.							
NOTE 3: For the applicable limit, see FCC 15.255(e)							

### 3.5 Transmitter Spurious Emissions

#### 3.5.1 Limit of Transmitter Spurious Emissions

Frequency Range	Limit
Radiated emissions below 40 GHz	FCC Part 15.209
Radiated emissions above 40 GHz – 200GHz	90 pW/cm <sup>2</sup> @ 3 m (Equivalent EIRP 102 μW, -9.91dBm)

NOTE: Spurious emissions shall not exceed the level of the fundamental emission.


#### 3.5.2 Measuring Instruments

Refer a measuring instruments list in this test report.

#### 3.5.3 Test Procedures

Method of measurement: Refer as ANSI C63.10-2009, clauses 6.3, 6.4, 6.5, 6.6 and 7.8.6.

#### 3.5.4 Test Setup






### **3.5.5 Test Result of Transmitter Spurious Emissions**

<b>Test Conditions:</b>	see ANSI C63.10, clause 5.11
<b>Test Setup:</b>	see ANSI C63.10, clauses 6.3, 6.4, 6.5, 6.6 and 7.8.6
<b>Test Frequency Band:</b>	60.48 GHz (HRP) Band
NOTE: If equipment having different channel plan and nominal channel bandwidth modes (see test report clause 1.1.1), the measurements are uninfluenced by different channel plan and nominal channel bandwidth modes, may not need to be repeated for all modes.	




3.5.5.1 60.48 GHz (HRP) band, Test Frequency F4, Radiated Testing

Test Conditions:	see ANSI C63.10, clause 5.11	Polarization:	Vertical
Test Engineer:	Sam Chen	Test Distance:	3 m
Test Range:	30 MHz – 1000 MHz		






Test Conditions:	see ANSI C63.10, clause 5.11	Polarization:	Horizontal
Test Engineer:	Sam Chen	Test Distance:	3 m
Test Range:	30 MHz – 1000 MHz		






<b>Test Conditions:</b>	see ANSI C63.10, clause 5.11	<b>Polarization:</b>	Vertical
<b>Test Engineer:</b>	Sam Chen	<b>Test Distance:</b>	3 m
<b>Test Range:</b>	1GHz – 40 GHz		







<b>Test Conditions:</b>	see ANSI C63.10, clause 5.11	<b>Polarization:</b>	Horizontal
<b>Test Engineer:</b>	Sam Chen	<b>Test Distance:</b>	3 m
<b>Test Range:</b>	1GHz – 40 GHz		





<b>Test Conditions:</b>	see ANSI C63.10, clause 5.11	<b>Test Range:</b>	40GHz – 200GHz
<b>Test Engineer:</b>	Sam Chen	<b>Test Distance:</b>	0.5 m

Frequency (GHz)	Measurement Distance (m)	Peak Power (dBm)	Rx Antenna Gain (dBi)	EIRP (dBm)
48.384	0.5	-61.00	23	-23.88
EIRP (W)	Specification Distance (m)	Power Density (W/m <sup>2</sup> )	Power Density (pW/cm <sup>2</sup> )	Limit (pW/cm <sup>2</sup> )
4.08809E-06	3	3.61E-08	36.14665	90.00

Note: The peak density is less than the average limit.

### 3.6 Frequency Stability

#### 3.6.1 Limit of Frequency Stability

Frequency Stability	Limit
Refer as FCC 15.255(f)	within the frequency bands
Note: These measurements shall also be performed at normal and extreme test conditions.	


#### 3.6.2 Measuring Instruments

Refer a measuring instruments list in this test report.

#### 3.6.3 Test Procedures

Method of measurement: Refer as ANSI C63.10-2009, clauses 6.8 and 7.8.7.

#### 3.6.4 Test Setup





### 3.6.5 Test Result of Frequency Stability

<b>Test Conditions:</b>	see ANSI C63.10, clause 5.11
<b>Test Setup:</b>	see ANSI C63.10, clauses 6.8 and 7.8.7
<b>Test Frequency Band:</b>	60.48 GHz (HRP) Band
Worse case modulation for this operating mode:	HRP – QPSK
Worse case data rate for this operating mode:	HRP – 0.952 Gb/s (Quarter Rate)
NOTE: If equipment having different channel plan and nominal channel bandwidth modes (see test report clause 1.1.1), the measurements are uninfluenced by different channel plan and nominal channel bandwidth modes, may not need to be repeated for all modes.	

#### 3.6.5.1 Frequency Stability with Respect to Ambient Temperature

Frequency Stability with Respect to Ambient Temperature			
<b>Test Conditions:</b> see ANSI C63.10, clause 5.11			
<b>Test Engineer:</b> Sam Chen			
Test results			
Test Temperature: (°C)	Measured Frequency (MHz)	Delta Frequency (kHz)	Limit (±kHz)
0	60482.3	-450	within band
10	60482.5	-250	within band
20	60482.75	reference	within band
30	60482.5	-250	within band
40	60482.45	-300	within band
<b>Measurement uncertainty:</b> $\pm 8.5 \times 10^{-8}$ Hz			
NOTE: 1. For the applicable limit, see FCC 15.255(f).			
2. The EUT is intended for indoor use only with a manufacturer’s specified temperature range of 0 to 40°C.			



### 3.6.5.2 Frequency Stability When Varying Supply Voltage

Frequency Stability When Varying Supply Voltage			
<b>Test Conditions:</b> see ANSI C63.10, clause 5.11			
<b>Test Engineer:</b> Sam Chen			
Test results			
Test Voltage: (Vdc)	Measured Frequency (MHz)	Delta Frequency (kHz)	Limit ( $\pm$ kHz)
4.25	60482.25	-500	within band
5	60482.75	reference	within band
5.75	60482.5	-250	within band
<b>Measurement uncertainty:</b> $\pm 8.5 \times 10^{-8}$ Hz			
NOTE: For the applicable limit, see FCC 15.255(f).			

### 3.7 Publicly-accessible Coordination Channel

#### 3.7.1 Limit of Publicly-accessible Coordination Channel

Frequency Range	Limit
57 GHz-57.05 GHz	No emissions appear in the range 57-57.05 GHz
NOTE: For the applicable limit, see FCC 15.255(d)	


#### 3.7.2 Measuring Instruments

Refer a measuring instruments list in this test report.

#### 3.7.3 Test Procedures

Method of measurement: Refer as ANSI C63.10-2009, clauses 6.3, 6.4, 6.5, 6.6 and 7.8.6.

#### 3.7.4 Test Setup





### **3.7.5 Test Result of Publicly-accessible Coordination Channel**

<b>Test Conditions:</b>	see ANSI C63.10, clause 5.11
<b>Test Setup:</b>	see ANSI C63.10, clauses 6.3, 6.4, 6.5, 6.6 and 7.8.6
<b>Test Frequency Band:</b>	60.48 GHz (HRP) Band
NOTE: If equipment having different channel plan and nominal channel bandwidth modes (see test report clause 1.1.1), the measurements are uninfluenced by different channel plan and nominal channel bandwidth modes, may not need to be repeated for all modes.	



3.7.5.1.1 60.48 GHz (HRP) band, Test Frequency F4, Radiated Testing

<b>Test Conditions:</b>	see ANSI C63.10, clause 5.11	<b>Test Range:</b>	57 GHz-57.05 GHz		
<b>Test Engineer:</b>	Sam Chen	<b>Test Distance:</b>	0.5 m		
<b>Duty Cycle:</b>	50 %				
<b>Rel. Humidity:</b>	61 %				
<b>Test Results</b>					
<b>Test Range</b>	<b>Emission Frequency (MHz)</b>	<b>Emission Observed (dBm)</b>	<b>Limit (dBm)</b>	<b>Margin (dB)</b>	<b>Remark</b>
57 GHz-57.05 GHz	N/F	N/F	-9.91	N/F	
<b>Measurement uncertainty:</b> ±2.7      dB					
NOTE 1: "N/F" means Nothing Found (No spurious emissions were detected.)					



### 3.8 Operation Restriction and Group Installation

#### 3.8.1 Limit of Operation Restriction and Group Installation

Item	Limit
Operation Restriction	Operation is not permitted for the following products: <ul style="list-style-type: none"> <li>♦ Equipment used on aircraft or satellites. (Refer as FCC 15.255 (a))</li> <li>♦ Field disturbance sensors, including vehicle radar systems, unless the field disturbance sensors are employed for fixed operation. (Refer as FCC 15.255 (a))</li> </ul>
Group Installation	Operation is not permitted for the following products: <ul style="list-style-type: none"> <li>♦ External phase-locking (Refer as FCC Part 15.255 (h))</li> </ul>

#### 3.8.2 Result of Operation Restriction

Manufacturer declares that EUT will not be used on aircraft or satellites. Then user manual will include a statement to caution EUT is not permitted for use on aircraft or satellites. EUT is a wireless video area network (WVAN) for the connection of consumer electronic (CE) audio and video devices.

#### 3.8.3 Result of Group Installation

The frequency, amplitude and phase of the transmit signal are set within the EUT. There are no external phase-locking inputs or any other means of combining two or more units together to realize a beam-forming array.

### 3.9 Transmitter Identification

#### 3.9.1 Limit of Transmitter Identification

Item	Limit
Transmitter Identification	Indoor use and transmitter emanate directed outside the building and peak power $\geq 0.1\text{mW}$ (EIRP) or $3\text{nW}/\text{cm}^2$ , transmitter identification data block must provide the following fields: FCC ID, Serial Number, information at least 24 bytes data
NOTE: For the applicable limit, see FCC 15.255(i)	

#### 3.9.2 Result of Transmitter Identification

EUT's application is the WirelessHD targets the wireless video area network (WVAN). All units of the WVAN are for indoor operation only. There are no outdoor units therefore no transmissions are directed outside the building. EUT is not applicable for transmitter Identification.

### 3.10 Maximum Permissible Exposure

#### 3.10.1 Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6
Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30
NOTE 1: f = frequency in MHz ; *Plane-wave equivalent power density				
NOTE 2: For the applicable limit, see FCC 1.1310				

#### 3.10.2 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



3.10.3 Result of Maximum Permissible Exposure

<b>Exposure Environment:</b> General Population / Uncontrolled Exposure						
<b>Test results</b>						
<b>Maximum EIRP Power of Test Frequency:</b>	<b>Average EIRP Power (dBm)</b>	<b>Average EIRP Power (mW)</b>	<b>Power Density (S) (mW/cm<sup>2</sup>)</b>	<b>Separation Distance (cm)</b>	<b>Limit of Power Density (S) (mW/cm<sup>2</sup>)</b>	
<b>LRP 62.80 GHz</b>	12.09	16.1821	0.003221	20	1.00	
<b>HRP 60.48 GHz</b>	35.29	3379.2474	0.672621	20	1.00	
<b>Measurement uncertainty:</b> ±2.7 dB						
NOTE: For the applicable limit, see FCC 1.1310						

## 4 List of Measuring Equipments

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 18, 2010	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 24, 2010	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Aug. 02, 2010	Radiation (03CH03-HY)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Nov. 17, 2010	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004	9 kHz - 40 GHz	Oct. 03, 2010	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Sep. 26, 2010	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May 20, 2010	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan.11, 2010	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Jan. 05, 2010	Radiation (03CH03-HY)
RF Cable-high	Woken	High Cable-3	-	1 GHz - 40 GHz	Nov. 17, 2010	Radiation (03CH03-HY)
RF Cable-high	Woken	High Cable-4	-	1 GHz - 40 GHz	Nov. 17, 2010	Radiation (03CH03-HY)
Mixer	OML	M19HW/A	U91113-1	40 ~ 60 GHz	Nov. 16, 2010**	Radiation (03CH03-HY)
Mixer	OML	M15HW/A	V91113-1	50 ~ 75 GHz	Nov. 16, 2009**	Radiation (03CH03-HY)
Amplifier	HXI	HLNAV-361	2K911130	57~66GHz	Feb. 12, 2010	Radiation (03CH03-HY)
Isolator	HXI	HM15-385-60-4	2K911125	60~64GHz	Feb. 12, 2010	Radiation (03CH03-HY)
Diplexer	OML	DPL313B	-	40~200GHz	N.C.R	Radiation (03CH03-HY)
Mixer	OML	M12HW/A	E91113-1	60 ~ 90 GHz	Nov. 16, 2010**	Radiation (03CH03-HY)
Mixer	OML	M08HW/A	F91113-1	90 ~ 140 GHz	Nov. 16, 2010**	Radiation (03CH03-HY)
Mixer	OML	M05HW/A	G91113-1	140 ~ 220 GHz	Nov. 16, 2010**	Radiation (03CH03-HY)
Standard Horn Antenna	Custom Microwave	HO19R	U91113-A	40 ~ 60 GHz	N.C.R	Radiation (03CH03-HY)
Standard Horn Antenna	Custom Microwave	HO15R	V91113-A	50 ~ 75 GHz	N.C.R	Radiation (03CH03-HY)
Standard Horn Antenna	Custom Microwave	HO12R	E91113-A	60 ~ 90 GHz	N.C.R	Radiation (03CH03-HY)
Standard Horn Antenna	Custom Microwave	HO08R	F91113-A	90 ~ 140 GHz	N.C.R	Radiation (03CH03-HY)
Standard Horn Antenna	Custom Microwave	HO05R	G91113-A	140 ~ 220 GHz	N.C.R	Radiation (03CH03-HY)



Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Remark
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Jan. 05, 2010	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 29, 2010*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSU26.5	100015	20Hz ~ 26.5GHz	Oct. 29, 2010	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jul. 25, 2010	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100666	DC ~ 30GHz	Jul. 26, 2010	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jul. 25, 2010	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Jul. 26, 2010*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Apr. 16, 2010	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Aug. 06, 2010	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Nov. 02, 2010	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Nov. 02, 2010	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Feb. 13, 2010	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 30, 2010	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	0917017	300MHz~40GHz	Nov. 02, 2010	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	0949003	300MHz~40GHz	Nov. 02, 2010	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Note: For “\*” Calibration Interval of instruments listed above is two year.

Note: For “\*\*” Calibration Interval of instruments listed above is three year.

Note: N.C.R. means Non-Calibration required.

## 5 Certification of TAF Accreditation



Certificate No. : L1190-070110

財團法人全國認證基金會  
Taiwan Accreditation Foundation

### Certificate of Accreditation

This is to certify that

**Sporton International Inc.**  
**EMC & Wireless Communications Laboratory**  
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix Accreditation Program for Designated Testing Laboratory
Specific Accreditation Program	: for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory

*Jay-San Chen*

Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : January 10, 2007

PI, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.