



# Test Report

For

**Applicant** : **AboCom Systems, Inc.**  
**Equipment Type** : **IP Sharing + Fast EtherSwitch For  
Cable/xDSL Modem**  
**Model** : **CAS2040**  
**FCC ID** : **MQ4CAS2040**

**Report No. : 007H024FI**



# Test Report Certification

## QuieTek Corporation

No.75-1, Wang-Yeh Valley, Yung-Hsing, Chiung-Lin,  
Hsin-Chu County, Taiwan, R.O.C.  
Tel : 886-3-592-8858, Fax: 886-3-592-8859  
E-Mail : quietek@ms24.hinet.net

Accredited by NIST(NVLAP), VCCI, BSMI, DNV, TUV

Applicant : AboCom Systems, Inc.  
Address : 1F, No.21, R&D Road II, Science-Based Industrial Park,  
Hsin-Chu , Taiwan, R.O.C.  
Equipment Type : IP Sharing + Fast EtherSwitch For Cable/xDSL Modem  
Model : CAS2040  
FCC ID. : MQ4CAS2040  
Measurement Standard : CISPR 22/1985  
Measurement Procedure : ANSI C63.4 /1992  
Operation Voltage : 120VAC/60Hz  
Classification : Class B  
Test Result : Complied  
Test Date : July 10, 2000  
Report No. : 007H024FI



The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented by: Zoe Lee

Test Engineer: Jimmy Huang

Approved: Kevin Wang



# TABLE OF CONTENTS

Description	Page
<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1 EUT Description.....	4
1.2 Tested System Details .....	5
1.3 EUT Configuration.....	7
1.4 EUT Exercise Software .....	8
1.5 Test performed .....	8
1.6 Test Facility .....	9
<b>2. CONDUCTED EMISSION .....</b>	<b>10</b>
2.1 Test Equipment List .....	10
2.2 Test Setup.....	10
2.3 Limits .....	10
2.4 Test Procedure.....	11
2.5 Test Results.....	11
<b>3. RADIATED EMISSION.....</b>	<b>12</b>
3.1 Test Equipment .....	12
3.2 Test Setup.....	12
3.3 Limits .....	13
3.4 Test Procedure.....	13
3.5 Test Results.....	13
<b>4. EMI REDUCTION METHOD DURING COMPLIANCE TESTING.....</b>	<b>14</b>
<b>5. ATTACHMENT.....</b>	<b>15</b>
ATTACHMENT 1: SUMMARY OF TEST RESULTS	
ATTACHMENT 2: EUT TEST PHOTOGRAPHS	
ATTACHMENT 3: EUT DETAILED PHOTOGRAPHS	



# 1. General Information

## 1.1 EUT Description

Applicant : AboCom Systems, Inc.

Address : 1F, No.21, R&D Road II, Science-Based Industrial Park,  
Hsin-Chu , Taiwan, R.O.C.

Equipment Type : IP Sharing + Fast EtherSwitch For Cable/xDSL Modem

Model : CAS2040

FCC ID : MQ4CAS2040

Operation Voltage : 120VAC/60Hz

Power Adapter : DVE, DSA-0151A-05A

Cable Out: Non-Shielded, 1.8m, 1pc

Remark :

1. The EUT is a IP Sharing + Fast EtherSwitch For Cable/xDSL Modem.
2. QuieTek had verified the construction and function in typical operation, then shown in this test report.



## 1.2 Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards ) are:

### 1.2.1 **IP Sharing + Fast EtherSwitch For Cable/xDSL Modem** (EUT)

Model Number :CAS2040  
Serial Number :N/A  
FCC ID :MQ4CAS2040  
Manufacturer :AboCom  
  
Power Adapter : DVE, DSA-0151A-05 A (U)  
Cable Out: Non-Shielded, 1.8m, 1pc

### 1.2.2 **Host Personal Computer**

Model Number : P2L97  
Serial Number : 92M4Y03978  
FCC ID : DoC  
Manufacturer : ASUS  
Power Cord : Non-shielded, 1.8m

### 1.2.3 **Monitor**

Model Number : CM752ET-311  
Serial Number : T8F005799  
FCC ID : DoC  
Manufacturer : HITACHI  
Data Cable : Shielded, 1.5m  
Power Cord : Shielded, 1.8m

### 1.2.4 **Keyboard**

Model Number : SK-2502  
Serial Number : M971237074  
FCC ID : GYUR41SK  
Manufacturer : HP  
Data Cable : Shielded, 1.8m



### 1.2.5 Modem

Model Number : 1414  
Serial Number : 980033032  
FCC ID : IFAXDM1414  
Manufacturer : ACEEX  
Data Cable : Shielded, 1.5m  
Power Adapter : ACCEX, SCP41-91000A  
Cable Output : Shielded, 1.5m

### 1.2.6 Modem

Model Number : 1414  
Serial Number : 980033033  
FCC ID : IFAXDM1414  
Manufacturer : ACEEX  
Data Cable : Shielded, 1.5m  
Power Adapter : ACCEX, SCP41-91000A  
Cable Output : Shielded, 1.5m

### 1.2.7 Mouse

Model Number : M-S34  
Serial Number : LZA71178588  
FCC ID : DZL211029  
Manufacturer : HP  
Data Cable : Shielded, 1.8m

### 1.2.8 Printer

Model Number : C2642A  
Serial Number : MY75J1D1D0  
FCC ID : B94C2642X  
Manufacturer : HP  
Data Cable : Shielded, 1.2m  
Power Adapter : NMB, C2175A  
Cable for AC IN: Non-shielded, 0.7m  
Cable for AC Out: Non-shielded, 1.5m



### 1.2.9 Earphone

Model Number : PH136  
Serial Number : N/A  
Manufacturer : BSD  
Data Cable : Shielded, 1.2m


### 1.2.10 Joystick

Model Number : JPD110  
Serial Number : 9814A15646  
FCC ID : DoC  
Manufacturer : Maxxtro  
Data Cable : Shielded, 1.7m

### 1.2.11 LAN Card

Model Number : DFE-500TX  
Serial Number : 0080C8 958320  
FCC ID : KA2APC500X3  
Manufacturer : D-LINK

## 1.3 EUT Configuration



## 1.4 EUT Exercise Software

The EUT exercise program used during conducted testing was designed to exercise the EUT in a manner similar to a typical use. The exercise sequence is listed as below:

- 1.4.1 Setup the EUT and simulators as shown on 3.2
- 1.4.2 Turn on the power of all equipment.
- 1.4.3 PC reads data from disk.
- 1.4.4 PC sends “H” pattern to printer, the printer will print “H” pattern on paper.
- 1.4.5 PC reads and writes data into and from modem.
- 1.4.6 PC will read data from floppy disk and then writes the data into floppy disk , same operation for hard disk.
- 1.4.7 PC will communicate with the partner PC through the internal Fax/modem module (Lan Module).
- 1.4.8 Repeat the above procedure 1.4.4 to 1.4.8

## 1.5 Test performed

Conducted emissions were investigated over the frequency range from **0.15MHz to 30MHz** using a receiver bandwidth of 9kHz.

Radiated emissions were investigated over the frequency range from **30MHz to 1000MHz** using a receiver bandwidth of 120kHz. Radiated testing was performed at an antenna to EUT distance of **10 meters**.





## 1.6 Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

Site Description: November 3, 1998 File on  
 Federal Communications Commission  
 FCC Engineering Laboratory  
 7435 Oakland Mills Road  
 Columbia, MD 21046  
 Reference 31040/SIT1300F2



September 30, 1998 Accreditation on NVLAP  
 NVLAP Lab Code: 200347-0

February 23, 1999 Accreditation on DNV  
 Statement No. : 413-99-LAB11



December 8, 1998 Registration on VCCI  
 Registration No. for No.2 Shielded Room C-858  
 Registration No. for No.1 Open Area Test Site R-823  
 Registration No. for No.2 Open Area Test Site R-835



January 04, 1999 Accreditation on TÜV Rheinland  
 Certificate No.: I9865712-9901



Name of firm : QuieTek Corporation

Site location : No.75-1, Wang-Yeh Valley, Yung-Hsing Tsuen,  
 Chung-Lin, Hsin-Chu County, Taiwan, R.O.C.

## 2. Conducted Emission


### 2.1 Test Equipment List

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/825442/17	May, 2000	
2	L.I.S.N.	R & S	ESH3-Z5/825016/6	May, 2000	EUT
3	L.I.S.N.	Kyoritsu	KNW-407/8-1420-3	May, 2000	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2	N/A	
5	N0.2 Shielded Room			N/A	

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

### 2.2 Test Setup



### 2.3 Limits

CISPR 22 Limits (dBuV)					FCC Part 15 Subpart B (dBuV)				
Frequency MHz	Class A		Class B		Frequency MHz	Class A		Class B	
	QP	AV	QP	AV		uV	dBuV	uV	dBuV
0.15 - 0.50	79	66	66-56	56-46	0.45-1.705	1000	60.0	250	48.0
0.50-5.0	73	60	56	46	1.705-30	3000	69.5	250	48.0
5.0 - 30	73	60	60	50					

Remarks : In the above table, the tighter limit applies at the band edges.

## 2.4 Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 /1992 on conducted measurement.

The bandwidth of the field strength meter (R & S Test Receiver ESCS 30) is set at 9kHz.

## 2.5 Test Results

The conducted emission from the EUT is measured and shown in attachment 1 of test report. The acceptance criterion was met and the EUT passed the test.



### 3. Radiated Emission


#### 3.1 Test Equipment

The following test equipment are used during the radiated emission test:

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Site # 1	X	Test Receiver	R & S	ESCS 30 / 825442/14	May, 2000
		Spectrum Analyzer	Advantest	R3261C / 71720140	May, 2000
		Pre-Amplifier	HP	8447D/3307A01812	May, 2000
	X	Bilog Antenna	Chase	CBL6112B / 12452	Sep., 1999
	X	Horn Antenna	EM	EM6917 / 103325	May, 2000
Site # 2	X	Test Receiver	R & S	ESCS 30 / 825442/17	May, 2000
		Spectrum Analyzer	Advantest	R3261C / 71720609	May, 2000
		Pre-Amplifier	HP	8447D/3307A01814	May, 2000
	X	Bilog Antenna	Chase	CBL6112B / 2455	Sep., 1999
	X	Horn Antenna	EM	EM6917 / 103325	May, 2000

- Note:
1. All equipment upon which need to calibrated are with calibration period of 1 year.
  - 2.. Mark "X" test instruments are used to measure the final test results.

#### 3.2 Test Setup



### 3.3 Limits

CISPR 22 Limits					FCC Part 15 Subpart B				
Frequency	Class A		Class B		Frequency	Class A		Class B	
MHz	Distance (m)	dBuV/m	Distance (m)	dBuV/m		uV/m	dBuV/m	uV/m	dBuV/m
30 – 230	10	40	10	30	30 – 88	90	39	100	40.0
230 – 1000	10	47	10	37	88 – 216	150	43.5	150	43.5
					216 – 960	210	46.5	200	46.0
					960 - 2000	300	49.5	500	54.0

- Remark: 1. The tighter limit shall apply at the edge between two frequency bands.
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
3. RF Line Voltage (dBuV/m) = 20 log RF Line Voltage (uV/m)

### 3.4 Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 10 meters . The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4 /1992 on radiated measurement.

The bandwidth below 1GHz setting on the field strength meter (R&S Test Receiver ESCS 30 ) is 120 kHz.

### 3.5 Test Results

The radiated emission from the EUT is measured and shown in attachment 1 of test report. The acceptance criterion was met and the EUT passed the test.

#### 4. EMI Reduction Method During Compliance Testing

No modification was made during testing.



## 5. Attachment

Attachment 1: Summary of Test Results	Number of Pages: 9
Attachment 2: EUT Test Photographs	Number of Pages: 4
Attachment 3: EUT detailed photographs	Number of Pages: 6



## Attachment 1 : Summary of Test Results

The test results in the emission were performed according to the requirements of measurement standard and process. QuieTek Corporation is assumed full responsibility for the accuracy and completeness of these measurements. The test data of the emission are listed as the attached data.

All the tests were carried out with the EUT in normal operation, which was defined as:

Mode 1: 100Mbps

Mode 2: 10Mbps

### **The EUT passed all the tests.**

The uncertainty is calculated in accordance with NAMAS NIS 81, The total uncertainty for this test is as follows:

➤ **Emission Test**

- Uncertainty in the Conducted Emission Test:  $< \pm 2.0$  dB
- Uncertainty in the field strength measured:  $< \pm 4.0$  dB



## CONDUCTED EMISSION DATA

Date of Test : July 4, 2000 EUT : CAS2040  
 Test Mode : Mode 1 Detect Mode : Quasi-Peak & Average

Frequency MHz	Cable Loss dB	LISN Factor dB	Reading Level Line1 dBuV	Measurement Level Line1 dBuV	Limits dBuV
0.505	0.06	0.10	33.72	33.88	48.00
0.735	0.08	0.10	34.11	34.29	48.00
1.098	0.11	0.10	36.06	36.27	48.00
2.028	0.14	0.13	36.77	37.04	48.00
*3.427	0.18	0.15	37.14	37.47	48.00
4.458	0.19	0.16	35.97	36.33	48.00

Remarks :

1. “ \* ” means that this data is the worst emission level.

## CONDUCTED EMISSION DATA

Date of Test : July 4, 2000 EUT : CAS2040  
 Test Mode : Mode 1 Detect Mode : Quasi-Peak & Average

Frequency MHz	Cable Loss dB	LISN Factor dB	Reading Level Line2 dBuV	Measurement Level Line2 dBuV	Limits dBuV
0.665	0.08	0.10	30.13	30.31	48.00
1.079	0.10	0.10	29.57	29.78	48.00
1.231	0.11	0.11	28.38	28.60	48.00
*2.122	0.15	0.13	32.87	33.15	48.00
3.513	0.18	0.15	32.46	32.79	48.00
4.200	0.19	0.16	30.88	31.23	48.00

Remarks :

1. “ \* ” means that this data is the worst emission level.

## CONDUCTED EMISSION DATA

Date of Test : July 4, 2000 EUT : CAS2040  
 Test Mode : Mode 2 Detect Mode : Quasi-Peak & Average

Frequency MHz	Cable Loss dB	LISN Factor dB	Reading Level Line1 dBuV	Measurement Level Line1 dBuV	Limits dBuV
0.501	0.06	0.10	32.83	32.99	48.00
0.677	0.08	0.10	31.31	31.49	48.00
0.981	0.10	0.10	35.85	36.05	48.00
1.427	0.12	0.12	33.12	33.36	48.00
*2.274	0.15	0.14	38.52	38.81	48.00
3.442	0.18	0.15	37.51	37.84	48.00

Remarks :

1. “ \* ” means that this data is the worst emission level.



## CONDUCTED EMISSION DATA

Date of Test : July 4, 2000 EUT : CAS2040  
 Test Mode : Mode 2 Detect Mode : Quasi-Peak & Average

Frequency MHz	Cable Loss dB	LISN Factor dB	Reading Level Line2 dBuV	Measurement Level Line2 dBuV	Limits dBuV
0.509	0.06	0.10	29.69	29.85	48.00
0.735	0.08	0.10	27.99	28.17	48.00
1.087	0.11	0.10	30.39	30.60	48.00
2.212	0.15	0.13	31.57	31.85	48.00
*3.454	0.18	0.15	32.54	32.87	48.00
4.208	0.19	0.16	30.55	30.90	48.00

Remarks :

1. “ \* ” means that this data is the worst emission level.

## RADIATED EMISSION DATA

Date of Test : July 4, 2000 EUT : CAS2040  
 Test Mode : Mode 1 Test Site : No.2 Open Test Site

Freq.	Cable Loss	Probe Factor	PreAMP	Reading Level	Measurement Horizontal	Margin	Limit	Ant	Turn
MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	dBuV/m	cm	deg
75.240	1.59	8.26	0.00	22.28	32.13	7.87	40.00	255	24
135.000	2.16	12.52	0.00	19.91	34.59	8.91	43.50	184	112
*300.000	3.76	13.50	0.00	24.15	41.41	4.59	46.00	140	199
495.010	4.77	17.96	0.00	16.64	39.36	6.64	46.00	142	171
550.000	5.06	19.01	0.00	12.59	36.66	9.34	46.00	222	175
600.000	5.31	18.95	0.00	14.07	38.33	7.67	46.00	222	95
650.000	5.58	19.29	0.00	12.45	37.31	8.69	46.00	219	53

**Remarks:**

- 1.All Readings below 1GHz are Quasi-Peak, above are average value.
- 2.“ \* ”, means this data is the worst emission level.
- 3.Emission Level = Reading Level + Antenna Factor + Cable loss

## RADIATED EMISSION DATA

Date of Test : July 4, 2000 EUT : CAS2040  
 Test Mode : Mode 1 Test Site : No.2 Open Test Site

Freq.	Cable Loss	Probe Factor	PreAMP	Reading Level	Measurement Vertical	Margin	Limit	Ant	Turn
MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	dBuV/m	cm	deg
*54.985	1.39	8.10	0.00	27.06	36.56	3.44	40.00	162	171
79.960	1.64	9.48	0.00	23.84	34.95	5.05	40.00	162	40
108.780	1.91	11.52	0.00	19.83	33.26	10.24	43.50	174	196
160.005	2.40	10.25	0.00	25.48	38.13	5.37	43.50	99	123
200.000	2.78	9.09	0.00	26.28	38.16	5.34	43.50	99	102
274.995	3.51	13.49	0.00	23.06	40.07	5.93	46.00	99	170
300.000	3.76	13.76	0.00	22.73	40.24	5.76	46.00	99	172
320.000	3.86	14.13	0.00	20.31	38.30	7.70	46.00	99	173
400.000	4.28	16.59	0.00	15.05	35.92	10.08	46.00	130	117
500.000	4.79	17.38	0.00	16.05	38.22	7.78	46.00	99	133
700.000	5.83	19.78	0.00	11.53	37.15	8.85	46.00	99	100

Remarks:

- 1.All Readings below 1GHz are Quasi-Peak, above are average value.
- 2.“ \* ”, means this data is the worst emission level.
- 3.Emission Level = Reading Level + Antenna Factor + Cable loss

## RADIATED EMISSION DATA

Date of Test : July 4, 2000 EUT : CAS2040  
 Test Mode : Mode 2 Test Site : No.2 Open Test Site

Freq.	Cable Loss	Probe Factor	PreAMP	Reading Level	Measurement Horizontal	Margin	Limit	Ant	Turn
MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	dBuV/m	cm	deg
54.985	1.39	6.81	0.00	22.78	30.98	9.02	40.00	99	203
134.985	2.16	12.52	0.00	21.86	36.54	6.96	43.50	243	128
175.010	2.55	10.64	0.00	20.75	33.94	9.56	43.50	206	93
*300.000	3.76	13.50	0.00	23.79	41.05	4.95	46.00	99	79
325.000	3.88	14.35	0.00	16.04	34.27	11.73	46.00	99	202
375.000	4.14	16.50	0.00	18.57	39.21	6.79	46.00	99	179
400.000	4.28	16.60	0.00	18.79	39.67	6.33	46.00	99	126
450.000	4.53	17.11	0.00	12.72	34.36	11.64	46.00	99	42
500.000	4.79	17.83	0.00	17.00	39.63	6.37	46.00	234	149
550.000	5.06	19.01	0.00	12.77	36.84	9.16	46.00	215	114
600.000	5.31	18.95	0.00	12.95	37.21	8.79	46.00	271	105

Remarks:

- 1.All Readings below 1GHz are Quasi-Peak, above are average value.
- 2.“ \* ”, means this data is the worst emission level.
- 3.Emission Level = Reading Level + Antenna Factor + Cable loss

## RADIATED EMISSION DATA

Date of Test : July 4, 2000 EUT : CAS2040  
 Test Mode : Mode 2 Test Site : No.2 Open Test Site

Freq.	Cable Loss	Probe Factor	PreAMP	Reading Level	Measurement Vertical	Margin	Limit	Ant	Turn
MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	dBuV/m	cm	deg
61.860	1.46	8.11	0.00	13.57	23.14	16.86	40.00	99	120
74.540	1.58	8.74	0.00	16.92	27.24	12.76	40.00	99	202
134.990	2.16	11.44	0.00	18.61	32.21	11.29	43.50	99	21
175.005	2.55	8.37	0.00	21.83	32.75	10.75	43.50	99	107
200.000	2.78	9.09	0.00	27.16	39.04	4.46	43.50	99	106
*300.000	3.76	13.76	0.00	24.65	42.16	3.84	46.00	165	192
350.000	4.01	15.20	0.00	16.80	36.01	9.99	46.00	146	198
400.000	4.28	16.59	0.00	16.17	37.04	8.96	46.00	99	161
500.000	4.79	17.38	0.00	17.65	39.82	6.18	46.00	99	87
600.000	5.31	18.96	0.00	14.82	39.09	6.91	46.00	99	64
625.000	5.44	19.30	0.00	15.27	40.02	5.98	46.00	127	164
700.000	5.83	19.78	0.00	13.34	38.96	7.04	46.00	99	97

Remarks:

- 1.All Readings below 1GHz are Quasi-Peak, above are average value.
- 2.“ \* ”, means this data is the worst emission level.
- 3.Emission Level = Reading Level + Antenna Factor + Cable loss




## Attachment 2: EUT Test Setup Photos

Front View of Conducted Test (Mode 1)




Back View of Conducted Test (Mode 1)




Front View of Conducted Test (Mode 2)




Back View of Conducted Test (Mode 2)




Front View of Radiated Test (Mode 1)



Back View of Radiated Test (Mode 1)



Front View of Radiated Test (Mode 2)



Back View of Radiated Test (Mode 2)

