



MPE Report

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

Refer Standard: KDB 447498 D01 General RF Exposure Guidance v06

FCC Part 2 §2.1091

1. Evaluation method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

2. Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

3. Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density



P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the maximum gain of the used antenna is 2dBi, the RF power density can be obtained.

4. Estimation Result

4.1 Conducted Power Results

Mode	Frequency(MHz)	Average Conducted Output Power (dBm)
IEEE 802.11b	2412	16.84
	2437	17.02
	2462	16.89
IEEE 802.11g	2412	12.83
	2437	13.17
	2462	13.27
IEEE 802.11n HT20	2412	13.07
	2437	13.15
	2462	13.19
IEEE 802.11n HT40	2422	10.98
	2437	10.87
	2452	10.96



4.2 Manufacturing tolerance

IEEE 802.11 b (Average)			
Frequency(MHz)	2412	2437	2462
Target (dBm)	16.0	17.0	16.0
Tolerance \pm (dB)	1.0	1.0	1.0

IEEE 802.11 g (Average)			
Frequency(MHz)	2412	2437	2462
Target (dBm)	12.0	13.0	13.0
Tolerance \pm (dB)	1.0	1.0	1.0

IEEE 802.11 n HT 20 (Average)			
Frequency(MHz)	2412	2437	2462
Target (dBm)	13.0	13.0	13.0
Tolerance \pm (dB)	1.0	1.0	1.0

IEEE 802.11 n HT 40 (Average)			
Frequency(MHz)	2422	2437	2452
Target (dBm)	10.0	10.0	10.0
Tolerance \pm (dB)	1.0	1.0	1.0



4.3 Measurement Results

Mode	Frequency (MHz)	Output power (Including tune-up tolerance) (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
IEEE 802.11b	2412	17	50.12	2	1.5848932	0.0158
	2437	18	63.10	2	1.5848932	0.0199
	2462	17	50.12	2	1.5848932	0.0158
IEEE 802.11g	2412	13	19.95	2	1.5848932	0.0063
	2437	14	25.12	2	1.5848932	0.0079
	2462	14	25.12	2	1.5848932	0.0079
IEEE 802.11n HT20	2412	14	25.12	2	1.5848932	0.0079
	2437	14	25.12	2	1.5848932	0.0079
	2462	14	25.12	2	1.5848932	0.0079
IEEE 802.11n HT40	2422	11	12.59	2	1.5848932	0.0040
	2437	11	12.59	2	1.5848932	0.0040
	2452	11	12.59	2	1.5848932	0.0040

Note: The estimation distance is 20cm

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.