



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Abocom Systems, Inc
Applicant Address	No.77, Yu-Yih Rd., Chu-Nan, Miao-Lih County 35059, Taiwan R.O.C.
FCC ID	MQ4NBG6503P
Manufacturer's company	Abocom Systems, Inc
Manufacturer Address	No.77, Yu-Yih Rd., Chu-Nan, Miao-Lih County 35059, Taiwan R.O.C.

Product Name	11ac 300Mbps+433Mbps Dualband router
Brand Name	AboCom
Model No.	NBG6503F/NBG6503P
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Jan. 30, 2013
Final Test Date	May 11, 2013
Submission Type	Original Equipment



Statement

Test result included is only for the IEEE 802.11n, IEEE 802.11b/g part and IEEE 802.11a/ac (5725 ~ 5850MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03 and KDB 662911 D01 v01r02.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.





Table of Contents

1. CERTIFICATE OF COMPLIANCE.....	1
2. SUMMARY OF THE TEST RESULT.....	2
3. GENERAL INFORMATION.....	3
3.1. Product Details	3
3.2. Accessories	5
3.3. Table for Filed Antenna	6
3.4. Table for Carrier Frequencies.....	7
3.5. Table for Test Modes.....	8
3.6. Table for Testing Locations.....	10
3.7. Table for Multiple List.....	10
3.8. Table for Supporting Units	10
3.9. Table for Parameters of Test Software Setting.....	11
3.10. EUT Operation during Test	12
3.11. Test Configurations	13
4. TEST RESULT.....	15
4.1. AC Power Line Conducted Emissions Measurement.....	15
4.2. Maximum Conducted Output Power Measurement	19
4.3. Power Spectral Density Measurement	22
4.4. 6dB Spectrum Bandwidth Measurement	31
4.5. Radiated Emissions Measurement.....	39
4.6. Emissions Measurement	66
4.7. Antenna Requirements.....	91
5. LIST OF MEASURING EQUIPMENTS	92
6. TEST LOCATION.....	94
APPENDIX A. TEST PHOTOS.....	A1 ~ A5
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE.....	B1 ~ B3
APPENDIX C. CO-LOCATION REPORT.....	C1 ~ C3



History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR331410-01AA	Rev. 01	Initial issue of report	May 22, 2013



1. CERTIFICATE OF COMPLIANCE

Product Name : 11ac 300Mbps+433Mbps Dualband router
Brand Name : AboCom
Model No. : NBG6503F/NBG6503P
Applicant : Abocom Systems, Inc
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jan. 30, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Sam Chen'.

Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	2.04 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	4.04 dB
4.3	15.247(e)	Power Spectral Density	Complies	10.80 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.17 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.08 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1GHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n/ac

Items	Description
Product Type	WLAN 5G: (1TX, 1RX) WLAN 2.4G: (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	see the below table for IEEE 802.11n/ac
Data Modulation	For 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n/ac
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	For 2.4GHz Band: 11 for 20MHz bandwidth ; 7 for 40MHz bandwidth For 5GHz Band: 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth ; 1 for 80MHz bandwidth
Channel Band Width (99%)	For 2.4GHz Band: MCS0 (20MHz): 22.96 MHz ; MCS0 (40MHz): 36.16 MHz For 5GHz Band: 802.11ac MCS0/Nss1 (20MHz): 34.24 MHz ; 802.11ac MCS0/Nss1 (40MHz): 66.40 MHz ; 802.11ac MCS0/Nss1 (80MHz): 75.84 MHz
Maximum Conducted Output Power	For 2.4GHz Band: MCS0 (20MHz): 25.96 dBm ; MCS0 (40MHz): 19.82 dBm For 5GHz Band: 802.11ac MCS0/Nss1 (20MHz): 22.35 dBm ; 802.11ac MCS0/Nss1 (40MHz): 22.66 dBm ; 802.11ac MCS0/Nss1 (80MHz): 15.49 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

802.11a/b/g

Items	Description
Product Type	WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 5
Channel Band Width (99%)	11b: 13.32 MHz ; 11g: 27.12 MHz ; 11a: 33.92 MHz
Maximum Conducted Output Power	11b: 18.30 dBm ; 11g: 24.10 dBm ; 11a: 22.61 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)			Two (TX)		
	20 MHz	40 MHz	80 MHz	20 MHz	40 MHz	80 MHz
Band width Mode						
IEEE 802.11a	V	X	X	X	X	X
IEEE 802.11b	V	X	X	X	X	X
IEEE 802.11g	V	X	X	X	X	X
IEEE 802.11n	V	V	X	V	V	X
IEEE 802.11ac	V	V	V	X	X	X

IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	2	M0-15
802.11n (HT40)	2	M0-15
802.11an (HT20)	1	M0-07
802.11an (HT40)	1	M0-07
802.11ac (VHT20)	1	MCS 0-9/Nss1
802.11ac (VHT40)	1	MCS 0-9/Nss1
802.11ac (VHT80)	1	MCS 0-9/Nss1

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT support VHT20, VHT40 and VHT80.

Note 3: Modulation modes consist of below configuration:
 11a: IEEE 802.11a, HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac

3.2. Accessories

Power	Brand	Model	Rating
Adapter	DVE	DSA-12G-12 FUS 120120	INPUT: 100-240V~50/60Hz 0.3A OUTPUT: +12V, 1A

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
					2.4G	5G
1	Cortec	AN2450-5512RS	Dipole Antenna	Reversed-SMA	2	2
2	Cortec	AN2400-5532RS	Dipole Antenna	Reversed-SMA	2	-

Note: The EUT has two antennas.

<For 2.4GHz Band>

For IEEE 802.11b/g mode (1TX/1RX):

Only Ant.1 can be use as transmit and receive antenna.

For IEEE 802.11n mode (2TX/2RX):


Ant.1 and Ant.2 can be used as transmitting/receiving antennas

Ant.1 and Ant.2 could transmit/receive simultaneously.

<For 5GHz Band>

For IEEE 802.11a/n/ac mode (1TX/1RX):

Only Ant.1 can be use as transmit and receive antenna.



3.4. Table for Carrier Frequencies

For 2.4GHz Band:

There are two bandwidth systems.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

For 5GHz Band:

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

For 80MHz bandwidth systems, use Channel 155.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

For 2.4GHz Band

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11n 20MHz	MCS0	1/6/11	1+2
	11n 40MHz	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Power Spectral Density	11n 20MHz	MCS0	1/6/11	1&2
	11n 40MHz	MCS0	3/6/9	1&2
	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
6dB Spectrum Bandwidth	11n 20MHz	MCS0	1/6/11	1+2
	11n 40MHz	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Radiated Emissions Below 1GHz	Normal Link	-	-	-
Radiated Emissions Above 1GHz	11n 20MHz	MCS0	1/6/11	1+2
	11n 40MHz	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Band Edge Emissions	11n 20MHz	MCS0	1/6/11	1+2
	11n 40MHz	MCS0	3/6/9	1+2
	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1

For 5GHz Band

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11ac 20MHz	MCS0/Nss1	149/157/165	1
	11ac 40MHz	MCS0/Nss1	151/159	1
	11ac 80MHz	MCS0/Nss1	155	1
	11a/BPSK	6 Mbps	149/157/165	1
Power Spectral Density	11ac 20MHz	MCS0/Nss1	149/157/165	1
	11ac 40MHz	MCS0/Nss1	151/159	1
	11ac 80MHz	MCS0/Nss1	155	1
	11a/BPSK	6 Mbps	149/157/165	1
6dB Spectrum Bandwidth	11ac 20MHz	MCS0/Nss1	149/157/165	1
	11ac 40MHz	MCS0/Nss1	151/159	1
	11ac 80MHz	MCS0/Nss1	155	1
	11a/BPSK	6 Mbps	149/157/165	1
Radiated Emissions Below 1GHz	Normal Link	-	-	-
Radiated Emissions Above 1GHz	11ac 20MHz	MCS0/Nss1	149/157/165	1
	11ac 40MHz	MCS0/Nss1	151/159	1
	11ac 80MHz	MCS0/Nss1	155	1
	11a/BPSK	6 Mbps	149/157/165	1
Band Edge Emissions	11ac 20MHz	MCS0/Nss1	149/157/165	1
	11ac 40MHz	MCS0/Nss1	151/159	1
	11ac 80MHz	MCS0/Nss1	155	1
	11a/BPSK	6 Mbps	149/157/165	1

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1. LAN / WAN (100Mbps) + Adapter+ Dipole Antenna

For Radiated Emission (30MHz~1GHz) test:

Mode 1. Lying + LAN / WAN (100Mbps) + Adapter+ Dipole Antenna

Mode 2. Upright + LAN / WAN (100Mbps) + Adapter+ Dipole Antenna

Due to Mode 1 generated the worst test result, it was recorded in this report.

For Radiated Emission (above 1GHz) test:

Mode 1.CTX + Lying

Mode 2.CTX + Upright

Due to Mode 1 generated the worst test result, it was recorded in this report.

<For MPE and Co-location Test>:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Maximum Permissible Exposure (Please refer to Appendix B) and Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Please refer section 6 for Test Site Address.

3.7. Table for Multiple List

All the models are identical, the different model names served as marketing strategy.

3.8. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6220	QDS-BRCM1049LE
Notebook	DELL	E6220	QDS-BRCM1049LE
Notebook	DELL	D420	E2KWM3945ABG
Notebook	DELL	D420	E2KWM3945ABG

3.9. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For 2.4GHz Band

Power Parameters of IEEE 802.11n MCS0 20MHz

Test Software Version	MT7620 QA V1.0.6.0		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 20MHz	05/06	1E/1C	06/05

Power Parameters of IEEE 802.11n MCS0 40MHz

Test Software Version	MT7620 QA V1.0.6.0		
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 40MHz	00/01	08/09	02/04

Power Parameters of IEEE 802.11b/g

Test Software Version	MT7620 QA V1.0.6.0		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	0C	0C	0B
IEEE 802.11g	08	1D	07

For 5GHz Band

Power Parameters of IEEE 802.11ac MCS0/Nss1 20MHz

Test Software Version	MT7620 QA V1.0.6.0		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0/Nss1 20MHz	1A	2F	21

Power Parameters of IEEE 802.11ac MCS0/Nss1 40MHz

Test Software Version	MT7620 QA V1.0.6.0	
Frequency	5755 MHz	5795 MHz
MCS0/Nss1 40MHz	15	21

Power Parameters of IEEE 802.11ac MCS0/Nss1 80MHz

Test Software Version	MT7620 QA V1.0.6.0
Frequency	5775 MHz
MCS0/Nss1 80MHz	9

Power Parameters of IEEE 802.11a


Test Software Version	MT7620 QA V1.0.6.0		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	1A	2F	2I

3.10. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


3.11. Test Configurations

3.11.1. AC Power Line Conduction Emissions and Radiation Emissions (30MHz~1GHz) Test Configuration



Item	Connection	Shield	Length
1	Power cable	No	1.5m
2	RJ-45 cable	No	10m
3	RJ-45 cable	No	10m
4	RJ-45 cable*3	No	1.5m

3.11.2. Radiation Emissions (above 1GHz) Test Configuration



Item	Connection	Shield	Length
1	Power cable	No	1.5m
2	RJ-45 cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	60%
Test Engineer	Parody Lin	Phase	Line
Configuration	Mode 1		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.30509	42.60	-7.50	50.10	42.25	0.15	0.20	AVERAGE
2	0.30509	43.13	-16.97	60.10	42.78	0.15	0.20	QP
3	0.33740	47.23	-2.04	49.27	46.88	0.15	0.20	AVERAGE
4	0.33740	47.08	-12.19	59.27	46.73	0.15	0.20	QP
5	0.64298	36.67	-19.33	56.00	36.31	0.16	0.20	QP
6	0.64298	35.89	-10.11	46.00	35.53	0.16	0.20	AVERAGE
7	3.381	36.53	-19.47	56.00	36.05	0.21	0.27	QP
8	3.381	29.48	-16.52	46.00	29.00	0.21	0.27	AVERAGE
9	5.774	37.54	-22.46	60.00	36.96	0.26	0.33	QP
10	5.774	30.83	-19.17	50.00	30.25	0.26	0.33	AVERAGE
11	9.253	27.48	-22.52	50.00	26.84	0.33	0.31	AVERAGE
12	9.253	34.35	-25.65	60.00	33.71	0.33	0.31	QP

Temperature	25°C	Humidity	60%
Test Engineer	Parody Lin	Phase	Neutral
Configuration	Mode 1		



	Freq	Level	Over	Limit	Read	LISN	Cable	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.30440	45.13	-4.99	50.12	44.85	0.08	0.20	NEUTRAL	AVERAGE
2	0.30440	45.20	-14.92	60.12	44.92	0.08	0.20	NEUTRAL	QP
3	0.33690	45.24	-4.04	49.28	44.96	0.08	0.20	NEUTRAL	AVERAGE
4	0.33690	45.34	-13.94	59.28	45.06	0.08	0.20	NEUTRAL	QP
5	0.81647	35.40	-20.60	56.00	35.11	0.09	0.20	NEUTRAL	QP
6	0.81647	33.42	-12.58	46.00	33.13	0.09	0.20	NEUTRAL	AVERAGE
7	1.628	35.05	-20.95	56.00	34.73	0.10	0.22	NEUTRAL	QP
8	1.628	30.90	-15.10	46.00	30.58	0.10	0.22	NEUTRAL	AVERAGE
9	3.454	37.87	-18.13	56.00	37.47	0.12	0.27	NEUTRAL	QP
10	3.454	32.32	-13.68	46.00	31.92	0.12	0.27	NEUTRAL	AVERAGE
11	5.898	33.76	-16.24	50.00	33.27	0.16	0.33	NEUTRAL	AVERAGE
12	5.898	38.77	-21.23	60.00	38.28	0.16	0.33	NEUTRAL	QP

Note:

Level = Read Level + LISN Factor + Cable Loss

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter output power.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03 section 9.2.2 Measurement using a power meter (PM).
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	56%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n/ac
Test Date	May 11, 2013		

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Ant.1+Ant.2

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
1	2412 MHz	15.40	15.80	18.61	30.00	Complies
6	2437 MHz	22.80	23.10	25.96	30.00	Complies
11	2462 MHz	15.74	15.62	18.69	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant.1+Ant.2

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
3	2422 MHz	13.10	13.70	16.42	30.00	Complies
6	2437 MHz	16.53	17.08	19.82	30.00	Complies
9	2452 MHz	13.90	14.80	17.38	30.00	Complies

For 5GHz Band

Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	21.68	30.00	Complies
157	5785 MHz	22.35	30.00	Complies
165	5825 MHz	21.33	30.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
151	5755 MHz	20.36	30.00	Complies
159	5795 MHz	22.66	30.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
155	5775 MHz	15.49	30.00	Complies

Temperature	25°C	Humidity	56%
Test Engineer	Benson Peng	Configurations	IEEE 802.11a/b/g
Test Date	May 11, 2013		

Configuration IEEE 802.11b / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	18.30	30.00	Complies
6	2437 MHz	18.28	30.00	Complies
11	2462 MHz	17.60	30.00	Complies

Configuration IEEE 802.11g / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	17.78	30.00	Complies
6	2437 MHz	24.10	30.00	Complies
11	2462 MHz	16.93	30.00	Complies

Configuration IEEE 802.11a / Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	21.55	30.00	Complies
157	5785 MHz	22.28	30.00	Complies
165	5825 MHz	22.61	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RB	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VB	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03 section 10.2 Method PKPSD (peak PSD) & KDB 662911 D01 v01r02 section In-Band Power Spectral Density (PSD) Measurements option (2) Measure and add $10 \log(\text{NANT})$ dB.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be ≤ 8 dBm.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	56%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n/ac

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Ant.1+Ant.2

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2		
1	2412 MHz	-12.56	-12.44	4.99	Complies
6	2437 MHz	-6.99	-5.81	4.99	Complies
11	2462 MHz	-13.30	-14.50	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2))) = 4.99dBm/3kHz

Configuration IEEE 802.11n MCS0 40MHz / Ant.1+Ant.2

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2		
3	2422 MHz	-18.40	-16.93	4.99	Complies
6	2437 MHz	-15.20	-13.53	4.99	Complies
9	2452 MHz	-16.80	-15.35	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2))) = 4.99dBm/3kHz

For 5GHz Band

Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Ant.1

Channel	Frequency	Power Density (dBm/3kHz)	Single Port Limit (dBm/3kHz)	Result
149	5745 MHz	-6.80	8.00	Complies
157	5785 MHz	-4.26	8.00	Complies
165	5825 MHz	-4.99	8.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Ant.1

Channel	Frequency	Power Density (dBm/3kHz)	Single Port Limit (dBm/3kHz)	Result
151	5755 MHz	-9.73	8.00	Complies
159	5795 MHz	-7.36	8.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Ant.1

Channel	Frequency	Power Density (dBm/3kHz)	Single Port Limit (dBm/3kHz)	Result
155	5775 MHz	-18.67	8.00	Complies

Temperature	25°C	Humidity	56%
Test Engineer	Benson Peng	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b / Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	-11.56	8.00	Complies
6	2437 MHz	-11.67	8.00	Complies
11	2462 MHz	-12.58	8.00	Complies

Configuration IEEE 802.11g / Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	-11.78	8.00	Complies
6	2437 MHz	-4.32	8.00	Complies
11	2462 MHz	-12.38	8.00	Complies


Configuration IEEE 802.11a / Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
149	5745 MHz	-7.01	8.00	Complies
157	5785 MHz	-4.32	8.00	Complies
165	5825 MHz	-5.37	8.00	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 2 / 2437 MHz




Date: 11.MAY.2013 15:55:41

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 2 / 2437 MHz




Date: 11.MAY.2013 16:01:37

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Ant. 1 / 5785 MHz




Date: 11.MAY.2013 16:27:14

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Ant. 1 / 5795 MHz




Date: 11.MAY.2013 16:30:04

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Ant. 1 / 5775 MHz




Date: 11.MAY.2013 16:31:23

Power Density Plot on Configuration IEEE 802.11b / Ant. 1 / 2412 MHz




Date: 11.MAY.2013 15:51:59

Power Density Plot on Configuration IEEE 802.11g / Ant. 1 / 2437 MHz



Date: 11.MAY.2013 15:49:28

Power Density Plot on Configuration IEEE 802.11a / Ant. 1 / 5785 MHz



Date: 11.MAY.2013 16:24:42

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100kHz
VB	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.0 DTS 6-dB signal bandwidth option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v01r02 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	25°C	Humidity	56%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n/ac

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.16	17.68	500	Complies
6	2437 MHz	10.68	22.96	500	Complies
11	2462 MHz	17.68	17.92	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	28.96	36.16	500	Complies
6	2437 MHz	29.00	36.16	500	Complies
9	2452 MHz	33.20	35.04	500	Complies

For 5GHz Band

Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	17.60	28.24	500	Complies
157	5785 MHz	17.68	34.24	500	Complies
165	5825 MHz	17.60	32.08	500	Complies

Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	35.52	45.76	500	Complies
159	5795 MHz	36.48	66.40	500	Complies

Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
155	5775 MHz	76.32	75.84	500	Complies

Temperature	20°C	Humidity	70%
Test Engineer	Benson Peng	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.08	12.32	500	Complies
6	2437 MHz	10.08	12.24	500	Complies
11	2462 MHz	10.08	12.32	500	Complies

Configuration IEEE 802.11g / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.56	16.56	500	Complies
6	2437 MHz	16.56	27.12	500	Complies
11	2462 MHz	16.64	16.64	500	Complies


Configuration IEEE 802.11a / Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.40	27.20	500	Complies
157	5785 MHz	16.48	33.92	500	Complies
165	5825 MHz	16.00	31.60	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2 / 2412 MHz




Date: 11.MAY.2013 14:44:02

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2 / 2422 MHz




Date: 11.MAY.2013 14:52:45

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Ant. 1 / 5745 MHz




Date: 11.MAY.2013 15:10:53

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Ant. 1 / 5755MHz




Date: 11.MAY.2013 15:12:16

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Ant. 1 / 5775 MHz




Date: 11.MAY.2013 15:14:49

6 dB Bandwidth Plot on Configuration IEEE 802.11b / Ant. 1 / 2412 MHz




Date: 11.MAY.2013 15:41:26

6 dB Bandwidth Plot on Configuration IEEE 802.11g / Ant. 1 / 2412 MHz



Date: 11.MAY.2013 15:46:49

6 dB Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 / 5825 MHz



Date: 11.MAY.2013 15:07:39

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1GHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1GHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	Normal Link
Test Date	Mar. 21, 2013		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	Mode 1

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	434.49	34.61	46.00	-11.39	47.01	2.60	16.15	31.15	100	327	HORIZONTAL Peak
2 pp	531.49	40.54	46.00	-5.46	51.43	2.89	17.60	31.38	200	326	HORIZONTAL Peak
3	579.99	36.89	46.00	-9.11	46.61	3.06	18.40	31.18	200	115	HORIZONTAL Peak
4	628.49	36.84	46.00	-9.16	46.45	3.19	18.62	31.42	150	1	HORIZONTAL Peak
5	821.52	37.35	46.00	-8.65	44.53	3.72	20.29	31.19	100	2	HORIZONTAL Peak
6 qp	870.02	35.60	46.00	-10.40	42.70	3.86	20.20	31.16	100	0	HORIZONTAL QP

Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	qp	43.58	29.78	40.00	-10.22	50.59	0.78	10.25	31.84	100	356 VERTICAL	QP
2	pp	106.63	36.98	43.50	-6.52	56.20	1.23	11.11	31.56	125	321 VERTICAL	Peak
3		141.55	33.54	43.50	-9.96	52.92	1.41	10.74	31.53	100	215 VERTICAL	Peak
4		338.46	31.98	46.00	-14.02	47.15	2.28	13.91	31.36	125	360 VERTICAL	Peak
5		482.99	35.25	46.00	-10.75	46.96	2.73	16.80	31.24	100	243 VERTICAL	Peak
6		579.99	36.14	46.00	-9.86	45.86	3.06	18.40	31.18	100	231 VERTICAL	Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11n MCS0 20MHz Ch 1 / Ant. 1 + Ant. 2
Test Date	Mar. 18, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4816.56	32.83	54.00	-21.17	31.54	3.31	33.02	35.04	Average	100	146	HORIZONTAL
2	4816.56	42.76	74.00	-31.24	41.47	3.31	33.02	35.04	Peak	100	146	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4829.90	31.17	54.00	-22.83	29.83	3.31	33.06	35.03	Average	100	60	VERTICAL
2	4829.90	40.99	74.00	-33.01	39.65	3.31	33.06	35.03	Peak	100	60	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11n MCS0 20MHz Ch 6 / Ant. 1 + Ant. 2
Test Date	Mar. 18, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4882.46	35.47	54.00	-18.53	34.01	3.33	33.16	35.03	Average	100	200	HORIZONTAL
2	4882.46	46.74	74.00	-27.26	45.28	3.33	33.16	35.03	Peak	100	200	HORIZONTAL
3	7311.00	32.81	54.00	-21.19	28.19	4.06	35.96	35.40	Average	100	251	HORIZONTAL
4	7311.00	43.45	74.00	-30.55	38.83	4.06	35.96	35.40	Peak	100	251	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4865.47	40.98	54.00	-13.02	39.56	3.33	33.12	35.03	Average	119	43	VERTICAL
2	4865.47	53.02	74.00	-20.98	51.60	3.33	33.12	35.03	Peak	119	43	VERTICAL
3	7311.00	34.44	54.00	-19.56	29.82	4.06	35.96	35.40	Average	100	110	VERTICAL
4	7311.00	44.55	74.00	-29.45	39.93	4.06	35.96	35.40	Peak	100	110	VERTICAL



Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11n MCS0 20MHz Ch11 / Ant. 1 + Ant. 2
Test Date	Mar. 18, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4924.00	29.76	54.00	-24.24	28.16	3.35	33.26	35.01	Average	100	177 HORIZONTAL
2	4924.00	39.37	74.00	-34.63	37.77	3.35	33.26	35.01	Peak	100	177 HORIZONTAL
3	7386.00	32.66	54.00	-21.34	27.91	4.06	36.09	35.40	Average	100	258 HORIZONTAL
4	7386.00	45.06	74.00	-28.94	40.31	4.06	36.09	35.40	Peak	100	258 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4924.00	29.95	54.00	-24.05	28.35	3.35	33.26	35.01	Average	100	122 VERTICAL
2	4924.00	41.05	74.00	-32.95	39.45	3.35	33.26	35.01	Peak	100	122 VERTICAL
3	7386.00	32.87	54.00	-21.13	28.12	4.06	36.09	35.40	Average	100	196 VERTICAL
4	7386.00	43.13	74.00	-30.87	38.38	4.06	36.09	35.40	Peak	100	196 VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11n MCS0 40MHz Ch 3 / Ant. 1 + Ant. 2
Test Date	Mar. 18, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4843.74	32.13	54.00	-21.87	30.75	3.32	33.09	35.03	Average	100	137	HORIZONTAL
2	4843.74	41.99	74.00	-32.01	40.61	3.32	33.09	35.03	Peak	100	137	HORIZONTAL
3	7266.00	32.57	54.00	-21.43	28.06	4.06	35.85	35.40	Average	100	218	HORIZONTAL
4	7266.00	42.88	74.00	-31.12	38.37	4.06	35.85	35.40	Peak	100	218	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4843.97	36.93	54.00	-17.07	35.55	3.32	33.09	35.03	Average	100	23	VERTICAL
2	4843.97	48.91	74.00	-25.09	47.53	3.32	33.09	35.03	Peak	100	23	VERTICAL
3	7266.00	32.35	54.00	-21.65	27.84	4.06	35.85	35.40	Average	100	102	VERTICAL
4	7266.00	42.00	74.00	-32.00	37.49	4.06	35.85	35.40	Peak	100	102	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11n MCS0 40MHz Ch 6 / Ant. 1 + Ant. 2
Test Date	Mar. 18, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.78	35.40	54.00	-18.60	33.94	3.33	33.16	35.03	Average	100	225	HORIZONTAL
2	4873.78	48.07	74.00	-25.93	46.61	3.33	33.16	35.03	Peak	100	225	HORIZONTAL
3	7311.00	32.67	54.00	-21.33	28.05	4.06	35.96	35.40	Average	100	147	HORIZONTAL
4	7311.00	43.97	74.00	-30.03	39.35	4.06	35.96	35.40	Peak	100	147	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.32	41.62	54.00	-12.38	40.16	3.33	33.16	35.03	Average	100	34	VERTICAL
2	4874.32	53.46	74.00	-20.54	52.00	3.33	33.16	35.03	Peak	100	34	VERTICAL
3	7311.00	32.41	54.00	-21.59	27.79	4.06	35.96	35.40	Average	100	135	VERTICAL
4	7311.00	42.19	74.00	-31.81	37.57	4.06	35.96	35.40	Peak	100	135	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11n MCS0 40MHz Ch 9 / Ant. 1 + Ant. 2
Test Date	Mar. 18, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4904.00	31.87	54.00	-22.13	30.36	3.34	33.19	35.02	Average	100	177 HORIZONTAL
2	4904.00	42.38	74.00	-31.62	40.87	3.34	33.19	35.02	Peak	100	177 HORIZONTAL
3	7356.00	32.37	54.00	-21.63	27.69	4.06	36.02	35.40	Average	100	255 HORIZONTAL
4	7356.00	43.67	74.00	-30.33	38.99	4.06	36.02	35.40	Peak	100	255 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4904.03	39.00	54.00	-15.00	37.49	3.34	33.19	35.02	Average	100	35 VERTICAL
2	4904.03	51.85	74.00	-22.15	50.34	3.34	33.19	35.02	Peak	100	35 VERTICAL
3	7356.00	32.31	54.00	-21.69	27.63	4.06	36.02	35.40	Average	100	112 VERTICAL
4	7356.00	42.40	74.00	-31.60	37.72	4.06	36.02	35.40	Peak	100	112 VERTICAL



Temperature	25.6°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz CH 149 / Ant. 1
Test Date	Feb. 08, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11490.96	38.75	54.00	-15.25	28.33	6.74	34.82	38.50	Average	193	100	HORIZONTAL
2 p	11497.52	50.71	74.00	-23.29	40.28	6.75	34.82	38.50	Peak	193	100	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11488.24	60.36	74.00	-13.64	49.94	6.74	34.82	38.50	Peak	122	184	VERTICAL
2 a	11492.80	48.14	54.00	-5.86	37.72	6.74	34.82	38.50	Average	122	184	VERTICAL



Temperature	25.6°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz CH 157 / Ant. 1
Test Date	Feb. 08, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11567.12	43.25	54.00	-10.75	32.82	6.77	34.84	38.50	Average	188	158	HORIZONTAL
2 p	11568.16	56.26	74.00	-17.74	45.83	6.77	34.84	38.50	Peak	188	158	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11566.72	48.82	54.00	-5.18	38.39	6.77	34.84	38.50	Average	123	184	VERTICAL
2 p	11569.20	61.49	74.00	-12.51	51.06	6.77	34.84	38.50	Peak	123	184	VERTICAL



Temperature	25.6°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz CH 165 / Ant. 1
Test Date	Feb. 08, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11646.48	55.44	74.00	-18.56	45.01	6.80	34.87	38.50	Peak	158	143	HORIZONTAL
2 a	11649.92	43.71	54.00	-10.29	33.28	6.80	34.87	38.50	Average	158	143	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11649.28	62.21	74.00	-11.79	51.78	6.80	34.87	38.50	Peak	126	197	VERTICAL
2 a	11649.60	50.11	54.00	-3.89	39.68	6.80	34.87	38.50	Average	126	197	VERTICAL



Temperature	25.6°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 40MHz CH 151 / Ant. 1
Test Date	Feb. 08, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11508.48	38.03	54.00	-15.97	27.60	6.75	34.82	38.50	Average	330	119	HORIZONTAL
2 p	11529.20	49.90	74.00	-24.10	39.47	6.76	34.83	38.50	Peak	330	119	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11509.92	43.23	54.00	-10.77	32.80	6.75	34.82	38.50	Average	133	138	VERTICAL
2 p	11510.64	55.03	74.00	-18.97	44.60	6.75	34.82	38.50	Peak	133	138	VERTICAL



Temperature	25.6°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 40MHz CH 159 / Ant. 1
Test Date	Feb. 08, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11590.80	50.50	74.00	-23.50	40.07	6.78	34.85	38.50	Peak	181	100	HORIZONTAL
2 a	11593.20	39.28	54.00	-14.72	28.85	6.78	34.85	38.50	Average	181	100	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11590.40	46.28	54.00	-7.72	35.85	6.78	34.85	38.50	Average	105	121	VERTICAL
2 p	11590.96	57.95	74.00	-16.05	47.52	6.78	34.85	38.50	Peak	105	121	VERTICAL



Temperature	25.6°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 80MHz CH 155 / Ant. 1
Test Date	Feb. 08, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11552.36	50.63	74.00	-23.37	40.20	6.77	34.84	38.50	Peak	309	100	HORIZONTAL
2 a	11555.44	38.19	54.00	-15.81	27.76	6.77	34.84	38.50	Average	309	100	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11549.84	41.19	54.00	-12.81	30.76	6.77	34.84	38.50	Average	135	132	VERTICAL
2 p	11553.64	53.27	74.00	-20.73	42.84	6.77	34.84	38.50	Peak	135	132	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11b CH 1 / Ant. 1
Test Date	Mar. 18, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.99	45.87	54.00	-8.13	44.53	3.31	33.06	35.03	Average	101	289	HORIZONTAL
2	4823.99	49.25	74.00	-24.75	47.91	3.31	33.06	35.03	Peak	101	289	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.99	53.83	54.00	-0.17	52.49	3.31	33.06	35.03	Average	103	35	VERTICAL
2	4823.99	55.52	74.00	-18.48	54.18	3.31	33.06	35.03	Peak	103	35	VERTICAL



Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11b CH 6 / Ant. 1
Test Date	Mar. 18, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.98	46.00	54.00	-8.00	44.54	3.33	33.16	35.03	Average	116	250	HORIZONTAL
2	4873.98	49.29	74.00	-24.71	47.83	3.33	33.16	35.03	Peak	116	250	HORIZONTAL
3	7311.00	32.71	54.00	-21.29	28.09	4.06	35.96	35.40	Average	100	164	HORIZONTAL
4	7311.00	43.67	74.00	-30.33	39.05	4.06	35.96	35.40	Peak	100	164	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.00	53.67	54.00	-0.33	52.21	3.33	33.16	35.03	Average	103	255	VERTICAL
2	4874.00	55.51	74.00	-18.49	54.05	3.33	33.16	35.03	Peak	103	255	VERTICAL
3	7309.91	33.46	54.00	-20.54	28.84	4.06	35.96	35.40	Average	100	194	VERTICAL
4	7309.91	43.55	74.00	-30.45	38.93	4.06	35.96	35.40	Peak	100	194	VERTICAL



Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11b CH 11 / Ant. 1
Test Date	Mar. 18, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.99	48.02	54.00	-5.98	46.42	3.35	33.26	35.01	Average	169	303	HORIZONTAL
2	4923.99	51.23	74.00	-22.77	49.63	3.35	33.26	35.01	Peak	169	303	HORIZONTAL
3	7386.00	32.51	54.00	-21.49	27.76	4.06	36.09	35.40	Average	100	237	HORIZONTAL
4	7386.00	42.44	74.00	-31.56	37.69	4.06	36.09	35.40	Peak	100	237	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.99	53.55	54.00	-0.45	51.95	3.35	33.26	35.01	Average	100	256	VERTICAL
2	4923.99	55.66	74.00	-18.34	54.06	3.35	33.26	35.01	Peak	100	256	VERTICAL
3	7388.69	34.10	54.00	-19.90	29.35	4.06	36.09	35.40	Average	100	0	VERTICAL
4	7388.69	44.53	74.00	-29.47	39.78	4.06	36.09	35.40	Peak	100	0	VERTICAL



Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11g CH 1 / Ant. 1
Test Date	Mar. 18, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	4824.00	30.73	54.00	-23.27	29.39	3.31	33.06	35.03	Average	100	124	HORIZONTAL
2	4824.00	39.01	74.00	-34.99	37.67	3.31	33.06	35.03	Peak	100	124	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	4824.16	37.85	54.00	-16.15	36.51	3.31	33.06	35.03	Average	104	35	VERTICAL
2	4824.16	48.61	74.00	-25.39	47.27	3.31	33.06	35.03	Peak	104	35	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11g CH 6 / Ant. 1
Test Date	Mar. 18, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	4874.00	32.14	54.00	-21.86	30.68	3.33	33.16	35.03	Average	100	211	HORIZONTAL
2	4874.00	43.25	74.00	-30.75	41.79	3.33	33.16	35.03	Peak	100	211	HORIZONTAL
3	7311.00	33.26	54.00	-20.74	28.64	4.06	35.96	35.40	Average	100	127	HORIZONTAL
4	7311.00	45.61	74.00	-28.39	40.99	4.06	35.96	35.40	Peak	100	127	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	4874.00	38.30	54.00	-15.70	36.84	3.33	33.16	35.03	Average	100	255	VERTICAL
2	4874.00	49.43	74.00	-24.57	47.97	3.33	33.16	35.03	Peak	100	255	VERTICAL
3	7311.00	35.20	54.00	-18.80	30.58	4.06	35.96	35.40	Average	100	291	VERTICAL
4	7311.00	43.74	74.00	-30.26	39.12	4.06	35.96	35.40	Peak	100	291	VERTICAL



Temperature	25.6°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11g CH 11 / Ant. 1
Test Date	Mar. 18, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4924.06	32.60	54.00	-21.40	31.00	3.35	33.26	35.01	Average	100	266	HORIZONTAL
2	4924.06	41.56	74.00	-32.44	39.96	3.35	33.26	35.01	Peak	100	266	HORIZONTAL
3	7386.00	32.63	54.00	-21.37	27.88	4.06	36.09	35.40	Average	100	180	HORIZONTAL
4	7386.00	42.43	74.00	-31.57	37.68	4.06	36.09	35.40	Peak	100	180	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4924.00	31.32	54.00	-22.68	29.72	3.35	33.26	35.01	Average	100	120	VERTICAL
2	4924.00	40.03	74.00	-33.97	38.43	3.35	33.26	35.01	Peak	100	120	VERTICAL
3	7386.00	32.85	54.00	-21.15	28.10	4.06	36.09	35.40	Average	100	198	VERTICAL
4	7386.00	43.36	74.00	-30.64	38.61	4.06	36.09	35.40	Peak	100	198	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 149 / Ant. 1
Test Date	Feb. 07, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11490.28	43.73	54.00	-10.27	33.31	6.74	34.82	38.50	Average	184	166	HORIZONTAL
2 p	11492.32	56.10	74.00	-17.90	45.68	6.74	34.82	38.50	Peak	184	166	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11487.12	60.86	74.00	-13.14	50.44	6.74	34.82	38.50	Peak	123	191	VERTICAL
2 a	11490.08	49.76	54.00	-4.24	39.34	6.74	34.82	38.50	Average	123	191	VERTICAL

Temperature	25.6°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 157 / Ant. 1
Test Date	Feb. 07, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11568.40	45.47	54.00	-8.53	35.04	6.77	34.84	38.50	Average	184	154	HORIZONTAL
2 p	11570.96	57.53	74.00	-16.47	47.11	6.77	34.85	38.50	Peak	184	154	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11570.08	50.68	54.00	-3.32	40.26	6.77	34.85	38.50	Average	123	185	VERTICAL
2 p	11570.80	64.06	74.00	-9.94	53.64	6.77	34.85	38.50	Peak	123	185	VERTICAL



Temperature	25.6°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 165 / Ant. 1
Test Date	Feb. 07, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11650.06	38.35	54.00	-15.65	29.63	5.16	38.86	35.30	Average	100	248	HORIZONTAL
2	11650.06	49.55	74.00	-24.45	40.83	5.16	38.86	35.30	Peak	100	248	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	11650.72	62.56	74.00	-11.44	52.13	6.80	34.87	38.50	Peak	100	213	VERTICAL
2 a	11652.28	50.31	54.00	-3.69	39.88	6.80	34.87	38.50	Average	100	213	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Conducted Out of Band Emission Measurement:

1. Test was performed in accordance with KDB 558074 D01 v03 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure
2. The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.
Only worst data of each operating mode is presented.

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Conducted Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.4.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	26°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11n MCS0 20MHz Ch 1, 6, 11 / Ant. 1 + Ant. 2
Test date	Mar. 18, 2013		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.84	73.00	74.00	-1.00	42.61	2.22	28.17	0.00	Peak	100	11	VERTICAL
2	2390.00	53.48	54.00	-0.52	23.09	2.22	28.17	0.00	Average	100	11	VERTICAL
3	2406.39	100.60			70.17	2.22	28.21	0.00	Average	100	11	VERTICAL
4	2407.19	110.84			80.41	2.22	28.21	0.00	Peak	100	11	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	53.49	54.00	-0.51	23.10	2.22	28.17	0.00	Average	100	145	VERTICAL
2	2390.00	69.12	74.00	-4.88	38.73	2.22	28.17	0.00	Peak	100	145	VERTICAL
3	2428.99	107.90			77.42	2.23	28.25	0.00	Average	100	145	VERTICAL
4	2429.63	117.76			87.28	2.23	28.25	0.00	Peak	100	145	VERTICAL
5	2485.42	51.90	54.00	-2.10	21.23	2.26	28.41	0.00	Average	100	145	VERTICAL
6	2489.27	68.01	74.00	-5.99	37.34	2.26	28.41	0.00	Peak	100	145	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2460.56	100.76			70.19	2.24	28.33	0.00	Average	100	203	VERTICAL
2	2461.20	110.38			79.81	2.24	28.33	0.00	Peak	100	203	VERTICAL
3	2483.50	53.61	54.00	-0.39	22.98	2.26	28.37	0.00	Average	100	203	VERTICAL
4	2483.50	70.83	74.00	-3.17	40.20	2.26	28.37	0.00	Peak	100	203	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	56%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11n MCS0 40MHz Ch 3, 6, 9 / Ant. 1 + Ant. 2
Test date	Mar. 18, 2013		

Channel 3

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.04	69.52	74.00	-4.48	39.14	2.21	28.17	0.00	Peak	100	145	VERTICAL
2	2389.68	53.43	54.00	-0.57	23.05	2.21	28.17	0.00	Average	100	145	VERTICAL
3	2405.33	96.41			65.98	2.22	28.21	0.00	Average	100	145	VERTICAL
4	2405.33	105.77			75.34	2.22	28.21	0.00	Peak	100	145	VERTICAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	53.60	54.00	-0.40	23.21	2.22	28.17	0.00	Average	100	205	VERTICAL
2	2390.00	68.51	74.00	-5.49	38.12	2.22	28.17	0.00	Peak	100	205	VERTICAL
3	2447.58	108.62			78.09	2.24	28.29	0.00	Peak	100	205	VERTICAL
4	2450.14	99.16			68.63	2.24	28.29	0.00	Average	100	205	VERTICAL
5	2484.46	50.63	54.00	-3.37	20.00	2.26	28.37	0.00	Average	100	205	VERTICAL
6	2487.03	65.81	74.00	-8.19	35.14	2.26	28.41	0.00	Peak	100	205	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2468.67	108.07			77.44	2.26	28.37	0.00	Peak	100	156	VERTICAL
2	2468.99	98.46			67.83	2.26	28.37	0.00	Average	100	156	VERTICAL
3	2487.99	53.74	54.00	-0.26	23.07	2.26	28.41	0.00	Average	100	156	VERTICAL
4	2487.99	69.17	74.00	-4.83	38.50	2.26	28.41	0.00	Peak	100	156	VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	20°C	Humidity	70%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. 1
Test date	Mar. 18, 2013		

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2389.36	58.28	74.00	-15.72	27.90	2.21	28.17	0.00	Peak	100	144 VERTICAL
2	2390.00	46.67	54.00	-7.33	16.28	2.22	28.17	0.00	Average	100	144 VERTICAL
3	2409.44	107.36			76.93	2.22	28.21	0.00	Peak	100	144 VERTICAL
4	2410.24	103.87			73.44	2.22	28.21	0.00	Average	100	144 VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2390.00	45.96	54.00	-8.04	15.57	2.22	28.17	0.00	Average	100	141 VERTICAL
2	2390.00	56.58	74.00	-17.42	26.19	2.22	28.17	0.00	Peak	100	141 VERTICAL
3	2435.08	104.84			74.32	2.23	28.29	0.00	Average	100	141 VERTICAL
4	2436.04	108.43			77.91	2.23	28.29	0.00	Peak	100	141 VERTICAL
5	2483.50	46.63	54.00	-7.37	16.00	2.26	28.37	0.00	Average	100	141 VERTICAL
6	2483.50	56.47	74.00	-17.53	25.84	2.26	28.37	0.00	Peak	100	141 VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2462.96	106.91			76.34	2.24	28.33	0.00	Peak	100	244 VERTICAL
2	2463.76	103.45			72.88	2.24	28.33	0.00	Average	100	244 VERTICAL
3	2483.50	45.72	54.00	-8.28	15.09	2.26	28.37	0.00	Average	100	244 VERTICAL
4	2483.50	56.84	74.00	-17.16	26.21	2.26	28.37	0.00	Peak	100	244 VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	20°C	Humidity	70%
Test Engineer	Andre Zhuo	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 1
Test date	Mar. 18, 2013		

Channel 1

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	53.85	54.00	-0.15	23.46	2.22	28.17	0.00	Average	100	141	VERTICAL
2	2390.00	69.06	74.00	-4.94	38.67	2.22	28.17	0.00	Peak	100	141	VERTICAL
3	2404.79	108.42			77.99	2.22	28.21	0.00	Peak	100	141	VERTICAL
4	2404.95	99.56			69.13	2.22	28.21	0.00	Average	100	141	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.36	66.16	74.00	-7.84	35.78	2.21	28.17	0.00	Peak	100	142	VERTICAL
2	2390.00	51.78	54.00	-2.22	21.39	2.22	28.17	0.00	Average	100	142	VERTICAL
3	2439.56	115.41			84.89	2.23	28.29	0.00	Peak	100	142	VERTICAL
4	2444.37	106.33			75.80	2.24	28.29	0.00	Average	100	142	VERTICAL
5	2483.50	53.85	54.00	-0.15	23.22	2.26	28.37	0.00	Average	100	142	VERTICAL
6	2485.10	70.89	74.00	-3.11	40.22	2.26	28.41	0.00	Peak	100	142	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2454.79	99.47			68.90	2.24	28.33	0.00	Average	100	142	VERTICAL
2	2455.11	108.71			78.14	2.24	28.33	0.00	Peak	100	142	VERTICAL
3	2483.50	53.92	54.00	-0.08	23.29	2.26	28.37	0.00	Average	100	142	VERTICAL
4	2483.66	71.53	74.00	-2.47	40.90	2.26	28.37	0.00	Peak	100	142	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level




Date: 7.MAY.2013 12:29:02

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 7.MAY.2013 12:30:45

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 7.MAY.2013 12:31:44

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 7.MAY.2013 12:34:12

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 7.MAY.2013 12:31:44

Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level




Date: 7.MAY.2013 12:37:07

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 7.MAY.2013 12:38:53

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 7.MAY.2013 12:39:42

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 / 30MHz~2400MHz (down 30dBc)




Date: 7.MAY.2013 12:42:11

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 / 2500MHz~26500MHz (down 30dBc)




Date: 7.MAY.2013 12:41:24

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Reference Level




Date: 7.MAY.2013 13:40:20

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 149 / 30MHz~5725MHz (down 30dBc)




Date: 7.MAY.2013 13:42:24

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 149 / 5850MHz~40000MHz (down 30dBc)




Date: 7.MAY.2013 13:43:37

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 165 / 30MHz~5725MHz (down 30dBc)




Date: 7.MAY.2013 13:47:33

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 165 / 5850MHz~40000MHz (down 30dBc)




Date: 7.MAY.2013 13:46:24

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Reference Level




Date: 7.MAY.2013 14:08:13

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 151 / 30MHz~5725MHz (down 30dBc)




Date: 7.MAY.2013 14:14:05

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 151 / 5850MHz~40000MHz (down 30dBc)




Date: 7.MAY.2013 14:15:01

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 159 / 30MHz~5725MHz (down 30dBc)




Date: 7.MAY.2013 14:10:29

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 159 / 5850MHz~40000MHz (down 30dBc)




Date: 7.MAY.2013 14:08:46

Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Reference Level




Date: 7.MAY.2013 14:54:01

Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / CH 155 / 30MHz~5725MHz (down 30dBc)




Date: 7.MAY.2013 14:55:26

Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / CH 155 / 5850MHz~40000MHz (down 30dBc)




Date: 7.MAY.2013 14:59:03

Plot on Configuration IEEE 802.11b / Reference Level




Date: 7.MAY.2013 12:18:53

Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 7.MAY.2013 12:19:34

Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 7.MAY.2013 12:20:18

Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 7.MAY.2013 12:22:30

Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 7.MAY.2013 12:21:46

Plot on Configuration IEEE 802.11g / Reference Level




Date: 7.MAY.2013 12:11:26

Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 7.MAY.2013 12:13:16

Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 7.MAY.2013 12:13:56

Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 7.MAY.2013 12:15:45

Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 7.MAY.2013 12:16:23

Plot on Configuration IEEE 802.11a / Reference Level




Date: 7.MAY.2013 13:26:41

Plot on Configuration IEEE 802.11a / CH 149 / 30MHz~5725MHz (down 30dBc)




Date: 7.MAY.2013 13:35:22

Plot on Configuration IEEE 802.11a / CH 149 / 5850MHz~40000MHz (down 30dBc)




Date: 7.MAY.2013 13:37:14

Plot on Configuration IEEE 802.11a / CH 165 / 30MHz~5725MHz (down 30dBc)



Date: 7.MAY.2013 13:31:20

Plot on Configuration IEEE 802.11a / CH 165 / 5850MHz~40000MHz (down 30dBc)



Date: 7.MAY.2013 13:30:46

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 26, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz~30MHz	Feb. 21, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 04, 2012	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	-	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Apr. 16, 2012	Radiation (O3CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (O3CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2012	Radiation (O3CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2012	Radiation (O3CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (O3CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (O3CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (O3CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 16, 2012	Radiation (O3CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Apr. 15, 2012	Radiation (O3CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (O3CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (O3CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 18, 2012	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 18, 2012	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (O3CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (O3CH01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Signal Generator	R&S	SMR40	100302	10MHz-40GHz	Nov. 27, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085