

FC

Test Report

For

Applicant : AboCom System , Inc.
Equipment Type : 10/100 Fast Ethernet+56K FAX
Modem PC Card
Model : LF560MX
FCC ID : MQ4PLM56

Report No. : 994007FI



Test Report Certification

Quietek Corporation

No.75-1, Wang-Yeh Valley, Yung-Hsing, Chiung-Lin,
Hsin-Chu County, Taiwan, R.O.C.
Tel : 886-3-592-8858, Fax: 886-3-592-8859
E-Mail : quietek@ms24.hinet.net

Accredited by NIST(NVLAP), VCCI, BSMI, DNV, TUV

Applicant : AboCom System , Inc.
Address : 12F-3 , No 333 , Sec 1 , Guan-Fu Road , Hsin-chu , Taiwan ,
R.O.C.
Equipment Type : 10/100 Fast Ethernet+56K FAX Modem PC Card
Model : LF560MX
FCC ID. : MQ4PLM56
Measurement Standard : FCC Part 15 Subpart B
Measurement Procedure : ANSI C63.4 /1992
Operation Voltage : 120Vac/60Hz
Classification : Class B
Test Result : Complied
Test Date : April 12, 1999
Report No. : 994007FI

The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented by: Lisa Chen

Test Engineer: Jeff Chen

Approved: Gene Chang

Lisa Chen

Jeff Chen

Gene Chang



TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION.....	4
1.1 EUT DESCRIPTION	4
1.2 TESTED SYSTEM DETAILS.....	5
1.3 EUT CONFIGURATION	8
1.4 EUT EXERCISE SOFTWARE.....	8
1.5 TEST PERFORMED	9
1.6 TEST FACILITY	10
2. CONDUCTED EMISSION	11
2.1 TEST EQUIPMENT LIST	11
2.2 TEST SETUP	11
2.3 LIMITS	11
2.4 TEST PROCEDURE.....	12
2.5 TEST RESULTS	12
3. RADIATED EMISSION.....	13
3.1 TEST EQUIPMENT	13
3.2 TEST SETUP	13
3.3 LIMITS	14
3.4 TEST PROCEDURE.....	14
3.5 TEST RESULTS	14
4. SUMMARY OF TEST RESULTS.....	15
5. EMI REDUCTION METHOD DURING COMPLIANCE TESTING.....	20
6. TEST PHOTOGRAPHS.....	21
7. EUT DETAIL PHOTOGRAPHS.....	23

ATTACHMENT

LABORATORY OF LICENSE



1. General Information

1.1 EUT Description

Applicant : AboCom System , Inc.
Address : 12F-3 , No 333 , Sec 1 , Guan-Fu Road , Hsin-chu , Taiwan , R.O.C.
Equipment Type : 10/100 Fast Ethernet+56K FAX Modem PC Card
Model : LF560MX
FCC ID : MQ4PLM56
Operation Voltage : 120Vac/60Hz

Remark: The data shown in this report reflects the worst-case data for each operation mode.



1.2 Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

- Notebook
 - Model Name : PC-5NU01-YA7LA
 - Model Number : 389
 - Manufacturer : Hitachi
 - External FDD : Hitachi, 3.5Inches FDD
 - Power Adaptor : Hitachi, PC-AP4800
 - FDD Cable: Shielded, 0.2m+1Cord
 - Cable IN: Non Shielded, 2m
 - CableOUT: Shielded, 1.5m

- Monitor
 - Model Number : CM752ET-311
 - Serial Number : T8F005799
 - FCC ID : DoC
 - Manufacturer : HITACHI
 - Data Cable : Shielded, 1.5m
 - Power Cord : Shielded, 1.8m

- 10/100 Fast Ethernet+56K FAX Modem PC Card (EUT)
 - Model Number : LF560MX
 - Serial Number : N/A
 - FCC ID : MQ4PLM56
 - Manufacturer : AboCom System , Inc.
 - Power Cord : Non-Shielded, 1.8m

- Keyboard
 - Model Number : 6311-TW2C
 - Serial Number : N/A
 - FCC ID : DoC
 - Manufacturer : ACER
 - Data Cable : Shielded, 1.5m

- Modem
 - Model Number : 1414
 - Serial Number : 980033041
 - FCC ID : IFAXDM1414
 - Manufacturer : ACEEX
 - Data Cable : Shielded,, 1.5m
 - Power Adapter : ACCEX, M/N: SCP41-91000A
 - Cable Output : Shielded, 1.5m



Printer
Model Number : C2642A
Serial Number : MY75L1D2XN
FCC ID : B94C2642X
Manufacturer : HP
Data Cable : Shielded,, 1.2m
Power Adapter : NMB, M/N: C2175A
Cable for AC IN: Non-Shielded, 0.7m
Cable for AC Out: Non-Shielded, 1.5m

Earphone
Model Number : PH136
Manufacturer : BSD
Data Cable : Shielded, 1.2m

Joystick
Model Number : JPD110
Serial Number : 9814A15646
Manufacturer : Maxxtro
FCC ID : DoC
Data Cable : Shielded, 1.7m

Speaker
Model Number : J-009
Serial Number : 97-C-019790-T
Manufacturer : JS
FCC ID : DoC
Data Cable : Shielded, 1.5m

Partner PC System1

Host Personal Computer
Model Number : VE 5/200 SERIES 4
Manufacturer : HP
Serial Number : SG80700310
FCC ID : DoC
Power Cord : Non-Shielded, 1.8m

Monitor
Model Number : CM752ET-311
Serial Number : T8F006364
FCC ID : DoC
Manufacturer : HITACHI
Data Cable : Shielded, 1.5m
Power Cord : Shielded, 1.8m



Keyboard
Model Number : 6311-TW2C
Serial Number : N/A
FCC ID : DoC
Manufacturer : ACER
Data Cable : Shielded, 1.5m

Mouse
Model Number : M-S34
Serial Number : LZB75078428
FCC ID : DZL211029
Manufacturer : HP
Data Cable : Shielded, 1.8m

Modem
Model Number : 1414
Serial Number : 980033040
FCC ID : IFAXDM1414
Manufacturer : ACEEX
Data Cable : Shielded,, 1.5m
Power Adapter : ACCEX, M/N: SCP41-91000A
Cable Output : Shielded, 1.5m

Partner PC System2


Host Personal Computer
Model Number : PIIL97
Manufacturer : ASUS
Serial Number : AS10228
FCC ID : DoC
Power Cord : Non-Shielded, 1.8m

Monitor
Model Number : CM752ET-311
Serial Number : T8F006364
FCC ID : DoC
Manufacturer : HITACHI
Data Cable : Shielded, 1.5m
Power Cord : Shielded, 1.8m

Keyboard
Model Number : 6311-TW2C
Serial Number : N/A
FCC ID : DoC
Manufacturer : ACER
Data Cable : Shielded, 1.5m



1.3 EUT Configuration



1.4 EUT Exercise Software

The EUT exercise program used during conducted testing was designed to exercise the EUT in a manner similar to a typical use. The exercise sequence is listed as below:

- 1.4.1 Setup the EUT and simulators as shown on 1.3
- 1.4.2 Turn on the power of all equipment.
- 1.4.3 Boot the PC from Hard Disk .
- 1.4.4 Data will communicate between notebook personal computer and partner personal computer(1) through Cardbus Fast Ethernet PC card (EUT) that is within Notebook PC.
- 1.4.5 The notebook personal computer's and partner computer's monitor will show the transmitting and receiving characteristics when the communication is success.
- 1.4.6 Telex signal also communicate between notebook personal computer and partner personal computer(2) through Cardbus Fast Ethernet PC card (EUT) that is within Notebook PC at same time.
- 1.4.7 Printer and modem will keep at standby mode during Scanner operation.
- 1.4.8 Repeat the above procedure 1.4.4 to 1.4.7

1.5 Test performed

Conducted emissions were investigated over the frequency range from **0.15MHz to 30MHz** using a receiver bandwidth of 9KHz.

Radiated emissions were investigated over the frequency range from **30MHz to 1000Mhz** using a receiver bandwidth of 120KHz. Radiated testing was performed at an antenna to EUT distance of 10 meters .

1.6 Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

Site Description: November 3, 1998 File on
 Federal Communications Commission
 FCC Engineering Laboratory
 7435 Oakland Mills Road
 Columbia, MD 21046
 Reference 31040/SIT1300F2



September 30, 1998 Accreditation on NVLAP
 NVLAP Lab Code: 200347-0

February 23, 1999 Accreditation on DNV
 Statement No. : 413-99-LAB11



December 8, 1998 Registration on VCCI
 Registration No. for No.2 Shielded Room C-858
 Registration No. for No.1 Open Area Test Site R-823
 Registration No. for No.2 Open Area Test Site R-835



January 04, 1999 Accreditation on TÜV Rheinland
 Certificate No.: I9865712-9901



Name of firm : QuieTek Corporation

Site location : No.75-1, Wang-Yeh Valley, Yung-Hsing Tsuen,
 Chung-Lin, Hsin-Chu County, Taiwan, R.O.C.



2. Conducted Emission


2.1 Test Equipment List

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal..	Remark
1	Test Receiver	R & S	ESCS 30/825442/17	May, 1998	
2	L.I.S.N.	R & S	ESH3-Z5/825016/6	May, 1998	EUT
3	L.I.S.N.	Kyoritsu	KNW-407/8-1420-3	May, 1998	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2	N/A	
5	N0.2 Shielded Room			N/A	

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

2.2 Test Setup



2.3 Limits

CISPR 22 Limits (dBuV)					FCC Part 15 Subpart B (dBuV)				
Frequency MHz	Class A		Class B		Frequency MHz	Class A		Class B	
	QP	AV	MHz	AV		uV	dBuV	uV	dBuV
0.15 - 0.50	79	66	66-56	56-46	0.45-1.705	1000	60.0	250	48.0
0.50-5.0	73	60	56	46	1.705-30	3000	69.5	250	48.0
5.0 - 30	73	60	60	50					

Remarks : In the Above Table, the tighter limit applies at the band edges.

2.4 Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 /1992 on conducted measurement.

The bandwidth of the field strength meter (R & S Test Receiver ESCS 30) is set at 9Khz.

2.5 Test Results

The emission from the EUT was below the specified limits. The worst case emissions are shown in Chapter 4. The acceptance criterion was met and the EUT passed the test.



3. Radiated Emission


3.1 Test Equipment

The following test equipment are used during the radiated emission test:

Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Site # 1	X Test Receiver	R & S	ESCS 30 / 825442/14	May, 1998
	Spectrum Analyzer	Advantest	R3261C / 71720140	May, 1998
	Pre-Amplifier	HP	8447D/3307A01812	May, 1998
	X Bilog Antenna	Chase	CBL6112B / 12452	Sep., 1998
	X Horn Antenna	EM	EM6917 / 103325	May, 1998
SITE # 2	X Test Receiver	R & S	ESCS 30 / 825442/17	May, 1998
	Spectrum Analyzer	Advantest	R3261C / 71720609	May, 1998
	Pre-Amplifier	HP	8447D/3307A01814	May, 1998
	X Bilog Antenna	Chase	CBL6112B / 2455	Sep., 1998
	X Horn Antenna	EM	EM6917 / 103325	May, 1998

- Note:
1. All equipment upon which need to calibrated are with calibration period of 1 year.
 - 2.. Mark "X" test instruments are used to measure the final test results.

3.2 Test Setup



3.3 Limits

CISPR 22 Limits (dBuV)					FCC Part 15 Subpart B (dBuV)				
Frequency MHz	Class A		Class B		Frequency	Class A		Class B	
	Distance (m)	dBuV/m	Distance (m)	dBuV/m		uV	dBuV	uV	dBuV
30 – 230	10	40	10	30	30 – 88	90	39	100	40.0
230 – 1000	10	47	10	37	88 – 216	150	43.5	150	43.5
					216 – 960	210	46.5	200	46.0
					960 - 2000	300	49.5	500	54.0

Remark: 1. The tighter limit shall apply at the edge between two frequency bands.

2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3. RF Line Voltage (dBuV) = 20 log RF Line Voltage (uV)

3.4 Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level.

The EUT was positioned such that the distance from antenna to the EUT was 10 meters .

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4 /1992 on radiated measurement.

The bandwidth below 1Ghz setting on the field strength meter (R&S Test Receiver ESCS 30) is 120 KHz.

3.5 Test Results

The emission from the EUT was below the specified limits. The worst case emissions are shown in Chapter 4. The acceptance criterion was met and the EUT passed the test.

4. **Summary of Test Results**

The test results in the emission was performed according to the requirements of measurement standard and process. QuieTek Corporation is assumed full responsibility for the accuracy and completeness of these measurements. The test data of the emission and immunity are listed as the attached data.

All the tests were carried out with the EUT in normal operation, which was defined as:

Mode1:10/100 Fast Ethernet + 56K FAX Modem PC Card

The EUT passed all the tests.

The uncertainty is calculated in accordance with NAMAS NIS 81, The total uncertainty for this test is as follows:

➤ **Emission Test**

- Uncertainty in the Conducted Emission Test: $< \pm 2.0 \text{ dB}$
- Uncertainty in the field strength measured: $< \pm 4.0 \text{ dB}$

Conducted mission Data

Date of Test : Apr .12, 1999 EUT : 10/100 Fast Ethernet+56K
 FAX Modem PC Card
 Test Mode : Mode 1 Detect Mode : Quasi-Peak & Average

Frequency MHz	Cable Loss dB	LISN Factor dB	Reading Level Line1 dBuV	Measurement Level Line1 dBuV	Limits dBuV
0.185	0.01	0.10	47.53	47.64	64.25
0.273	0.03	0.10	42.16	42.29	61.04
0.550	0.07	0.10	39.06	39.23	56.00
0.733	0.08	0.10	38.93	39.11	56.00
0.918	0.10	0.10	38.62	38.82	56.00
*2.661	0.16	0.14	39.92	40.22	56.00

Average:

0.185	0.01	0.10	38.50	38.61	54.25
0.273	0.03	0.10	37.10	37.23	51.04
0.550	0.07	0.10	38.40	38.57	46.00
0.733	0.08	0.10	38.30	38.48	46.00
0.918	0.10	0.10	37.40	37.60	46.00
2.661	0.16	0.14	34.80	35.10	46.00

Remarks :

1. “ * ” means that this data is the worst emission level.



Conducted mission Data

Date of Test : Apr .12, 1999 EUT : 10/100 Fast Ethernet+56K
 FAX Modem PC Card
 Test Mode : Mode 1 Detect Mode : Quasi-Peak & Average

Frequency MHz	Cable Loss dB	LISN Factor dB	Reading Level Line2 dBuV	Measurement Level Line2 dBuV	Limits dBuV
0.181	0.01	0.10	46.03	46.14	64.43
0.271	0.03	0.10	40.66	40.79	61.08
0.551	0.07	0.10	39.79	39.96	56.00
0.734	0.08	0.10	40.00	40.18	56.00
0.919	0.10	0.10	39.61	39.81	56.00
*4.863	0.20	0.17	41.21	41.58	56.00

Average:

0.181	0.01	0.10	36.70	36.81	54.43
0.271	0.03	0.10	35.30	35.43	51.08
0.551	0.07	0.10	39.00	39.17	46.00
0.734	0.08	0.10	39.40	39.58	46.00
0.919	0.10	0.10	38.50	38.70	46.00
4.400	0.19	0.16	33.60	33.96	46.00

Remarks :

1. “ * ” means that this data is the worst emission level.



Radiated Emission Data

Date of Test : Apr.12, 1999 EUT : 10/100 Fast Ethernet+56K
 FAX Modem PC Card
 Test Mode : Mode 1 Detect Mode : Quasi-Peak

Frequency MHz	Cable Loss dB	Ant Factor dB/m	Reading Level		Emission Level		Limits dBuV/m	Ant Pos cm	Table Pos deg
			Horizontal	Horizontal	Horizontal	Horizontal			
147.452	2.28	10.94	0.00	5.74	18.96	11.04	30.00	401	32
174.995	2.55	9.76	0.00	8.16	20.47	9.53	30.00	401	44
200.000	2.78	9.30	0.00	4.99	17.07	12.93	30.00	401	203
*250.000	3.27	12.61	0.00	12.70	28.58	8.42	37.00	401	43
275.000	3.51	12.91	0.00	7.64	24.07	12.93	37.00	401	120
300.000	3.76	13.36	0.00	9.93	27.04	9.96	37.00	401	33
350.000	4.01	14.25	0.00	7.28	25.54	11.46	37.00	296	50
400.000	4.28	15.85	0.00	2.96	23.09	13.91	37.00	296	182

Remarks:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. " * ", means this data is the worst emission level.
3. Emission Level = Reading Level + Antenna Factor + Cable loss



Radiated Emission Data

Date of Test : Apr.12, 1999 EUT : 10/100 Fast Ethernet+56K
 Test Mode : Mode 1 Detect Mode : FAX Modem PC Card
 : Quasi-Peak

Frequency MHz	Cable Loss dB	Ant Factor dB/m	Reading Level Vertical dBuV/m	Emission Level Vertical dBuV/m	Limits dBuV/m	Ant Pos cm	Table Pos deg
74.590	1.58	6.83	0.00	13.31	21.72	8.28	30.00 99 128
118.900	2.01	11.49	0.00	6.11	19.61	10.39	30.00 99 73
132.658	2.14	11.35	0.00	5.17	18.66	11.34	30.00 99 203
*147.453	2.28	10.68	0.00	13.12	26.08	3.92	30.00 99 203
150.000	2.31	10.43	0.00	13.27	26.01	3.99	30.00 99 145
200.000	2.78	9.07	0.00	13.75	25.61	4.39	30.00 99 79
225.001	3.03	9.68	0.00	12.37	25.07	4.93	30.00 99 125
300.000	3.76	13.56	0.00	9.55	26.86	10.14	37.00 99 98
350.000	4.01	14.80	0.00	7.44	26.25	10.75	37.00 99 173

Remarks:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. " * ", means this data is the worst emission level.
3. Emission Level = Reading Level + Antenna Factor + Cable loss



5. EMI Reduction Method During Compliance Testing

No modification was made during testing.

