



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	AboCom Systems, Inc.
Applicant Address	No.77, Youyi Rd., Chu Nan Chen, Miao Lih Hsien 350, Taiwan R.O.C.
FCC ID	MQ4WR5201
Manufacturer's company	AboCom Systems, Inc.
Manufacturer Address	No.77, Youyi Rd., Chu Nan Chen, Miao Lih Hsien 350, Taiwan R.O.C.

Product Name	802.11 b/g/n Wireless Broadband Router
Brand Name	AboCom
Model Name	WR5201, WR5202, WR5203
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Jan. 11, 2008
Final Test Date	Jan. 17, 2008
Submission Type	Original Equipment
Multiple Listing	Please refer to section 3.7



Statement

Test result included is only for the Draft n part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	5
3.5. Table for Test Modes	6
3.6. Table for Testing Locations.....	6
3.7. Table for Multiple Listing.....	6
3.8. Table for Supporting Units	6
3.9. Table for Parameters of Test Software Setting	7
3.10. Test Configurations	8
4. TEST RESULT	10
4.1. AC Power Line Conducted Emissions Measurement.....	10
4.2. Maximum Peak Output Power Measurement	17
4.3. Power Spectral Density Measurement	26
4.4. 6dB Spectrum Bandwidth Measurement	31
4.5. Radiated Emissions Measurement	36
4.6. Band Edge Emissions Measurement	54
4.7. Antenna Requirements	59
5. LIST OF MEASURING EQUIPMENTS	60
6. TEST LOCATION.....	62
7. TAF CERTIFICATE OF ACCREDITATION	63
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A13
APPENDIX B. TEST PHOTOS.....	B1 ~ B5
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....	C1 ~C3



History of This Test Report

Original Issue Date: Jan. 22, 2008

Report No.: FR811603AA

No additional attachment.

Additional attachment were issued as following record:

Attachment No.	Issue Date	Description



1. CERTIFICATE OF COMPLIANCE

Product Name : 802.11 b/g/n Wireless Broadband Router
Brand Name : AboCom
Model Name : WR5201
Applicant : AboCom Systems, Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jan. 11, 2008 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Wayne Hsu 20.1.08'.

Wayne Hsu

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	6.54 dB
4.2	15.247(b)(3)	Maximum Peak Conducted Output Power	Complies	5.01 dB
4.3	15.247(e)	Power Spectral Density	Complies	19.98 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.11 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.67 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	WLAN (2TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Adapter
Modulation	see the below table for draft n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for Draft n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS8 (20MHz) : 17.59 MHz MCS8 (40MHz) : 36.02 MHz
Conducted Output Power	MCS8 (20MHz) : 24.99 dBm MCS8 (40MHz) : 24.11 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)		Two (TX)	
Band width Mode	20 MHz	40 MHz	20 MHz	40 MHz
Draft n	X	X	V	V

Draft n spec

MCS Index	Nss	Modulation	R	NBPS	NCBPS		NDBPS		Data rate(Mbps)			
					800nsGI		20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
					20MHz	40MHz						
0	1	BPSK	$\frac{1}{2}$	1	52	108	26	54	6.5	13.5		
1	1	QPSK	$\frac{1}{2}$	2	104	216	52	108	13.0	27.0		
2	1	QPSK	$\frac{3}{4}$	2	104	216	78	162	19.5	40.5		
3	1	16-QAM	$\frac{1}{2}$	4	208	432	104	216	26.0	54.0		
4	1	16-QAM	$\frac{3}{4}$	4	208	432	156	324	39.0	81.0		
5	1	64-QAM	$\frac{2}{3}$	6	312	648	208	432	52.0	108.0		
6	1	64-QAM	$\frac{3}{4}$	6	312	648	234	486	58.5	121.5		
7	1	64-QAM	$\frac{5}{6}$	6	312	648	260	540	65.0	135.0		
8	2	BPSK	$\frac{1}{2}$	1	104	216	52	108	13.0	27.0		
9	2	QPSK	$\frac{1}{2}$	2	208	432	104	216	26.0	54.0		
10	2	QPSK	$\frac{3}{4}$	2	208	432	156	324	39.0	81.0		
11	2	16-QAM	$\frac{1}{2}$	4	416	864	208	432	52.0	108.0		
12	2	16-QAM	$\frac{3}{4}$	4	416	864	312	648	78.0	162.0		
13	2	64-QAM	$\frac{2}{3}$	6	624	1296	416	864	104.0	216.0		
14	2	64-QAM	$\frac{3}{4}$	6	624	1296	468	972	117.0	243.0		
15	2	64-QAM	$\frac{5}{6}$	6	624	1296	520	1080	130.0	270.0		

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPS	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

3.2. Accessories


Power	Brand	Model	Rating
Adapter 1	LEADER	MT12-4120100-A1	Input: 120VAC, 60Hz, 0.3A Output: 12VDC, 1.0A

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Remark
0	WHA YU	C068-510195-A	Dipole Antenna	Reversed-SMA	1.8	TX / RX Ant.
1	WHA YU	C068-510195-A	Dipole Antenna	Reversed-SMA	1.8	TX / RX Ant.
2	WHA YU	C068-510195-A	Dipole Antenna	Reversed-SMA	1.8	RX Ant.

Note: The EUT has three antennas.

Ant. 0 & Ant. 1 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are two bandwidth systems for draft n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	0+1
Maximum Peak Conducted Output Power	MCS8/20MHz	13 Mbps	1/6/11	0 / 1 / 0+1
	MCS8/40MHz	27 Mbps	3/6/9	0 / 1 / 0+1
Power Spectral Density 6dB Spectrum Bandwidth	MCS8/20MHz	13 Mbps	1/6/11	0+1
	MCS8/40MHz	27 Mbps	3/6/9	0+1
Radiated Emissions 9kHz~1GHz	Normal Link	Auto	-	0+1
Radiated Emissions 1GHz~10 th Harmonic	MCS8/20MHz	13 Mbps	1/6/11	0+1
	MCS8/40MHz	27 Mbps	3/6/9	0+1
Band Edge Emissions	MCS8/20MHz	13 Mbps	1/11	0+1
	MCS8/40MHz	27 Mbps	3/9	0+1

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Multiple Listing

The models listed below are series model to WR5201.

Model Name: (1) WR5202

(2) WR5203

All the models are identical, the difference of models is only for marketing strategy.

3.8. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D400	E2K24GBRL
Notebook	DELL	D400	E2K24GBRL
Notebook	DELL	D505	E2K24GBRL

3.9. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of Draft n MCS8 20MHz

Test Software Version	QA		
Frequency	2412 MHz	2437 MHz	2462 MHz
Draft n Ant. 0 + Ant. 1	08/0D	0A/0C	09/0A

Power Parameters of Draft n MCS8 40MHz

Test Software Version	QA		
Frequency	2422 MHz	2437 MHz	2452 MHz
Draft n Ant. 0 + Ant. 1	03/07	09/0B	07/07

During the test, the following programs under WIN XP were executed:


Executed "Ping.exe" to link with the remote workstation to receive and transmit signal by LAN and WLAN.

Executed "LAN Test" to traffic packet data generated software and keep 10% traffic load to link with the remote workstation by LAN and WAN.


3.10. Test Configurations

3.10.1. Radiation Emissions Test Configuration


Test Configuration: 9KHz~1GHz



Test Configuration: Above 1GHz



3.10.2. AC Power Line Conduction Emissions Test Configuration



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	58%
Test Engineer	Andy Tsai	Phase	Line
Configuration	Normal Link		




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.16327	53.41	-11.89	65.30	53.01	0.20	0.20	QP	LINE
2	0.16327	45.19	-10.11	55.30	44.79	0.20	0.20	AVERAGE	LINE
3	0.20833	53.74	-9.53	63.27	53.44	0.10	0.20	QP	LINE
4	0.20833	29.30	-23.97	53.27	29.00	0.10	0.20	AVERAGE	LINE
5	0.24352	50.09	-11.89	61.98	49.79	0.10	0.20	QP	LINE
6	0.24352	41.31	-10.67	51.98	41.01	0.10	0.20	AVERAGE	LINE
7	0.26734	50.79	-10.41	61.20	50.49	0.10	0.20	QP	LINE
8	0.26734	29.76	-21.44	51.20	29.46	0.10	0.20	AVERAGE	LINE
9	0.32412	39.34	-10.26	49.60	39.04	0.10	0.20	AVERAGE	LINE
10	0.32412	49.64	-9.96	59.60	49.34	0.10	0.20	QP	LINE
11	0.41927	46.04	-11.43	57.46	45.74	0.10	0.20	QP	LINE
12	0.41927	24.02	-23.45	47.46	23.72	0.10	0.20	AVERAGE	LINE
13	0.46122	26.31	-20.36	46.67	26.02	0.09	0.20	AVERAGE	LINE
14	0.46122	45.74	-10.93	56.67	45.45	0.09	0.20	QP	LINE
15	0.56409	43.62	-12.38	56.00	43.35	0.07	0.20	QP	LINE
16	0.56409	34.68	-11.32	46.00	34.41	0.07	0.20	AVERAGE	LINE
17	0.70925	25.61	-20.40	46.00	25.36	0.05	0.20	AVERAGE	LINE
18	0.70925	44.03	-11.98	56.00	43.78	0.05	0.20	QP	LINE
19	0.84977	25.61	-20.40	46.00	25.38	0.03	0.20	AVERAGE	LINE
20	0.84977	43.75	-12.26	56.00	43.52	0.03	0.20	QP	LINE
21	1.043	43.32	-12.68	56.00	43.13	0.00	0.19	QP	LINE
22	1.043	34.06	-11.94	46.00	33.87	0.00	0.19	AVERAGE	LINE
23	1.295	30.14	-15.86	46.00	30.00	0.00	0.14	AVERAGE	LINE



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	Po1/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
24	1.295	43.82	-12.18	56.00	43.68	0.00	0.14	QP	LINE
25	1.815	33.68	-12.32	46.00	33.51	0.00	0.17	AVERAGE	LINE
26	1.815	44.43	-11.57	56.00	44.26	0.00	0.17	QP	LINE
27	2.273	43.38	-12.62	56.00	43.18	0.00	0.20	QP	LINE
28	2.273	31.43	-14.57	46.00	31.23	0.00	0.20	AVERAGE	LINE
29	2.794	40.94	-15.06	56.00	40.74	0.00	0.20	QP	LINE
30	2.794	27.69	-18.31	46.00	27.49	0.00	0.20	AVERAGE	LINE
31	3.528	35.03	-10.97	46.00	34.73	0.00	0.30	AVERAGE	LINE
32	3.528	41.59	-14.41	56.00	41.29	0.00	0.30	QP	LINE
33	4.574	43.86	-12.14	56.00	43.55	0.01	0.30	QP	LINE
34	4.574	35.75	-10.25	46.00	35.44	0.01	0.30	AVERAGE	LINE
35	5.774	35.91	-14.09	50.00	35.58	0.03	0.30	AVERAGE	LINE
36	5.774	44.05	-15.95	60.00	43.72	0.03	0.30	QP	LINE
37	7.069	46.14	-13.86	60.00	45.77	0.05	0.32	QP	LINE
38	7.069	38.05	-11.95	50.00	37.68	0.05	0.32	AVERAGE	LINE

Temperature	25°C	Humidity	58%
Test Engineer	Andy Tsai	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.16067	54.61	-10.82	65.43	54.11	0.30	0.20	QP	NEUTRAL
2	0.16067	44.58	-10.85	55.43	44.08	0.30	0.20	AVERAGE	NEUTRAL
3	0.20396	54.08	-9.37	63.45	53.68	0.20	0.20	QP	NEUTRAL
4	0.20396	29.88	-23.57	53.45	29.48	0.20	0.20	AVERAGE	NEUTRAL
5	0.24165	50.72	-11.32	62.04	50.34	0.18	0.20	QP	NEUTRAL
6	0.24165	41.46	-10.58	52.04	41.08	0.18	0.20	AVERAGE	NEUTRAL
7	0.26442	52.46	-8.83	61.29	52.09	0.17	0.20	QP	NEUTRAL
8	0.26442	32.17	-19.12	51.29	31.80	0.17	0.20	AVERAGE	NEUTRAL
9	0.32340	51.81	-7.81	59.62	51.48	0.13	0.20	QP	NEUTRAL
10	0.32340	35.43	-14.19	49.62	35.10	0.13	0.20	AVERAGE	NEUTRAL
11	0.40785	47.77	-9.92	57.69	47.47	0.10	0.20	QP	NEUTRAL
12	0.40785	26.68	-21.01	47.69	26.38	0.10	0.20	AVERAGE	NEUTRAL
13	0.45136	29.34	-17.51	46.85	29.04	0.10	0.20	AVERAGE	NEUTRAL
14	0.45136	50.30	-6.55	56.85	50.00	0.10	0.20	QP	NEUTRAL
15	0.58031	28.33	-17.67	46.00	28.03	0.10	0.20	AVERAGE	NEUTRAL
16	0.58031	49.46	-6.54	56.00	49.16	0.10	0.20	QP	NEUTRAL
17	0.71219	47.66	-8.34	56.00	47.36	0.10	0.20	QP	NEUTRAL
18	0.71219	31.95	-14.05	46.00	31.65	0.10	0.20	AVERAGE	NEUTRAL
19	0.84172	45.36	-10.64	56.00	45.06	0.10	0.20	QP	NEUTRAL
20	0.84172	26.80	-19.20	46.00	26.50	0.10	0.20	AVERAGE	NEUTRAL
21	1.037	35.78	-10.22	46.00	35.49	0.10	0.19	AVERAGE	NEUTRAL
22	1.037	45.22	-10.78	56.00	44.93	0.10	0.19	QP	NEUTRAL
23	1.289	45.84	-10.16	56.00	45.60	0.10	0.14	QP	NEUTRAL



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
24	1.289	26.58	-19.42	46.00	26.34	0.10	0.14	AVERAGE	NEUTRAL
25	1.480	26.34	-19.66	46.00	26.14	0.10	0.10	AVERAGE	NEUTRAL
26	1.480	44.40	-11.60	56.00	44.20	0.10	0.10	QP	NEUTRAL
27	1.753	42.50	-13.50	56.00	42.25	0.10	0.15	QP	NEUTRAL
28	1.753	34.29	-11.71	46.00	34.04	0.10	0.15	AVERAGE	NEUTRAL
29	2.065	32.17	-13.83	46.00	31.87	0.10	0.20	AVERAGE	NEUTRAL
30	2.065	45.59	-10.41	56.00	45.29	0.10	0.20	QP	NEUTRAL
31	2.331	30.59	-15.41	46.00	30.29	0.10	0.20	AVERAGE	NEUTRAL
32	2.331	44.74	-11.26	56.00	44.44	0.10	0.20	QP	NEUTRAL
33	2.779	28.25	-17.75	46.00	27.95	0.10	0.20	AVERAGE	NEUTRAL
34	2.779	44.16	-11.84	56.00	43.86	0.10	0.20	QP	NEUTRAL
35	3.623	41.28	-14.72	56.00	40.88	0.10	0.30	QP	NEUTRAL
36	3.623	27.25	-18.75	46.00	26.85	0.10	0.30	AVERAGE	NEUTRAL
37	4.269	28.15	-17.85	46.00	27.75	0.10	0.30	AVERAGE	NEUTRAL
38	4.269	42.94	-13.06	56.00	42.54	0.10	0.30	QP	NEUTRAL
39	5.447	32.63	-17.37	50.00	32.23	0.10	0.30	AVERAGE	NEUTRAL
40	5.447	40.25	-19.75	60.00	39.85	0.10	0.30	QP	NEUTRAL

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Peak Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	PEAK
Trace	MAX HOLD
Sweep Time	Auto

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with FCC Conference Call, June 10, 2003.
3. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Peak Output Power

Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n

Configuration Draft n MCS0 20MHz Ant. 0

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	21.14	30.00	Complies
6	2437 MHz	22.23	30.00	Complies
11	2462 MHz	20.36	30.00	Complies

Configuration Draft n MCS0 20MHz Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	21.53	30.00	Complies
6	2437 MHz	21.71	30.00	Complies
11	2462 MHz	20.83	30.00	Complies

Configuration Draft n MCS8 20MHz Ant. 0 + Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	24.35	30.00	Complies
6	2437 MHz	24.99	30.00	Complies
11	2462 MHz	23.61	30.00	Complies

Configuration Draft n MCS0 40MHz Ant. 0

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	18.47	30.00	Complies
6	2437 MHz	21.01	30.00	Complies
9	2452 MHz	19.89	30.00	Complies


Configuration Draft n MCS0 40MHz Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	18.41	30.00	Complies
6	2437 MHz	21.19	30.00	Complies
9	2452 MHz	19.02	30.00	Complies

Configuration Draft n MCS8 40MHz Ant. 0 + Ant. 1


Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	21.45	30.00	Complies
6	2437 MHz	24.11	30.00	Complies
9	2452 MHz	22.49	30.00	Complies

Peak Output Power Plot on Configuration Drafft n MCS8 20MHz Ant. 0 / 2412 MHz




Date: 16.JAN.2008 15:10:01

Peak Output Power Plot on Configuration Drafft n MCS8 20MHz Ant. 0 / 2437 MHz




Date: 16.JAN.2008 15:12:09

Peak Output Power Plot on Configuration Drafft n MCS8 20MHz Ant. 0 / 2462 MHz




Date: 16.JAN.2008 15:15:33

Peak Output Power Plot on Configuration Drafft n MCS8 20MHz Ant. 1 / 2412 MHz




Date: 16.JAN.2008 15:09:37

Peak Output Power Plot on Configuration Drafft n MCS8 20MHz Ant. 1 / 2437 MHz




Date: 16.JAN.2008 15:13:13

Peak Output Power Plot on Configuration Drafft n MCS8 20MHz Ant. 1 / 2462 MHz




Date: 16.JAN.2008 15:15:02

Peak Output Power Plot on Configuration Drafft n MCS8 40MHz Ant. 0 / 2422 MHz



Date: 16.JAN.2008 15:05:47


Peak Output Power Plot on Configuration Drafft n MCS8 40MHz Ant. 0 / 2437 MHz



Date: 16.JAN.2008 15:02:25




Peak Output Power Plot on Configuration Drafft n MCS8 40MHz Ant. 0 / 2452 MHz



Date: 16.JAN.2008 14:53:06

Peak Output Power Plot on Configuration Drafft n MCS8 40MHz Ant. 1 / 2422 MHz



Date: 16.JAN.2008 15:06:10

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.
5. Measuring multiple antennas, the connector is required to link with Power Meter through a combiner.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n


Configuration Draft n MCS8 20MHz Ant. 0 + Ant. 1

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-12.68	8.00	Complies
6	2437 MHz	-11.98	8.00	Complies
11	2462 MHz	-13.24	8.00	Complies

Configuration Draft n MCS8 40MHz Ant. 0 + Ant. 1


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-16.25	8.00	Complies
6	2437 MHz	-13.08	8.00	Complies
9	2452 MHz	-14.70	8.00	Complies

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. 0 + Ant. 1 / 2412 MHz




Date: 16.JAN.2008 14:30:33

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. 0 + Ant. 1 / 2437 MHz




Date: 16.JAN.2008 14:33:57

Power Density Plot on Configuration Draft n MCS8 20MHz Ant. 0 + Ant. 1 / 2462 MHz




Date: 16.JAN.2008 14:35:00

Power Density Plot on Configuration Draft n MCS8 40MHz Ant. 0 + Ant. 1 / 2422 MHz




Date: 16.JAN.2008 14:37:32

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. 0 + Ant. 1 / 2437 MHz



Date: 16.JAN.2008 14:39:11

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. 0 + Ant. 1 / 2452 MHz



Date: 16.JAN.2008 14:40:31

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.
4. Measuring multiple antennas, the connector is required to link with Power Meter through a combiner.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Drafft n


Configuration Drafft n MCS8 20MHz Ant. 0 + Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.62	17.56	500	Complies
6	2437 MHz	17.66	17.59	500	Complies
11	2462 MHz	17.66	17.59	500	Complies

Configuration Drafft n MCS8 40MHz Ant. 0 + Ant. 1


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.41	36.02	500	Complies
6	2437 MHz	36.41	35.96	500	Complies
9	2452 MHz	36.41	36.02	500	Complies

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. 0 + Ant. 1 / 2412 MHz




Date: 16.JAN.2008 14:30:08

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. 0 + Ant. 1 / 2437 MHz




Date: 16.JAN.2008 14:33:41

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. 0 + Ant. 1 / 2462 MHz




Date: 16.JAN.2008 14:34:45

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. 0 + Ant. 1 / 2422 MHz




Date: 16.JAN.2008 14:37:07

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. 0 + Ant. 1 / 2437 MHz



Date: 16.JAN.2008 14:38:46

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. 0 + Ant. 1 / 2452 MHz



Date: 16.JAN.2008 14:40:06

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1000KHz / 1000KHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Normal Link

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Normal Link

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	266.680	43.74	-2.26	46.00	59.00	13.58	2.50	31.34	QP	100	332	HORIZONTAL
2 !	480.030	45.32	-0.68	46.00	55.50	17.62	3.13	30.93	QP	100	183	HORIZONTAL
3 Ⓢ	533.370	45.89	-0.11	46.00	54.90	18.57	3.23	30.81	QP	100	253	HORIZONTAL
4 !	641.100	42.18	-3.82	46.00	49.62	19.51	3.42	30.38	Peak	100	-4	HORIZONTAL
5 !	800.060	45.32	-0.68	46.00	51.00	20.70	3.80	30.18	QP	124	325	HORIZONTAL
6 !	933.070	40.23	-5.77	46.00	44.03	21.80	3.97	29.58	Peak	100	-4	HORIZONTAL

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	133.340	42.89	-0.61	43.50	60.60	12.22	1.70	31.63	QP	100	75	VERTICAL
2	265.710	38.77	-7.23	46.00	53.97	13.64	2.50	31.34	Peak	400	0	VERTICAL
3	479.110	39.95	-6.05	46.00	50.14	17.60	3.13	30.93	Peak	400	0	VERTICAL
4 !	533.370	43.99	-2.01	46.00	53.00	18.57	3.23	30.81	QP	100	278	VERTICAL
5 !	641.100	41.85	-4.15	46.00	49.30	19.51	3.42	30.38	Peak	400	0	VERTICAL
6 !	800.060	43.22	-2.78	46.00	48.90	20.70	3.80	30.18	QP	100	173	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS8 20MHz Ch 1 Ant. 0 + Ant. 1

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	6431.990	47.68	-6.32	54.00	41.65	34.31	6.77	35.06	AVERAGE	100	194	HORIZONTAL
2	6432.030	54.70	-19.30	74.00	48.68	34.31	6.77	35.06	PERK	100	194	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg	
1	6431.960	59.12	-14.88	74.00	53.10	34.31	6.77	35.06	PEAK	100	108	VERTICAL
2 !	6432.010	50.01	-3.99	54.00	43.99	34.31	6.77	35.06	AVERAGE	100	108	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS8 20MHz Ch 6 Ant. 0 + Ant. 1

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	6498.680	47.99	-6.01	54.00	41.97	34.30	6.73	35.01	AVERAGE	100	242	HORIZONTAL
2	6498.680	56.14	-17.86	74.00	50.12	34.30	6.73	35.01	PEAK	100	242	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg	
1	6498.540	59.10	-14.90	74.00	53.08	34.30	6.73	35.01	PEAK	100	106	VERTICAL
2 !	6498.660	50.05	-3.95	54.00	44.03	34.30	6.73	35.01	AVERAGE	100	106	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS8 20MHz Ch11 Ant. 0 + Ant. 1

Horizontal




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	6565.340	48.31	-5.69	54.00	42.15	34.40	6.80	35.04	AVERAGE	100	4	HORIZONTAL
2	6565.340	55.34	-18.66	74.00	49.18	34.40	6.80	35.04	PEAK	100	4	HORIZONTAL

Vertical




	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	6565.320	51.40	-2.60	54.00	45.24	34.40	6.80	35.04	AVERAGE	100	111	VERTICAL
2	6565.320	59.46	-14.54	74.00	53.29	34.40	6.80	35.04	PEAK	100	111	VERTICAL

Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS8 40MHz Ch 3 Ant. 0 + Ant. 1

Horizontal


	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	6458.660	47.29	-6.71	54.00	41.26	34.31	6.75	35.04	AVERAGE	100	356	HORIZONTAL
2	6458.820	56.29	-17.71	74.00	50.27	34.31	6.75	35.04	PEAK	100	356	HORIZONTAL

Vertical




	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp		Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark	Pos	Pos	Pol/Phase
			dB	dBuV/m	dBuV	dB	dB		cm	deg	
1	6458.600	59.15	-14.85	74.00	53.13	34.31	6.75	35.04	PERK	100	109 VERTICAL
2 !	6458.660	50.05	-3.95	54.00	44.03	34.31	6.75	35.04	AVERAGE	100	109 VERTICAL




Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS8 40MHz Ch 6 Ant. 0 + Ant. 1

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	6498.640	55.67	-18.33	74.00	49.64	34.30	6.73	35.01	PEAK	100	355	HORIZONTAL
2	6498.660	46.62	-7.38	54.00	40.60	34.30	6.73	35.01	AVERAGE	100	355	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	6498.620	58.47	-15.53	74.00	52.45	34.30	6.73	35.01	PEAK	100	112	VERTICAL
2 !	6498.680	50.36	-3.64	54.00	44.34	34.30	6.73	35.01	AVERAGE	100	112	VERTICAL


Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS8 40MHz Ch 9 Ant. 0 + Ant. 1

Horizontal



	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Remark	Ant	Table	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	Pol/Phase
1	6538.500	56.66	-17.34	74.00	50.56	34.37	6.76	35.03	100	243	HORIZONTAL
2	6538.670	47.26	-6.74	54.00	41.15	34.37	6.76	35.03	100	243	HORIZONTAL

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	6538.620	59.87	-14.13	74.00	53.76	34.37	6.76	35.03	PEAK	100	289	VERTICAL
2 !	6538.670	50.36	-3.64	54.00	44.25	34.37	6.76	35.03	AVERAGE	100	289	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS8 20MHz Ch 1, 6, 11 Ant. 0 + Ant. 1

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 !	2390.000	53.33	-0.67	54.00	21.01	28.17	4.15	0.00	AVERAGE	109	133	VERTICAL
2 !	2390.000	68.74	-5.26	74.00	36.41	28.17	4.15	0.00	PEAK	109	133	VERTICAL
3 @	2409.200	111.57			79.21	28.21	4.15	0.00	PEAK	109	133	VERTICAL
4 @	2419.400	101.71			69.32	28.21	4.18	0.00	AVERAGE	109	133	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	2389.600	56.85	-17.15	74.00	24.54	28.17	4.13	0.00	PEAK	103	16	VERTICAL
2	2390.000	46.80	-7.20	54.00	14.47	28.17	4.15	0.00	AVERAGE	103	16	VERTICAL
3 @	2438.400	110.48			78.02	28.29	4.18	0.00	PEAK	103	16	VERTICAL
4 @	2440.200	99.69			67.23	28.29	4.18	0.00	AVERAGE	103	16	VERTICAL
5 !	2483.500	48.19	-5.81	54.00	15.60	28.36	4.23	0.00	AVERAGE	103	16	VERTICAL
6	2484.900	60.30	-13.70	74.00	27.71	28.36	4.23	0.00	PEAK	103	16	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	2455.400	110.67			78.15	28.32	4.20	0.00	PEAK	101	0	VERTICAL
2 @	2469.400	99.61			67.06	28.32	4.23	0.00	AVERAGE	101	0	VERTICAL
3 !	2483.500	52.58	-1.42	54.00	19.99	28.36	4.23	0.00	AVERAGE	101	0	VERTICAL
4	2483.700	66.38	-7.62	74.00	33.79	28.36	4.23	0.00	PEAK	101	0	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	23°C	Humidity	62%
Test Engineer	Jacky Ho	Configurations	Draft n MCS8 40MHz Ch 3, 6, 9 Ant. 0 + Ant. 1

Channel 3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	2388.400	64.48	-9.52	74.00	30.63	28.05	5.80	0.00	PEAK	100	263	VERTICAL
2 !	2390.000	53.04	-0.96	54.00	19.15	28.05	5.84	0.00	AVERAGE	100	263	VERTICAL
3	2407.600	103.31			69.38	28.09	5.84	0.00	PEAK	100	263	VERTICAL
4	2424.000	92.62			58.62	28.13	5.87	0.00	AVERAGE	100	263	VERTICAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	2390.000	65.71	-8.29	74.00	33.39	28.17	4.15	0.00	PEAK	100	123	VERTICAL
2 !	2390.000	51.89	-2.11	54.00	19.56	28.17	4.15	0.00	AVERAGE	100	123	VERTICAL
3 @	2428.200	97.35			64.92	28.25	4.18	0.00	AVERAGE	100	123	VERTICAL
4 @	2430.600	107.39			74.96	28.25	4.18	0.00	PEAK	100	123	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	2460.400	105.79			73.27	28.32	4.20	0.00	PEAK	103	4	VERTICAL
2 @	2467.600	95.69			63.14	28.32	4.23	0.00	AVERAGE	103	4	VERTICAL
3 !	2487.100	53.09	-0.91	54.00	20.50	28.36	4.23	0.00	AVERAGE	103	4	VERTICAL
4	2489.900	66.26	-7.74	74.00	33.63	28.40	4.23	0.00	PEAK	103	4	VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration Drafft n MCS8 20MHz Ant. 0 + Ant. 1 / 2412 MHz



Date: 16.JAN.2008 14:30:42


High Band Edge Plot on Configuration Drafft n MCS8 20MHz Ant. 0 + Ant. 1 / 2462 MHz



Date: 16.JAN.2008 14:35:09


For Emission not in Restricted Band

Low Band Edge Plot on Configuration Drafft n MCS8 40MHz Ant. 0 + Ant. 1 / 2422 MHz



Date: 16.JAN.2008 14:37:41

High Band Edge Plot on Configuration Drafft n MCS8 40MHz Ant. 0 + Ant. 1 / 2452 MHz



Date: 16.JAN.2008 14:40:40

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Mar. 03, 2007	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 20, 2007	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2007	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2007	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN T400	21653	9kHz –30MHz	Mar. 27, 2007	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 14, 2007	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 14, 2008	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jun. 07, 2007	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100305	9 kHz - 40 GHz	Sep. 27, 2007	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 21, 2007	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May 04, 2007	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	NCR	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Dec. 17, 2007	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jun. 27, 2007	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jun. 27, 2007	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 27, 2007	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 04, 2007*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 03, 2007	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Jan. 14, 2008	Conducted (TH01-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2007	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2007	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Nov. 14, 2007	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 07, 2007	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

* Calibration Interval of instruments listed above is two year.

NCR means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-070110

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.

EMC & Wireless Communications Laboratory

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : January 10, 2007

P1, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.