



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Abocom Systems, Inc
Applicant Address	No.77, Yu-Yih Rd., Chu-Nan, Miao-Lih County 35059, Taiwan R.O.C.
FCC ID	MQ4WR5205
Manufacturer's company	Abocom Systems, Inc
Manufacturer Address	No.77, Yu-Yih Rd., Chu-Nan, Miao-Lih County 35059, Taiwan R.O.C.

Product Name	802.11n 2T2R Router with USB2.0 Port; 802.11n 2T2R Router
Brand Name	Abocom
Model Name	WR5205; WR5206
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Apr. 24, 2009
Final Test Date	Jun. 29, 2009
Submission Type	Original Equipment
Multiple Listing	Please refer to section 3.7



Statement

Test result included in this report is for the Draft n and 802.11b/g part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents


1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	7
3.6. Table for Testing Locations.....	8
3.7. Table for Multiple Listing.....	9
3.8. Table for Supporting Units	9
3.9. Table for Parameters of Test Software Setting	10
3.10. Test Configurations	11
4. TEST RESULT	14
4.1. AC Power Line Conducted Emissions Measurement.....	14
4.2. Maximum Conducted Output Power Measurement.....	20
4.3. Power Spectral Density Measurement	33
4.4. 6dB Spectrum Bandwidth Measurement	41
4.5. Radiated Emissions Measurement	50
4.6. Band Edge Emissions Measurement	82
4.7. Antenna Requirements	91
5. LIST OF MEASURING EQUIPMENTS	92
6. TEST LOCATION.....	94
7. TAF CERTIFICATE OF ACCREDITATION	95
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A31
APPENDIX B. TEST PHOTOS.....	B1 ~ B8
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....	C1 ~C6
APPENDIX D. CO-LOCATION REPORT.....	D1 ~ D7



1. CERTIFICATE OF COMPLIANCE

Product Name : 802.11n 2T2R Router with USB2.0 Port; 802.11n 2T2R Router
Brand Name : Abocom
Model Name : WR5205; WR5206
Applicant : Abocom Systems, Inc
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Apr. 24, 2009 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Jordan Hsiao 2009.7.7'.

Jordan Hsiao

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	4.52 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	5.98 dB
4.3	15.247(e)	Power Spectral Density	Complies	12.32 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.04 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.05 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Draft n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	see the below table for draft n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for Draft n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS0 (20MHz): 17.72 MHz ; MCS0 (40MHz): 34.72 MHz
Conducted Output Power	MCS0 (20MHz): 24.02 dBm ; MCS0 (40MHz): 19.03 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

802.11b/g

Items	Description
Product Type	802.11b/g :WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 14.48 MHz ; 11g: 16.40 MHz
Conducted Output Power	11b: 19.17 dBm ; 11g: 20.83 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)		Two (TX)	
	20 MHz	40 MHz	20 MHz	40 MHz
Band width Mode				
802.11b	V	X	X	X
802.11g	V	X	X	X
Draft n	X	X	V	V

Draft n spec

MCS Index	Nss	Modulation	R	NBPCS	NCBPS		NDBPS		Datarate(Mbps)			
					20MHz	40MHz	20MHz	40MHz	800nsGI		400nsGI	
									20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0	14.444	30
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0	28.889	60
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0	43.333	90
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0	57.778	120
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0	86.667	180
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0	115.556	240
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0	130.000	270
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0	144.444	300

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPCS	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

3.2. Accessories

Power	Brand	Model	Rating	Remark
Adapter 1	DVE	DSA-20P-10 US 120180	Input: 100-240VAC, 50/60Hz, 0.7A Output: 12VDC, 1.5A	Collocated with EUT 1
Adapter 2	SPEC LIN	SW1201500-W01	Input: 100-240VAC, 50/60Hz, 0.5A Output: 12VDC, 1.5A	Collocated with EUT 1
Adapter 3	DVE	DSA-12G-12 FUS 120120	Input: 100-240VAC, 50/60Hz, 0.7A Output: 12VDC, 1.5A	Collocated with EUT 2

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Cortec	R-AN2400-5701RS	Dipole Antenna	Reversed-SMA	2.00
2	Cortec	R-AN2400-5701RS	Dipole Antenna	Reversed-SMA	2.00


Note: The EUT has two antennas.

For 802.11b/g mode:

Only Ant. A can be use as transmit and receive antenna.

For Draft n mode:

Ant. A and Ant. B can both transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are two bandwidth systems for draft n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Peak Conducted Output Power	MCS0/20MHz	6.5 Mbps	1/6/11	A / B / A+B
	MCS0/40MHz	13.5 Mbps	3/6/9	A / B / A+B
	11b/BPSK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	A
Power Spectral Density 6dB Spectrum Bandwidth	MCS0/20MHz	6.5 Mbps	1/6/11	A+B
	MCS0/40MHz	13.5 Mbps	3/6/9	A+B
	11b/BPSK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	A
Radiated Emissions 9kHz~1GHz	CTX	-	-	-
Radiated Emissions 1GHz~10 th Harmonic	MCS0/20MHz	6.5 Mbps	1/6/11	A+B
	MCS0/40MHz	13.5 Mbps	3/6/9	A+B
	11b/BPSK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	A
Band Edge Emissions	MCS0/20MHz	6.5 Mbps	1/11	A+B
	MCS0/40MHz	13.5 Mbps	3/9	A+B
	11b/BPSK	1 Mbps	1/11	A
	11g/BPSK	6 Mbps	1/11	A

Note :

All the test modes were illustrated as below:

EUT 1 (Model Name: WR5205) with WWAN

EUT 1 would be collocated with Adapter 1 / Adapter 2 when it sold in market.

EUT 2 (Model Name: WR5206) without WWAN

EUT 2 would be collocated with Adapter 3 when it sold in market.

<For EUT 1>:

Test Mode 1: EUT 1 switch on **LAN+WLAN+WAN** + Adapter 1

Test Mode 2: EUT 1 switch on **LAN+WLAN+WAN** + Adapter 2

Test Mode 3: EUT 1 switch on **LAN+WLAN+WWAN** + Adapter 1

Test Mode 4: EUT 1 switch on **LAN+WLAN+WWAN** + Adapter 2

<For Conducted Emissions Test>:

Due to Mode 4 generated the worst test result, so it was recorded in this report.

<For Radiated Emissions Test Below 1GHz>:

Test Mode 1: EUT 1 + Adapter 1

Test Mode 2: EUT 1 + Adapter 2

Due to Mode 2 generated the worst test result, so it was recorded in this report.

<For MPE and Co-location Test>:

The EUT could be applied with three express 3G Dongle; therefore Maximum Permissible Exposure (please refer to Appendix C) and Co-location (please refer to Appendix D) tests are added for simultaneously transmit between wireless LAN and 3G card function.

Interface	Brand	Model	FCC ID
3G USB Dongle 1	ZTE	MF626	Q78-ZTEMF626
3G USB Dongle 2	CHT	E169	QISE169
3G USB Dongle 3	CHT	E220	QISE220

After Radiated Emissions Test Below 1GHz test, the Adapter 2 generated the worst test result, so Adapter 2 was selected for Co-location Test.

Test Mode 1: EUT 1 switch on **LAN+WLAN+WWAN** + Adapter 2 with 3G USB Dongle 1

Test Mode 2: EUT 1 switch on **LAN+WLAN+WWAN** + Adapter 2 with 3G USB Dongle 2

Test Mode 3: EUT 1 switch on **LAN+WLAN+WWAN** + Adapter 2 with 3G USB Dongle 3

<For EUT 2>:

<For Conducted Emissions Test>:

Test Mode 1: EUT 2 switch on **LAN+WLAN+WAN** + Adapter 3

<For Radiated Emissions Test Below 1GHz>:

Test Mode 1: EUT 2 + Adapter 3

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	480872	IC 4088	-
CO04-HY	Conduction	Hwa Ya	480872	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Multiple Listing

The product Name/Model names are listed in the following table.

Model Name	Product Name	Description	Accessories
WR5205	802.11n 2T2R Router with USB2.0 Port	WR5205 with USB Port, it has WWAN.	1. Adapter 1: Brand Name: DVE Model No.: DSA-20P-10 US 120180 2. Adapter 2: Brand Name: SPEC LIN Model No.: SW1201500-W01
WR5206	802.11n 2T2R Router	WR5206 without USB Port, it has not WWAN.	1. Adapter 3: Brand Name: DVE Model No.: DSA-12G-12 FUS 120120

Note: There are two type of EUT, but their internal circuit boards are exactly identical.

3.8. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D520	E2KWM3945ABG
Notebook	DELL	PP25L	E2K4965AGNM
Notebook	DELL	PP25L	E2K4965AGNM
Notebook	ASUS	EEEEPC8G-W001	PPD-AR5BXB63
CMU200	ROHDE&SCHWARZ	108087	N/A
3G USB Dongle	ZTE	MF626	Q78-ZTEMF626
3G USB Dongle	CHT	E169	QISE169
3G USB Dongle	CHT	E220	QISE220

3.9. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of Draft n MCS0 20MHz

Test Software Version	QA_RT3052 V1.0.0.2		
Frequency	2412 MHz	2437 MHz	2462 MHz
Draft n MCS0 20MHz Ant. A	18	1E	11
Draft n MCS0 20MHz Ant. B	1A	1F	13

Power Parameters of Draft n MCS0 40MHz

Test Software Version	QA_RT3052 V1.0.0.2		
Frequency	2422 MHz	2437 MHz	2452 MHz
Draft n MCS0 40MHz Ant. A	0F	13	0F
Draft n MCS0 40MHz Ant. B	11	14	11

Power Parameters of IEEE 802.11b/g

Test Software Version	QA_RT3052 V1.0.0.2		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b Ant. A	13	17	17
IEEE 802.11g Ant. A	18	1F	1A

During the test, "Ping.exe" under WIN XP was executed to link with the remote workstation to receive and transmit signal by LAN and WLAN

At the same time, "QA_RT3052 V1.0.0.2" was executed the test program to control the EUT continuously transmit RF signal.


3.10. Test Configurations

3.10.1. Radiation Emissions Test Configuration

<For EUT 1>


Test Configuration: Wi-fi

Test Mode: Mode 2



Test Configuration: Co-location


Test Mode: Mode 1~Mode 3



<For EUT 2>

Test Configuration: Wi-fi


Test Mode: Mode 1



3.10.2. AC Power Line Conduction Emissions Test Configuration


<For EUT 1 >

Test Mode: Mode 4



<For EUT 2 >

Test Mode: Mode 1



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation

There is no deviation with the original standard.


4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

4.1.7. Results of AC Power Line Conducted Emissions Measurement


<For EUT 1>:

Temperature	24°C	Humidity	60%
Test Engineer	Howar Sung	Phase	Line
Configuration	Normal Link / Mode 4		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.17354	49.05	-15.74	64.79	48.79	0.06	0.20	QP
2	0.17354	40.54	-14.25	54.79	40.28	0.06	0.20	AVERAGE
3	0.44208	36.94	-20.08	57.02	36.71	0.03	0.20	QP
4	0.44208	29.52	-17.50	47.02	29.29	0.03	0.20	AVERAGE
5	0.69725	39.48	-16.52	56.00	39.25	0.03	0.20	QP
6	0.69725	34.34	-11.66	46.00	34.11	0.03	0.20	AVERAGE
7	0.86185	35.80	-20.20	56.00	35.57	0.03	0.20	QP
8	0.86185	24.04	-21.96	46.00	23.81	0.03	0.20	AVERAGE
9	3.681	32.47	-23.53	56.00	32.08	0.09	0.30	QP
10	3.681	17.76	-28.24	46.00	17.37	0.09	0.30	AVERAGE
11	9.352	29.10	-30.90	60.00	28.47	0.33	0.30	QP
12	9.352	17.94	-32.06	50.00	17.31	0.33	0.30	AVERAGE
13	24.068	28.85	-31.15	60.00	27.28	1.07	0.50	QP
14	24.068	27.76	-22.24	50.00	26.19	1.07	0.50	AVERAGE

Temperature	24°C	Humidity	60%
Test Engineer	Howar Sung	Phase	Neutral
Configuration	Normal Link / Mode 4		




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.17215	48.64	-16.21	64.86	48.35	0.09	0.20	QP
2	0.17215	40.13	-14.72	54.86	39.84	0.09	0.20	AVERAGE
3	0.43687	41.21	-15.91	57.12	40.94	0.07	0.20	QP
4 @	0.43687	37.93	-9.19	47.12	37.66	0.07	0.20	AVERAGE
5	0.60431	39.66	-16.34	56.00	39.39	0.07	0.20	QP
6	0.60431	35.13	-10.87	46.00	34.86	0.07	0.20	AVERAGE
7	1.111	30.41	-25.59	56.00	30.16	0.07	0.17	QP
8	1.111	18.45	-27.55	46.00	18.20	0.07	0.17	AVERAGE
9	2.334	31.79	-24.21	56.00	31.49	0.10	0.20	QP
10	2.334	17.89	-28.11	46.00	17.59	0.10	0.20	AVERAGE
11	5.194	27.40	-32.60	60.00	26.89	0.21	0.30	QP
12	5.194	20.77	-29.23	50.00	20.26	0.21	0.30	AVERAGE
13	11.963	30.11	-29.89	60.00	29.24	0.47	0.40	QP
14	11.963	26.03	-23.97	50.00	25.16	0.47	0.40	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.


<For EUT 2>:

Temperature	24°C	Humidity	60%
Test Engineer	Howar Sung	Phase	Line
Configuration	Normal Link / Mode 1		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15240	44.58	-21.28	65.87	44.31	0.07	0.20	QP
2	0.15240	30.51	-25.35	55.87	30.24	0.07	0.20	AVERAGE
3	0.28029	43.42	-17.39	60.81	43.18	0.04	0.20	QP
4	0.28029	30.85	-19.96	50.81	30.61	0.04	0.20	AVERAGE
5	2.650	16.26	-29.74	46.00	15.99	0.07	0.20	AVERAGE
6	2.650	28.59	-27.41	56.00	28.32	0.07	0.20	QP
7	4.672	23.05	-22.95	46.00	22.61	0.14	0.30	AVERAGE
8	4.672	34.36	-21.64	56.00	33.92	0.14	0.30	QP
9	11.437	31.14	-18.86	50.00	30.32	0.42	0.40	AVERAGE
10	11.437	40.08	-19.92	60.00	39.26	0.42	0.40	QP
11	24.066	35.83	-24.17	60.00	34.26	1.07	0.50	QP
12	24.066	30.80	-19.20	50.00	29.23	1.07	0.50	AVERAGE

Temperature	24°C	Humidity	56%
Test Engineer	Howar Sung	Phase	Neutral
Configuration	Normal Link / Mode 1		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.20075	41.06	-22.52	63.58	40.78	0.08	0.20	QP
2	0.20075	37.10	-16.48	53.58	36.82	0.08	0.20	AVERAGE
3	0.27881	49.47	-11.39	60.85	49.19	0.08	0.20	QP
4	0.27881	46.34	-4.52	50.85	46.06	0.08	0.20	AVERAGE
5	3.720	28.37	-17.63	46.00	27.94	0.13	0.30	AVERAGE
6	3.720	37.27	-18.73	56.00	36.84	0.13	0.30	QP
7	5.221	30.27	-19.73	50.00	29.76	0.21	0.30	AVERAGE
8	5.221	39.49	-20.51	60.00	38.98	0.21	0.30	QP
9	11.498	33.34	-26.66	60.00	32.49	0.45	0.40	QP
10	11.498	25.06	-24.94	50.00	24.21	0.45	0.40	AVERAGE
11	24.065	38.82	-21.18	60.00	37.22	1.10	0.50	QP
12	24.065	34.73	-15.27	50.00	33.13	1.10	0.50	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1MHz
VB	3MHz
Detector	RMS
Trace	Max Hold
Sweep Time	Auto

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005.
3. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	22°C	Humidity	58%
Test Engineer	Jacky Ho	Configurations	Draft n
Test Date	May. 26, 2009		

Configuration Draft n MCS0 20MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	19.04	30.00	Complies
6	2437 MHz	21.18	30.00	Complies
11	2462 MHz	15.04	30.00	Complies

Configuration Draft n MCS0 20MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	19.05	30.00	Complies
6	2437 MHz	20.83	30.00	Complies
11	2462 MHz	15.31	30.00	Complies

Configuration Draft n MCS0 20MHz Ant. A + Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	22.06	30.00	Complies
6	2437 MHz	24.02	30.00	Complies
11	2462 MHz	18.19	30.00	Complies

Configuration Draft n MCS0 40MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	13.96	30.00	Complies
6	2437 MHz	15.82	30.00	Complies
9	2452 MHz	13.60	30.00	Complies

Configuration Draft n MCS0 40MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	14.33	30.00	Complies
6	2437 MHz	16.22	30.00	Complies
9	2452 MHz	14.10	30.00	Complies

Configuration Draft n MCS0 40MHz Ant. A + Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	17.16	30.00	Complies
6	2437 MHz	19.03	30.00	Complies
9	2452 MHz	16.87	30.00	Complies

Temperature	22°C	Humidity	58%
Test Engineer	Jacky Ho	Configurations	802.11b/g
Test Date	Jun. 08, 2009 ~ Jun. 10, 2009		


Configuration IEEE 802.11b Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	17.65	30.00	Complies
6	2437 MHz	19.17	30.00	Complies
11	2462 MHz	18.66	30.00	Complies

Configuration IEEE 802.11g Ant. A


Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	18.10	30.00	Complies
6	2437 MHz	20.83	30.00	Complies
11	2462 MHz	18.27	30.00	Complies

Conducted Output Power Plot on Configuration Draft n MCS0 40MHz Ant. A / 2452 MHz




Date: 26.MAY.2009 21:03:23

Conducted Output Power Plot on Configuration Draft n MCS0 40MHz Ant. B / 2422 MHz




Date: 26.MAY.2009 21:07:21

Conducted Output Power Plot on Configuration IEEE 802.11b Ant. A / 2412 MHz




Date: 10.JUN.2009 11:16:46

Conducted Output Power Plot on Configuration IEEE 802.11b Ant. A / 2437 MHz




Date: 10.JUN.2009 11:03:33

Conducted Output Power Plot on Configuration IEEE 802.11g Ant. A / 2437 MHz



Date: 8.JUN.2009 18:30:55

Conducted Output Power Plot on Configuration IEEE 802.11g Ant. A / 2462 MHz



Date: 8.JUN.2009 18:33:51

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	30 kHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	10s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 30kHz and the sweep time to 10s and record the maximum peak value.
5. Measuring multiple antennas, the connector is required to link with spectrum analyser through a combiner.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	22°C	Humidity	58%
Test Engineer	Jacky Ho	Configurations	Draft n
Test Date	Jun. 08, 2009		

Configuration Draft n MCS0 20MHz Ant. A + Ant. B

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-7.01	8.00	Complies
6	2437 MHz	-4.32	8.00	Complies
11	2462 MHz	-11.24	8.00	Complies

Configuration Draft n MCS0 40MHz Ant. A + Ant. B

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-12.53	8.00	Complies
6	2437 MHz	-11.36	8.00	Complies
9	2452 MHz	-13.46	8.00	Complies

Temperature	22°C	Humidity	58%
Test Engineer	Jacky Ho	Configurations	802.11b/g
Test Date	Jun. 08, 2009		


Configuration IEEE 802.11b Ant. A

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-12.41	8.00	Complies
6	2437 MHz	-10.29	8.00	Complies
11	2462 MHz	-10.84	8.00	Complies

Configuration IEEE 802.11g Ant. A


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-12.32	8.00	Complies
6	2437 MHz	-9.85	8.00	Complies
11	2462 MHz	-12.39	8.00	Complies

Power Density Plot on Configuration Drafft n MCS0 20MHz Ant. A + Ant. B / 2412 MHz




Date: 8.JUN.2009 19:02:10

Power Density Plot on Configuration Drafft n MCS0 20MHz Ant. A + Ant. B / 2437 MHz




Date: 8.JUN.2009 19:18:33

Power Density Plot on Configuration Drafft n MCS0 20MHz Ant. A + Ant. B / 2462 MHz




Date: 8.JUN.2009 19:08:45

Power Density Plot on Configuration Drafft n MCS0 40MHz Ant. A + Ant. B / 2422 MHz




Date: 8.JUN.2009 19:22:10

Power Density Plot on Configuration Drafft n MCS0 40MHz Ant. A + Ant. B / 2437 MHz




Date: 8.JUN.2009 19:27:41

Power Density Plot on Configuration Drafft n MCS0 40MHz Ant. A + Ant. B / 2452 MHz




Date: 8.JUN.2009 19:30:46

Power Density Plot on Configuration IEEE 802.11b Ant. A / 2412 MHz




Date: 8.JUN.2009 18:47:27

Power Density Plot on Configuration IEEE 802.11b Ant. A / 2437 MHz




Date: 8.JUN.2009 18:49:55

Power Density Plot on Configuration IEEE 802.11b Ant. A / 2462 MHz




Date: 8.JUN.2009 18:52:39

Power Density Plot on Configuration IEEE 802.11g Ant. A / 2412 MHz




Date: 8.JUN.2009 18:38:42

Power Density Plot on Configuration IEEE 802.11g Ant. A / 2437 MHz



Date: 8.JUN.2009 18:41:39

Power Density Plot on Configuration IEEE 802.11g Ant. A / 2462 MHz



Date: 8.JUN.2009 18:44:28

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.
4. Measuring multiple antennas, the connector is required to link with spectrum analyzer through a combiner.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	22°C	Humidity	58%
Test Engineer	Jacky Ho	Configurations	Draft n
Test Date	Jun. 08, 2009		

Configuration Draft n MCS0 20MHz Ant. A + Ant. B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.60	17.72	500	Complies
6	2437 MHz	17.56	17.68	500	Complies
11	2462 MHz	17.68	17.72	500	Complies

Configuration Draft n MCS0 40MHz Ant. A + Ant. B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	32.80	34.56	500	Complies
6	2437 MHz	33.44	34.72	500	Complies
9	2452 MHz	34.48	36.24	500	Complies

Temperature	22°C	Humidity	58%
Test Engineer	Jacky Ho	Configurations	802.11b/g
Test Date	Jun. 08, 2009		


Configuration IEEE 802.11b Ant. A

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	11.08	14.36	500	Complies
6	2437 MHz	11.12	14.48	500	Complies
11	2462 MHz	11.12	14.44	500	Complies

Configuration IEEE 802.11g Ant. A


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.40	16.40	500	Complies
6	2437 MHz	16.40	16.40	500	Complies
11	2462 MHz	16.40	16.40	500	Complies

6 dB Bandwidth Plot on Configuration Draft n MCS0 20MHz Ant. A + Ant. B / 2412 MHz




Date: 8.JUN.2009 19:00:43

6 dB Bandwidth Plot on Configuration Draft n MCS0 20MHz Ant. A + Ant. B / 2437 MHz




Date: 8.JUN.2009 19:17:04

6 dB Bandwidth Plot on Configuration Draft n MCS0 20MHz Ant. A + Ant. B / 2462 MHz




Date: 8.JUN.2009 19:07:17

6 dB Bandwidth Plot on Configuration Draft n MCS0 40MHz Ant. A + Ant. B / 2422 MHz




Date: 8.JUN.2009 19:33:14

6 dB Bandwidth Plot on Configuration Draft n MCS0 40MHz Ant. A + Ant. B / 2437 MHz




Date: 8.JUN.2009 19:40:26

6 dB Bandwidth Plot on Configuration Draft n MCS0 40MHz Ant. A + Ant. B / 2452 MHz




Date: 8.JUN.2009 19:29:18

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. A / 2412 MHz




Date: 8.JUN.2009 18:46:00

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. A / 2437 MHz




Date: 8.JUN.2009 18:48:27

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. A / 2462 MHz




Date: 8.JUN.2009 18:51:12

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. A / 2412 MHz




Date: 8.JUN.2009 18:37:14

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. A / 2437 MHz



Date: 8.JUN.2009 18:40:11

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. A / 2462 MHz



Date: 8.JUN.2009 18:43:00

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	CTX

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);


Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)

<For EUT 1 >


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	CTX / Mode 2

Horizontal



	Over	Limit	Read	Antenna	Cable	Preamp		Ant	Table			
Freq	Level	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos			
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg			
1 @	249.220	41.98	-4.02	46.00	54.39	12.70	1.90	27.00	Peak	100	0	HORIZONTAL
2 @	382.110	45.96	-0.04	46.00	55.58	15.59	2.26	27.47	QP	100	204	HORIZONTAL
3	444.190	37.10	-8.90	46.00	45.60	16.75	2.57	27.82	Peak	100	0	HORIZONTAL
4	498.510	37.51	-8.49	46.00	45.30	17.60	2.70	28.09	Peak	100	0	HORIZONTAL
5	641.100	39.43	-6.57	46.00	45.44	18.90	3.15	28.06	Peak	100	0	HORIZONTAL
6	897.180	37.51	-8.49	46.00	40.82	20.51	3.59	27.41	Peak	100	0	HORIZONTAL
7	960.230	41.08	-12.92	54.00	43.63	20.99	3.62	27.16	Peak	100	0	HORIZONTAL

Vertical



	Over	Limit	Read	Antenna	Cable	Preamp		Ant	Table
1 @	2 !	3 @	4 @	5	6	7 @	Remark	Pos	Pos
MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB	cm	deg
126.030	40.13	-3.37	43.50	54.12	12.22	1.26	27.47 Peak	400	0
184.230	39.08	-4.42	43.50	52.32	12.32	1.62	27.18 Peak	400	0
250.020	45.60	-0.40	46.00	58.00	12.70	1.90	27.00 QP	100	231
382.110	43.56	-2.44	46.00	53.18	15.59	2.26	27.47 Peak	400	0
498.510	38.75	-7.25	46.00	46.54	17.60	2.70	28.09 Peak	400	0
641.100	37.56	-8.44	46.00	43.57	18.90	3.15	28.06 Peak	400	0
897.180	42.41	-3.59	46.00	45.72	20.51	3.59	27.41 Peak	400	0

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<For EUT 2>


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	CTX / Mode 1

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg	
1	126.030	29.78	-13.72	43.50	43.77	12.22	1.26	27.47	Peak	100	0	HORIZONTAL
2	249.220	36.14	-9.86	46.00	48.55	12.70	1.90	27.00	Peak	100	0	HORIZONTAL
3	382.110	38.39	-7.61	46.00	48.01	15.59	2.26	27.47	Peak	100	0	HORIZONTAL
4	510.150	37.00	-9.00	46.00	44.64	17.74	2.72	28.10	Peak	100	0	HORIZONTAL
5	576.110	39.64	-6.36	46.00	46.40	18.49	2.85	28.10	Peak	100	0	HORIZONTAL
6	641.100	34.84	-11.16	46.00	40.85	18.90	3.15	28.06	Peak	100	0	HORIZONTAL
7	897.180	35.86	-10.14	46.00	39.17	20.51	3.59	27.41	Peak	100	0	HORIZONTAL

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg	
1	126.030	35.57	-7.93	43.50	49.56	12.22	1.26	27.47	Peak	400	0	VERTICAL
2 !	159.980	37.55	-5.95	43.50	51.32	12.03	1.50	27.30	Peak	400	0	VERTICAL
3 @	194.900	39.42	-4.08	43.50	54.80	10.07	1.67	27.13	Peak	100	233	VERTICAL
4 !	382.110	41.31	-4.69	46.00	50.93	15.59	2.26	27.47	Peak	400	0	VERTICAL
5	498.510	36.65	-9.35	46.00	44.44	17.60	2.70	28.09	Peak	400	0	VERTICAL
6	641.100	38.69	-7.31	46.00	44.70	18.90	3.15	28.06	Peak	400	0	VERTICAL
7	897.180	36.71	-9.29	46.00	40.02	20.51	3.59	27.41	Peak	400	0	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	Draft n MCS0 20MHz Ch 1 / Ant. A + Ant. B

Horizontal



	Freq	Level	Limit	Over	Read		Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	Pos	Pos
1	4824.530	32.85	54.00	-21.15	30.87	1.98	AVERAGE	HORIZONTAL 0 100
2	4825.450	41.96	74.00	-32.04	39.98	1.98	PEAK	HORIZONTAL 0 100


Vertical



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	Level	Factor	Remark	Pos	Pos
					dB			deg	cm
1	4823.060	46.19	74.00	-27.81	44.21	1.98	PEAK	120	169
2	4826.500	39.11	54.00	-14.89	37.13	1.98	AVERAGE	120	169


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	Draft n MCS0 20MHz Ch 6 / Ant. A + Ant. B

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			deg	cm
1	4872.400	38.36	54.00	-15.64	36.26	2.10	AVERAGE	HORIZONTAL	138	155
2	4873.210	49.90	74.00	-24.10	47.80	2.10	PEAK	HORIZONTAL	138	155


Vertical



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	Line	Limit	Level	Factor	Remark	Pos	Pos
			dBuV/m	dB	dBuV	dB		deg	cm
1	4873.950	46.27	54.00	-7.73	44.17	2.10	AVERAGE	355	128
2	4874.920	64.74	74.00	-9.26	62.64	2.10	PEAK	355	128


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	Draft n MCS0 20MHz Ch11 / Ant. A + Ant. B

Horizontal



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	Remark	Pos	Pos
								deg	cm
1	4922.110	42.93	74.00	-31.07	40.71	2.22	PEAK	244	143
2	4923.530	33.93	54.00	-20.07	31.71	2.22	AVERAGE	244	143


Vertical



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	Line	Limit	Level	Factor	Remark	Pos	Pos
			dBuV/m	dB	dBuV	dB		deg	cm
1	4923.200	53.91	74.00	-20.09	51.69	2.22	PEAK	123	100
2	4923.570	39.32	54.00	-14.68	37.10	2.22	AVERAGE	123	100


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	Draft n MCS0 40MHz Ch 3 / Ant. A + Ant. B

Horizontal



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBUV/m	dBUV/m	dB	dBUV	dB	Remark	Pos	Pos
								deg	cm
1	4843.120	33.10	54.00	-20.90	31.08	2.02	AVERAGE	360	99
2	4845.050	46.23	74.00	-27.77	44.20	2.02	PEAK	360	99


Vertical



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	Remark	Pos	Pos
								deg	cm
1	4844.410	36.91	54.00	-17.09	34.89	2.02	AVERAGE	34	100
2	4844.810	49.50	74.00	-24.50	47.47	2.02	PEAK	34	100


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	Draft n MCS0 40MHz Ch 6 / Ant. A + Ant. B

Horizontal



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	Remark	Pos	Pos
								deg	cm
1	4871.830	42.05	74.00	-31.95	39.95	2.10	PEAK	138	154
2	4874.010	33.48	54.00	-20.52	31.38	2.10	AVERAGE	138	154


Vertical



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	Remark	Pos	Pos
								deg	cm
1	4874.070	38.10	54.00	-15.90	36.00	2.10	AVERAGE	355	130
2	4874.320	50.55	74.00	-23.45	48.45	2.10	PEAK	355	130


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	Draft n MCS0 40MHz Ch 9 / Ant. A + Ant. B

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			deg	cm
1	4901.930	41.21	74.00	-32.79	39.07	2.14	PEAK	HORIZONTAL	360	100
2	4904.310	32.96	54.00	-21.04	30.81	2.14	AVERAGE	HORIZONTAL	360	100

Vertical



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	Level	Factor	Remark	Pos	Pos
					dB			deg	cm
1	4924.010	45.90	54.00	-8.10	43.68	2.22	AVERAGE	189	114
2	4924.080	51.06	74.00	-22.94	48.84	2.22	PEAK	189	114

Note:


The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	802.11b CH 1 / Ant. A

Horizontal



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	Remark	Pos	Pos
								deg	cm
1	4823.970	50.33	74.00	-23.67	48.35	1.98	PEAK	HORIZONTAL	178
2	4824.010	45.24	54.00	-8.76	43.26	1.98	AVERAGE	HORIZONTAL	178


Vertical



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	Level	Factor	Remark	Pos	Pos
					dBuV	dB		deg	cm
1	4823.980	53.65	74.00	-20.35	51.67	1.98	PEAK	106	149
2 !	4824.010	50.42	54.00	-3.58	48.44	1.98	AVERAGE	106	149


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	802.11b CH 6 / Ant. A

Horizontal




	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	Remark	Pos	Pos
								deg	cm
1	4873.968	47.23	74.00	-26.77	45.13	2.10	PEAK	327	133
2	4874.008	37.17	54.00	-16.83	35.07	2.10	AVERAGE	327	133
3	7308.240	50.73	54.00	-3.27	45.00	5.73	AVERAGE	151	100
4	7310.040	56.27	74.00	-17.73	50.54	5.73	PEAK	151	100

Vertical




	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	Limit	Level	Factor	Remark	Pos	Pos
				dB	dBuV	dB		deg	cm
1	4874.012	44.12	54.00	-9.88	42.02	2.10	AVERAGE	299	100
2	4874.116	49.28	74.00	-24.72	47.18	2.10	PEAK	299	100
3	7307.480	58.75	74.00	-15.25	53.02	5.73	PEAK	214	100
4	7308.280	53.80	54.00	-0.20	48.07	5.73	AVERAGE	214	100

Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	802.11b CH 11 / Ant. A

Horizontal


	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	Remark	Pos	Pos
								deg	cm
1	4924.048	37.30	54.00	-16.70	35.08	2.22	AVERAGE	HORIZONTAL	183 100
2	4924.084	47.34	74.00	-26.66	45.12	2.22	PEAK	HORIZONTAL	183 100
3	7385.160	56.37	74.00	-17.63	50.49	5.88	PEAK	HORIZONTAL	288 100
4 !	7385.240	50.51	54.00	-3.49	44.64	5.88	AVERAGE	HORIZONTAL	288 100


Vertical



	Freq	Level	Limit	Over	Read	Factor	Remark	Pol/Phase	Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			Pos	Pos
									deg	cm
1	4923.912	51.54	74.00	-22.46	49.32	2.22	PEAK	VERTICAL	142	100
2	4924.012	46.61	54.00	-7.39	44.39	2.22	AVERAGE	VERTICAL	142	100
3 !	7385.260	53.38	54.00	-0.62	47.50	5.88	AVERAGE	VERTICAL	214	104
4	7386.960	58.26	74.00	-15.74	52.39	5.88	PEAK	VERTICAL	214	104


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	802.11g CH 1 / Ant. A

Horizontal



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	Remark	Pos	Pos
								deg	cm
1	4826.600	48.30	74.00	-25.70	46.33	1.98	PEAK	0	100
2	4826.670	32.78	54.00	-21.22	30.80	1.98	AVERAGE	0	100


Vertical



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	Level	Factor	Remark	Pos	Pos
					dB			deg	cm
1	4821.410	37.54	54.00	-16.46	35.56	1.98	AVERAGE	154	107
2	4823.350	52.13	74.00	-21.87	50.15	1.98	PEAK	154	107


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	802.11g CH 6 / Ant. A

Horizontal



	Freq	Level	Limit	Over	Read		Pol/Phase	Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		Pos	Pos
								deg	cm
1	4876.180	50.85	74.00	-23.15	48.75	2.10	PEAK	HORIZONTAL	6 102
2	4877.680	35.30	54.00	-18.70	33.21	2.10	AVERAGE	HORIZONTAL	6 102


Vertical



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	Line	Limit	Level	Factor	Remark	Pos	Pos
			dBuV/m	dB	dBuV	dB		deg	cm
1	4875.720	41.78	54.00	-12.22	39.68	2.10	AVERAGE	319	103
2	4876.280	59.62	74.00	-14.38	57.52	2.10	PEAK	319	103


Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	802.11g CH 11 / Ant. A

Horizontal



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBUV/m	dBUV/m	dB	dBUV	dB	Remark	Pos	Pos
							Pol/Phase	deg	cm
1	4925.230	46.13	74.00	-27.87	43.91	2.22	PEAK	360	100
2	4926.370	33.15	54.00	-20.85	30.93	2.22	AVERAGE	360	100

Vertical



	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	Remark	Pos	Pos
								deg	cm
1	4922.020	35.67	54.00	-18.33	33.45	2.22	AVERAGE	319	100
2	4922.230	47.66	74.00	-26.34	45.45	2.22	PEAK	319	100

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	Draft n MCS0 20MHz Ch 1, 6, 11 / Ant. A + Ant. B
Test Date	May 26, 2009		

Channel 1

	Freq	Level	Limit	Over	Read	Factor	Remark	Pol/Phase	Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			deg	cm
1 !	2390.000	53.12	54.00	-0.88	22.19	30.93	AVERAGE	VERTICAL	42	100
2 !	2390.000	72.54	74.00	-1.46	41.61	30.93	PEAK	VERTICAL	42	100
3	2415.200	114.84			83.86	30.98	PEAK	VERTICAL	42	100
4	2415.200	105.08			74.10	30.98	AVERAGE	VERTICAL	42	100

Item 3, 4 are the fundamental frequency at 2412 MHz

Channel 6

	Freq	Level	Limit	Over	Read	Factor	Remark	Pol/Phase	Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			deg	cm
1	2389.400	59.63	74.00	-14.37	28.70	30.93	PEAK	VERTICAL	59	100
2	2390.000	47.65	54.00	-6.35	16.72	30.93	AVERAGE	VERTICAL	59	100
3	2438.400	118.80			87.73	31.07	PEAK	VERTICAL	59	100
4	2438.600	109.71			78.63	31.07	AVERAGE	VERTICAL	59	100
5 !	2483.500	50.69	54.00	-3.31	19.51	31.18	AVERAGE	VERTICAL	59	100
6	2484.300	63.45	74.00	-10.55	32.27	31.18	PEAK	VERTICAL	59	100

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Limit	Over	Read	Factor	Remark	Pol/Phase	Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			deg	cm
1	2463.800	114.29			83.17	31.13	PEAK	VERTICAL	60	100
2	2463.800	104.83			73.71	31.13	AVERAGE	VERTICAL	60	100
3 !	2483.500	53.79	54.00	-0.21	22.61	31.18	AVERAGE	VERTICAL	60	100
4 !	2483.500	72.51	74.00	-1.49	41.33	31.18	PEAK	VERTICAL	60	100

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	Draft n MCS0 40MHz Ch 3, 6, 9 / Ant. A + Ant. B
Test Date	May 26, 2009		

Channel 3

	Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			deg	cm
1	2382.000	65.59	74.00	-8.41	34.69	30.89	PEAK	VERTICAL	60	100
2 !	2390.000	52.10	54.00	-1.90	21.17	30.93	AVERAGE	VERTICAL	60	100
3	2437.200	109.31			78.24	31.07	PEAK	VERTICAL	60	100
4	2437.200	100.14			69.07	31.07	AVERAGE	VERTICAL	60	100

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			deg	cm
1 !	2359.600	51.08	54.00	-2.92	20.24	30.84	AVERAGE	VERTICAL	60	100
2	2381.600	65.65	74.00	-8.35	34.76	30.89	PEAK	VERTICAL	60	100
3	2438.600	103.58			72.51	31.07	AVERAGE	VERTICAL	60	100
4	2438.600	112.75			81.68	31.07	PEAK	VERTICAL	60	100
5 !	2483.500	51.33	54.00	-2.67	20.15	31.18	AVERAGE	VERTICAL	60	100
6	2483.500	66.06	74.00	-7.94	34.88	31.18	PEAK	VERTICAL	60	100

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

	Freq	Level	Limit Line	Over Limit	Read Level	Factor	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			deg	cm
1	2457.200	97.90			66.77	31.13	AVERAGE	VERTICAL	283	100
2	2457.600	107.14			76.01	31.13	PEAK	VERTICAL	283	100
3	2490.300	65.40	74.00	-8.60	34.17	31.22	PEAK	VERTICAL	283	100
4 !	2491.100	52.03	54.00	-1.97	20.80	31.22	AVERAGE	VERTICAL	283	100

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	802.11b CH 1, 6, 11 / Ant. A
Test Date	May 26, 2009		

Channel 1

	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	Line	Limit	Level	Factor	Remark	Pos	Pos
			dBuV/m	dB	dBuV	dB		deg	cm
1 !	2386.200	53.10	54.00	-0.90	22.17	30.93	AVERAGE	346	99
2	2386.200	62.49	74.00	-11.51	31.56	30.93	PEAK	346	99
3 @	2411.200	111.16			80.18	30.98	AVERAGE	346	99
4	2413.200	114.97			83.99	30.98	PEAK	346	99

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	Line	Limit	Level	Factor	Remark	Pos	Pos
			dBuV/m	dB	dBuV	dB		deg	cm
1	2388.000	51.88	74.00	-22.12	20.95	30.93	PEAK	118	100
2	2390.000	46.69	54.00	-7.31	15.76	30.93	AVERAGE	118	100
3 @	2434.400	107.82			76.74	31.07	AVERAGE	118	100
4 @	2435.600	111.20			80.12	31.07	PEAK	118	100
5	2483.500	56.34	74.00	-17.66	25.16	31.18	PEAK	118	100
6	2483.500	46.34	54.00	-7.66	15.16	31.18	AVERAGE	118	100

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Limit	Over	Read			Table	Ant
	MHz	dBuV/m	Line	Limit	Level	Factor	Remark	Pos	Pos
			dBuV/m	dB	dBuV	dB		deg	cm
1 @	2463.600	111.13			80.01	31.13	PEAK	146	100
2 @	2464.800	107.88			76.75	31.13	AVERAGE	146	100
3	2484.100	59.57	74.00	-14.43	28.39	31.18	PEAK	146	100
4 !	2484.300	49.38	54.00	-4.62	18.20	31.18	AVERAGE	146	100

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	802.11g CH 1, 6, 11 / Ant. A
Test Date	Jun. 08, 2009		

Channel 1

	Freq	Level	Limit	Over	Read	Factor	Remark	Pol/Phase	Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			deg	cm
1 !	2390.000	53.63	54.00	-0.37	22.70	30.93	AVERAGE	VERTICAL	62	100
2 !	2390.000	70.20	74.00	-3.80	39.27	30.93	PEAK	VERTICAL	62	100
3 ☺	2406.000	100.60			69.62	30.98	AVERAGE	VERTICAL	62	100
4	2406.400	107.31			76.33	30.98	PEAK	VERTICAL	62	100

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Factor	Remark	Pol/Phase	Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			deg	cm
1	2388.000	61.40	74.00	-12.60	30.47	30.93	PEAK	VERTICAL	62	100
2 !	2390.000	49.06	54.00	-4.94	18.13	30.93	AVERAGE	VERTICAL	62	100
3 ☺	2435.800	102.85			71.77	31.07	AVERAGE	VERTICAL	62	100
4	2438.400	112.07			81.00	31.07	PEAK	VERTICAL	62	100
5 !	2483.500	49.00	54.00	-5.00	17.82	31.18	AVERAGE	VERTICAL	62	100
6	2484.300	61.53	74.00	-12.47	30.35	31.18	PEAK	VERTICAL	62	100

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	Factor	Remark	Pol/Phase	Table	Ant
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB			deg	cm
1	2465.800	104.20			73.08	31.13	PEAK	VERTICAL	113	100
2	2467.600	95.23			64.10	31.13	AVERAGE	VERTICAL	113	100
3 !	2483.500	53.95	54.00	-0.05	22.77	31.18	AVERAGE	VERTICAL	113	100
4 !	2483.500	73.27	74.00	-0.73	42.09	31.18	PEAK	VERTICAL	113	100

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration Drafft n MCS0 20MHz Ant. A + Ant. B / 2412 MHz



Date: 8.JUN.2009 19:02:18


High Band Edge Plot on Configuration Drafft n MCS0 20MHz Ant. A + Ant. B / 2462 MHz



Date: 8.JUN.2009 19:08:53


For Emission not in Restricted Band

Low Band Edge Plot on Configuration Drafft n MCS0 40MHz Ant. A + Ant. B / 2422 MHz




Date: 8.JUN.2009 19:22:18

High Band Edge Plot on Configuration Drafft n MCS0 40MHz Ant. A + Ant. B / 2452 MHz




Date: 8.JUN.2009 19:47:07

Low Band Edge Plot on Configuration IEEE 802.11b Ant. A / 2412 MHz




Date: 8.JUN.2009 18:47:36

High Band Edge Plot on Configuration IEEE 802.11b Ant. A / 2462 MHz




Date: 8.JUN.2009 18:52:48

Low Band Edge Plot on Configuration IEEE 802.11g Ant. A / 2412 MHz



Date: 8.JUN.2009 18:38:49

High Band Edge Plot on Configuration IEEE 802.11g Ant. A / 2462 MHz



Date: 8.JUN.2009 18:44:36

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Apr. 15, 2009	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 23, 2009	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2009	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2009	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN T400	21653	9kHz – 30MHz	Jun. 11, 2009	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 07, 2009	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 23, 2009	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jul. 21, 2008	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Apr. 06, 2009*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100023	9 kHz - 30 GHz	Feb 02, 2009	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul 28, 2008*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 12, 2008	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Apr. 29, 2009	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan.16, 2009	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Jan. 05, 2009	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Jan. 05, 2009	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSU26.5	100015	20Hz ~ 26.5GHz	Oct. 29, 2008	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jul. 11, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jul. 11, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jul. 11, 2008	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 30, 2009*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 13, 2009	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Jul. 18, 2008	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2008	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2008	Conducted (TH01-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Dec. 14, 2008	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 25, 2009	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Note: *Calibration Interval of instruments listed above is two year.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-070110

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.

EMC & Wireless Communications Laboratory

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : January 10, 2007

P1, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.