

# Appendix B. Maximum Permissible Exposure

FCC ID: MQ4WR5503U Page No. : B1 of B3



## 1. Maximum Permissible Exposure

### 1.1. Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.25 m normally can be maintained between the user and the device.

(A) Limits for Occupational / Controlled Exposure

| Frequency Range<br>(MHz) | Electric Field<br>Strength (E) (V/m) | Magnetic Field Power Density (S) Strength (H) (A/m) (mW/ cm²) |            | Averaging Time<br> E  <sup>2</sup> , H  <sup>2</sup> or S<br>(minutes) |  |
|--------------------------|--------------------------------------|---|------------|--|--|
| 0.3-3.0                  | 614                                  | 1.63  | (100)*     | 6  |  |
| 3.0-30                   | 1842 / f                             | 4.89 / f  | (900 / f)* | 6  |  |
| 30-300                   | 61.4                                 | 0.163   | 1.0        | 6  |  |
| 300-1500                 |                                      |   | F/300      | 6  |  |
| 1500-100,000             |                                      |   | 5          | 6  |  |

#### (B) Limits for General Population / Uncontrolled Exposure

| Frequency Range<br>(MHz) | Electric Field Strength (E) (V/m)  Magnetic Field Strength (H) (A/m) |        | Power Density (S)<br>(mW/ cm²) | Averaging Time<br> E ², H ² or S<br>(minutes) |  |
|--------------------------|--|--------|--------------------------------|---|--|
| 0.3-1.34                 | 614  | 1.63   | (100)*                         | 30  |  |
| 1.34-30                  | 824/f  | 2.19/f | (180/f)*                       | 30  |  |
| 30-300                   | 27.5   | 0.073  | 0.2                            | 30  |  |
| 300-1500                 |  |        | F/1500                         | 30  |  |
| 1500-100,000             |  |        | 1.0                            | 30  |  |

Note: f = frequency in MHz; \*Plane-wave equivalent power density

#### 1.2. MPE Calculation Method

E (V/m) = 
$$\frac{\sqrt{30 \times P \times G}}{d}$$
 Power Density:  $Pd$  (W/m²) =  $\frac{E^2}{377}$ 

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

FCC ID: MQ4WR5503U Page No. : B2 of B3



Report No.: FR150419

## 1.3. Calculated Result and Limit

Antenna Type: PIFA Antenna

Max Conducted Power for IEEE 802.11n MCS8 20MHz: 22.90 dBm

| Antenna Gain<br>(dBi) | Antenna Gain<br>(numeric) | Average<br>Output Power<br>(dBm) | Average<br>Output Power<br>(mW) | Power Density<br>(S)<br>(mW/cm²) | Limit of Power<br>Density (\$)<br>(mW/cm²) | Test Result |
|-----------------------|---------------------------|----------------------------------|---------------------------------|----------------------------------|--|-------------|
| 2                     | 1.5849                    | 22.9045                          | 195.1846                        | 0.061574                         | 1  | Complies    |

FCC ID: MQ4WR5503U Page No. : B3 of B3