

Maximum Permissible Exposure (MPE) Evaluation Report

Report No. : EME-041008

Model No. : WUG2660


Issued Date : Nov. 5, 2004

**Applicant : AboCom Systems, Inc.
1F, No. 21, Yanfa 2nd Rd., SBIP, HsinChu City 300,
Taiwan**

**Test By : Intertek Testing Services Taiwan Ltd.
No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,
Shiang-Shan District, Hsinchu City, Taiwan**


This test report consists of 5 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Intertek Laboratory. The test result in this report only applies to the tested sample.

Project Engineer



Jackey Chiu

Reviewed By



Jerry Liu

Table of Contents

| | |
|----------------------------------|---|
| Summary of Tests | 3 |
| 1. Introduction | 4 |
| 2. RF Exposure Limit..... | 4 |
| 3. RF Exposure calculations..... | 5 |
| 4. Test results | 5 |

Summary of Tests

MPE Evaluation meet FCC OET No. 65: 1997/ IEEE C95.1-1999

802.11b/g Wireless LAN USB 2.0 Adapter-Model: WUG2660

FCC ID: MQ4WUG2660

| Test | Reference | Results |
|----------------|--|----------|
| MPE Evaluation | FCC Guidelines for Human Exposure IEEE C95.1 | Complies |

1. Introduction

The EUT operates in the 2.4GHz ISM band. Due to the EUT (include antenna) at its normal operation distance is at least 20 cm from the human body, the EUT was defined as a Mobile Device.

The EUT operates in the 2.4GHz ISM band. The EUT (antenna included) is compliant with modular approval and the normal operation distance (after installing in other device, such as router or access point), 20cm from the human body; therefore, the EUT is defined as a Mobile Device.

The reason to do the MPE Evaluation is to avoid the RF hazard to human body. The maximum output power and gain of the antenna were used to calculate the limited Power density (S) at 20cm distance away from the product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

Limits for Maximum Permissible Exposure (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational / Control Exposures | | | | |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | - | - | F/300 | 6 |
| 1500-100,000 | - | - | 5 | 6 |
| (B) Limits for General Population / Uncontrolled Exposure | | | | |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | - | - | F/1500 | 30 |
| 1500-100,000 | - | - | 1.0 | 30 |

F= Frequency in MHz

3. RF Exposure calculations

From §FCC 1.1310 table 1, the maximum permissible RF exposure for an uncontrolled environment is 1mW/(cm²)
 Power density (S) is calculated by the following formula:

$$S = (P * G)/4\pi R^2$$

where, S = Power density (mW/cm²)

P = Output power to antenna (mW)

R = Distance between radiating structure and observation point (cm)

G = Gain of antenna in numeric

$\pi = 3.1416$

Example:

Assume a mobile device operates at 2412MHz and its maximum output power is 50mW, and the maximum gain of antenna is 1 (numeric) /0dBi.

then the power density (S) = $(50 * 1)/4*\pi*20^2 = 0.00995$ (mW/cm²)

4. Test results

Test Mode: 802.11b operation mode (DSSS Modulation)

| Channel | Channel Frequency (MHz) | Maximum antenna gain (numeric)* | Output power to antenna (mW) | Power density (mW/cm ²) | Limit of power density (mW/cm ²) |
|---------|-------------------------|---------------------------------|------------------------------|-------------------------------------|--|
| 1 | 2412 | 2 | 76.73 | 0.03046 | 1.0 |
| 6 | 2437 | 2 | 77.44 | 0.03074 | 1.0 |
| 11 | 2462 | 2 | 76.20 | 0.03025 | 1.0 |

Note: “*” The antenna gain is the maximum gain among three antennas.

Test Mode: 802.11g operation mode (OFDM Modulation)

| Channel | Channel Frequency (MHz) | Maximum antenna gain (numeric)* | Output power to antenna (mW) | Power density (mW/cm ²) | Limit of power density (mW/cm ²) |
|---------|-------------------------|---------------------------------|------------------------------|-------------------------------------|--|
| 1 | 2412 | 2 | 96.16 | 0.03817 | 1.0 |
| 6 | 2437 | 2 | 95.49 | 0.03790 | 1.0 |
| 11 | 2462 | 2 | 95.06 | 0.03773 | 1.0 |

Note: “*” The antenna gain is the maximum gain among three antennas.

The Notice in Installation Manual has been stated as below:

While installing and operating this transmitter, the radio frequency exposure limit of 1mW/(cm*cm) may be exceeded at distances close to the transmitter. therefore, the user must maintain a minimum distance of 20 cm from the device at all time.