



**ETS Dr.GenZ Taiwan PS Co., Ltd.**

**FCC Registration No.: 930600**

**Industry Canada filed test laboratory Reg. No. IC 5679**

**Accredited Testing Laboratory**



**A2LA Cert.No.: 2300.01**

**PTCRB Accredited Type Certification Test House**

# **FCC**

# **TEST - REPORT**

**FCC RULES PART 15 / SUBPART C**

**FCC ID: MQ5RF-688DTX**

**Test report no.: W6M20508-6150-C-1**

## TABLE OF CONTENTS

|          |                                                         |           |
|----------|---------------------------------------------------------|-----------|
| <b>1</b> | <b>GENERAL INFORMATION .....</b>                        | <b>3</b>  |
| 1.1      | NOTES .....                                             | 3         |
| 1.2      | TESTING LABORATORY .....                                | 4         |
| 1.2.1    | Location .....                                          | 4         |
| 1.2.2    | Details of accreditation status .....                   | 4         |
| 1.3      | DETAILS OF APPROVAL HOLDER .....                        | 4         |
| 1.4      | APPLICATION DETAILS .....                               | 5         |
| 1.5      | GENERAL INFORMATION OF TEST ITEM .....                  | 5         |
| 1.6      | TEST STANDARDS .....                                    | 6         |
| <b>2</b> | <b>TECHNICAL TEST .....</b>                             | <b>7</b>  |
| 2.1      | SUMMARY OF TEST RESULTS .....                           | 7         |
| 2.2      | TEST ENVIRONMENT .....                                  | 7         |
| 2.3      | TEST EQUIPMENT LIST .....                               | 8         |
| <b>3</b> | <b>TEST RESULTS (ENCLOSURE).....</b>                    | <b>13</b> |
| 3.1      | PEAK OUTPUT POWER (TRANSMITTER) .....                   | 14        |
| 3.2      | EQUIVALENT ISOTROPIC RADIATED POWER .....               | 15        |
| 3.2.1    | Transmitter .....                                       | 15        |
| 3.3      | RF EXPOSURE COMPLIANCE REQUIREMENTS .....               | 15        |
| 3.4      | TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS..... | 16        |
| 3.5      | SPURIOUS EMISSIONS (TX) .....                           | 17        |
| 3.6      | MINIMUM 6 dB BANDWIDTH .....                            | 20        |
| 3.7      | PEAK POWER SPECTRAL DENSITY.....                        | 21        |
| 3.8      | RADIATED EMISSIONS FROM RECEIVER SECTION .....          | 22        |
| 3.9      | POWER LINE CONDUCTED EMISSION .....                     | 24        |
|          | <b>APPENDIX .....</b>                                   | <b>27</b> |
|          | APPENDIX A.....                                         | 28        |
|          | APPENDIX B.....                                         | 29        |
|          | APPENDIX C.....                                         | 30        |
|          | APPENDIX D.....                                         | 31        |
|          | APPENDIX E.....                                         | 32        |
|          | APPENDIX F .....                                        | 33        |
|          | APPENDIX G.....                                         | 34        |
|          | APPENDIX H.....                                         | 35        |

Registration number: W6M20508-6150-C-1

FCC ID: MQ5RF-688DTX

**1 General Information****1.1 Notes**

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has Passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.


The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the ETS DR. GENZ TAIWAN PS CO., LTD.

**Tester:**

19.09.2005

Orville Chang



Date

ETS-Lab.

Name

Signature

**Technical responsibility for area of testing:**

19.09.2005

Steven Chung



Date

ETS

Name

Signature

Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

## **1.2 Testing laboratory**

### **1.2.1 Location**

OATS  
No.5-1, Shuang Sing Village,  
LiShuei Rd., Wanli Township,  
Taipei County 207, Taiwan (R.O.C.)

Company  
ETS Dr.Genx Taiwan PS Co., Ltd.  
6F, NO. 58, LANE 188, RUEY-KUANG RD.  
NEIHU, TAIPEI 114, TAIWAN R.O.C.  
Tel : 886-2-66068877  
Fax : 886-2-66068879

### **1.2.2 Details of accreditation status**

**Accredited testing laboratory**

**A2LA-registration number: 2300.01**

**FCC filed test laboratory Reg. No. 930600**

**Industry Canada filed test laboratory Reg. No. IC 5679**

**PTCRB Accredited Type Certification Test House**

## **1.3 Details of approval holder**

Name : TELEAN TECHNOLOGY LTD.  
Street : 1601-3, 16/F, FO Tan Industrial, Center, 26-28 Au Pui Wan Street,  
Fo Tan Shatin, N.T.  
Town : ./.  
Country : HONG KONG  
Telephone : +(852)2693-2773  
Fax : +(852)2693-1526  
  
Contac : Mr. Alan Mok  
Telephone : +(852)2693-2773

Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

#### 1.4 Application details

Date of receipt of application : 30.08.2005  
Date of receipt of test item : 05.09.2005  
Date of test : from 05.09.2005 to 16.09.2005


#### 1.5 General information of Test item

Type of test item : 2.4GHz Digital Wireless Headphone System  
Model Number : RF-6888D  
Hardware : 1.0  
Software : 1.0  
Serial number : without  
Photos : see Annex

#### Technical data

Frequency band : 2.4 GHz – 2.4835 GHz  
Frequency ( ch A) : 2.410 GHz  
Frequency ( ch B) : 2.446 GHz  
Frequency ( ch C) : 2.473 GHz  
Number of Channels : 8  
Operation modes : Simplex  
Modulation Type : FSK

Fixed point-to-point operation: ☐ Yes / ☒ No  
Type of Antenna Receiver : PCB Antenna  
Type of Antenna Transmitter : inverted-F / omni-directional  
Antenna gain of Antenna Receiver : 0.87 dBi  
Antenna gain of Antenna Transmitter : -3 dBi  
Power supply of TX & RX : 12 VDC ( ac / dc Adaptor )



Registration number: W6M20508-6150-C-1

FCC ID: MQ5RF-688DTX

Host device: none

Classification :

|                                              |                                     |
|----------------------------------------------|-------------------------------------|
| Fixed Device                                 | <input type="checkbox"/>            |
| Mobile Device (Human Body distance > 20cm)   | <input type="checkbox"/>            |
| Portable Device (Human Body distance < 20cm) | <input checked="" type="checkbox"/> |

**Transmitter**

**Unom**

**Power ( ch A)** : Conducted: 11.77 dBm

**Power ( ch B)** : Conducted: 11.44 dBm

**Power ( ch C)** : Conducted: 11.15 dBm

**Manufacturer:**

(if applicable)

Name : ./.

Street : ./.

Town : ./.

Country : ./.

Additional information: --

**1.6 Test standards**

Technical standard : FCC RULES PART 15 / SUBPART C § 15.247

Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

## **2 Technical test**

### **2.1 Summary of test results**

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



**or**

The deviations as specified in 2.5 were ascertained in the course of the tests performed.



### **2.2 Test environment**

|                               |                              |
|-------------------------------|------------------------------|
| Temperature                   | : 23 °C                      |
| Relative humidity content     | : 20 ... 75 %                |
| Air pressure                  | : 86 ... 103 kPa             |
| Details of power supply TX    | : 12 VDC ( ac / dc Adaptor ) |
| Details of power supply RX    | : 12 VDC ( ac / dc Adaptor ) |
| Extreme conditions parameters | : --                         |

Registration number: W6M20508-6150-C-1

FCC ID: MQ5RF-688DTX

### 2.3 Test Equipment List

| No.          | Test equipment                                     | Type                | Serial No.                | Manufacturer                          | Next Cal. Date |
|--------------|----------------------------------------------------|---------------------|---------------------------|---------------------------------------|----------------|
| ETSTW-CE 001 | EMI TEST RECEIVER                                  | ESHS10              | 842121/013                | R&S                                   | 2005/11/8      |
| ETSTW-CE 002 | PREREULATOR MODE DC POWER SUPPLY                   |                     |                           |                                       |                |
| ETSTW-CE 003 | AC POWER SOURCE                                    | APS-9102            | D161137                   | GW                                    |                |
| ETSTW-CE 004 | ZWEILEITER-V-NETZNACHBILDUNG<br>TWO-LINE V-NETWORK | ESH3-Z5             | 840731/011                | R&S                                   | 2006/11/8      |
| ETSTW-CE 005 | Line-Impedance Stabilisation Network               | NNBM 8126D          | 137                       | Schwarzbeck                           | 2006/11/3      |
| ETSTW-CE 006 | IMPULS-BEGRENZER PULSE LIMITER                     | ESH3-Z2             | 100226                    | R&S                                   | 2006/11/10     |
| ETSTW-CE 007 | SPECTRUM ANALYZER 5GHz                             | FSB                 | 849670/001                | R&S                                   |                |
| ETSTW-CE 008 | ABSORBING CLAMP                                    | MDS 21              | 3469                      | ABSORPTIONS-<br>MESSWANDLER-<br>ZANGE | 2006/11/4      |
| ETSTW-CE 009 | TEMP.&HUMIDITY CHAMBER                             | GTH-225-40-1P-U     | MAA0305-009               | GIANT FORCE                           | 2005/5/10      |
| ETSTW-CE 010 | Comb Generator-conducted                           |                     |                           | ETS                                   |                |
| ETSTW-CE 011 | Power Line Conducted Emission Only                 |                     |                           | ETS                                   |                |
| ETSTW-CE 012 | Dual-Phase-V-Network                               | NNB-2/16Z           | 03/10201                  | Telemeter                             | 2006/4/11      |
| ETSTW-CS 001 | SIGNAL GENERATOR                                   | SMX                 | 849254/003                | R&S                                   | 2005/10/31     |
| ETSTW-CS 002 | COUPLING AND DECOUPLING NETWORK                    | CDN S751            | 19263                     | CHAFFNER                              | 2006/11/3      |
| ETSTW-CS 003 | COUPLING AND DECOUPLING NETWORK                    | CDN T400            | 19820                     | CHAFFNER                              | 2006/11/3      |
| ETSTW-CS 004 | COUPLING AND DECOUPLING NETWORK                    | CDN M016            | 20053                     | CHAFFNER                              | 2006/11/3      |
| ETSTW-CS 005 | RF Power Amplifier                                 | 100A250A            | 306547                    | AR                                    | 2005/11/3      |
| ETSTW-CS 006 | Terminal 50Ω Load                                  | 50T-116 M           |                           | JFW                                   |                |
| ETSTW-CS 007 | Terminal 50Ω Load                                  | 50T-116 F           |                           | JFW                                   |                |
| ETSTW-CS 008 | 6 dB Attenuator                                    | HFP-5100-3/06 N M/F | 2010876106                |                                       |                |
| ETSTW-RE 001 | Controller                                         | CD 1000             | C01000/154/867<br>/004/L  | Heinrich Deisel                       |                |
| ETSTW-RE 002 | Function Generator                                 | 33220A              | MY43004982                | Agilent                               | 2005/11/3      |
| ETSTW-RE 003 | EMI TEST RECEIVER                                  | ESI                 | 831438/001                | R&S                                   | 2005/11/16     |
| ETSTW-RE 004 | EMI TEST RECEIVER                                  | ESI                 | 831459/012                | R&S                                   | 2005/11/9      |
| ETSTW-RE 005 | EMI TEST RECEIVER                                  | ESVS10              | 843207/020                | R&S                                   | 2005/11/1      |
| ETSTW-RE 008 | Controller                                         | HD100               | C0100-L/047/<br>6670703/L | Heinrich Deisel                       |                |
| ETSTW-RE 009 | Controller                                         | HD100               | 100/341                   | Heinrich Deisel                       |                |
| ETSTW-RE 010 | PROGRAMMABLE LINEAR POWER<br>SUPPLY                | LPS-305             | 30503070181               | MOTECH                                |                |
| ETSTW-RE 011 | PROGRAMMABLE LINEAR POWER<br>SUPPLY                | LPS-305             | 30503070165               | MOTECH                                |                |
| ETSTW-RE 012 | TUNABLE BANDREJECT FILTER                          | D.C 0309            | 146                       | K&L                                   |                |
| ETSTW-RE 013 | TUNABLE BANDREJECT FILTER                          | D.C 0036            | 397                       | K&L                                   |                |
| ETSTW-RE 014 | DUAL TRACKING WITH 5V FIXED                        | GPC-3030D           |                           | GW                                    |                |
| ETSTW-RE 015 | ANTENNA                                            | HK116               | 841489/003                | R&S                                   |                |
| ETSTW-RE 016 | ANTENNA                                            | HL223               | 848953/006                | R&S                                   |                |
| ETSTW-RE 017 | ANTENNA                                            | HL025               | 352886/001                | R&S                                   |                |



Registration number: W6M20508-6150-C-1

FCC ID: MQ5RF-688DTX

|               |                                       |                  |                |             |            |
|---------------|---------------------------------------|------------------|----------------|-------------|------------|
| ETSTW-RE 018  | ANTENNA                               | AT4560           | 27212          | AR          | 2006/11/7  |
| ETSTW-RE 019  | ANTENNA , HORN                        | 22240-25         | 121074         | FM          |            |
| ETSTW-RE 020  | MICROWAVE HORN ANTENNA                | AT4002A          | 306915         | AR          |            |
| ETSTW-RE 021  | SWEEP GENERATOR                       | SWM05            | 835130/010     | R&S         | 2005/11/10 |
| ETSTW-RE 022  | AMPLIFIER                             | 8447D            | 2944A09837     | Agilent     | 2005/11/1  |
| ETSTW-RE 023  | Shielded room                         | SR 1             |                | Frankonia   |            |
| ETSTW-RE 024  | Anechoic Chamber                      | CHC 1            |                | Frankonia   |            |
| ETSTW-RE 025  | Anechoic Chamber                      | CHC 2            |                | Frankonia   |            |
| ETSTW-RE 026  | Open Area Test Site                   | 10m              |                | ETS         |            |
| ETSTW-RE 027  | Passive Loop Antenna                  | 6512             | 34563          | EMCO        | 2006/6/29  |
| ETSTW-RE 028  | Log-Periodic DipoleArray Antenna      | 3148             | 34429          | EMCO        | 2006/6/14  |
| ETSTW-RE 029  | Biconical Antenna                     | 3109             | 33524          | EMCO        | 2006/6/16  |
| ETSTW-RE 030  | Double-Ridged Waveguide Horn Antenna  | 3117             | 35224          | EMCO        | 2006/5/4   |
| ETSTW-RE 031  | Comb Generator-radiated               |                  |                | ETS         |            |
| ETSTW-RE 032  | Millivoltmeter                        | URV 55           | 849086/013     | R&S         | 2005/11/17 |
| ETSTW-RE 033  | 4CH 1GHz 5GS/s DSO                    | WAVERUNNER 6100A | LCRY0604P14508 | LeCory      |            |
| ETSTW-RE 034  | Power Sensor                          | URV5-Z4          | 839313/006     | R&S         | 2005/11/17 |
| ETSTW-RE 035  | 1.5GHz Active Voltage Probe           | HFP1500          | 2332           | LeCory      |            |
| ETSTW-RE 036  | 100MHz High Voltage Diff Probe        | ADP305           | 3305           | LeCory      |            |
| ETSTW-RE 037  | Log-Periodic DipoleArray Antenna      | 3148             | 00034546       | EMCO        | 2006/11/17 |
| ETSTW-RE 038  | Log-Periodic DipoleArray Antenna      | 3148             | 00034547       | EMCO        | 2006/11/17 |
| ETSTW-RE 039  | Biconical Antenna                     | 3110B            | 41760          | EMCO        | 2006/11/17 |
| ETSTW-RE 040  | Biconical Antenna                     | 3110B            | 41761          | EMCO        | 2006/11/17 |
| ETSTW-RE 041  | Anechoic Chamber                      | CHC 3            |                | Frankonia   |            |
| ETSTW-RE 042  | ANTENNA                               | HK116            | 100172         | R&S         | 2007/1/13  |
| ETSTW-RE 043  | ANTENNA                               | HL223            | 100166         | R&S         | 2006/4/15  |
| ETSTW-RE 044  | ANTENNA                               | HL050            | 100094         | R&S         |            |
| ETSTW-RE 048  | Triple Loop Antenna                   | HXYZ 9170        | HXYZ 9170-134  | Schwarzbeck | 2006/3/21  |
| ETSTW-EMI 001 | HARMONICS 1000                        | HAR1000-1P       | 93             | EMC-PARTNER | 2005/11/17 |
| ETSTW-EMS 001 | Clamp BASELSTRASSE 160 CH-4242 LAUFEN | CN-EFT1000       | 354            | EMC-PARTNER | 2005/11/1  |
| ETSTW-EMS 002 | Frequency Converter                   | YF-6020          | 0308014        |             |            |
| ETSTW-EMS 003 | EMC Immunity Test System              | TRA2000IN6       | 579            | EMC-PARTNER | 2005/11/1  |
| ETSTW-EMS 004 | ESD generator minizap                 | ESD2000          | 016            | EMC-PARTNER | 2005/11/1  |
| ETSTW-EMS 005 | Attenautor (50Ω)                      | VERI50           | 051            | EMC-PARTNER | 2006/8/30  |
| ETSTW-EMS 006 | Attenautor (1 KΩ)                     | VERI1K           | 019            | EMC-PARTNER | 2006/10/20 |
| ETSTW-EMS 007 | 20GΩ Divider                          | ESD-VERI-V       | 021            | EMC-PARTNER | 2006/3/16  |
| ETSTW-RS 001  | 14" COLOR VIDEO MONITOR               | TP-1480HR        | P009799        | TOPICA      |            |
| ETSTW-RS 002  | 14" COLOR VIDEO MONITOR               | TP-1480HR        | P009814        | TOPICA      |            |
| ETSTW-RS 003  | RF Power Amplifier                    | 30S1G3           | 306933         | AR          |            |
| ETSTW-RS 004  | RF Power Amplifier                    | 150W1000         | 307009         | AR          | 2005/11/18 |

Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

|               |                                      |                                          |             |                |            |
|---------------|--------------------------------------|------------------------------------------|-------------|----------------|------------|
| ETSTW-RS 005  | Electric Field Probe Type 8.3        | EMR-20                                   | BN 2244/20  | GW             | 2005/9/3   |
| ETSTW-RS 006  | SIGNAL GENERATOR                     | SML03                                    | 101551      | R&S            | 2005/11/15 |
| ETSTW-RS 007  | AUDIO ANALYZER                       | UPA3                                     | 843458/029  | R&S            | 2005/11/15 |
| ETSTW-EMS 008 | Safety Test Solutions                | ELT-400                                  | E-0039      | Narda          | 2006/1/3   |
| ETSTW-EMS 009 | Magnetic Field Antenna               | MF1000-1                                 | 104         | EMC-PARTNER    | 2006/12/2  |
| ETSTW-GSM 01  | SIM Simulator                        | IT3                                      | B2004-50106 | ORGA           |            |
| ETSTW-GSM 02  | Universal Radio Communication Tester | CMU 200                                  | 103489      | R&S            |            |
| ETSTW-GSM 03  | Agilent 8960 Test Set 1              | E5515C                                   | GB44052675  | Agilent        | 2006/7/13  |
| ETSTW-GSM 04  | Agilent 8960 Test Set 2              | E5515C                                   | GB44052665  | Agilent        | 2006/7/13  |
| ETSTW-GSM 05  | Agilent 8960 Test Set 3              | E5515C                                   | GB44052852  | Agilent        | 2006/7/16  |
| ETSTW-GSM 06  | Agilent 8960 Test Set 4              | E5515C                                   | GB44052984  | Agilent        | 2006/7/15  |
| ETSTW-GSM 07  | Agilent 8960 Test Set 5              | E5515C                                   | GB44052658  | Agilent        | 2006/7/13  |
| ETSTW-GSM 08  | Agilent 8960 Test Set 6              | E5515C                                   | GB44052666  | Agilent        | 2006/7/15  |
| ETSTW-GSM 09  | Controler PC                         | Dell GX 270                              | 700F61J     | Dell           |            |
| ETSTW-GSM 10  | Combiner Wessex / Anite              | B4605/100                                | 053         | Wessex / Anite | 2006/7/13  |
| ETSTW-GSM 11  | GSM 850,900,1800,1900 Test system    | TS8950G                                  |             | R&S            | 2005/10/31 |
| ETSTW-GSM 12  | Acoustical Calibrator                | 4231                                     | 2463874     | Brüel&Kjær     | 2005/11/17 |
| ETSTW-GSM 13  | Conditioning Amplifier               | 2690--0S2                                | 2437856     | Brüel&Kjær     |            |
| ETSTW-GSM 14  | Telephone Test Head                  | 4602B                                    | 2465324     | Brüel&Kjær     |            |
| ETSTW-GSM 15  | Mouth Simulator                      | 4227                                     | 2462516     | Brüel&Kjær     |            |
| ETSTW-GSM 16  | TEMP.&HUMIDITY CHAMBER               | GTH-120-40-1P-U                          | MAA0501002  | GIANT FORCE    | 2005/12/29 |
| ETSTW-GSM 17  | ANTENNT COPLER                       | CMU-Z10                                  | 100988      | R&S            |            |
| ETSTW-GSM 18  | AUDIO ANALYZER                       | UPL16                                    | 100173      | R&S            | 2005/9/23  |
| ETSTW-GSM 19  | Band Reject Filter                   | WRCTF824/849-822/851-40/12+9SS           | 3           | WI             |            |
| ETSTW-GSM 20  | Band Reject Filter                   | WRCD1747/1748-1743/1752-32/5SS           | 1           | WI             |            |
| ETSTW-GSM 21  | Band Reject Filter                   | WRCD1879.5/ 1880.5-1875.5/ 1884.5-32/5SS | 3           | WI             |            |
| ETSTW-GSM 22  | Band Reject Filter                   | WRCT901.9/903.1-904.25-50/8SS            | 1           | WI             |            |

Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

## 2.4 General Test Procedure

**POWER LINE CONDUCTED INTERFERENCE:** The procedure used was ANSI STANDARD C63.4-2003 using a 50 $\mu$ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

**RADIATION INTERFERENCE:** The test procedure used was according to ANSI STANDARD C63.4-2003 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23°C with a humidity of 40 %.

**FORMULA OF CONVERSION FACTORS:** The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB $\mu$ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:


|            |                                                          |
|------------|----------------------------------------------------------|
| Freq (MHz) | METER READING + ACF + CABLE LOSS (to the receiver) = FS  |
| 33         | 20 dB $\mu$ V + 10.36 dB + 6 dB = 36.36 dB $\mu$ V/m @3m |

The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2000 Section 13.1.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by ETS Dr.Genx Taiwan PS Co., Ltd. at the registered open field test site located at No.5-1, Shuang Sing Village, LiShuei Rd., Wanli Township, Taipei County 207, Taiwan (R.O.C.) The Registration Number: 930600.



Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor =  $20 \log (\text{dwell time}/T)$

$T = 100\text{ms}$  when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANTENNA & GROUND:

**This unit uses inverted-F / omni-directional and PCB Antenna. (see photos)**

Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

### 3 Test results (enclosure)

| TEST CASE                                             | Para. Number | Required                            | Test passed                         | Test failed              |
|-------------------------------------------------------|--------------|-------------------------------------|-------------------------------------|--------------------------|
| Peak Output Power                                     | 15.247(b)(3) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Equivalent radiated Power                             | 15.247(b)(3) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Spurious Emissions radiated – Transmitter operating   | 15.247(c)    | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Band Edge Measurement                                 | 15.247(c)    | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Minimum 6 dB Bandwidth                                | 15.247(a)(2) | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Peak Power Spectral Density                           | 15.247(d)    | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Radiated Emission from Digital Part And Receiver L.O. | 15.109       | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Power Line Conducted Emission                         | 15.207       | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |

The follows is intended to leave blank.

Registration number: W6M20508-6150-C-1

FCC ID: MQ5RF-688DTX

**3.1 Peak Output Power (transmitter)**

FCC Rule: 15.247(b)(3)

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

| Test condition                 |                          | Conducted Power |           |           |
|--------------------------------|--------------------------|-----------------|-----------|-----------|
|                                |                          | Channel A       | Channel B | Channel C |
|                                |                          | [dBm]           | [dBm]     | [dBm]     |
| $T_{nom} = 23^{\circ}\text{C}$ | $V_{nom} = 12 \text{ V}$ | 11.77           | 11.44     | 11.15     |
| Measurement uncertainty        |                          | < 3 dB          |           |           |

| Test condition<br>$T_{nom} = 23^{\circ}\text{C}$ , $V_{nom} = 12 \text{ V}$ | Signal Field strength TX highest power mode<br>dB $\mu\text{V/m}$ |
|-----------------------------------------------------------------------------|-------------------------------------------------------------------|
| Frequency [MHz]                                                             |                                                                   |
| 2473                                                                        | 104.98                                                            |
| Measurement uncertainty                                                     | < 3 dB                                                            |

Limits:

| Frequency<br>MHz | Power<br>dBm |
|------------------|--------------|
| 902 - 928        | 30           |
| 2400 – 2483.5    | 30           |
| 5725 – 5850      | 30           |

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to-point operation consider §15.247 (b)(4)

Test equipment used: ETSTW-RE 003 , ETSTW-RE 012 , ETSTW-RE 017 , ETSTW-RE 024

Registration number: W6M20508-6150-C-1

FCC ID: MQ5RF-688DTX

### 3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain

EIRP = 11.77dBm + -3 dBi

= 8.77dBm

Limit: EIRP = +36 dBm for Antenna gain &lt;6dBi

#### 3.2.1 Transmitter

##### Integral Antenna:

At the transmitter the measurement was transacted with the modulation declared by the manufacturer and the maximum available output power of the EUT.

In this arrangement the EUT fulfils the requirements of the FCC rules § 15.247, subpart C, section b.

### 3.3 RF Exposure Compliance Requirements

The test sample is a WLAN access point intended for fixed installation.

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{PG}{4\pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain G = AG-D

| Item | Unit               | Value     | Remarks          |
|------|--------------------|-----------|------------------|
| P    | mW                 | 15.0314   | Peak value       |
| D    | dB                 |           |                  |
| AG   | dBi                | 1         |                  |
| G    |                    | -3        | Calculated Value |
| R    | cm                 | 20        | Assumed value    |
| S    | mW/cm <sup>2</sup> | 0.0029903 | Calculated value |

Limits:

| Limit for General Population / Uncontrolled Exposure |                                        |
|------------------------------------------------------|----------------------------------------|
| Frequency<br>(MHz)                                   | Power Density<br>(mW/cm <sup>2</sup> ) |
| 1500 – 100.000                                       | 1,0                                    |

Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

### 3.4 Transmitter Radiated Emissions in Restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 1000 MHz.

For radiated emission tests, the analyzer setting was as followings:

Frequency  $\leq$  1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements)

Frequency  $>$  1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements)

Frequency  $>$  1 GHz , RBW:1 MHz , VBW: 100Hz (Average measurements)

Limits.

For frequencies below 1GHz:

| Frequency of Emission<br>(MHz) | Field strength<br>(microvolts/meter) | Field Strength<br>(dB microvolts/meter) |
|--------------------------------|--------------------------------------|-----------------------------------------|
| 30 - 88                        | 100                                  | 40.0                                    |
| 88 - 216                       | 150                                  | 43.5                                    |
| 216 - 960                      | 200                                  | 46.0                                    |
| Above                          | 500                                  | 54.0                                    |

For frequencies above 1GHz (Average measurements).

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction =  $20 \log (\text{dwell time} / 100\text{ms})$

No duty cycle correction was added to the reading.

$54.0\text{dB } \mu\text{V/m} + 20 \text{ dB} = 74 \text{ dB } \mu\text{V/m}$

Remarks: see attached diagrams

Test equipment used: ETS 0125, ETS 0271



Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

### 3.5 Spurious Emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

FCC Rule: 15.247(c), 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies below 1GHz:

Max. reading – 20 dB

$104.98\text{dB } \mu\text{V/m} - 20\text{ dB} = 84.98\text{dB } \mu\text{V/m}$

Guidance on Measurement of DSSS Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty Cycle correction =  $20 \log (\text{dwell time}/100\text{ms})$

For frequencies above 1GHz (Peak measurements).

Limit = max. aver. Reading-20dB+20dB(because Peak detector is used)

$84.98\text{dB } \mu\text{V/m}$

For frequencies above 1GHz (Average measurements).

Max. reading – 20dB

No duty cycle correction was added to the reading

$104.98\text{dB } \mu\text{V/m} - 20\text{ dB} = 84.98\text{dB } \mu\text{V/m}$

Remarks: see attached diagrams

Test equipment used: ETSTW-RE 003 , ETSTW-RE 012 , ETSTW-RE 015 , ETSTW-RE 016 , ETSTW-RE 017 , ETSTW-RE 024

Registration number: W6M20508-6150-C-1

FCC ID: MQ5RF-688DTX

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance with point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value and exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Duty-Cycle Correction Factor".

#### Summary table with radiated data of the test plots

| Freq | Used Ch | Frequency Marker [MHz] | Polarization | corrections dB | Corrected Reading [dBuV/m] | Compliance Limit [dBuV/m] | Detector | BW [MHz] | Margin |
|------|---------|------------------------|--------------|----------------|----------------------------|---------------------------|----------|----------|--------|
| 1    |         | 161,503                | V            |                | 28,8                       | 84,98                     | PK       | 0,1      | 56.18  |
| 2    |         | 246,493                | V            |                | 31,89                      | 46                        | PK       | 0,1      | 14,11  |
| 3    |         | 2395,19                | V            |                | 53,86                      | 84,98                     | PK       | 1        | 31.12  |
| 4    |         | 4817,635               | V            |                | 52,8                       | 54                        | PK       | 1        | 1,2    |
| 4    |         | 7230,461               | V            |                | 62,07                      | 84,98                     | PK       | 1        | 22,91  |
| 1    |         | 196,934                | H            |                | 25,69                      | 84,98                     | PK       | 0,1      | 59.29  |
| 2    |         | 243,287                | H            |                | 36,45                      | 46                        | PK       | 0,1      | 9,55   |
| 3    |         | 2395,19                | H            |                | 52,36                      | 84,98                     | PK       | 1        | 32.62  |
| 4    |         | 4817,635               | H            |                | 51,80                      | 54                        | PK       | 1        | 2,2    |
| 4    |         | 7238,477               | H            |                | 58,58                      | 84,98                     | PK       | 1        | 26,4   |
| 1    |         | 64,068                 | V            |                | 26,70                      | 84,98                     | PK       | 0,1      | 58.28  |
| 1    |         | 161,503                | V            |                | 27,82                      | 84,98                     | PK       | 0,1      | 57.16  |
| 2    |         | 246,493                | V            |                | 32,28                      | 46                        | PK       | 0,1      | 13,72  |
| 4    |         | 4889,779               | V            |                | 54,20                      | 74                        | PK       | 1        | 19,8   |
| 4    |         | 4889,779               | V            |                | 45,37                      | 54                        | AV       | 1        | 8,63   |
| 4    |         | 7334,669               | V            |                | 61,52                      | 74                        | PK       | 1        | 12,48  |
| 4    |         | 7334,669               | V            |                | 51,70                      | 54                        | AV       | 1        | 2,3    |
| 1    |         | 192,164                | H            |                | 29,25                      | 84,98                     | PK       | 0,1      | 55.73  |
| 2    |         | 243,287                | H            |                | 37,36                      | 46                        | PK       | 0,1      | 8,64   |
| 4    |         | 4889,799               | H            |                | 53,63                      | 54                        | PK       | 1        | 0,37   |
| 4    |         | 7342,685               | H            |                | 59,55                      | 74                        | PK       | 1        | 14,45  |
| 4    |         | 7342,685               | H            |                | 49,53                      | 54                        | AV       | 1        | 4,47   |
| 1    |         | 63,727                 | V            |                | 24,85                      | 84,98                     | PK       | 0,1      | 60.13  |

Registration number: W6M20508-6150-C-1

FCC ID: MQ5RF-688DTX

|   |  |          |   |  |       |       |    |     |       |
|---|--|----------|---|--|-------|-------|----|-----|-------|
| 1 |  | 161,503  | V |  | 28,42 | 84,98 | PK | 0,1 | 56,56 |
| 2 |  | 243,287  | V |  | 32,57 | 46    | PK | 0,1 | 13,43 |
| 3 |  | 2488,675 | V |  | 57,79 | 74    | PK | 1   | 16,21 |
| 3 |  | 2488,675 | V |  | 52,78 | 54    | AV | 1   | 1,22  |
| 4 |  | 4945,892 | V |  | 55,46 | 74    | PK | 1   | 18,54 |
| 4 |  | 4945,892 | V |  | 48,1  | 54    | AV | 1   | 5,9   |
| 4 |  | 7422,846 | V |  | 62,67 | 74    | PK | 1   | 11,33 |
| 4 |  | 7422,846 | V |  | 52,69 | 54    | AV | 1   | 1,31  |
| 1 |  | 124,369  | H |  | 26,99 | 43,5  | PK | 0,1 | 16,51 |
| 2 |  | 246,493  | H |  | 36,39 | 46    | PK | 0,1 | 9,61  |
| 3 |  | 2486,605 | H |  | 56,76 | 74    | PK | 1   | 17,24 |
| 3 |  | 2486,605 | H |  | 52,18 | 54    | AV | 1   | 1,82  |
| 4 |  | 4945,892 | H |  | 54,05 | 74    | PK | 1   | 19,95 |
| 4 |  | 4945,892 | H |  | 46,28 | 54    | AV | 1   | 7,72  |
| 4 |  | 7422,846 | H |  | 59,54 | 74    | PK | 1   | 14,46 |
| 4 |  | 7422,846 | H |  | 49,77 | 54    | AV | 1   | 4,23  |

Freq. – Frequency Range:

|    |     |   |          |
|----|-----|---|----------|
| 1: | 30  | - | 200 MHz  |
| 2: | 200 | - | 1000 MHz |
| 3: | 1   | - | 4 GHz    |
| 4: | 4   | - | 8 GHz    |
| 5: | 8   | - | 12 GHz   |
| 6: | 12  | - | 17 GHz   |
| 7: | 17  | - | 26.5 GHz |

All not in the table noted test results are more than 20 dB below the relevant limits.

All other not noted test polts do not contain significant test results in relation to the limits.

**TEST RESULT (Transmitter):** The unit DOES meet the FCC requirements.

Comment: see attached diagrams

Test equipment used: ETSTW-RE 003, ETSTW-RE 015, ETSTW-RE 016, ETSTW-RE 017, ETSTW-RE 024

Registration number: W6M20508-6150-C-1

FCC ID: MQ5RF-688DTX

### 3.6 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission.

The 6 dB bandwidth is the frequency difference between the two markers.

| Test conditions                       |                                 | 6 dB Bandwidth  |                 |                 |
|---------------------------------------|---------------------------------|-----------------|-----------------|-----------------|
|                                       |                                 | Channel A       | Channel B       | Channel C       |
| $T_{\text{nom}} = 23^{\circ}\text{C}$ | $V_{\text{nom}} = 12 \text{ V}$ | 2.160000000 MHz | 2.070500000 MHz | 2.088000000 MHz |
| Measurement uncertainty               |                                 |                 | < 10 Hz         |                 |

#### Limits:

| Frequency Range<br>MHz | Limits      |
|------------------------|-------------|
| 902-928                | min 500 kHz |
| 2400-2483.5            | min 500 kHz |
| 5725-5850              | min 500 kHz |

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: see attached diagram

Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

### 3.7 Peak Power Spectral Density

Peak Power Spectral density is a measured at low, middle and high channel.  
The peak output power is measured with a measurement bandwidth of 10 MHz and displayed on diagram together with Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, appreciate frequency span and sweep time.

| Test conditions                |                          | Peak Power Spectral Density (3 kHz) |                    |                    |
|--------------------------------|--------------------------|-------------------------------------|--------------------|--------------------|
|                                |                          | Channel A<br>[dBm]                  | Channel B<br>[dBm] | Channel C<br>[dBm] |
| $T_{nom} = 23^{\circ}\text{C}$ | $V_{nom} = 12 \text{ V}$ | 1.12                                | 1.51               | 0.45               |
| Measurement uncertainty        |                          | < 3 Hz                              |                    |                    |

#### Limits:

| Frequency Range<br>MHz | dBm |
|------------------------|-----|
| 902-928                | 8   |
| 2400-2483,5            | 8   |
| 5725-5850              | 8   |

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: see attached diagram

Registration number: W6M20508-6150-C-1

FCC ID: MQ5RF-688DTX

**3.8 Radiated Emissions from Receiver Section**

FCC Rule: 15.109

**Summary table with radiated data of the test plots**  
(headset)

| Freq | Used Ch | Frequency Marker [MHz] | Polarization | corrections dB | Corrected Reading [dBuV/m] | Compliance Limit [dBuV/m] | Detector | BW [MHz] | Margin |
|------|---------|------------------------|--------------|----------------|----------------------------|---------------------------|----------|----------|--------|
| 4    |         | 4649,871               | V            |                | 50,12                      | 54                        | PK       | 1        | 3,88   |
| 4    |         | 4601,432               | H            |                | 51,36                      | 54                        | PK       | 1        | 2,64   |

**(Digital-Transmitter)**

| Freq | Used Ch | Frequency Marker [MHz] | Polarization | corrections dB | Corrected Reading [dBuV/m] | Compliance Limit [dBuV/m] | Detector | BW [MHz] | Margin |
|------|---------|------------------------|--------------|----------------|----------------------------|---------------------------|----------|----------|--------|
| 1    |         | 180,922                | V            |                | 28,32                      | 43,5                      | PK       | 0,1      | 15,18  |
| 1    |         | 180,922                | H            |                | 30,26                      | 43,5                      | PK       | 0,1      | 13,24  |
| 1    |         | 169,339                | H            |                | 27,67                      | 43,5                      | PK       | 0,1      | 15,83  |
| 1    |         | 135,611                | H            |                | 25,37                      | 43,5                      | PK       | 0,1      | 18,13  |
| 2    |         | 243,287                | V            |                | 26,58                      | 46                        | PK       | 0,1      | 19,42  |
| 2    |         | 246,493                | H            |                | 27,21                      | 46                        | PK       | 0,1      | 18,79  |

**(Digital- headset)**

| Freq | Used Ch | Frequency Marker [MHz] | Polarization | corrections dB | Corrected Reading [dBuV/m] | Compliance Limit [dBuV/m] | Detector | BW [MHz] | Margin |
|------|---------|------------------------|--------------|----------------|----------------------------|---------------------------|----------|----------|--------|
| 1    |         | 67,134                 | V            |                | 27,22                      | 40                        | PK       | 0,1      | 12,78  |
| 1    |         | 161,503                | V            |                | 28,68                      | 43,5                      | PK       | 0,1      | 14,82  |
| 1    |         | 124,369                | H            |                | 27,05                      | 43,5                      | PK       | 0,1      | 16,45  |
| 1    |         | 161,503                | H            |                | 28,74                      | 43,5                      | PK       | 0,1      | 14,76  |
| 1    |         | 200                    | H            |                | 30,25                      | 43,5                      | PK       | 0,1      | 13,25  |
| 2    |         | 246,493                | V            |                | 32,77                      | 46                        | PK       | 0,1      | 13,23  |
| 2    |         | 243,287                | H            |                | 36,13                      | 46                        | PK       | 0,1      | 9,87   |
| 2    |         | 246,493                | H            |                | 35,06                      | 46                        | PK       | 0,1      | 10,94  |

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

| Frequency of Emission<br>(MHz) | Field Strength<br>(microvolts/meter) | Field Strength<br>(dBmicrovolts/meter) |
|--------------------------------|--------------------------------------|----------------------------------------|
| 30 – 88                        | 100                                  | 40.0                                   |
| 88 – 216                       | 150                                  | 43.5                                   |
| 216 – 960                      | 200                                  | 46.0                                   |
| Above 960                      | 500                                  | 54.0                                   |

Test equipment used: ETSTW-RE 015, ETSTW-RE 016, ETSTW-RE 017, ETSTW-CS 001,  
ETSTW-RE 026, ETSTW-RE 003, ETSTW-RE 025

Comment: see attached diagram

### 3.9 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

| Frequency | Level (dBμV)     |                  |
|-----------|------------------|------------------|
|           | quasi-peak       | average          |
| 150 kHz   | lower limit line | Lower limit line |

#### Measurement Result: “\_ Fin AV”

(active mode)

| Frequency Marker [MHz] | Type | Corrected Reading [dBuV] | Compliance AVLimit [dBuV] | BW [MHz] | Margin(AV) |
|------------------------|------|--------------------------|---------------------------|----------|------------|
| 0,16                   | N    | 8,21                     | 54                        | 0,01     | 45,79      |
| 0,325                  | N    | 4,33                     | 48,4                      | 0,01     | 44,07      |
| 18,625                 | N    | 13,21                    | 50                        | 0,01     | 36,79      |
| 19,87                  | N    | 8,26                     | 50                        | 0,01     | 41,74      |

| Frequency Marker [MHz] | Type | Corrected Reading [dBuV] | Compliance AVLimit [dBuV] | BW [MHz] | Margin(AV) |
|------------------------|------|--------------------------|---------------------------|----------|------------|
| 0,16                   | L1   | 7,84                     | 54                        | 0,01     | 46,16      |
| 0,325                  | L1   | 4,6                      | 48,4                      | 0,01     | 43,8       |
| 18,625                 | L1   | 11,74                    | 50                        | 0,01     | 38,26      |
| 19,87                  | L1   | 7,28                     | 50                        | 0,01     | 42,72      |



Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

**Measurement Result: “\_ Fin QP”**

(active mode)

| Frequency Marker [MHz] | Type | Corrected Reading [dBuV] | Compliance QPLimit [dBuV] | BW [MHz] | Margin(QP) |
|------------------------|------|--------------------------|---------------------------|----------|------------|
| 0,16                   | N    | 14,33                    | 64                        | 0,01     | 49,67      |
| 0,325                  | N    | 12,84                    | 58,4                      | 0,01     | 45,56      |
| 18,625                 | N    | 21,32                    | 60                        | 0,01     | 38,68      |
| 19,87                  | N    | 19,83                    | 60                        | 0,01     | 40,17      |

| Frequency Marker [MHz] | Type | Corrected Reading [dBuV] | Compliance QPLimit [dBuV] | BW [MHz] | Margin(QP) |
|------------------------|------|--------------------------|---------------------------|----------|------------|
| 0,16                   | L1   | 14,33                    | 64                        | 0,01     | 49,67      |
| 0,325                  | L1   | 13,62                    | 58,4                      | 0,01     | 44,78      |
| 18,625                 | L1   | 19,66                    | 60                        | 0,01     | 40,34      |
| 19,87                  | L1   | 16,33                    | 60                        | 0,01     | 43,67      |

**Measurement Result: “\_ Fin AV”**

(charging mode)

| Frequency Marker [MHz] | Type | Corrected Reading [dBuV] | Compliance AVLlimit [dBuV] | BW [MHz] | Margin(AV) |
|------------------------|------|--------------------------|----------------------------|----------|------------|
| 0,165                  | N    | 9,6                      | 54                         | 0,01     | 44,4       |
| 1,515                  | N    | 2,6                      | 48,4                       | 0,01     | 45,8       |
| 9,555                  | N    | 2,8                      | 50                         | 0,01     | 47,2       |
| 24,575                 | N    | 4,1                      | 50                         | 0,01     | 45,9       |

| Frequency Marker [MHz] | Type | Corrected Reading [dBuV] | Compliance AVLlimit [dBuV] | BW [MHz] | Margin(AV) |
|------------------------|------|--------------------------|----------------------------|----------|------------|
| 0,165                  | L1   | 9,5                      | 54                         | 0,01     | 44,5       |
| 1,185                  | L1   | 2,6                      | 48,4                       | 0,01     | 45,8       |
| 13,205                 | L1   | 3,6                      | 50                         | 0,01     | 46,4       |
| 16,98                  | L1   | 3,1                      | 50                         | 0,01     | 46,9       |

Registration number: W6M20508-6150-C-1

FCC ID: MQ5RF-688DTX

**Measurement Result: “\_ Fin QP”**

(charging mode)

| Frequency Marker [MHz] | Type | Corrected Reading [dBuV] | Compliance QPLimit [dBuV] | BW [MHz] | Margin(QP) |
|------------------------|------|--------------------------|---------------------------|----------|------------|
| 0,165                  | N    | 13,6                     | 64                        | 0,01     | 50,4       |
| 1,515                  | N    | 7,7                      | 58,4                      | 0,01     | 50,7       |
| 9,555                  | N    | 7,9                      | 60                        | 0,01     | 52,1       |
| 24,575                 | N    | 9,4                      | 60                        | 0,01     | 50,6       |


| Frequency Marker [MHz] | Type | Corrected Reading [dBuV] | Compliance QPLimit [dBuV] | BW [MHz] | Margin(QP) |
|------------------------|------|--------------------------|---------------------------|----------|------------|
| 0,165                  | L1   | 13,3                     | 64                        | 0,01     | 50,7       |
| 1,185                  | L1   | 7,7                      | 58,4                      | 0,01     | 50,7       |
| 13,205                 | L1   | 8,3                      | 60                        | 0,01     | 51,7       |
| 16,98                  | L1   | 8,2                      | 60                        | 0,01     | 51,8       |

**Limits:**

| Frequency of Emission (MHz) | Conducted Limit (dBuV) |          |
|-----------------------------|------------------------|----------|
|                             | Quasi Peak             | Average  |
|                             | 66 to 56               | 56 to 46 |
|                             | 56                     | 46       |
|                             | 60                     | 50       |

Test equipment used: ETSTW-CE 004, ETSTW-CE 001, ETSTW-RE 023

Comment: see attached diagram



Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

## **Appendix**

- A Peak Output Power
- B Spurious Emissions radiated
- C Band Edge Measurement
- D Minimum 6dB Bandwidth
- E Peak Power Spectral Density
- F Radiated Emissions from Receiver Section
- G Power Line Conducted Emission
- H Pictures




Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

## **Appendix A**


### **Peak Output Power**

**The measurement diagram are wideband pre-scan results; only for reference.**




22.BMP

Date: 7.SEP.2005 14:18:11



22.BMP

Date: 7.SEP.2005 14:16:32




22.BMP

Date: 7.SEP.2005 14:17:25

## Carrier power (Field Strength)

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL025  
Freq: 2.409GHz, Emax: 101.73dBμV/m, RBW: 1MHz






## Carrier power (Field Strength)

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL025  
Freq: 2.409GHz, Emax: 97.21dBµV/m, RBW: 1MHz



## Carrier power (Field Strength)

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL025  
Freq: 2.447GHz, Emax: 102.78dBμV/m, RBW: 1MHz



## Carrier power (Field Strength)

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL025  
Freq: 2.447GHz, Emax: 98.79dBµV/m, RBW: 1MHz



## Carrier power (Field Strength)

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL025  
Freq: 2.474GHz, Emax: 104.98dBμV/m, RBW: 1MHz



## Carrier power (Field Strength)

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL025  
Freq: 2.474GHz, Emax: 101.05dBμV/m, RBW: 1MHz





Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

## **Appendix B**


Spurious Emissions radiated

**The measurement diagram are wideband pre-scan results; only for reference.**

## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HK 116  
Freq: 161.503MHz, Emax: 28.80dBµV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HK 116  
Freq: 196.934MHz, Emax: 29.08dBµV/m, RBW: 100kHz






## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL 223,  
Freq: 943.888MHz, Emax: 36.57dBμV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL 223,  
Freq: 996.794MHz, Emax: 37.42dBμV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, amplif.  
Freq: 2.395GHz, Emax: 53.86dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, amplif.  
Freq: 2.395GHz, Emax: 52.36dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 7.230GHz, Emax: 62.07dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 7.238GHz, Emax: 58.58dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 11.711GHz, Emax: 49.06dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 11.976GHz, Emax: 48.84dBμV/m, RBW: 1MHz






## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 17.808GHz, Emax: 52.77dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 17.723GHz, Emax: 52.87dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, amplif.  
Freq: 26.057GHz, Emax: 51.92dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Low Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, amplif.  
Freq: 26.347GHz, Emax: 51.97dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HK 116  
Freq: 198.297MHz, Emax: 28.26dBµV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HK 116  
Freq: 192.164MHz, Emax: 29.25dBμV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL 223,  
Freq: 972.745MHz, Emax: 36.88dBμV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL 223,  
Freq: 243.287MHz, Emax: 37.36dBμV/m, RBW: 100kHz






## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, amplif.  
Freq: 3.800GHz, Emax: 47.00dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, amplif.  
Freq: 3.739GHz, Emax: 45.94dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 7.335GHz, Emax: 61.52dBμV/m, RBW: 1MHz




| Frequency (MHz) | AV (dBμV/m) | Limit (dBμV/m) | Margin (dBμV/m) |
|-----------------|-------------|----------------|-----------------|
| 4889.779559     | 45.37       | 54             | 8.63            |
| 7334.669339     | 51.70       | 54             | 2.3             |

## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 7.343GHz, Emax: 59.55dBμV/m, RBW: 1MHz




| Frequency (MHz) | AV (dBμV/m) | Limit (dBμV/m) | Margin (dBμV/m) |
|-----------------|-------------|----------------|-----------------|
| 7342.685371     | 49.53       | 54             | 4.47            |

## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 11.623GHz, Emax: 48.93dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 11.808GHz, Emax: 49.13dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 17.699GHz, Emax: 53.04dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 17.808GHz, Emax: 52.78dBμV/m, RBW: 1MHz






## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, amplif.  
Freq: 25.512GHz, Emax: 51.84dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D Middle Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, amplif.  
Freq: 25.291GHz, Emax: 52.57dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HK 116  
Freq: 161.503MHz, Emax: 28.42dBµV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HK 116  
Freq: 199.659MHz, Emax: 30.93dBμV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL 223,  
Freq: 993.587MHz, Emax: 37.58dBμV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL 223,  
Freq: 972.745MHz, Emax: 36.97dBμV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, amplif.  
Freq: 2.489GHz, Emax: 57.75dBµV/m, RBW: 1MHz




| Frequency (MHz) | AV (dBµV/m) | Limit (dBµV/m) | Margin (dBµV/m) |
|-----------------|-------------|----------------|-----------------|
| 2488.675351     | 52.78       | 54             | 1.22            |

## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, amplif.  
Freq: 2.487GHz, Emax: 56.76dBμV/m, RBW: 1MHz




| Frequency (MHz) | AV (dBμV/m) | Limit (dBμV/m) | Margin (dBμV/m) |
|-----------------|-------------|----------------|-----------------|
| 2486.605210     | 52.18       | 54             | 1.82            |



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 7.423GHz, Emax: 62.67dBμV/m, RBW: 1MHz




| Frequency (MHz) | AV (dBμV/m) | Limit (dBμV/m) | Margin (dBμV/m) |
|-----------------|-------------|----------------|-----------------|
| 4945.891784     | 48.10       | 54             | 5.9             |
| 7422.845691     | 52.69       | 54             | 1.31            |

## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 7.423GHz, Emax: 59.54dBμV/m, RBW: 1MHz




| Frequency (MHz) | AV (dBμV/m) | Limit (dBμV/m) | Margin (dBμV/m) |
|-----------------|-------------|----------------|-----------------|
| 4945.891784     | 46.28       | 54             | 7.72            |
| 7422.845691     | 49.77       | 54             | 4.23            |

## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 11.607GHz, Emax: 49.22dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 11.776GHz, Emax: 49.39dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 17.784GHz, Emax: 53.65dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.  
Freq: 17.711GHz, Emax: 52.96dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, amplif.  
Freq: 25.614GHz, Emax: 51.62dBμV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D High Channel  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: HL025, amplif.  
Freq: 25.393GHz, Emax: 53.04dBμV/m, RBW: 1MHz








Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX


## **Appendix C**

### Band Edge Measurement




22.BMP

Date: 7.SEP.2005 13:35:52



22.BMP


Date: 7.SEP.2005 13:43:02



Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX


## **Appendix D**

### Minimum 6dB Bandwidth




22.BMP

Date: 7.SEP.2005 14:09:11



22.BMP

Date: 7.SEP.2005 13:44:23



22.BMP

Date: 7.SEP.2005 13:41:06




Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

## **Appendix E**


### Peak Power Spectral Density






POWER DENSITY 2410 MHz

Date: 15.SEP.2005 09:41:10



POWER DENSITY 2437 MHz

Date: 15.SEP.2005 09:44:50



POWER DENSITY 2473 MHz

Date: 15.SEP.2005 09:32:23



Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

## **Appendix F**


### Radiated Emissions from Receiver Section

**The measurement diagram are wideband pre-scan results; only for reference.**

## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HK 116  
Freq:180.922MHz Emax:26.63dBμV/m RBW: 100 kHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HK 116  
Freq:180.922MHz Emax:30.71dBμV/m RBW: 100 kHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.  
Freq:929.459MHz Emax:36.58dBμV/m RBW: 100 kHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.  
Freq:964.729MHz Emax:36.49dBμV/m RBW: 100 kHz






## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 3 VDC ( 1.5v Battery x 2 )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL25, ampl.  
Freq:2.335GHz Emax:47.50dBμV/m RBW: 1 MHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 3 VDC ( 1.5v Battery x 2 )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL25, ampl.  
Freq:2.335GHz Emax:45.80dBμV/m RBW: 1 MHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 3 VDC ( 1.5v Battery x 2 )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL25, ampl.  
Freq:4.649GHz Emax:50.12dBμV/m RBW: 1 MHz



**Field Strength under normal conditions**

**FCC RULES PART 15, SUBPART B**


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 3 VDC ( 1.5v Battery x 2 )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL25, ampl.  
Freq:4.601GHz Emax:51.36dBμV/m RBW: 1 MHz



**Field Strength under normal conditions**

**FCC RULES PART 15, SUBPART B**


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 3 VDC ( 1.5v Battery x 2 )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL25, ampl.  
Freq:11.631GHz Emax:52.38dBμV/m RBW: 1 MHz



**Field Strength under normal conditions**

**FCC RULES PART 15, SUBPART B**


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 3 VDC ( 1.5v Battery x 2 )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL25, ampl.  
Freq:11.535GHz Emax:52.56dBuV/m RBW: 1 MHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 3 VDC ( 1.5v Battery x 2 )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL25, ampl.  
Freq:17.964GHz Emax:53.56dBμV/m RBW: 1 MHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 3 VDC ( 1.5v Battery x 2 )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL25, ampl.  
Freq:17.772GHz Emax:53.20dBμV/m RBW: 1 MHz






## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HK 116  
Freq:161.503MHz Emax:28.68dBμV/m RBW: 100 kHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HK 116  
Freq:200.000MHz Emax:30.25dBμV/m RBW: 100 kHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.  
Freq:959.920MHz Emax:36.46dBμV/m RBW: 100 kHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.  
Freq:918.236MHz Emax:36.62dBμV/m RBW: 100 kHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HK 116  
Freq:180.922MHz Emax:28.32dBμV/m RBW: 100 kHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HK 116  
Freq:180.922MHz Emax:30.26dBμV/m RBW: 100 kHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.  
Freq:894.188MHz Emax:36.67dBμV/m RBW: 100 kHz



## Field Strength under normal conditions

### FCC RULES PART 15, SUBPART B

EUT: 2.4GHz Digital Wireless Headphone System  
MODEL NO.: RF-6888D  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Test Site / Operator: ETS / Orville Chang  
Temperature/Voltage: Temp.: 23°C/ Unom.: 12 VDC ( ac / dc Adaptor )  
Test Specification: according to subpart B  
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.  
Freq:971.142MHz Emax:36.44dBμV/m RBW: 100 kHz







Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

## **Appendix G**


### Power Line Conducted Emission

**The measurement diagram are wideband pre-scan results; only for reference.**

# EMI voltage test in the ac-mains according to FCC Part 15

## Class B


EUT: 2.4GHz Digital Wireless Headphone System  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Operating Condition: Unom : 12 VDC ( ac / dc Adaptor ) , Tnom : 23 °C  
Test Site: ETS  
Operator: Orville Chang  
Test Specification: V-network: ESH3-Z5 N  
Comment: model: RF-6888D mode: active  
Start of Test: 9/8/05 / 8:37:27PM



# EMI voltage test in the ac-mains according to FCC Part 15

## Class B


EUT: 2.4GHz Digital Wireless Headphone System  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Operating Condition: Unom : 12 VDC ( ac / dc Adaptor ) , Tnom : 23 °C  
Test Site: ETS  
Operator: Orville Chang  
Test Specification: V-network: ESH3-Z5 L1  
Comment: model: RF-6888D mode: active



EMI voltage test in the ac-mains according to FCC Part 15

Class B


EUT: 2.4GHz Digital Wireless Headphone System  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Operating Condition: Unom : 12 VDC ( AC / DC Adaptor ) , Tnom : 23 °C  
Test Site: ETS  
Operator: Dennis  
Test Specification: V-network: ESH3-Z5 N  
Comment: model: RF-6888D mode: CHARGING MORD




# EMI voltage test in the ac-mains according to FCC Part 15

## Class B

EUT: 2.4GHz Digital Wireless Headphone System  
Approval Holder: TELEAN TECHNOLOGY LTD.  
Operating Condition: Unom : 12 VDC ( AC / DC Adaptor ) , Tnom : 23 °C  
Test Site: ETS  
Operator: Dennis  
Test Specification: V-network: ESH3-Z5 L1  
Comment: model: RF-6888D mode: CHARGING MORD





Registration number: W6M20508-6150-C-1  
FCC ID: MQ5RF-688DTX

## **Appendix H**

### Pictures