

ETS Dr.GenZ Taiwan PS Co., Ltd.

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679

Accredited Testing Laboratory

A2LA Cert.No.: 2300.01

FCC TEST - REPORT

FCC Part 15 C for IEEE 802.11 b device

FCC ID: MQ5RF-777D-TX

Test report no.: W6M20505-5937-C-1

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	NOTES	3
1.2	TESTING LABORATORY	4
1.2.1	Location	4
1.2.2	Details of accreditation status	4
1.3	DETAILS OF APPROVAL HOLDER	4
1.4	APPLICATION DETAILS	5
1.5	GENERAL INFORMATION OF TEST ITEM	5
1.6	TEST STANDARDS	6
2	TECHNICAL TEST	7
2.1	SUMMARY OF TEST RESULTS	7
2.2	TEST ENVIRONMENT	7
2.3	TEST EQUIPMENT LIST	8
2.4	GENERAL TEST PROCEDURE	12
3.1	PEAK OUTPUT POWER (TRANSMITTER)	15
3.2	EQUIVALENT ISOTROPIC RADIATED POWER	16
3.2.1	Transmitter	16
3.3	RF EXPOSURE COMPLIANCE REQUIREMENTS	16
3.4	TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS	17
3.5	SPURIOUS EMISSIONS (TX)	18
3.6	MINIMUM 6 dB BANDWIDTH	22
3.7	PEAK POWER SPECTRAL DENSITY	23
3.8	RADIATED EMISSIONS FROM RECEIVER SECTION OF TRANSCEIVER	24
3.9	POWER LINE CONDUCTED EMISSION	25



Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has Passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that is performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the ETS DR. GENZ TAIWAN PS CO., LTD.


Specific Conditions:

Usage of the hereunder tested device in combination with other integrated or external antennas requires at least additional output power measurements, spurious emission measurements, conducted emission measurements (AC supply lines) and radio frequency exposure evaluations for each individual configuration performed, for certification by FCC.


The test sample is able to work according IEEE 802.11 b.

This report is related to FCC Part 15 C (DSSS device).

Tester:

15.06.2005	Jay Chaing	
Date	ETS-Lab. Name	Signature

Technical responsibility for area of testing:

15.06.2005	Steven Chung	
Date	ETS Name	Signature

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Shuang Sing Village,
LiShuei Rd., Wanli Township,
Taipei County 207, Taiwan (R.O.C.)

Company

ETS Dr.Genx Taiwan PS Co., Ltd.
6F, NO. 58, LANE 188, RUEY-KUANG RD.
NEIHU, TAIPEI 114, TAIWAN R.O.C.
Tel : 886-2-66068877
Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA-registration number: 2300.01

FCC filed test laboratory Reg. No. 930600

Industry Canada filed test laboratory Reg. No. IC 5679

1.3 Details of approval holder

Name	: TELEAN TECHNOLOGY LTD.
Street	: 1601-3, 16/F, FO Tan Industrial Center, 26-28 Au Pui Wan Street
Town	: Fo Tan Shatin
Country	: N.T.HONG KONG
Telephone	: +(852)2693-2773
Fax	: +(852)2693-1526
Contact	: Mr. Alan Mok
Telephone	: +(852)2693-2773

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

1.4 Application details

Date of receipt of application : 27.05.2005
Date of receipt of test item : 31.05.2005
Date of test : from 01.06.2004 to 13.06.2005

1.5 General information of Test item

Type of test item : 2.4GHz Digital Wireless Headphone System
Model Number : RF-777D
Hardware : 1.0
Software : 1.0
Serial number : without
Photos : see Annex

Technical data

Frequency band : 2.4 GHz – 2.4835 GHz
Frequency (ch A) : 2.410 GHz
Frequency (ch B) : 2.447 GHz
Frequency (ch C) : 2.472 GHz
Number of Channels : 8
Operation modes : simplex
Modulation Type : FSK

Fixed point-to-point operation : ☐ Yes / ☒ No
Type of Antenna : inverted-F / omni-directional
Antenna gain of Antenna : -3 dBi
Antenna Power supply : 120VAC (AC/DC ADAPTER)



Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

Host device: none

Classification :

Fixed Device	☐
Mobile Device (Human Body distance > 20cm)	☒
Portable Device (Human Body distance < 20cm)	☐

Transmitter

Unom

Power (ch A) : Conducted: 9.24 dBm
Power (ch B) : Conducted: 8.61 dBm
Power (ch C) : Conducted: 8.14 dBm

Manufacturer:
(if applicable)

Name : ./.
 Street : ./.
 Town : ./.
 Country : ./.

1.6 Test standards

Technical standard : FCC RULES PART 15 / SUBPART C § 15.247

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified in 2.5 were ascertained in the course of the tests performed.



2.2 Test environment

Temperature	: 23 °C
Relative humidity content	: 20 ... 75 %
Air pressure	: 86 ... 103 kPa
Details of power supply	: 120 VAC (ac/dc adaptor)
Extreme conditions parameters	: --

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2005/11/8
ETSTW-CE 002	PREREULATOR MODE DC POWER SUPPLY				
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	
ETSTW-CE 004	ZWEILEITER-V-NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2006/11/8
ETSTW-CE 005	Line-Impedance Stabilisation Network	NNBM 8126D	137	Schwarzbeck	2006/11/3
ETSTW-CE 006	IMPULS-BEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2006/11/10
ETSTW-CE 007	SPECTRUM ANALYZER 5GHz	FSB	849670/001	R&S	
ETSTW-CE 008	ABSORBING CLAMP	MDS 21	3469	ABSORPTIONS-MESSWANDLER-ZANGE	2006/11/4
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2005/5/10
ETSTW-CE 010	Comb Generator-conducted			ETS	
ETSTW-CE 011	Power Line Conducted Emission Only			ETS	
ETSTW-CE 012	Dual-Phase-V-Network	NNB-2/16Z	03/10201	Telemeter	2006/4/11
ETSTW-CS 001	SIGNAL GENERATOR	SMX	849254/003	R&S	2005/10/31
ETSTW-CS 002	COUPLING AND DECOUPLING NETWORK	CDN S751	19263	CHAFFNER	2006/11/3
ETSTW-CS 003	COUPLING AND DECOUPLING NETWORK	CDN T400	19820	CHAFFNER	2006/11/3
ETSTW-CS 004	COUPLING AND DECOUPLING NETWORK	CDN M016	20053	CHAFFNER	2006/11/3
ETSTW-CS 005	RF Power Amplifier	100A250A	306547	AR	2005/11/3
ETSTW-CS 006	Terminal 50Ω Load	50T-116 M		JFW	
ETSTW-CS 007	Terminal 50Ω Load	50T-116 F		JFW	
ETSTW-CS 008	6 dB Attenuator	HFP-5100-3/06 N M/F	2010876106		
ETSTW-RE 001	Controller	CD 1000	C01000/154/867 /004/L	Heinrich Deisel	
ETSTW-RE 002	Function Generator	33220A	MY43004982	Agilent	2005/11/3
ETSTW-RE 003	EMI TEST RECEIVER	ESI	831438/001	R&S	2005/11/16
ETSTW-RE 004	EMI TEST RECEIVER	ESI	831459/012	R&S	2005/11/9
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	2005/11/1
ETSTW-RE 008	Controller	HD100	C0100-L/047/6670703/L	Heinrich Deisel	
ETSTW-RE 009	Controller	HD100	100/341	Heinrich Deisel	
ETSTW-RE 010	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070181	MOTECH	

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

ETSTW-RE 011	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070165	MOTECH	
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0036	397	K&L	
ETSTW-RE 014	DUAL TRACKING WITH 5V FIXED	GPC-3030D		GW	
ETSTW-RE 015	ANTENNA	HK116	841489/003	R&S	
ETSTW-RE 016	ANTENNA	HL223	848953/006	R&S	
ETSTW-RE 017	ANTENNA	HL025	352886/001	R&S	
ETSTW-RE 018	ANTENNA	AT4560	27212	AR	2006/11/7
ETSTW-RE 019	ANTENNA , HORN	22240-25	121074	FM	
ETSTW-RE 020	MICROWAVE HORN ANTENNA	AT4002A	306915	AR	
ETSTW-RE 021	SWEEP GENERATOR	SWM05	835130/010	R&S	2005/11/10
ETSTW-RE 022	AMPLIFIER	8447D	2944A09837	Agilent	2005/11/1
ETSTW-RE 023	Shielded room	SR 1		Frankonia	
ETSTW-RE 024	Anechoic Chamber	CHC 1		Frankonia	
ETSTW-RE 025	Anechoic Chamber	CHC 2		Frankonia	
ETSTW-RE 026	Open Area Test Site	10m		ETS	
ETSTW-RE 027	Passive Loop Antenna	6512	34563	EMCO	2006/6/29
ETSTW-RE 028	Log-Periodic DipoleArray Antenna	3148	34429	EMCO	2006/6/14
ETSTW-RE 029	Biconical Antenna	3109	33524	EMCO	2006/6/16
ETSTW-RE 030	Double-Ridged Waveguide Horn Antenna	3117	35224	EMCO	2006/5/4
ETSTW-RE 031	Comb Generator-radiated			ETS	
ETSTW-RE 032	Millivoltmeter	URV 55	849086/013	R&S	2005/11/17
ETSTW-RE 033	4CH 1GHz 5GS/s DSO	WAVERUNNER 6100A	LCRY0604P14 508	LeCory	
ETSTW-RE 034	Power Sensor	URV5-Z4	839313/006	R&S	2005/11/17
ETSTW-RE 035	1.5GHz Active Voltage Probe	HFP1500	2332	LeCory	
ETSTW-RE 036	100MHz High Voltage Diff Probe	ADP305	3305	LeCory	
ETSTW-RE 037	Log-Periodic DipoleArray Antenna	3148	00034546	EMCO	2006/11/17
ETSTW-RE 038	Log-Periodic DipoleArray Antenna	3148	00034547	EMCO	2006/11/17
ETSTW-RE 039	Biconical Antenna	3110B	41760	EMCO	2006/11/17
ETSTW-RE 040	Biconical Antenna	3110B	41761	EMCO	2006/11/17
ETSTW-RE 041	Anechoic Chamber	CHC 3		Frankonia	
ETSTW-RE 042	ANTENNA	HK116	100172	R&S	2007/1/13
ETSTW-RE 043	ANTENNA	HL223	100166	R&S	2006/4/15
ETSTW-RE 044	ANTENNA	HL050	100094	R&S	
ETSTW-RE 048	Triple Loop Antenna	HXYZ 9170	HXYZ 9170-134	Schwarzbeck	2006/3/21

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

ETSTW-EMI 001	HARMONICS 1000	HAR1000-1P	93	EMC-PARTNER	2005/11/17
ETSTW-EMS 001	Clamp BASELSTRASSE 160 CH-4242 LAUFEN	CN-EFT1000	354	EMC-PARTNER	2005/11/1
ETSTW-EMS 002	Frequency Converter	YF-6020	0308014		
ETSTW-EMS 003	EMC Immunity Test System	TRA2000IN6	579	EMC-PARTNER	2005/11/1
ETSTW-EMS 004	ESD generator minizap	ESD2000	016	EMC-PARTNER	2005/11/1
ETSTW-EMS 005	Attenautor (50Ω)	VERI50	051	EMC-PARTNER	2006/8/30
ETSTW-EMS 006	Attenautor (1 KΩ)	VERI1K	019	EMC-PARTNER	2006/10/20
ETSTW-EMS 007	20GΩ Divider	ESD-VERI-V	021	EMC-PARTNER	2006/3/16
ETSTW-RS 001	14" COLOR VIDEO MONITOR	TP-1480HR	P009799	TOPICA	
ETSTW-RS 002	14" COLOR VIDEO MONITOR	TP-1480HR	P009814	TOPICA	
ETSTW-RS 003	RF Power Amplifier	30S1G3	306933	AR	
ETSTW-RS 004	RF Power Amplifier	150W1000	307009	AR	2005/11/18
ETSTW-RS 005	Electric Field Probe Type 8.3	EMR-20	BN 2244/20	GW	2005/9/3
ETSTW-RS 006	SIGNAL GENERATOR	SML03	101551	R&S	2005/11/15
ETSTW-RS 007	AUDIO ANALYZER	UPA3	843458/029	R&S	2005/11/15
ETSTW-EMS 008	Safety Test Solutions	ELT-400	E-0039	Narda	2006/1/4
ETSTW-EMS 009	Magnetic Field Antenna	MF1000-1	104	EMC-PARTNER	2006/12/2
ETSTW-GSM 01	SIM Simulator	IT3	B2004-50106	ORGA Testsystems GmbH	
ETSTW-GSM 02	Universal Radio Communication Tester	CMU 200	103489	R&S	
ETSTW-GSM 03	Agilent 8960 Test Set 1	E5515C	GB44052675	Agilent	2006/7/14
ETSTW-GSM 04	Agilent 8960 Test Set 2	E5515C	GB44052665	Agilent	2006/7/14
ETSTW-GSM 05	Agilent 8960 Test Set 3	E5515C	GB44052852	Agilent	2006/7/17
ETSTW-GSM 06	Agilent 8960 Test Set 4	E5515C	GB44052984	Agilent	2006/7/16
ETSTW-GSM 07	Agilent 8960 Test Set 5	E5515C	GB44052658	Agilent	2006/7/14
ETSTW-GSM 08	Agilent 8960 Test Set 6	E5515C	GB44052666	Agilent	2006/7/16
ETSTW-GSM 09	Controler PC	Dell GX 270	700F61J	Dell	
ETSTW-GSM 10	Combiner Wessex / Anite	B4605/100	053	Wessex / Anite	07.06
ETSTW-GSM 11	GSM 850,900,1800,1900 Test system	TS8950G		Rohde & Schwarz	11.05
ETSTW-GSM 12	Acoustical Calibrator	4231	2463874	Brüel&Kjær	

Registration number: W6M20505-5937-C-1

FCC ID: MQ5RF-777D-TX

ETSTW-GSM 13	Conditioning Amplifier	2690--0S2	2437856	Brüel&Kjær	
ETSTW-GSM 14	Telephone Test Head	4602B	2465324	Brüel&Kjær	2005/11/17
ETSTW-GSM 15	Mouth Simulator	4227	2462516	Brüel&Kjær	
ETSTW-GSM 16	TEMP.&HUMIDITY CHAMBER	GTH-120-40-1P-U	MAA0501002	GIANT FORCE	12/290/200 5
ETSTW-GSM 17	ANTENNT COPLER	CMU-Z10	100988	R&S	

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2003 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2003 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23°C with a humidity of 40 %.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz)	METER READING + ACF + CABLE LOSS (to the receiver) = FS
33	20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m

The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2000 Section 13.1.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by ETS Dr.Genx Taiwan PS Co., Ltd. at the registered open field test site located at No.5-1, Shuang Sing Village, LiShuei Rd., Wanli Township, Taipei County 207, Taiwan (R.O.C.) The Registration Number: 930600.

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor = $20 \log (\text{dwell time}/T)$

T = 100ms when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANTENNA & GROUND:

This unit uses inverted-F / omni-directional. (see photo).



Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)(3)	☒	☒	☐
Equivalent radiated Power	15.247(b)(3)	☒	☒	☐
Spurious Emissions radiated – Transmitter operating	15.247(c)	☒	☒	☐
Band Edge Measurement	15.247(c)	☒	☒	☐
Minimum 6 dB Bandwidth	15.247(a)(2)	☒	☒	☐
Peak Power Spectral Density	15.247(d)	☒	☒	☐
Radiated Emission from Digital Part and Receiver L.O.	15.109	☒	☒	☐
Power Line Conducted Emission	15.207	☒	☒	☐

The follows is intended to leave blank.

Registration number: W6M20505-5937-C-1

FCC ID: MQ5RF-777D-TX

3.1 Peak Output Power (transmitter)

FCC Rule: 15.247(b)(3)

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

Test condition		Conducted Power		
		Channel A	Channel B	Channel C
		[dBm]	[dBm]	[dBm]
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120 \text{ V}$	9.24	8.61	8.14
Measurement uncertainty		< 3 dB		

Test condition $T_{nom} = 23^{\circ}\text{C}$, $V_{nom} = 120 \text{ V}$	Signal Field strength TX highest power mode dB $\mu\text{V/m}$
Frequency [MHz]	
2472	104.14
Measurement uncertainty	< 3 dB

Remarks: The diagrams for the field strength measurements are included in Appendix.

Limits:

Frequency MHz	Power dBm
902 - 928	30
2400 – 2483.5	30
5725 – 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to-point operation consider §15.247 (b)(4)

Test equipment used: ETSTW-RE 003 , ETSTW-RE 012 , ETSTW-RE 017 , ETSTW-RE 024

Registration number: W6M20505-5937-C-1

FCC ID: MQ5RF-777D-TX

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain

EIRP = 9.24 dBm + -3 dBi

= 6.24 dBm

Limit: EIRP = +36 dBm for Antenna gain <6dBi

3.2.1 Transmitter

Integral Antenna:

At the transmitter the measurement was transacted with the modulation declared by the manufacturer and the maximum available output power of the EUT.

In this arrangement the EUT fulfils the requirements of the FCC rules § 15.247, subpart C, section b.

3.3 RF Exposure Compliance Requirements

The test sample is a WLAN access point intended for fixed installation.

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{PG}{4\pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain G = AG-D

Item	Unit	Value	Remarks
P	mW	8.4	Peak value
D	dB		
AG	dBi		
G		1.0	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.0016711	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm ²)
1500 – 100.000	1,0

Registration number: W6M20505-5937-C-1

FCC ID: MQ5RF-777D-TX

3.4 Transmitter Radiated Emissions in Restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 1000 MHz.

For radiated emission tests, the analyzer setting was as followings:

Frequency $\leq$ 1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements)

Frequency $>$ 1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements)

Frequency $>$ 1 GHz , RBW:1 MHz , VBW: 100Hz (Average measurements)

Limits.

For frequencies below 1GHz:

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of DSSS Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the setting shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = $20 \log (\text{dwell time} / 100\text{ms})$

No duty cycle correction was added to the reading.

$54.0\text{dB } \mu\text{V/m} + 20 \text{ dB} = 74 \text{ dB } \mu\text{V/m}$

Remarks: see attached diagrams

Test equipment used: ETS 0125, ETS 0271

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

3.5 Spurious Emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

FCC Rule: 15.247(c), 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies below 1GHz:

Max. reading – 20 dB

104.14dB μ V/m- 20 dB= 84.14dB μ V/m

Guidance on Measurement of DSSS Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty Cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

For frequencies above 1GHz (Peak measurements).

Limit = max. aver. Reading-20dB+20dB(because Peak detector is used)

84.14dB μ V/m

For frequencies above 1GHz (Average measurements).

Max. reading – 20dB

No duty cycle correction was added to the reading

104.14dB μ V/m- 20 dB= 84.14 B μ V/m

Remarks: see attached diagrams

Test equipment used: ETSTW-RE 003 , ETSTW-RE 012 , ETSTW-RE 015 , ETSTW-RE 016 , ETSTW-RE 017 , ETSTW-RE 024

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance with point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value and exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Duty-Cycle Correction Factor".


Summary table with radiated data of the test plots

Freq,	Used Ch,	Frequency Marker [MHz]	Polarization	corrections dB	Corrected Reading [dBuV/m]	Compliance Limit [dBuV/m]	Detector	BW [MHz]	Margin
1	1	73.607	H		19.33	40	PK	0.1	20.67
1	1	73.607	V		27.09	40	PK	0.1	12.91
1	1	163.206	H		26.86	43.5	PK	0.1	16.64
1	1	163.206	V		32.1	43.5	PK	0.1	11.4
2	1	265.730	H		27.39	46	PK	0.1	18.61
2	1	265.730	V		32.79	46	PK	0.1	13.21
2	1	405.210	H		30.67	46	PK	0.1	15.33
2	1	405.210	V		29.94	46	PK	0.1	16.06
3	1	2395.190	H		51.97	84.14	PK	1	29.17
3	1	2395.190	V		52.15	84.14	PK	1	28.99
4	1	4817.635	H		52.14	54	PK	1	1.86
4	1	4817.635	V		53.11	54	PK	1	0.89
4	1	7230.460	H		54.33	84.14	PK	1	26.81
4	1	7230.460	V		56.91	84.14	PK	1	24.23
1	5	73.675	H		19.01	40	PK	0.1	20.99
1	5	73.674	V		27.87	40	PK	0.1	12.13
1	5	163.204	H		30.87	43.5	PK	0.1	12.63
1	5	163.204	V		32.21	43.5	PK	0.1	11.29
2	5	260.921	H		32.97	46	PK	0.1	13.03
2	5	260.921	V		34.58	46	PK	0.1	11.42
3	5	3933.867	H		44.11	54	PK	1	9.89
3	5	3933.867	V		45.72	54	PK	1	8.28

Registration number: W6M20505-5937-C-1

FCC ID: MQ5RF-777D-TX

4	5	4893.114	H		52.87	54	PK	1	31.27
4	5	4893.114	V		56.26	74	PK	1	27.88
4	5	4893.114	V		48.3	54	AV	1	5.7
4	5	7339.522	H		54.16	74	PK	1	19.84
4	5	7339.522	H		43.1	54	AV	1	10.9
4	5	7339.522	V		55.07	74	PK	1	18.93
4	5	7339.522	V		46.1	54	AV	1	7.9
5	5	11494.989	H		49.05	54	PK	1	4.95
5	5	11494.989	V		48.36	54	PK	1	5.64
6	5	17831.663	H		53.44	54	PK	1	0.56
6	5	17831.663	V		53.15	54	PK	1	0.85
1	8	73.687	H		18.5	40	PK	0.1	21.5
1	8	73.687	V		27.87	40	PK	0.1	12.13
1	8	163.474	H		28.11	43.5	PK	0.1	15.39
1	8	163.474	V		32.23	43.5	PK	0.1	11.27
2	8	249.699	H		28.15	43.5	PK	0.1	15.35
2	8	249.699	V		31.43	43.5	PK	0.1	12.07
3	8	2488.433	H		58.71	74	PK	1	15.29
3	8	2488.433	H		53.2	54	AV	1	0.8
3	8	2488.433	V		62.11	74	PK	1	11.89
3	8	2488.433	V		53.53	54	AV	1	0.47
4	8	4945.094	H		55.62	74	PK	1	18.38
4	8	4945.094	H		46.17	54	AV	1	7.83
4	8	4945.094	V		58.79	74	PK	1	15.21
4	8	4945.094	V		50.53	54	AV	1	3.47
4	8	7422.845	H		53.92	54	PK	1	0.08
4	8	7422.845	V		56.26	74	PK	1	17.74
4	8	7422.845	V		45.41	54	AV	1	8.59



Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

Freq. – Frequency Range:

1:	30	-	200 MHz
2:	200	-	1000 MHz
3:	1	-	4 GHz
4:	4	-	8 GHz
5:	8	-	12 GHz
6:	12	-	17 GHz
7:	17	-	26.5 GHz

All not in the table noted test results are more than 20 dB below the relevant limits.
All other not noted test polts do not contain significant test results in relation to the limits.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Comment: see attached diagrams

Test equipment used: ETSTW-RE 003, ETSTW-RE 015, ETSTW-RE 016, ETSTW-RE 017, ETSTW-RE 024

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

3.6 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission.

The 6 dB bandwidth is the frequency difference between the two markers.

Test conditions		6 dB Bandwidth		
		Channel A	Channel B	Channel C
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120 \text{ V}$	1.6032 MHz	1.6032 MHz	1.8236 MHz
Measurement uncertainty			< 10 Hz	

Limits:

Frequency Range MHz	Limits
902-928	min 500 kHz
2400-2483.5	min 500 kHz
5725-5850	min 500 kHz

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: see attached diagram

Registration number: W6M20505-5937-C-1

FCC ID: MQ5RF-777D-TX

3.7 Peak Power Spectral Density

Peak Power Spectral density is measured at low, middle and high channel.

The peak output power is measured with a measurement bandwidth of 10 MHz and displayed on diagram together with Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, appropriate frequency span and sweep time.

Test conditions		Peak Power Spectral Density (3 kHz)		
		Channel A [dBm]	Channel B [dBm]	Channel C [dBm]
$T_{nom} = 23^{\circ}\text{C}$	$V_{nom} = 120 \text{ V}$	-1.83	-4.6	-4.12
Measurement uncertainty		< 3 Hz		

Limits:

Frequency Range MHz	dBm
902-928	8
2400-2483,5	8
5725-5850	8

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: see attached diagram

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

3.8 Radiated Emissions from Receiver Section of Transceiver

FCC Rule: 15.109

Freq,	Used Ch,	Frequency Marker [MHz]	Polari-zation	corrections dB	Corrected Reading [dBuV/m]	Compliance Limit [dBuV/m]	Detec-tor	BW [MHz]	Margin
1	1	180.974	H		43.12	84.14	PK	0.1	38.02
1	1	180.974	V		35.42	84.14	PK	0.1	45.72
2	1	260.921	H		42.41	46	PK	0.1	3.59
2	1	260.921	V		32.63	46	PK	0.1	13.37
2	1	496.593	H		32.79	46	PK	0.1	13.21
2	1	496.593	V		35.38	46	PK	0.1	10.62
3	1	2310.621	H		49.11	54	PK	1	4.89
3	1	2310.621	V		45.73	54	PK	1	8.27
4	1	4633.285	H		48.46	54	PK	1	5.54
4	1	4633.285	V		49.43	54	PK	1	4.57

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

3.9 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

Frequency	Level (dBμV)	
	quasi-peak	average
150 kHz	lower limit line	Lower limit line

Measurement Result: "_Fin AV"

Frequency Marker [MHz]	Type	Corrected Reading [dBuV]	Compliance AVLimit [dBuV]	BW [MHz]	Margin(AV)
10.26	N	3.00	50	0.01	39.74
9.15	N	2.90	50	0.01	40.85
23.41	N	3.10	50	0.01	26.59

Frequency Marker [MHz]	Type	Corrected Reading [dBuV]	Compliance AVLimit [dBuV]	BW [MHz]	Margin(AV)
10.26	L1	3.20	50	0.01	46.8
9.15	L1	3.30	50	0.01	46.7
23.41	L1	3.10	50	0.01	46.9

Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

Measurement Result: "_Fin QP"

Frequency Marker [MHz]	Type	Corrected Reading [dBuV]	Compliance QPLimit [dBuV]	BW [MHz]	Margin(QP)
10.26	N	12.10	60	0.01	47.9
9.15	N	12.20	60	0.01	47.8
23.41	N	12.10	60	0.01	47.9

Frequency Marker [MHz]	Type	Corrected Reading [dBuV]	Compliance QPLimit [dBuV]	BW [MHz]	Margin(QP)
10.26	L1	12.30	60	PK	47.7
9.15	L1	13.10	60	PK	46.9
23.41	L1	12.20	60	PK	47.8

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 004, ETSTW-CE 001, ETSTW-RE 023

Comment: see attached diagram

Appendix

- A Peak Output Power
- B Spurious Emissions radiated – Transmitter operating
- C Band Edge Measurement
- D Minimum 6dB Bandwidth
- E Peak Power Spectral Density
- F Radiated Emissions from Receiver Section of Transceiver
- G Power Line Conducted Emission
- H Pictures




Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D

Appendix A

Peak Output Power



Marker 1 [T1] RBW 2 MHz RF Att 20 dB
Ref Lvl 9.24 dBm VBW 2 MHz
16 dBm 2.41062425 GHz SWT 500 ms Unit dBm




Center 2.410073146 GHz 1 MHz/ Span 10 MHz

Title: MAX OUTPUT POWER LOW CHANNEL
Comment A: TELEAN TECHNOLOGY LTD.
Date: 12.JUN.2005 13:28:54



Ref Lvl 16 dBm
Marker 1 [T1] 8.61 dBm
2.44662014 GHz
RBW 2 MHz
RF Att 20 dB
VBW 2 MHz
SWT 500 ms
Unit dBm




Center 2.446149198 GHz 1 MHz/ Span 10 MHz

Title: MAX OUTPUT POWER MIDDLE CHANNEL
Comment A: TELEAN TECHNOLOGY LTD.
Date: 12.JUN.2005 13:25:52



Marker 1 [T1] RBW 2 MHz RF Att 20 dB
Ref Lvl 8.14 dBm VBW 2 MHz
16 dBm 2.47227916 GHz SWT 500 ms Unit dBm




Center 2.473030661 GHz 1 MHz/ Span 10 MHz

Title: MAX OUTPUT POWER HIGH CHANNEL
Comment A: TELEAN TECHNOLOGY LTD.
Date: 12.JUN.2005 13:27:48

Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.409GHz, Emax: 98.92dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.409GHz, Emax: 97.49dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.447GHz, Emax: 101.99dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.447GHz, Emax: 99.33dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.474GHz, Emax: 104.14dBμV/m, RBW: 1MHz




Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.474GHz, Emax: 100.05dBμV/m, RBW: 1MHz





Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D


Appendix B

Spurious Emissions radiated – Transmitter operating

Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 196.593MHz, Emax: 38.31dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 196.593MHz, Emax: 34.33dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 998.397MHz, Emax: 37.00dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 982.365MHz, Emax: 37.35dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.394GHz, Emax: 52.19dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.395GHz, Emax: 51.99dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.230GHz, Emax: 56.32dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.230GHz, Emax: 56.32dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.230GHz, Emax: 54.33dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.824GHz, Emax: 49.16dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.703GHz, Emax: 48.95dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.772GHz, Emax: 53.14dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.844GHz, Emax: 52.97dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 25.614GHz, Emax: 51.84dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Low channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 25.376GHz, Emax: 52.04dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 196.593MHz, Emax: 37.90dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 196.593MHz, Emax: 34.75dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 991.984MHz, Emax: 37.70dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 499.800MHz, Emax: 37.60dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 3.934GHz, Emax: 45.72dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 3.874GHz, Emax: 45.69dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 4.890GHz, Emax: 56.26dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.343GHz, Emax: 54.16dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.776GHz, Emax: 49.20dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.816GHz, Emax: 49.39dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.832GHz, Emax: 53.15dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.832GHz, Emax: 53.44dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 24.916GHz, Emax: 52.07dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D Middle channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 25.665GHz, Emax: 52.24dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 196.593MHz, Emax: 37.53dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 193.186MHz, Emax: 34.54dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 998.397MHz, Emax: 36.95dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 980.762MHz, Emax: 36.45dBμV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.488GHz, Emax: 58.07dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.488GHz, Emax: 57.28dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 4.946GHz, Emax: 58.38dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 4.946GHz, Emax: 54.59dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.760GHz, Emax: 49.89dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.703GHz, Emax: 49.41dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.747GHz, Emax: 53.31dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.687GHz, Emax: 53.32dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 26.023GHz, Emax: 51.48dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D High channel
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 25.325GHz, Emax: 51.64dBμV/m, RBW: 1MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:180.922MHz Emax:34.01dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:180.922MHz Emax:42.97dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:499.800MHz Emax:38.55dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:256.112MHz Emax:41.82dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:2.311GHz Emax:44.52dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:2.299GHz Emax:46.87dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:4.633GHz Emax:48.96dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:4.617GHz Emax:47.86dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.567GHz Emax:52.35dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.776GHz Emax:52.40dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.844GHz Emax:53.67dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.820GHz Emax:53.61dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Freq:25.751GHz Emax:48.66dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B

EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Freq:25.648GHz Emax:48.49dBμV/m RBW: 1 MHz






Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D

Appendix C

Band Edge Measurement




Ref Lvl 16 dBm
Marker 1 [T1] -57.02 dBm
2.40000000 GHz
RBW 100 kHz
RF Att 20 dB
VBW 100 kHz
SWT 500 ms
Unit dBm



Center 2.4118 GHz 4 MHz/ Span 40 MHz

Title: BANDEGE LOW CHANNEL
Comment A: TELEAN TECHNOLOGY LTD.
Date: 12.JUN.2005 14:12:19







Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D

Appendix D


Minimum 6dB Bandwidth







Ref Lvl 16 dBm
Marker 1 [T1 ndB] 6.00 dB
BW 1.82364729 MHz
RBW 100 kHz
VBW 300 kHz
SWT 500 ms
RF Att 20 dB
Unit dBm



Center 2.472911824 GHz 1 MHz/ Span 10 MHz

Title: 6dB BANDWIDTH HIGH CHANNEL
Comment A: TELEAN TECHNOLOGY LTD.
Date: 12.JUN.2005 13:45:33




Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D

Appendix E

Peak Power Spectral Density



Marker 1 [T2] RBW 3 kHz RF Att 20 dB
Ref Lvl -1.83 dBm VBW 100 kHz
16 dBm 2.40994158 GHz SWT 500 s Unit dBm



Center 2.410063327 GHz 150 kHz/ Span 1.5 MHz

Title: POWER DENSITY LOW CHANNEL
Comment A: TELEAN TECHNOLOGY LTD.
Date: 12.JUN.2005 13:55:39




Ref Lvl
16 dBm

Marker 1 [T2]

-4.60 dBm
2.44593096 GHz

RBW 3 kHz RF Att 20 dB
VBW 100 kHz
SWT 500 s Unit dBm



Center 2.445803206 GHz


150 kHz/

Span 1.5 MHz

Title: POWER DENSITY MIDDLE CHANNEL
Comment A: TELEAN TECHNOLOGY LTD.
Date: 12.JUN.2005 14:03:46



Marker 1 [T2] RBW 3 kHz RF Att 20 dB
Ref Lvl -4.12 dBm VBW 100 kHz
16 dBm 2.47291182 GHz SWT 500 ms Unit dBm



Center 2.472911824 GHz 150 kHz/ Span 1.5 MHz

Title: POWER DENSITY HIGH CHANNEL
Comment A: TELEAN TECHNOLOGY LTD.
Date: 12.JUN.2005 13:52:41



Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D


Appendix F

Radiated Emissions from Receiver Section of Transceiver

Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:180.922MHz Emax:34.01dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:180.922MHz Emax:42.97dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:499.800MHz Emax:38.55dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:256.112MHz Emax:41.82dBμV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:2.311GHz Emax:44.52dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:2.299GHz Emax:46.87dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:4.633GHz Emax:48.96dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:4.617GHz Emax:47.86dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.567GHz Emax:52.35dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:11.776GHz Emax:52.40dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.844GHz Emax:53.67dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL25, ampl.
Freq:17.820GHz Emax:53.61dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Freq:25.751GHz Emax:48.66dBμV/m RBW: 1 MHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B

EUT: 2.4GHz Digital Wireless Headphone System
MODEL NO.: RF-777D
Approval Holder: TELEAN TECHNOLOGY LTD.
Test Site / Operator: ETS / Mike Wu
Temperature/Voltage: Temp.: 23°C/ Unom.: 120 VAC (AC\DC Adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL025, ampl.
Freq:25.648GHz Emax:48.49dBμV/m RBW: 1 MHz





Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX


Appendix G

Power Line Conducted Emission

EMI voltage test in the ac-mains according to FCC Part 15

Class B


EUT: 2.4GHz Digital Wireless Headphone System
Manufacturer: TELEAN TECHNOLOGY LTD.
Operating Condition: Unom: 120VAC (AC/DC ADAPTOR) , Tnom: 23°C
Test Site: ETS
Operator: Mike Wu
Test Specification: V-network: ESH3-Z5 N
Comment: model:RF-777D mode: active



EMI voltage test in the ac-mains according to FCC Part 15

Class B

EUT: 2.4GHz Digital Wireless Headphone System
Manufacturer: TELEAN TECHNOLOGY LTD.
Operating Condition: Unom: 120VAC (AC/DC ADAPTOR) , Tnom: 23°C
Test Site: ETS
Operator: Mike Wu
Test Specification: V-network: ESH3-Z5 L1
Comment: model:RF-777D mode: active





Registration number: W6M20505-5937-C-1
FCC ID: MQ5RF-777D-TX

Appendix H

Pictures