



R0.5⁺⁰_{-0.1}(*4)

NOTES

- 1.) SURFACE MATERIAL: PET 0.05mmTHK.(+/-10%) WITH BACK ACRYLIC ADHESIVE.
- 2.) PRINT: PERMANENT BLACK OPAQUE INK.
- 3.) FINISH: SURFACE WITH PET COATING.
- 4.) TOTAL THICKNESS TO BE 0.13±0.02mm.
- 5.) LINER SPEC: ROLL TYPE, GLASSING PAPER, 82 g/m² (REF.) SURFACE WITH SILICON COATING.
- 6.) LABEL MARKING TO COMPLY WITH UL'S RECOGNIZED COMPONENT MARKING AND LABELING SYSTEMS. ALL LABEL MATERIAL AND ADHESIVE MUST BE UL COMPLIANT/CERTIFIED.
- 7.) FINISHED: MEET XAC's RoHS REQUIREMENT
- 8.) BLANK LABEL USE: P/N 241879000
- 9.) MODEL & H/N & P/N: TEXT HEIGHT 1.1MM
H/N: For Hardware Number(PCI Requirement)

TABLE 1

ITEM	MODEL	P/N	H/N
1	xCE-25C	002236020	CE25617EBBE6C1

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE :		MODEL NO	↓CE-25	0 ← mm → 20		XAC Automation Corp. A Partner You Can Trust
.X	0.35	ANGLE	±0.5°	DO NOT SCALE DRAWING		
.X	0.20	RADIUS	R0.5			
.XX	0.10			THIRD ANGLE PROJECTION		
.XXX	0.05					
MATERIAL :	SEE NOTE	APPROVED	DATE	TITLE LABEL ASS'Y PRODUCT XCE25MFI(ROHS)		
FINISH :	SEE NOTE	CHECKED	DATE			
DESIGNER		DESIGNER	DATE	PAPER SIZE: A4 DWG NO. 189588000C01 VER. C01		

REV	LTR	DATE	EC No.	REV. DESCRIPTION	DESIGNER	APPROVED