

RF EXPOSURE REPORT

REPORT NO.: SA980331H02A **MODEL NO.:** 8002R, FD-30

FCC ID: MQT-FD30

ACCORDING: FCC Guidelines for Human Exposure

IEEE C95.1

APPLICANT: XAC AUTOMATION CORP.

ADDRESS: 4F, No. 30, INDUSTRY E. RD. IX,

SCIENCE-BASED INDUSTRIAL

PARK, HSINCHU, TAIWAN

ISSUED BY: Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch

LAB LOCATION: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung

Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien

307, Taiwan

1



RF Exposure Measurement

1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency	Electric Field	Magnetic Field	Power Density	Average Time			
Range	Strength (V/m)	Strength (A/m)	(mW/cm ²)	(minutes)			
(MHz)							
(A)Limits For Occupational / Control Exposures							
0.3-3.0	614	1.63	*(100)	6			
3.0-30	1842/f	4.89/f	*(900/f ²)	6			
30-300	61.4	0.163	1.0	6			
300-1500			f/300	6			
1500-100,000			5	6			
(B)Limits For General Population / Uncontrolled Exposure							
0.3-1.34	614	1.63	*(100)	30			
1.34-30	824/f	2.19/f	*(180/f ²)	30			
30-300	27.5	0.073	0.2	30			
300-1500			f/1500	30			
1500-100,000			1.0	30			

f = Frequency in MHz

Report No.: SA980331H02A Reference No.: 980507H15



3. EUT Operating condition
The software provided by Manufacturer enabled the EUT to transmit and receive data at
the operating channel.

This device is classified as General Population/Uncontrolled Device.

Report No.: SA980331H02A Reference No.: 980507H15

4. Classification



5. Output Power & RF Exposure value:

For mini Din to USB cable Mode:

Channel Frequency (MHz)	Electric field (dBuV/m)	Electric field (V/m)	Limit of Electric field (V/m)
13.56	72.1	0.0040	60.77

Note: Limit of Electric field=824/f

For mini Din to RJ12 cable Mode:

Channel Frequency (MHz)	Electric field (dBuV/m)	Electric field (V/m)	Limit of Electric field (V/m)
13.56	73.00	0.0045	60.77

Note: Limit of Electric field=824/f

Report No.: SA980331H02A Reference No.: 980507H15