

EMC TEST REPORT For FCC



Test Report No. : CTK03-F032

Date of Issue : April 17, 2003

Model/Type No: : B19AF

Kind of Product : LCD Monitor

Applicant : Hansol Electronics Inc.

Applicant Address : 27-29, Hanchon-Ri, Ducksan-Myun, Jinchon-Gun, Chungbuk,
365-840, Korea

Manufacturer : Hansol Electronics Inc.

Manufacturer Address : 27-29, Hanchon-Ri, Ducksan-Myun, Jinchon-Gun, Chungbuk,
365-840, Korea

Contact Person : Mr. S. P. Yang

Telephone : +82-43-530-8503

Received Date : March 26, 2003


Test period : Start: April 16, 2003 End: April 16, 2003

Test Results : ☒ **In Compliance** ☐ **Not in Compliance**

The test results presented in this report relate only to the object tested.


CERTiTEK Standards Laboratory Co., Ltd. is accredited by Korea Laboratory Accreditation Scheme (KOLAS) which signed the International Laboratory Accreditation Cooperation (ILAC) Mutual Recognition Arrangement (MRA) for the above test item(s) and test method(s).

Tested by



Joon Pak
EMC Test Engineer
Date: April 17, 2003

Reviewed by



James Hong
EMC Technical Manager
Date: April 17, 2003

REPORT REVISION HISTORY

Date	Revision	Page No
April 17, 2003	(CTK03-F032) Issued	All

This report shall not be reproduced except in full, without the written approval of CERTiTEK Standards Laboratory Co., Ltd. This document may be altered or revised by CERTiTEK Standards Laboratory Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CERTiTEK Standards Laboratory Co., Ltd. will constitute fraud and shall nullify the document.

TABLE OF CONTENTS

1.0 General Product Description	4
1.1 Model Differences	4
1.2 Device Modifications.....	4
1.3 EUT Configuration(s)	5
1.4 Test Software	5
1.5 EUT Operating Mode(s).....	5
1.6 Calibration Details of Equipment Used for Measurement	6
1.7 Test Facility	6
1.8 Measurement Procedure	6
1.9 Laboratory Accreditations and Listings	7
2.0 Emissions Test Regulations.....	8
2.1 Conducted Voltage Emissions	9
2.2 Radiated Electric Field Emissions.....	10
Configurations	11
APPENDIX A - TEST DATA.....	12
Conducted Voltage Emissions (Quasi-Peak reading)	12
Radiated Electric Field Emissions (Quasi-Peak reading).....	14

1.0 General Product Description

1.0.1 Tested Equipment

- ☒ Unless otherwise indicated, all tests were conducted on Model B19AF.
- ☐ Tests performed on Model _____ were considered to be representative of Model(s) _____.

1.0.2 Equipment Size, Mobility and Identification

Dimensions: 380 by 176 by 368 ☒ mm ☐ in
Mobility: ☐ Hand-Held ☒ Table-top ☐ Floor-standing
Serial No.: Not Applicable

1.0.3 Electrical Ratings

Input: 90-240Vac, 50/60Hz, 0.65A
Output: Not applicable

1.0.4 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

Voltage: 120V
Frequency: 60Hz

1.0.5 Clock & Other Frequencies Utilized

12MHz

1.1 Model Differences

Not applicable

1.2 Device Modifications

The following modifications were necessary for compliance: Not applicable

1.3 EUT Configuration(s)

See Appendix A for individual test set-up configuration(s). The following peripheral devices and/or interface cables were connected during the measurement:

☒ Peripheral Devices

Device	Manufacturer	Model No.	Serial No.	FCC ID or DoC
PC	Samsung	M6050	812092ERB00347	DOC
PS/2 Mouse	PANWEST	Cyber Beetle	PM1F184045737	DOC
USB Mouse	PANWEST	Cyber Beetle	PM1F154000055	DOC
Serial Mouse	Microsoft	BASM1	4475951-20000	DOC
PS/2 Keyboard	San Hawk Tecing Co., Ltd	KB120	-	D840902 MIC
Earphone	-	HI-SONIC	-	-

☒ Cable Description

#	Description	Ferrited	Length (m)	Other Details
1	PC Power Cable, Unshielded	No	1.8	Connect to AC Power
2	EUT Power Cable, Unshielded	No	1.8	Connect to AC Power
3	EUT Analog Cable, Shielded	Yes	1.8	Between EUT and PC
4	EUT DVI Cable, Shielded	Yes	1.8	Between EUT and PC
5	EUT Audio In Cable, Shielded	Yes	1.5	Between EUT and PC
6	PS/2 Mouse Cable, Shielded	No	1.8	Connect to PC
7	USB Mouse Cable, Shielded	No	1.8	Connect to PC
8	Serial Mouse Cable, Shielded	No	1.8	Connect to PC
9	PS/2 Keyboard Cable, Shielded	No	1.5	Connect to PC
10	Earphone Cable, Unshielded	No	3.0	Connect to EUT

n/a = not available

1.4 Test Software

☐ Pinging

☒ Name / Manufacturer / Version / Type of Patten
- EMC Test / Compaq Computer / 1.0 / Scrolling 'H'

1.5 EUT Operating Mode(s)

Equipment under test was operated during the measurement under the following conditions:

☒ Test program (H-Pattern)

☐ Test program (color bar)

☐ Standby

☐ Test program (customer specific)

☐ Practice operation

☒ Resolution / Refresh Rate - 1280 X 1024, 75Hz

1.6 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

1.7 Test Facility

The measurement facility is located at 386-1, Ho-Dong, Yongin-City, Kyungki-Do, Korea 449-100. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.8 Measurement Procedure

Preliminary AC power line conducted emissions tests were performed shielded room. To find worst mode, several typical mode and typical cable position were tested. Final AC power line conducted emissions test was performed shielded room. (location is same as Preliminary test)






Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

Preliminary radiated emissions test were performed anechoic chamber (Distance of antenna and EUT was 3 m). To find worst mode, several typical mode and typical cable position were tested and peak level and frequency were recorded.

Final radiated emissions test was performed Open Area Test Site. Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

* Measurement procedures was In accordance with ANSI C63.4-1992 7.2.3, 7.2.4, 8.3.1.1, 8.3.1.2

1.9 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3 and 10 meter Open Area Test Sites to perform FCC Part 15/18 measurements.	 93250
JAPAN	VCCI	10 meter Open Area Test Site and one conducted site.	 R-948, C-986
KOREA	MIC	10 meter Open Area Test Site and EMS (ESD, RS, EFT/Burst, Surge)	 No. 51, KR0025
International	KOLAS	EMC	 NO-119
Europe	GLAS	EMC EN 55011, EN 55022, EN 55024, EN 61326, EN 50130-4, EN 50081-1, EN 50081-2, EN 50082-1, EN 50082-2, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11, EN 61000-3-2, EN 61000-3-3	 No.13000796-02

2.0 Emissions Test Regulations

The emissions tests were performed according to following regulations:

☐ EN 50081-1:1992

☐ EN 55011:1998 +A1:1999

☐ Group 1

☐ Group 2

☐ Class A

☐ Class B

☐ EN 55013:1990 +A12:1994 +A13:1996 +A14:1999

☐ EN 55013:2001

☐ EN 55014-1:1993 +A1:1997 +A2:1999

☐ Household appliances and similar

☐ Portable tools

☐ Semiconductor devices

☐ EN 55014-1:2000

☐ EN 55014-2:1997

☐ EN 55015:1996 +A1:1997 +A2:1999

☐ EN 55015:2000

☐ EN 55020:1994 +A11:1996 +A13:1999 +A14:1999

☐ EN 55020:1994 +A11:1996 +A12:1999 +A13:1999 +A14:1999

☐ EN 55022:1994 +A1:1995 +A2:1997

☐ Class A

☐ Class B

☐ EN 55022:1998 +A1:2000

☐ Class A

☐ Class B

☐ EN 61000-3-2:1995 +A1:1998 +A2:1998

☐ EN 61000-3-2:1995 +A1:1998 +A2:1998 +A14:2000

☐ EN 61000-3-2:2000

☐ EN 61000-3-3:1995

☐ VCCI V-3/99.05 : 1999

☐ Class A

☐ Class B

☒ FCC Part 15 SUBPART B

☐ Class A

☒ Class B

☐ AS 3548 (1992)

☐ Class A

☐ Class B

☒ CISPR 22 (1993)

☐ Class A

☒ Class B

The unit was tested to CISPR 22 and complied with the alternate methods allowed by FCC under paragraphs 15.107 and 15.109.

2.1 Conducted Voltage Emissions

Test Date

April 16, 2003

Test Location

EMI-CE: Shielded Room

Test Instruments

<input checked="" type="checkbox"/> Field Strength Meter	Rohde & Schwarz	ESHS30	828144/002
--	-----------------	--------	------------

Test Accessories

<input type="checkbox"/> LISN	EMCO	3825/2	9206-1971
<input checked="" type="checkbox"/> LISN	EMCO	3825/2	9409-2246
<input checked="" type="checkbox"/> LISN	EMCO	3825/2	9607-2574
<input checked="" type="checkbox"/> Control PC	HP	Vectra 500	SG72000192

Frequency Range of Measurement

☒ 150 kHz to 30 MHz
☐ 450 kHz to 30 MHz
☐ _____

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

<input checked="" type="checkbox"/> MET	minimum margin is 9.5 dBuV (average) at 24.08 MHz
<input type="checkbox"/> NOT MET	limit exceeded by maximum of ____ dBuV at ____ MHz
<input type="checkbox"/> NOT APPLICABLE	

Remarks

See Appendix A for test data.

2.2 Radiated Electric Field Emissions

Test Date

April 16, 2003

Test Location

- ☒ EMI-OATS: Testing was performed at a test distance of 10 m
☐ EMI-OATS: Testing was performed at a test distance of 3 m

Test Instruments

☒ Field Strength Meter Rohde & Schwarz ESVS30 826638/008

Test Accessories

<input checked="" type="checkbox"/> ULTRA Broadband Antenna	Rohde & Schwarz	HL562	361324/014
<input type="checkbox"/> Biconical Antenna	Schwarzbeck	BBA9106	41-00201
<input type="checkbox"/> Biconical Antenna	EMCO	3110B	9607-2564
<input type="checkbox"/> Log-periodic Antenna	EMCO	3146	9607-4567

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Settings

IF Band Width: 120 kHz

Test Results


The requirements are:

- ☒ MET minimum margin is 3.4 dB (uV/m) at 70.54 MHz
☐ NOT MET limit exceeded by maximum of ____ dB(uV/m) at ____ MHz
☐ NOT APPLICABLE

Remarks

See Appendix A for test data



Configuration



APPENDIX A – TEST DATA

Conducted Voltage Emissions (Quasi-Peak reading)

Frequency [MHz]	Correction Factor		Line	Quasi-peak				Average			
				Limit	Reading	Result	Margin	Limit	Reading	Result	Margin
	LISN	Cable		[dBuV]	[dBuV]	[dBuV]	[dB]	[dBuV]	[dBuV]	[dBuV]	[dB]
0.15	2.2	0.1	L	66.0	48.3	50.6	15.4	56.0	9.1	11.4	44.6
0.15	2.2	0.1	N	66.0	48.9	51.2	14.8	56.0	11.0	13.3	42.7
0.18	2.2	0.1	N	64.7	42.8	45.1	19.7	54.7	5.2	7.5	47.2
0.18	1.7	0.1	L	64.5	44.2	46.0	18.5	54.5	13.9	15.7	38.8
0.19	1.7	0.1	L	64.0	43.4	45.2	18.9	54.0	5.9	7.7	46.3
0.21	1.7	0.1	N	63.4	50.2	52.0	11.4	53.4	40.5	42.3	11.1
0.21	1.7	0.1	L	63.4	47.4	49.2	14.2	53.4	31.4	33.2	20.2
24.08	0.5	0.4	L	60.0	40.8	41.7	18.3	50.0	39.7	40.6	9.5
24.49	0.5	0.4	L	60.0	41.3	42.2	17.8	50.0	26.6	27.5	22.5
24.59	0.5	0.4	N	60.0	38.9	39.8	20.2	50.0	30.9	31.8	18.3
24.80	0.5	0.4	N	60.0	39.6	40.5	19.5	50.0	30.8	31.7	18.3
24.90	0.5	0.4	L	60.0	40.8	41.7	18.3	50.0	31.3	32.2	17.8
25.10	0.5	0.4	N	60.0	40.1	41.0	19.0	50.0	31.0	31.9	18.1
25.20	0.5	0.4	N	60.0	39.5	40.4	19.6	50.0	31.0	31.9	18.2
25.20	0.5	0.4	L	60.0	41.1	42.0	18.0	50.0	33.9	34.8	15.2
25.62	0.5	0.4	N	60.0	40.2	41.1	18.9	50.0	30.7	31.6	18.4



Radiated Electric Field Emissions (Quasi-Peak reading)

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor		Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
				Antenna	Cable			
42.27	11.6	V	1.0	12.8	1.3	30.0	25.7	4.3
70.54	18.3	V	1.0	6.7	1.6	30.0	26.6	3.4
114.46	12.8	V	1.0	9.5	2.0	30.0	24.3	5.7
132.65	14.9	H	4.0	8.6	2.3	30.0	25.8	4.2
379.21	15.8	H	1.2	13.1	3.9	37.0	32.8	4.2
398.06	14.2	H	2.2	13.5	4.1	37.0	31.8	5.2
400.18	11.9	V	3.2	13.5	4.1	37.0	29.5	7.5
631.25	9.3	H	1.0	17.4	5.3	37.0	32.0	5.0