

1	2	3	4	5		6																																																																																																					
US/CA/TW				Remark	Description	Editor	Date																																																																																																				
<p style="text-align: center;">来料印刷</p>				<p style="text-align: center;">工厂随线打印</p>				<p>Wi-Fi Connection: Arial, bold, 6pt</p> <p>Local Login: Arial, 6pt</p> <p>SSID: ASUS_XX</p> <p>Password: XXXXXXXXXXXX</p> <p>Username: XXXXXXXXXXXX</p> <p>条码长度依实际打印长度为主</p> <p>MAC位数及内容由ASUS提供，由条码房分配</p> <p>二维码类型为: QR CODE,尺寸不小于 15*15mm</p> <p>扫描内容如下:</p> <p>WiFi P: ASUS_XX P: XXXXXXXXXXXX S: 11M8GPNXXXXXXXXX L: GUP: XXXXXXXXXXXX</p> <p>XX为20 MAC后两位 WiFi Password GUI Password</p>																																																																																																			
<p>贴附物表面(在对应的方格填充黑色):</p> <p><input type="checkbox"/> 塑料面 <input type="checkbox"/> 塑料弧面 <input type="checkbox"/> 铁机壳面/金属面 <input type="checkbox"/> 金属 (铝材质)</p> <p><input type="checkbox"/> 光油/覆膜彩盒 <input type="checkbox"/> 牛皮盒外裱 <input type="checkbox"/> 光油彩盒90度折角封口</p> <p><input type="checkbox"/> 牛皮彩盒90度折角封口 <input type="checkbox"/> 电源线180度对折角</p> <p><input type="checkbox"/> 电源/PLC产品高温 <input type="checkbox"/> 其它()</p>				<p style="text-align: right;">来料方式: 卷装</p>																																																																																																							
<p>NOTES (技术要求):</p> <p>1. 黑色印刷, 无边框, R1.5; (Black printing, no frame, R1.5)</p> <p>2. 材料: 50#消银龙, 过哑膜, 背DC111油胶; (Material: 50# Silver PET with matte printing film, oil adhesive)</p> <p>3. 原材料及后处理工艺均能满足我司《环保技术标准》要求。 (Raw materials and the corresponding post processing should meet requirements defined in the T&W Environmental Protection Technical Standards)</p>				<table border="1"> <thead> <tr> <th>DIM</th> <th>TOL±</th> <th>△</th> <th></th> <th></th> <th></th> <th colspan="2">CUSTOMER:</th> <th colspan="2">T&W 同维</th> </tr> </thead> <tbody> <tr> <td>RANGE</td> <td>C1</td> <td>C2</td> <td>C3</td> <td>C4</td> <td></td> <td>ASUS</td> <td colspan="3">SHENZHEN GONGJIN ELECTRONICS CO., LTD.</td> </tr> <tr> <td>0-6</td> <td>0.1</td> <td>0.1</td> <td>0.15</td> <td>0.2</td> <td></td> <td colspan="2">MODEL:</td> <td colspan="2">PART NO:</td> </tr> <tr> <td>6-30</td> <td>0.2</td> <td>0.3</td> <td>0.4</td> <td>0.5</td> <td></td> <td colspan="2">EBA63</td> <td colspan="2">6110000XXXXX</td> </tr> <tr> <td>30-80</td> <td>0.25</td> <td>0.5</td> <td>0.9</td> <td>1.2</td> <td></td> <td>UNITS</td> <td>mm</td> <td>VER:</td> <td>V01</td> </tr> <tr> <td>80-180</td> <td>0.3</td> <td>0.8</td> <td>1.2</td> <td>1.5</td> <td></td> <td>MATL</td> <td>/</td> <td>SCALE</td> <td>N/A</td> </tr> <tr> <td>180-315</td> <td>0.5</td> <td>1.3</td> <td>1.8</td> <td>3</td> <td></td> <td>FINISH</td> <td>/</td> <td>CHECK</td> <td>王 强</td> </tr> <tr> <td>315-500</td> <td>0.7</td> <td>1.5</td> <td>2.5</td> <td>4</td> <td></td> <td>SHEET</td> <td>1/1</td> <td>PDE</td> <td>N/A</td> </tr> <tr> <td>500-800</td> <td>0.9</td> <td>1.8</td> <td>3</td> <td>5</td> <td></td> <td colspan="2">DATE:</td> <td colspan="2">23-07-18</td> </tr> <tr> <td>ANG.TOL±</td> <td>0°-30'0.1"</td> <td>30°-45'0.2"</td> <td>60°-90'0.3"</td> <td></td> <td></td> <td colspan="4"></td> </tr> </tbody> </table>				DIM	TOL±	△				CUSTOMER:		T&W 同维		RANGE	C1	C2	C3	C4		ASUS	SHENZHEN GONGJIN ELECTRONICS CO., LTD.			0-6	0.1	0.1	0.15	0.2		MODEL:		PART NO:		6-30	0.2	0.3	0.4	0.5		EBA63		6110000XXXXX		30-80	0.25	0.5	0.9	1.2		UNITS	mm	VER:	V01	80-180	0.3	0.8	1.2	1.5		MATL	/	SCALE	N/A	180-315	0.5	1.3	1.8	3		FINISH	/	CHECK	王 强	315-500	0.7	1.5	2.5	4		SHEET	1/1	PDE	N/A	500-800	0.9	1.8	3	5		DATE:		23-07-18		ANG.TOL±	0°-30'0.1"	30°-45'0.2"	60°-90'0.3"						
DIM	TOL±	△				CUSTOMER:		T&W 同维																																																																																																			
RANGE	C1	C2	C3	C4		ASUS	SHENZHEN GONGJIN ELECTRONICS CO., LTD.																																																																																																				
0-6	0.1	0.1	0.15	0.2		MODEL:		PART NO:																																																																																																			
6-30	0.2	0.3	0.4	0.5		EBA63		6110000XXXXX																																																																																																			
30-80	0.25	0.5	0.9	1.2		UNITS	mm	VER:	V01																																																																																																		
80-180	0.3	0.8	1.2	1.5		MATL	/	SCALE	N/A																																																																																																		
180-315	0.5	1.3	1.8	3		FINISH	/	CHECK	王 强																																																																																																		
315-500	0.7	1.5	2.5	4		SHEET	1/1	PDE	N/A																																																																																																		
500-800	0.9	1.8	3	5		DATE:		23-07-18																																																																																																			
ANG.TOL±	0°-30'0.1"	30°-45'0.2"	60°-90'0.3"																																																																																																								