

FCC Test Report

Report No.: RF160728C11

FCC ID: MSQ-BAPAC1750

Test Model: BAP-AC1750

Received Date: July 28, 2016

Test Date: Oct. 02 to Nov. 09, 2016

Issued Date: Dec. 07, 2016

Applicant: ASUSTek COMPUTER INC.

Address: 4F, No. 150, Li-Te Rd., Peitou, Taipei 112, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (1): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information.....	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	10
3.2.1 Test Mode Applicability and Tested Channel Detail.....	11
3.3 Duty Cycle of Test Signal	13
3.4 Description of Support Units	14
3.4.1 Configuration of System under Test	15
3.5 General Description of Applied Standards	18
4 Test Types and Results	19
4.1 Radiated Emission and Bandedge Measurement.....	19
4.1.1 Limits of Radiated Emission and Bandedge Measurement	19
4.1.2 Test Instruments	20
4.1.3 Test Procedures.....	21
4.1.4 Deviation from Test Standard	21
4.1.5 Test Setup.....	22
4.1.6 EUT Operating Conditions.....	23
4.1.7 Test Results	24
4.2 Conducted Emission Measurement	37
4.2.1 Limits of Conducted Emission Measurement.....	37
4.2.2 Test Instruments	37
4.2.3 Test Procedures.....	38
4.2.4 Deviation from Test Standard	38
4.2.5 Test Setup.....	38
4.2.6 EUT Operating Conditions.....	38
4.2.7 Test Results (Mode 1).....	39
4.2.8 Test Results (Mode 2).....	41
4.3 6dB Bandwidth Measurement	43
4.3.1 Limits of 6dB Bandwidth Measurement.....	43
4.3.2 Test Setup.....	43
4.3.3 Test Instruments	43
4.3.4 Test Procedure	43
4.3.5 Deviation from Test Standard	43
4.3.6 EUT Operating Conditions.....	43
4.3.7 Test Result.....	44
4.4 Conducted Output Power Measurement.....	46
4.4.1 Limits of Conducted Output Power Measurement	46
4.4.2 Test Setup.....	46
4.4.3 Test Instruments	46
4.4.4 Test Procedures.....	46
4.4.5 Deviation from Test Standard	46
4.4.6 EUT Operating Conditions.....	46
4.4.7 Test Results	47
4.5 Power Spectral Density Measurement.....	48
4.5.1 Limits of Power Spectral Density Measurement	48
4.5.2 Test Setup.....	48
4.5.3 Test Instruments	48
4.5.4 Test Procedure	48
4.5.5 Deviation from Test Standard	49

4.5.6 EUT Operating Condition	49
4.5.7 Test Results	50
4.6 Conducted Out of Band Emission Measurement.....	53
4.6.1 Limits of Conducted Out of Band Emission Measurement.....	53
4.6.2 Test Setup.....	53
4.6.3 Test Instruments	53
4.6.4 Test Procedure	53
4.6.5 Deviation from Test Standard	53
4.6.6 EUT Operating Condition	54
4.6.7 Test Results	54
5 Pictures of Test Arrangements.....	67
Appendix – Information on the Testing Laboratories	68

Release Control Record

Issue No.	Description	Date Issued
RF160728C11	Original release.	Dec. 07, 2016

1 Certificate of Conformity

Product: Business Dual-band Wireless-AC Access Point

Brand: ASUS

Test Model: BAP-AC1750

Sample Status: ENGINEERING SAMPLE

Applicant: ASUSTek COMPUTER INC.

Test Date: Oct. 02 to Nov. 09, 2016

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Wendy Wu, **Date:** Dec. 07, 2016

Wendy Wu / Specialist

Approved by : May Chen, **Date:** Dec. 07, 2016

May Chen / Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -7.81dB at 0.42344MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -1.1dB at 2390.00MHz, 2483.50MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is i-pex(MHF)not a standard connector.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.83 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.36 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	3.47 dB
	6GHz ~ 18GHz	3.75 dB
	18GHz ~ 40GHz	3.30 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Business Dual-band Wireless-AC Access Point
Brand	ASUS
Test Model	BAP-AC1750
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	DC 12V from power adapter or DC 56V from POE
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode only
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: up to 11Mbps 802.11a/g: up to 54Mbps 802.11n: up to 450Mbps 802.11ac: up to 1300Mbps
Operating Frequency	2.4GHz: 2.412 ~ 2.462GHz 5GHz: 5.18 ~ 5.24GHz, 5.745 ~ 5.825GHz
Number of Channel	2.4GHz: 802.11b, 802.11g, 802.11n (HT20), VHT20: 11 802.11n (HT40), VHT40: 7 5GHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20): 9 802.11n (HT40), 802.11ac (VHT40): 4 802.11ac (VHT80): 2
Output Power	2.4GHz: 993.877mW 5GHz: 5.18GHz ~ 5.24GHz: 657.486mW 5.745GHz ~ 5.825GHz: 637.99mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter x 1
Data Cable Supplied	NA

Note:

1. Simultaneously transmission condition.

Condition	Technology	
1	WLAN (2.4GHz)	WLAN (5GHz)
Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.		

2. The antenna provided to the EUT, please refer to the following table:

2.4GHz Band						
Antenna No	Brand	Model	Antenna Gain (dBi) <Including cable loss>	Frequency range (GHz)	Antenna Type	Connector Type
Chain (0)	Adant	STAR-X3	4	2.4~2.4835	monopole	i-pex(MHF)
Chain (1)	Adant	STAR-X3	4	2.4~2.4835	monopole	i-pex(MHF)
Chain (2)	Adant	STAR-X3	4	2.4~2.4835	monopole	i-pex(MHF)
5GHz Band						
Antenna No	Brand	Model	Antenna Gain (dBi) <Including cable loss>	Frequency range (GHz)	Antenna Type	Connector Type
Chain (0)	Adant	STAR-X3	6	5.15~5.85	monopole	i-pex(MHF)
Chain (1)	Adant	STAR-X3	6	5.15~5.85	monopole	i-pex(MHF)
Chain (2)	Adant	STAR-X3	6	5.15~5.85	monopole	i-pex(MHF)

3. The EUT must be supplied with a PoE or power adapter and following below table:

Adapter		
Brand	Model No.	Spec.
Asian Power Devices Inc.	WA-24Q12R	Input: 100-240V~ 50-60Hz, 0.7A Max Output: 12V/ 2A DC output cable (unshielded, 1.5m)
POE (test only not sale together)		
Brand	Model No.	Spec.
CARRIER	G0545-560-060-PSE1000	Input: 100-240V~1A MAX 50/60Hz Output: 56V/ 0.6A +(4,5)pins,-(7,8)pins

4. The EUT has been pre-tested under following test modes:

Pre-test Mode	Power
Mode A	Power from POE
Mode B	Power from adapter

From the above modes, the worst spurious emission was found in **Mode A**. Therefore only the test data of the modes were recorded in this report.

5. The EUT incorporates a MIMO function.

2.4GHz Band			
MODULATION MODE	DATA RATE (MCS)	TX & RX CONFIGURATION	
802.11b	1 ~ 11Mbps	3TX	3RX
802.11g	6 ~ 54Mbps	3TX	3RX
802.11n (HT20)	MCS 0~7	3TX	3RX
	MCS 8~15	3TX	3RX
	MCS 16~23	3TX	3RX
802.11n (HT40)	MCS 0~7	3TX	3RX
	MCS 8~15	3TX	3RX
	MCS 16~23	3TX	3RX
5GHz Band			
MODULATION MODE	DATA RATE (MCS)	TX & RX CONFIGURATION	
802.11a	6 ~ 54Mbps	3TX	3RX
802.11n (HT20)	MCS 0~7	3TX	3RX
	MCS 8~15	3TX	3RX
	MCS 16~23	3TX	3RX
802.11n (HT40)	MCS 0~7	3TX	3RX
	MCS 8~15	3TX	3RX
	MCS 16~23	3TX	3RX
802.11ac (VHT20)	MCS 0~8, Nss=1	3TX	3RX
	MCS 0~8, Nss=2	3TX	3RX
	MCS0~9 Nss=3	3TX	3RX
802.11ac (VHT40)	MCS 0~9, Nss=1	3TX	3RX
	MCS 0~9, Nss=2	3TX	3RX
	MCS0~9 Nss=3	3TX	3RX
802.11ac (VHT80)	MCS 0~9, Nss=1	3TX	3RX
	MCS 0~9, Nss=2	3TX	3RX
	MCS0~9 Nss=3	3TX	3RX

6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
1	√	√	√	√	Power from POE
2	-	-	√	-	Power from adapter

Where RE≥1G: Radiated Emission above 1GHz &
 Bandedge Measurement
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 2 axis. The worst case was found when positioned on **X-plane**.
NOTE: “-”means no effect.

Radiated Emission Test (Above 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	6	OFDM	BPSK	6

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	6	OFDM	BPSK	6

Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	22deg. C, 65%RH	120Vac, 60Hz	Robert Cheng
RE<1G	22deg. C, 65%RH	120Vac, 60Hz	Robert Cheng
PLC	26deg. C, 62%RH	120Vac, 60Hz	Eagle Chen
APCM	25deg. C, 60%RH	120Vac, 60Hz	Gary Cheng

3.3 Duty Cycle of Test Signal

If duty cycle of test signal is $\geq 98\%$, duty factor is not required.


If duty cycle of test signal is $< 98\%$, duty factor shall be considered.

802.11b: Duty cycle = $12.206/12.325 = 0.99$

802.11g: Duty cycle = $2.024/2.065 = 0.98$

802.11n (HT20): Duty cycle = $1.884/1.919 = 0.982$

802.11n (HT40): Duty cycle = $0.927/0.966 = 0.96$, Duty factor = $10 * \log(1/0.96) = 0.18$



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	DELL	E5430	HYV4VY1	FCC DoC	Provided by Lab
B.	POE	CARRIER	G0845-560-060-PSE1000	NA	NA	Supplied by client
C.	HUB	ZyXEL	ES-116P	S060H02000215	FCC DoC	Provided by Lab
D.	iPod	Apple	MC749TA/A	CC4DMFJUDFDM	NA	Provided by Lab


Note:

1. All power cords of the above support units are non-shielded (1.8m).


ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	RJ-45 Cable	1	10	No	0	Provided by Lab
2.	DC Cable	1	1.5	No	0	Supplied by client
3.	RJ-45 Cable	1	1	No	0	Provided by Lab
4.	RJ-45 Cable	1	10	No	0	Provided by Lab
5.	USB Cable	1	0.1	Yes	0	Provided by Lab

3.4.1 Configuration of System under Test


POE Mode (for Conducted Emission test):



POE Mode (for other test):



Adapter Mode:



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

KDB 558074 D01 DTS Meas Guidance v03r05

KDB 662911 D01 Multiple Transmitter Output v02r01

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_uV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY50010156	Aug. 18, 2016	Aug. 17, 2017
Pre-Amplifier ^(*) EMCI	EMC001340	980142	Jan. 20, 2016	Jan. 19, 2018
Loop Antenna ^(*) Electro-Metrics	EM-6879	264	Dec. 16, 2014	Dec. 15, 2016
RF Cable	NA	LOOPCAB-001 LOOPCAB-002	Jan. 18, 2016	Jan. 17, 2017
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-05	May 07, 2016	May 06, 2017
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-156	Jan. 04, 2016	Jan. 03, 2017
RF Cable	8D	966-3-1 966-3-2 966-3-3	Apr. 02, 2016	Apr. 01, 2017
Horn_Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Jan. 20, 2016	Jan. 19, 2017
Pre-Amplifier Agilent	8449B	3008A02465	Apr. 05, 2016	Apr. 04, 2017
RF Cable	EMC104-SM-SM-2000 EMC104-SM-SM-5000 EMC104-SM-SM-5000	150317 150321 150322	Mar. 30, 2016	Mar. 29, 2017
Spectrum Analyzer Keysight	N9030A	MY54490520	July 29, 2016	July 28, 2017
Pre-Amplifier EMCI	EMC184045	980143	Jan. 15, 2016	Jan. 14, 2017
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Jan. 08, 2016	Jan. 07, 2017
RF Cable	SUCOFLEX 102	36432/2 36441/2	Jan. 16, 2016	Jan. 15, 2017
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. *The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. 3.
4. The FCC Site Registration No. is 147459
5. Loop antenna was used for all emissions below 30 MHz.
6. The CANADA Site Registration No. is 20331-1
7. Tested Date: Oct. 02, 2016

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Connected the EUT with the Laptop which is placed on remote site.
- Contorlling software (artgui.exe[Ver 2.3]) has been activated to set the EUT on specific status.

4.1.7 Test Results

Above 1GHz Data:

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	52.4 PK	74.0	-21.6	1.60 H	287	56.6	-4.2
2	2390.00	39.7 AV	54.0	-14.3	1.60 H	287	43.9	-4.2
3	*2412.00	97.0 PK			3.10 H	45	101.1	-4.1
4	*2412.00	94.1 AV			3.10 H	45	98.2	-4.1
5	4824.00	42.3 PK	74.0	-31.7	3.31 H	248	40.0	2.3
6	4824.00	38.5 AV	54.0	-15.5	3.31 H	248	36.2	2.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.0 PK	74.0	-15.0	3.20 V	147	63.2	-4.2
2	2390.00	52.4 AV	54.0	-1.6	3.20 V	147	56.6	-4.2
3	*2412.00	114.6 PK			3.20 V	147	118.7	-4.1
4	*2412.00	112.4 AV			3.20 V	147	116.5	-4.1
5	4824.00	48.8 PK	74.0	-25.2	1.37 V	352	46.5	2.3
6	4824.00	44.1 AV	54.0	-9.9	1.37 V	352	41.8	2.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	51.8 PK	74.0	-22.2	1.60 H	298	56.0	-4.2
2	2390.00	38.7 AV	54.0	-15.3	1.60 H	298	42.9	-4.2
3	*2437.00	97.6 PK			3.15 H	53	101.6	-4.0
4	*2437.00	95.0 AV			3.15 H	53	99.0	-4.0
5	2483.50	51.9 PK	74.0	-22.1	1.60 H	298	55.9	-4.0
6	2483.50	38.9 AV	54.0	-15.1	1.60 H	298	42.9	-4.0
7	4874.00	42.7 PK	74.0	-31.3	3.33 H	255	40.2	2.5
8	4874.00	39.0 AV	54.0	-15.0	3.33 H	255	36.5	2.5
9	7311.00	54.2 PK	74.0	-19.8	2.80 H	231	45.3	8.9
10	7311.00	49.1 AV	54.0	-4.9	2.80 H	231	40.2	8.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.1 PK	74.0	-19.9	3.55 V	143	58.3	-4.2
2	2390.00	41.6 AV	54.0	-12.4	3.55 V	143	45.8	-4.2
3	*2437.00	115.1 PK			3.55 V	143	119.1	-4.0
4	*2437.00	113.0 AV			3.55 V	143	117.0	-4.0
5	2483.50	50.0 PK	74.0	-24.0	3.55 V	143	54.0	-4.0
6	2483.50	37.1 AV	54.0	-16.9	3.55 V	143	41.1	-4.0
7	4874.00	49.2 PK	74.0	-24.8	1.00 V	84	46.7	2.5
8	4874.00	44.4 AV	54.0	-9.6	1.00 V	84	41.9	2.5
9	7311.00	56.3 PK	74.0	-17.7	2.65 V	184	47.4	8.9
10	7311.00	51.6 AV	54.0	-2.4	2.65 V	184	42.7	8.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	96.8 PK			3.08 H	61	100.9	-4.1
2	*2462.00	93.8 AV			3.08 H	61	97.9	-4.1
3	2483.50	54.0 PK	74.0	-20.0	1.61 H	285	58.0	-4.0
4	2483.50	43.1 AV	54.0	-10.9	1.61 H	285	47.1	-4.0
5	4924.00	42.2 PK	74.0	-31.8	3.30 H	250	39.7	2.5
6	4924.00	38.3 AV	54.0	-15.7	3.30 H	250	35.8	2.5
7	7386.00	53.6 PK	74.0	-20.4	2.83 H	247	44.3	9.3
8	7386.00	48.8 AV	54.0	-5.2	2.83 H	247	39.5	9.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	114.4 PK			3.55 V	143	118.5	-4.1
2	*2462.00	112.2 AV			3.55 V	143	116.3	-4.1
3	2483.50	52.9 PK	74.0	-21.1	3.55 V	143	56.9	-4.0
4	2483.50	43.8 AV	54.0	-10.2	3.55 V	143	47.8	-4.0
5	4924.00	48.7 PK	74.0	-25.3	1.00 V	120	46.2	2.5
6	4924.00	44.1 AV	54.0	-9.9	1.00 V	120	41.6	2.5
7	7386.00	55.9 PK	74.0	-18.1	2.65 V	178	46.6	9.3
8	7386.00	51.6 AV	54.0	-2.4	2.65 V	178	42.3	9.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.6 PK	74.0	-19.4	3.10 H	54	58.8	-4.2
2	2390.00	38.5 AV	54.0	-15.5	3.10 H	54	42.7	-4.2
3	*2412.00	105.1 PK			3.10 H	54	109.2	-4.1
4	*2412.00	94.6 AV			3.10 H	54	98.7	-4.1
5	4824.00	40.4 PK	74.0	-33.6	3.22 H	258	38.1	2.3
6	4824.00	30.2 AV	54.0	-23.8	3.22 H	258	27.9	2.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.4 PK	74.0	-2.6	3.20 V	145	75.6	-4.2
2	2390.00	52.3 AV	54.0	-1.7	3.20 V	145	56.5	-4.2
3	*2412.00	113.3 PK			3.20 V	145	117.4	-4.1
4	*2412.00	101.9 AV			3.20 V	145	106.0	-4.1
5	4824.00	49.2 PK	74.0	-24.8	1.18 V	354	46.9	2.3
6	4824.00	37.9 AV	54.0	-16.1	1.18 V	354	35.6	2.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.1 PK	74.0	-6.9	3.10 H	65	71.3	-4.2
2	2390.00	45.4 AV	54.0	-8.6	3.10 H	65	49.6	-4.2
3	*2437.00	115.6 PK			3.10 H	65	119.6	-4.0
4	*2437.00	105.1 AV			3.10 H	65	109.1	-4.0
5	2483.50	63.0 PK	74.0	-11.0	3.10 H	65	67.0	-4.0
6	2483.50	41.2 AV	54.0	-12.8	3.10 H	65	45.2	-4.0
7	4874.00	40.3 PK	74.0	-33.7	3.18 H	259	37.8	2.5
8	4874.00	30.2 AV	54.0	-23.8	3.18 H	259	27.7	2.5
9	7311.00	52.3 PK	74.0	-21.7	2.77 H	258	43.4	8.9
10	7311.00	40.8 AV	54.0	-13.2	2.77 H	258	31.9	8.9

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	72.9 PK	74.0	-1.1	3.12 V	227	77.1	-4.2
2	2390.00	50.9 AV	54.0	-3.1	3.12 V	227	55.1	-4.2
3	*2437.00	123.3 PK			3.18 V	132	127.3	-4.0
4	*2437.00	112.4 AV			3.18 V	132	116.4	-4.0
5	2483.50	68.1 PK	74.0	-5.9	3.12 V	155	72.1	-4.0
6	2483.50	46.9 AV	54.0	-7.1	3.12 V	155	50.9	-4.0
7	4874.00	47.9 PK	74.0	-26.1	2.45 V	122	45.4	2.5
8	4874.00	36.4 AV	54.0	-17.6	2.45 V	122	33.9	2.5
9	7311.00	63.9 PK	74.0	-10.1	2.46 V	203	55.0	8.9
10	7311.00	51.3 AV	54.0	-2.7	2.46 V	203	42.4	8.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	107.6 PK			3.12 H	45	111.7	-4.1
2	*2462.00	97.3 AV			3.12 H	45	101.4	-4.1
3	2483.50	54.2 PK	74.0	-19.8	3.12 H	45	58.2	-4.0
4	2483.50	38.1 AV	54.0	-15.9	3.12 H	45	42.1	-4.0
5	4924.00	40.9 PK	74.0	-33.1	3.18 H	268	38.4	2.5
6	4924.00	30.6 AV	54.0	-23.4	3.18 H	268	28.1	2.5
7	7386.00	49.7 PK	74.0	-24.3	2.82 H	245	40.4	9.3
8	7386.00	38.1 AV	54.0	-15.9	2.82 H	245	28.8	9.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	114.9 PK			3.49 V	132	119.0	-4.1
2	*2462.00	104.6 AV			3.49 V	132	108.7	-4.1
3	2483.50	72.7 PK	74.0	-1.3	3.56 V	360	76.7	-4.0
4	2483.50	47.2 AV	54.0	-6.8	3.56 V	360	51.2	-4.0
5	4924.00	48.4 PK	74.0	-25.6	2.45 V	115	45.9	2.5
6	4924.00	36.7 AV	54.0	-17.3	2.45 V	115	34.2	2.5
7	7386.00	58.4 PK	74.0	-15.6	2.46 V	195	49.1	9.3
8	7386.00	46.1 AV	54.0	-7.9	2.46 V	195	36.8	9.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.2 PK	74.0	-19.8	3.10 H	62	58.4	-4.2
2	2390.00	38.3 AV	54.0	-15.7	3.10 H	62	42.5	-4.2
3	*2412.00	107.1 PK			3.10 H	62	111.2	-4.1
4	*2412.00	97.3 AV			3.10 H	62	101.4	-4.1
5	4824.00	40.8 PK	74.0	-33.2	3.13 H	280	38.5	2.3
6	4824.00	30.7 AV	54.0	-23.3	3.13 H	280	28.4	2.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.7 PK	74.0	-2.3	3.36 V	128	75.9	-4.2
2	2390.00	52.6 AV	54.0	-1.4	3.36 V	128	56.8	-4.2
3	*2412.00	114.5 PK			3.40 V	321	118.6	-4.1
4	*2412.00	104.5 AV			3.40 V	321	108.6	-4.1
5	4824.00	49.4 PK	74.0	-24.6	1.23 V	342	47.1	2.3
6	4824.00	38.3 AV	54.0	-15.7	1.23 V	342	36.0	2.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.9 PK	74.0	-7.1	3.06 H	46	71.1	-4.2
2	2390.00	45.1 AV	54.0	-8.9	3.06 H	46	49.3	-4.2
3	*2437.00	112.4 PK			3.06 H	46	116.4	-4.0
4	*2437.00	102.1 AV			3.06 H	46	106.1	-4.0
5	2483.50	63.3 PK	74.0	-10.7	3.06 H	46	67.3	-4.0
6	2483.50	41.6 AV	54.0	-12.4	3.06 H	46	45.6	-4.0
7	4874.00	40.9 PK	74.0	-33.1	3.17 H	249	38.4	2.5
8	4874.00	30.6 AV	54.0	-23.4	3.17 H	249	28.1	2.5
9	7311.00	52.2 PK	74.0	-21.8	2.76 H	262	43.3	8.9
10	7311.00	40.9 AV	54.0	-13.1	2.76 H	262	32.0	8.9

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	72.9 PK	74.0	-1.1	3.48 V	205	77.1	-4.2
2	2390.00	50.4 AV	54.0	-3.6	3.48 V	205	54.6	-4.2
3	*2437.00	119.0 PK			3.04 V	321	123.0	-4.0
4	*2437.00	109.6 AV			3.04 V	321	113.6	-4.0
5	2483.50	68.8 PK	74.0	-5.2	3.73 V	147	72.8	-4.0
6	2483.50	47.0 AV	54.0	-7.0	3.73 V	147	51.0	-4.0
7	4874.00	47.9 PK	74.0	-26.1	2.43 V	132	45.4	2.5
8	4874.00	36.2 AV	54.0	-17.8	2.43 V	132	33.7	2.5
9	7311.00	64.2 PK	74.0	-9.8	2.42 V	194	55.3	8.9
10	7311.00	51.3 AV	54.0	-2.7	2.42 V	194	42.4	8.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.9 PK			3.14 H	49	113.0	-4.1
2	*2462.00	98.1 AV			3.14 H	49	102.2	-4.1
3	2483.50	54.6 PK	74.0	-19.4	3.14 H	49	58.6	-4.0
4	2483.50	38.5 AV	54.0	-15.5	3.14 H	49	42.5	-4.0
5	4924.00	41.1 PK	74.0	-32.9	3.18 H	261	38.6	2.5
6	4924.00	30.6 AV	54.0	-23.4	3.18 H	261	28.1	2.5
7	7386.00	49.8 PK	74.0	-24.2	2.83 H	240	40.5	9.3
8	7386.00	38.4 AV	54.0	-15.6	2.83 H	240	29.1	9.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	116.0 PK			3.21 V	142	120.1	-4.1
2	*2462.00	105.4 AV			3.21 V	142	109.5	-4.1
3	2483.50	72.9 PK	74.0	-1.1	3.24 V	140	76.9	-4.0
4	2483.50	51.0 AV	54.0	-3.0	3.24 V	140	55.0	-4.0
5	4924.00	48.1 PK	74.0	-25.9	2.49 V	107	45.6	2.5
6	4924.00	36.4 AV	54.0	-17.6	2.49 V	107	33.9	2.5
7	7386.00	58.2 PK	74.0	-15.8	2.43 V	210	48.9	9.3
8	7386.00	46.0 AV	54.0	-8.0	2.43 V	210	36.7	9.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.7 PK	74.0	-5.3	3.12 H	57	72.9	-4.2
2	2390.00	46.6 AV	54.0	-7.4	3.12 H	57	50.8	-4.2
3	*2422.00	100.2 PK			3.12 H	57	104.3	-4.1
4	*2422.00	90.1 AV			3.12 H	57	94.2	-4.1
5	4844.00	40.6 PK	74.0	-33.4	3.22 H	263	38.3	2.3
6	4844.00	28.6 AV	54.0	-25.4	3.22 H	263	26.3	2.3
7	7266.00	40.3 PK	74.0	-33.7	2.82 H	255	31.5	8.8
8	7266.00	34.5 AV	54.0	-19.5	2.82 H	255	25.7	8.8

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.6 PK	74.0	-4.4	3.34 V	138	73.8	-4.2
2	2390.00	52.9 AV	54.0	-1.1	3.34 V	138	57.1	-4.2
3	*2422.00	107.9 PK			3.24 V	88	112.0	-4.1
4	*2422.00	97.8 AV			3.24 V	88	101.9	-4.1
5	4844.00	41.3 PK	74.0	-32.7	2.51 V	116	39.0	2.3
6	4844.00	30.1 AV	54.0	-23.9	2.51 V	116	27.8	2.3
7	7266.00	52.7 PK	74.0	-21.3	2.38 V	209	43.9	8.8
8	7266.00	40.3 AV	54.0	-13.7	2.38 V	209	31.5	8.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.3 PK	74.0	-4.7	3.15 H	51	73.5	-4.2
2	2390.00	47.1 AV	54.0	-6.9	3.15 H	51	51.3	-4.2
3	*2437.00	103.1 PK			3.15 H	51	107.1	-4.0
4	*2437.00	93.6 AV			3.15 H	51	97.6	-4.0
5	2483.50	65.4 PK	74.0	-8.6	3.15 H	51	69.4	-4.0
6	2483.50	43.5 AV	54.0	-10.5	3.15 H	51	47.5	-4.0
7	4874.00	40.7 PK	74.0	-33.3	3.24 H	262	38.2	2.5
8	4874.00	28.5 AV	54.0	-25.5	3.24 H	262	26.0	2.5
9	7311.00	39.7 PK	74.0	-34.3	2.88 H	251	30.8	8.9
10	7311.00	34.0 AV	54.0	-20.0	2.88 H	251	25.1	8.9

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.7 PK	74.0	-3.3	3.03 V	133	74.9	-4.2
2	2390.00	52.8 AV	54.0	-1.2	3.03 V	133	57.0	-4.2
3	*2437.00	110.9 PK			3.10 V	144	114.9	-4.0
4	*2437.00	101.4 AV			3.10 V	144	105.4	-4.0
5	2483.50	71.1 PK	74.0	-2.9	3.10 V	153	75.1	-4.0
6	2483.50	50.8 AV	54.0	-3.2	3.10 V	153	54.8	-4.0
7	4874.00	43.2 PK	74.0	-30.8	2.54 V	120	40.7	2.5
8	4874.00	31.7 AV	54.0	-22.3	2.54 V	120	29.2	2.5
9	7311.00	52.5 PK	74.0	-21.5	2.40 V	200	43.6	8.9
10	7311.00	40.2 AV	54.0	-13.8	2.40 V	200	31.3	8.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	101.9 PK			3.13 H	48	106.0	-4.1
2	*2452.00	92.5 AV			3.13 H	48	96.6	-4.1
3	2483.50	69.4 PK	74.0	-4.6	3.13 H	48	73.4	-4.0
4	2483.50	47.2 AV	54.0	-6.8	3.13 H	48	51.2	-4.0
5	4904.00	40.5 PK	74.0	-33.5	3.19 H	278	38.0	2.5
6	4904.00	28.6 AV	54.0	-25.4	3.19 H	278	26.1	2.5
7	7356.00	40.2 PK	74.0	-33.8	2.88 H	249	31.0	9.2
8	7356.00	34.1 AV	54.0	-19.9	2.88 H	249	24.9	9.2

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	109.7 PK			3.15 V	147	113.8	-4.1
2	*2452.00	100.1 AV			3.15 V	147	104.2	-4.1
3	2483.50	71.2 PK	74.0	-2.8	2.60 V	156	75.2	-4.0
4	2483.50	52.9 AV	54.0	-1.1	2.60 V	156	56.9	-4.0
5	4904.00	42.7 PK	74.0	-31.3	2.55 V	101	40.2	2.5
6	4904.00	31.1 AV	54.0	-22.9	2.55 V	101	28.6	2.5
7	7356.00	52.6 PK	74.0	-21.4	2.37 V	198	43.4	9.2
8	7356.00	40.4 AV	54.0	-13.6	2.37 V	198	31.2	9.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

Below 1GHz Data:
802.11g

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.63	31.7 QP	40.0	-8.3	1.05 H	179	41.0	-9.3
2	43.80	26.6 QP	40.0	-13.4	1.50 H	243	34.6	-8.0
3	82.09	30.4 QP	40.0	-9.6	1.50 H	126	43.1	-12.7
4	375.00	32.5 QP	46.0	-13.5	1.05 H	296	38.0	-5.5
5	400.01	35.0 QP	46.0	-11.0	1.05 H	112	40.0	-5.0
6	480.01	34.5 QP	46.0	-11.5	1.50 H	56	37.4	-2.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.61	32.7 QP	40.0	-7.3	1.50 V	45	42.0	-9.3
2	47.80	35.5 QP	40.0	-4.5	1.50 V	360	43.2	-7.7
3	82.21	35.5 QP	40.0	-4.5	1.50 V	41	48.2	-12.7
4	357.50	31.5 QP	46.0	-14.5	1.50 V	86	37.7	-6.2
5	480.01	30.8 QP	46.0	-15.2	1.50 V	162	33.7	-2.9
6	875.04	35.0 QP	46.0	-11.0	1.50 V	251	31.1	3.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	100375	May 09, 2016	May 08, 2017
Line-Impedance Stabilization Network (for EUT) SCHWARZBECK	NSLK-8127	8127-522	Aug. 31, 2016	Aug. 30, 2017
Line-Impedance Stabilization Network (for Peripheral) R&S	ENV216	100072	June 13, 2016	June 12, 2017
RF Cable	5D-FB	COACAB-002	Mar. 04, 2016	Mar. 03, 2017
10 dB PAD Mini-Circuits	HAT-10+	CONATT-003	Sep. 13, 2016	Sep. 12, 2017
50 ohms Terminator	N/A	EMC-03	Sep. 29, 2016	Sep. 28, 2017
50 ohms Terminator	N/A	EMC-02	Sep. 29, 2016	Sep. 28, 2017
Software BVADT	BVADT_Cond_V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3. The VCCI Con C Registration No. is C-3611.
4. Tested Date: Nov. 09, 2016

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results (Mode 1)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16172	10.14	35.36	24.73	45.50	34.87	65.38	55.38	-19.88	-20.51
2	0.35313	10.11	32.28	26.45	42.39	36.56	58.89	48.89	-16.50	-12.33
3	0.42344	10.11	37.01	29.46	47.12	39.57	57.38	47.38	-10.26	-7.81
4	1.07422	10.13	30.53	22.41	40.66	32.54	56.00	46.00	-15.34	-13.46
5	1.92969	10.24	25.65	17.81	35.89	28.05	56.00	46.00	-20.11	-17.95
6	2.65625	10.27	25.50	17.67	35.77	27.94	56.00	46.00	-20.23	-18.06
7	16.88672	10.70	19.86	16.21	30.56	26.91	60.00	50.00	-29.44	-23.09

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.18	35.74	25.95	45.92	36.13	65.79	55.79	-19.87	-19.66
2	0.35703	10.09	31.79	25.01	41.88	35.10	58.80	48.80	-16.92	-13.70
3	0.42344	10.09	36.36	29.16	46.45	39.25	57.38	47.38	-10.93	-8.13
4	0.75156	10.16	25.75	16.22	35.91	26.38	56.00	46.00	-20.09	-19.62
5	1.08984	10.21	29.32	20.57	39.53	30.78	56.00	46.00	-16.47	-15.22
6	1.78516	10.17	25.71	18.32	35.88	28.49	56.00	46.00	-20.12	-17.51
7	2.20703	10.18	24.93	17.59	35.11	27.77	56.00	46.00	-20.89	-18.23

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.2.8 Test Results (Mode 2)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.14	39.28	28.27	49.42	38.41	66.00	56.00	-16.58	-17.59
2	0.16562	10.13	36.89	24.76	47.02	34.89	65.18	55.18	-18.16	-20.29
3	0.18516	10.13	33.67	23.99	43.80	34.12	64.25	54.25	-20.45	-20.13
4	0.37266	10.11	27.84	24.49	37.95	34.60	58.44	48.44	-20.49	-13.84
5	0.39219	10.11	26.90	24.06	37.01	34.17	58.02	48.02	-21.01	-13.85
6	4.33203	10.32	18.87	9.33	29.19	19.65	56.00	46.00	-26.81	-26.35
7	20.66797	10.83	23.40	18.30	34.23	29.13	60.00	50.00	-25.77	-20.87

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

Phase Of Power : Neutral (N)

No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16172	10.16	37.67	25.47	47.83	35.63	65.38	55.38	-17.55	-19.75
2	0.18516	10.11	33.67	21.13	43.78	31.24	64.25	54.25	-20.47	-23.01
3	0.21250	10.07	29.10	22.09	39.17	32.16	63.11	53.11	-23.94	-20.95
4	0.36875	10.09	31.26	29.43	41.35	39.52	58.53	48.53	-17.18	-9.01
5	0.39219	10.09	29.83	27.82	39.92	37.91	58.02	48.02	-18.10	-10.11
6	4.28906	10.33	19.76	11.67	30.09	22.00	56.00	46.00	-25.91	-24.00
7	20.09766	10.84	24.15	18.57	34.99	29.41	60.00	50.00	-25.01	-20.59

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSP40	100060	May 11, 2016	May 10, 2017

NOTE: 1. The test was performed in Oven room 2.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. Tested Date: Nov. 09, 2016

4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2		
1	2412	10.13	10.15	10.15	0.5	PASS
6	2437	10.11	10.13	10.14	0.5	PASS
11	2462	10.14	10.13	10.13	0.5	PASS

802.11g


Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2		
1	2412	16.43	16.45	16.49	0.5	PASS
6	2437	16.41	16.42	16.40	0.5	PASS
11	2462	16.48	16.44	16.45	0.5	PASS

802.11n (HT20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2		
1	2412	17.64	17.64	17.64	0.5	Pass
6	2437	17.64	17.62	17.62	0.5	Pass
11	2462	17.68	17.68	17.69	0.5	Pass

802.11n (HT40)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2		
3	2422	36.49	36.47	36.51	0.5	Pass
6	2437	36.36	36.48	36.43	0.5	Pass
9	2452	36.18	36.15	36.08	0.5	Pass



4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.4.2 Test Setup



4.4.3 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power meter Anritsu	ML2495A	1014008	May 5, 2016	May 4, 2017
Power sensor Anritsu	MA2411B	0917122	May 5, 2016	May 4, 2017

NOTE: 1. The test was performed in Oven room 2.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. Tested Date: Nov. 09, 2016

4.4.4 Test Procedures

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor. Record the power level.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

4.4.7 Test Results

802.11b

Chan.	Chan. Freq. (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	24.74	24.95	24.47	890.358	29.50	30	Pass
6	2437	25.13	25.26	25.13	987.412	29.94	30	Pass
11	2462	24.22	24.55	24.22	813.584	29.10	30	Pass

802.11g

Chan.	Chan. Freq. (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	21.29	21.51	21.03	402.93	26.05	30	Pass
6	2437	25.01	25.50	25.08	993.877	29.97	30	Pass
11	2462	19.68	19.87	19.44	277.85	24.44	30	Pass

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	19.09	19.34	18.83	243.381	23.86	30	Pass
6	2437	24.92	24.91	24.45	898.81	29.54	30	Pass
11	2462	19.33	19.76	19.27	264.856	24.23	30	Pass

802.11n (HT40)


Chan.	Chan. Freq. (MHz)	Avg. Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
3	2422	16.33	16.67	16.32	132.261	21.21	30	Pass
6	2437	20.67	20.89	20.42	349.579	25.44	30	Pass
9	2452	18.14	18.22	18.05	195.363	22.91	30	Pass

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 Test Setup



4.5.3 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSP40	100060	May 11, 2016	May 10, 2017

- NOTE:**
1. The test was performed in Oven room 2.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. Tested Date: Nov. 09, 2016

4.5.4 Test Procedure

802.11b, 802.11g, 802.11n (HT20):

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.

802.11n (HT40):

- a) Measure the duty cycle (x).
- b) Set instrument center frequency to DTS channel center frequency.
- c) Set span to at least 1.5 times the OBW.
- d) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- e) Set VBW $\geq 3 \times \text{RBW}$.
- f) Detector = power averaging (RMS) or sample detector (when RMS not available).
- g) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- h) Sweep time = auto couple.
- i) Do not use sweep triggering. Allow sweep to “free run”.
- j) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- k) Use the peak marker function to determine the maximum amplitude level.
- l) Add $10 \log(1/x)$, where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6

4.5.7 Test Results

802.11b

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=3) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-6.68	4.77	-1.91	5.23	Pass
	6	2437	-6.56	4.77	-1.79	5.23	Pass
	11	2462	-8.16	4.77	-3.39	5.23	Pass
1	1	2412	-6.05	4.77	-1.28	5.23	Pass
	6	2437	-6.17	4.77	-1.40	5.23	Pass
	11	2462	-7.43	4.77	-2.66	5.23	Pass
2	1	2412	-7.38	4.77	-2.61	5.23	Pass
	6	2437	-7.24	4.77	-2.47	5.23	Pass
	11	2462	-8.02	4.77	-3.25	5.23	Pass

Note: 1. Directional gain = 4dBi + 10log(3) = 8.77dBi > 6dBi , so the power density limit shall be reduced to 8-(8.77-6) = 5.23dBm.

802.11g

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=3) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-11.91	4.77	-7.14	5.23	Pass
	6	2437	-7.97	4.77	-3.20	5.23	Pass
	11	2462	-9.94	4.77	-5.17	5.23	Pass
1	1	2412	-12.08	4.77	-7.31	5.23	Pass
	6	2437	-8.02	4.77	-3.25	5.23	Pass
	11	2462	-11.92	4.77	-7.15	5.23	Pass
2	1	2412	-11.89	4.77	-7.12	5.23	Pass
	6	2437	-8.67	4.77	-3.90	5.23	Pass
	11	2462	-13.93	4.77	-9.16	5.23	Pass

Note: 1. Directional gain = 4dBi + 10log(3) = 8.77dBi > 6dBi , so the power density limit shall be reduced to 8-(8.77-6) = 5.23dBm.

802.11n (HT20)

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=3) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-13.90	4.77	-9.13	5.23	Pass
	6	2437	-9.48	4.77	-4.71	5.23	Pass
	11	2462	-13.42	4.77	-8.65	5.23	Pass
1	1	2412	-13.65	4.77	-8.88	5.23	Pass
	6	2437	-8.28	4.77	-3.51	5.23	Pass
	11	2462	-11.88	4.77	-7.11	5.23	Pass
2	1	2412	-13.71	4.77	-8.94	5.23	Pass
	6	2437	-9.46	4.77	-4.69	5.23	Pass
	11	2462	-14.56	4.77	-9.79	5.23	Pass


Note: 1. Directional gain = 4dBi + 10log(3) = 8.77dBi > 6dBi , so the power density limit shall be reduced to 8-(8.77-6) = 5.23dBm.

802.11n (HT40)

TX chain	Channel	Freq. (MHz)	PSD W/O Duty Factor (dBm/3kHz)	10 log (N=3) dB	Duty Factor (dB)	TOTAL PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	3	2422	-19.41	4.77	0.18	-14.46	5.23	Pass
	6	2437	-16.03	4.77	0.18	-11.08	5.23	Pass
	9	2452	-17.85	4.77	0.18	-12.90	5.23	Pass
1	3	2422	-15.66	4.77	0.18	-10.71	5.23	Pass
	6	2437	-15.28	4.77	0.18	-10.33	5.23	Pass
	9	2452	-9.30	4.77	0.18	-4.35	5.23	Pass
2	3	2422	-19.42	4.77	0.18	-14.47	5.23	Pass
	6	2437	-15.47	4.77	0.18	-10.52	5.23	Pass
	9	2452	-18.38	4.77	0.18	-13.43	5.23	Pass

Note: 1. Directional gain = 4dBi + 10log(3) = 8.77dBi > 6dBi , so the power density limit shall be reduced to 8-(8.77-6) = 5.23dBm.

2. Refer to section 3.3 for duty cycle spectrum plot.



4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSP40	100060	May 11, 2016	May 10, 2017

- NOTE:**
1. The test was performed in Oven room 2.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. Tested Date: Nov. 09, 2016

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.


4.6.6 EUT Operating Condition

Same as Item 4.3.6


4.6.7 Test Results


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.


802.11b




CHAIN 0




CHAIN 1


CHAIN 2



802.11g



CHAIN 0




CHAIN 1






BUREAU
VERITAS


CHAIN 2




802.11n (HT20)




CHAIN 0




CHAIN 1




CHAIN 2





802.11n (HT40)



CHAIN 0



CHAIN 1


CHAIN 2


5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---