




FCC Test Report

APPLICANT : ASUSTek COMPUTER
EQUIPMENT : PDA Phone
BRAND NAME : garmin  asus
MODEL NAME : nuvifone G60
FCC ID : MSQ-CALF
STANDARD : 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
Tx/Rx FREQUENCY RANGE : GSM850 : 824.2 ~ 848.8 MHz /
869.2 ~ 893.8 MHz
GSM1900 : 1850.2 ~ 1909.8 MHz /
1930.2 ~ 1989.8 MHz
WCDMA Band V : 826.4 ~ 846.6 MHz /
871.4 ~ 891.6 MHz
WCDMA Band II : 1852.4 ~ 1907.6 MHz /
1932.4 ~ 1987.6 MHz
MAX. ERP/EIRP POWER : GSM850 (GPRS) : 0.94 W
GSM850 (EDGE) : 0.26 W
GSM1900 (GSM) : 1.79 W
GSM1900 (EDGE) : 1.58 W
WCDMA Band V : 0.15 W
WCDMA Band II : 0.31 W
EMISSION DESIGNATOR : GSM : 300KGXW
EDGE : 300KG7W
WCDMA : 4M22F9W

The product was received on May 09, 2008 and completely tested on Nov. 04, 2008. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Roy Wu / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

SUMMARY OF TEST RESULT 3

REVISION HISTORY..... 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test..... 6

 1.4 Testing Site..... 8

 1.5 Applied Standards 8

 1.6 Ancillary Equipment List 8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9

 2.1 Test Mode..... 9

 2.2 Connection Diagram of Test System 9

3 TEST RESULT 10

 3.1 Conducted Output Power Measurement 10

 3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement 13

 3.3 Occupied Bandwidth and Band Edge Measurement 18

 3.4 Conducted Emission Measurement 31

 3.5 Field Strength of Spurious Radiation Measurement 47

 3.6 Frequency Stability Measurement..... 62

4 LIST OF MEASURING EQUIPMENTS..... 66

5 UNCERTAINTY OF EVALUATION 67

6 CERTIFICATION OF TAF ACCREDITATION 69

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS
3.2	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts for FCC (<6.3 Watts for IC)	PASS
3.2	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS
3.3	§2.1049 §22.917(a) §24.238(a)	N/A	Occupied Bandwidth	N/A	PASS
3.3	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS
3.4	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Conducted Emission	< 43+10log ₁₀ (P[Watts])	PASS
3.5	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS
3.6	§2.1055 §22.355 §24.235	RSS-132(4.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG850905-03	Rev. 01	Initial issue of report	Jul. 17, 2009



1 General Description

1.1 Applicant

ASUSTek COMPUTER


4F., No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

1.2 Manufacturer

ProTek (Shanghai) Ltd.









No. 3768, Xiu Yan Road, Nanhui District, 201315 Shanghai, P.R.C.

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	PDA Phone
Brand Name	garmin  asus
Model Name	nuvifone G60
FCC ID	MSQ-CALF
Tx Frequency	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz WCDMA Band II : 1850 MHz ~ 1910 MHz
Rx Frequency	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz WCDMA Band II : 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna	GSM850 : 32.63 dBm GSM1900 : 29.50 dBm WCDMA Band V : 22.70 dBm WCDMA Band II : 22.93 dBm
Maximum ERP/EIRP	GSM850 (GPRS) : 0.94 W (29.71 dBm) GSM850 (EDGE) : 0.26 W (24.10 dBm) GSM1900 (GSM) : 1.79 W (32.53 dBm) GSM1900 (EDGE) : 1.58 W (31.98 dBm) WCDMA Band V : 0.15 W (21.70 dBm) WCDMA Band II : 0.31 W (24.90 dBm)
Antenna Type	Fixed Internal Antenna
HW Version	R1.9
SW Version	OS: 1.32.2 Modem: V2.19.2-7-4-US
Type of Modulation	GSM / GPRS : GMSK EDGE : 8PSK WCDMA : QPSK HSDPA : QPSK / 16QAM
Type of Emission	GSM : 300KGXW EDGE : 300KG7W WCDMA : 4M22F9W
EUT Stage	Identical Prototype

Remark: For other wireless features of this EUT, the test report will be issued separately.

List of Accessory:

Specification of Accessory		
AC Adapter	Manufacturer	Phihong Technology Co., Ltd
	Brand Name	garmin  asus
	Model Name	PSAI05R-050Q
	Power Rating	I/P:100-240Vac, 50-60Hz, 0.3A; O/P: 5Vdc, 1A
Battery 1	Manufacturer	TD HiTech Energy Inc.
	Brand Name	garmin  asus
	Model Name	361-00039-00
	Power Rating	3.7V, 1100mAh
Battery 2	Manufacturer	Palladium Energy Inc.
	Brand Name	garmin  asus
	Model Name	361-00039-01
	Power Rating	3.7V, 1200mAh
Car Charger 1	Manufacturer	Ever Win International
	Brand Name	garmin  asus
	Model Name	CLA05D-050C
	Power Rating	I/P: 10-30V, 1A; O/P: 5V, 1A
	Power Cord Type	1.8 meter shielded cable with ferrite core
Car Charger 2	Manufacturer	Phihong Technology Co., Ltd.
	Brand Name	garmin  asus
	Model Name	GSM CLA
	Power Rating	I/P: 10-30V, 1A; O/P: 5V, 1A
	Power Cord Type	1.6 meter shielded cable with ferrite core
Earphone	Brand Name	garmin  asus
	Model Name	VDF009-W04-7ADIS-BK1
	Signal Line Type	1.27 meter non-shielded cable without ferrite core
USB Cable	Manufacturer	Foxlink
	Brand Name	garmin  asus
	Model Name	FY663223-A
	Signal Line Type	1.04 meter shielded cable with ferrite core
Car Kit	Manufacturer	Global Lighting Technologies Inc.
	Brand Name	garmin  asus
	Model Name	011-01856-10
LCD Panel	Brand Name	Sharp Corporation
	Model Name	LQ036T1DG01

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. For accessories equipped with this EUT, please refer to the appendix of the external photo.
3. This RF report is not related to battery source. Only battery 1 was used for the RF testing.



1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH02-HY	03CH07-HY	TW1022/4086B-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- ♦ 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI C63.4-2003
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ IC RSS-132, RSS-133

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Code
1.	GSM Base Station	R&S	CMU200	N/A	N/A	Unshielded, 1.8m

2 Test Configuration of Equipment Under Test

2.1 Test Mode


During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GPRS Link ■ EDGE Link ■ GPRS Link + WLAN Link 	<ul style="list-style-type: none"> ■ GPRS Link ■ EDGE Link
GSM 1900	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE Link
WCDMA Band V	<ul style="list-style-type: none"> ■ WCDMA Link 	<ul style="list-style-type: none"> ■ WCDMA Link ■ HSDPA Link
WCDMA Band II	<ul style="list-style-type: none"> ■ WCDMA Link 	<ul style="list-style-type: none"> ■ WCDMA Link ■ HSDPA Link

2.2 Connection Diagram of Test System



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

3.1.4 Test Setup





3.1.5 Test Result of Conducted Output Power

Cellular				
Modes	Channel	Frequency (MHz)	Conducted Power	
			(dBm)	(Watts)
GPRS	128 (Low)	824.2	32.33	1.71
	189 (Mid)	836.4	32.49	1.77
	251 (High)	848.8	32.63	1.83
EDGE	128 (Low)	824.2	26.81	0.48
	189 (Mid)	836.4	26.82	0.48
	251 (High)	848.8	26.77	0.48
WCDMA Band V	12.2k bps	4132 (Low)	22.69	0.19
		4182 (Mid)	22.70	0.19
		4233 (High)	22.58	0.18
	AMR	4132 (Low)	22.69	0.19
		4182 (Mid)	22.70	0.19
		4233 (High)	22.60	0.18
	HSDPA subtest-1	4132 (Low)	22.53	0.18
		4182 (Mid)	22.53	0.18
		4233 (High)	22.40	0.17
	HSDPA subtest-2	4132 (Low)	22.49	0.18
		4182 (Mid)	22.49	0.18
		4233 (High)	22.33	0.17
	HSDPA subtest-3	4132 (Low)	21.73	0.15
		4182 (Mid)	21.70	0.15
		4233 (High)	21.54	0.14
	HSDPA subtest-4	4132 (Low)	21.10	0.13
		4182 (Mid)	21.07	0.13
		4233 (High)	20.89	0.12



PCS					
Modes		Channel	Frequency (MHz)	Conducted Power	
				(dBm)	(Watts)
GSM		512 (Low)	1850.2	29.34	0.86
		661 (Mid)	1880.0	29.48	0.89
		810 (High)	1909.8	29.50	0.89
EDGE		512 (Low)	1850.2	26.27	0.42
		661 (Mid)	1880.0	26.42	0.44
		810 (High)	1909.8	26.43	0.44
WCDMA Band II	12.2k bps	9262 (Low)	1852.4	22.93	0.20
		9400 (Mid)	1880.0	22.31	0.17
		9538 (High)	1907.6	21.99	0.16
	AMR	9262 (Low)	1852.4	22.92	0.20
		9400 (Mid)	1880.0	22.30	0.17
		9538 (High)	1907.6	22.02	0.16
	HSDPA subtest-1	9262 (Low)	1852.4	22.80	0.19
		9400 (Mid)	1880.0	22.20	0.17
		9538 (High)	1907.6	21.90	0.15
	HSDPA subtest-2	9262 (Low)	1852.4	22.69	0.19
		9400 (Mid)	1880.0	22.14	0.16
		9538 (High)	1907.6	21.77	0.15
	HSDPA subtest-3	9262 (Low)	1852.4	21.85	0.15
		9400 (Mid)	1880.0	21.30	0.13
		9538 (High)	1907.6	20.96	0.12
	HSDPA subtest-4	9262 (Low)	1852.4	21.24	0.13
		9400 (Mid)	1880.0	20.67	0.12
		9538 (High)	1907.6	20.37	0.11

3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.2.1 Description of the ERP/EIRP Measurement

ERP/EIRP is measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was placed on a table with 1.0 meter height in a fully anechoic chamber.
2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiated power.
4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
5. Taking the record of maximum ERP/EIRP.
6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
7. The conducted power at the terminal of the dipole antenna is measured.
8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
9. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

P_s (dBm) : Input power to substitution antenna.

G_s (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

AF (dB/m) : Receive antenna factor

R_t : The highest received signal in spectrum analyzer for EUT.

R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.2.4 Test Setup





3.2.5 Test Result of ERP

GSM850 (GPRS) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-18.30	-48.12	0.00	-1.08	28.74	0.75
836.40	-18.16	-48.28	0.00	-0.93	29.19	0.83
848.80	-17.88	-48.35	0.00	-0.76	29.71	0.94
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-35.49	-47.97	0.00	-1.08	11.40	0.01
836.40	-35.32	-48.01	0.00	-0.93	11.76	0.01
848.80	-34.84	-48.05	0.00	-0.76	12.45	0.02

GSM850 (EDGE) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-23.67	-48.12	0.00	-1.08	23.37	0.22
836.40	-23.75	-48.28	0.00	-0.93	23.60	0.23
848.80	-23.49	-48.35	0.00	-0.76	24.10	0.26
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-40.34	-47.97	0.00	-1.08	6.55	0.00
836.40	-40.43	-48.01	0.00	-0.93	6.65	0.00
848.80	-40.13	-48.05	0.00	-0.76	7.16	0.01



WCDMA Band V Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-26.13	-48.12	0.00	-1.08	20.91	0.12
836.40	-25.65	-48.28	0.00	-0.93	21.70	0.15
846.60	-26.68	-48.35	0.00	-0.76	20.91	0.12
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-43.20	-47.97	0.00	-1.08	3.69	0.00
836.40	-42.92	-48.01	0.00	-0.93	4.16	0.00
846.60	-44.06	-48.05	0.00	-0.76	3.23	0.00



3.2.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-21.74	-51.88	0.00	1.96	32.10	1.62
1880.00	-22.53	-52.99	0.00	2.00	32.46	1.76
1909.80	-23.73	-54.28	0.00	1.98	32.53	1.79
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-22.03	-52.13	0.00	1.96	32.06	1.61
1880.00	-23.17	-53.17	0.00	2.00	32.00	1.58
1909.80	-24.00	-54.13	0.00	1.98	32.11	1.63

GSM1900 (EDGE) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-25.23	-51.88	0.00	1.96	28.61	0.73
1880.00	-23.35	-52.99	0.00	2.00	31.64	1.46
1909.80	-24.72	-54.28	0.00	1.98	31.54	1.43
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-24.88	-52.13	0.00	1.96	29.21	0.83
1880.00	-23.19	-53.17	0.00	2.00	31.98	1.58
1909.80	-24.38	-54.13	0.00	1.98	31.73	1.49



WCDMA Band II Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-28.95	-51.88	0.00	1.96	24.89	0.31
1880.00	-30.72	-52.99	0.00	2.00	24.27	0.27
1907.60	-32.10	-54.28	0.00	1.98	24.16	0.26
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-29.19	-52.13	0.00	1.96	24.90	0.31
1880.00	-30.49	-53.17	0.00	2.00	24.68	0.29
1907.60	-31.44	-54.13	0.00	1.98	24.67	0.29

3.3 Occupied Bandwidth and Band Edge Measurement

3.3.1 Description of Occupied Bandwidth and Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the low, middle and high channels for the highest RF powers were measured.
3. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.
4. The RBW was replaced by 10 kHz, due to the spectrum analyzer IF-Filter including an excess of the limit. A worst case correction factor of $10 \log (1\% \text{ BW}/\text{measurement RBW})$ was implemented.

3.3.4 Test Setup






3.3.5 Test Result (Plots) of Occupied Bandwidth


Band :	GSM 850	Power Stage :	High
Test Mode :	GPRS Link		

99% Occupied Bandwidth Plot on Channel 189



Date: 27.OCT.2008 20:45:55

26dB Bandwidth Plot on Channel 189




Date: 27.OCT.2008 20:43:34




Band :	GSM 850	Power Stage :	High
Test Mode :	EDGE Link		

99% Occupied Bandwidth Plot on Channel 189



Date: 27.OCT.2008 22:27:46

26dB Bandwidth Plot on Channel 189




Date: 27.OCT.2008 21:44:42




Band :	GSM 1900	Power Stage :	High
Test Mode :	GSM Link		

99% Occupied Bandwidth Plot on Channel 661



Date: 27.OCT.2008 23:57:10

26dB Bandwidth Plot on Channel 661




Date: 27.OCT.2008 23:55:25




Band :	GSM 1900	Power Stage :	High
Test Mode :	EDGE Link		

99% Occupied Bandwidth Plot on Channel 661



Date: 28.OCT.2008 01:27:47

26dB Bandwidth Plot on Channel 661




Date: 28.OCT.2008 01:26:03




Band :	WCDMA Band V	Power Stage :	High
Test Mode :	WCDMA Link		

99% Occupied Bandwidth Plot on Channel 4182



Date: 28.OCT.2008 01:58:12

26dB Bandwidth Plot on Channel 4182




Date: 28.OCT.2008 01:56:58




Band :	WCDMA Band II	Power Stage :	High
Test Mode :	WCDMA Link		

99% Occupied Bandwidth Plot on Channel 9400



Date: 28.OCT.2008 03:12:14

26dB Bandwidth Plot on Channel 9400




Date: 28.OCT.2008 03:10:52



3.3.6 Test Result (Plots) of Conducted Band Edges


Band :	GSM850	Power Stage :	High
Test Mode :	GPRS Link		

Lower Band Edge Plot on Channel 128



Date: 27.OCT.2008 20:49:18

Higher Band Edge Plot on Channel 251




Date: 27.OCT.2008 20:51:42




Band :	GSM850	Power Stage :	High
Test Mode :	EDGE Link		

Lower Band Edge Plot on Channel 128



Date: 27.OCT.2008 22:37:14

Higher Band Edge Plot on Channel 251




Date: 27.OCT.2008 22:38:55




Band :	GSM1900	Power Stage :	High
Test Mode :	GSM Link		

Lower Band Edge Plot on Channel 512



Date: 27.OCT.2008 23:59:18

Higher Band Edge Plot on Channel 810




Date: 28.OCT.2008 00:45:56




Band :	GSM1900	Power Stage :	High
Test Mode :	EDGE Link		

Lower Band Edge Plot on Channel 512



Date: 28.OCT.2008 01:09:52

Higher Band Edge Plot on Channel 810




Date: 28.OCT.2008 01:18:07




Band :	WCDMA Band V	Power Stage :	High
Test Mode :	WCDMA Link		

Lower Band Edge Plot on Channel 4132



Date: 28.OCT.2008 02:51:02

Higher Band Edge Plot on Channel 4233




Date: 28.OCT.2008 02:48:15




Band :	WCDMA Band II	Power Stage :	High
Test Mode :	WCDMA Link		

Lower Band Edge Plot on Channel 9262



Date: 28.OCT.2008 03:15:06

Higher Band Edge Plot on Channel 9538



Date: 28.OCT.2008 03:16:58

3.4 Conducted Emission Measurement

3.4.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GPRS Link		

Conducted Emission Plot between 30M-1G



Date: 27.OCT.2008 23:31:52


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 27.OCT.2008 21:05:10




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 27.OCT.2008 21:10:58

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 27.OCT.2008 21:12:44




Band :	GSM850	Channel :	CH189
Test Mode :	EDGE Link		

Conducted Emission Plot between 30M-1G



Date: 27.OCT.2008 23:33:50


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 27.OCT.2008 21:31:34




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 27.OCT.2008 21:22:29

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 27.OCT.2008 21:18:08




Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link		

Conducted Emission Plot between 30M-1G



Date: 28.OCT.2008 00:48:53


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 28.OCT.2008 00:49:48




Conducted Emission Plot between 3G-7G



Date: 28.OCT.2008 00:51:49


Conducted Emission Plot between 7G-13.6G



Date: 28.OCT.2008 00:53:28



Conducted Emission Plot between 13.6G-19.1G




Date: 28.OCT.2008 00:54:27




Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE Link		

Conducted Emission Plot between 30M-1G



Date: 28.OCT.2008 01:04:06


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 28.OCT.2008 01:03:38




Conducted Emission Plot between 3G-7G



Date: 28.OCT.2008 00:59:49


Conducted Emission Plot between 7G-13.6G



Date: 28.OCT.2008 00:59:14



Conducted Emission Plot between 13.6G-19.1G




Date: 28.OCT.2008 00:58:42




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	WCDMA Link		

Conducted Emission Plot between 30M-1G



Date: 28.OCT.2008 02:56:24


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 28.OCT.2008 03:07:30




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 28.OCT.2008 03:31:34

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 28.OCT.2008 02:58:29




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	WCDMA Link		

Conducted Emission Plot between 30M-1G



Date: 28.OCT.2008 03:08:16


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 28.OCT.2008 03:06:09




Conducted Emission Plot between 3G-7G



Date: 28.OCT.2008 03:03:58


Conducted Emission Plot between 7G-13.6G



Date: 28.OCT.2008 03:03:26



Conducted Emission Plot between 13.6G-19.1G



Date: 28.OCT.2008 03:00:54

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. Emission level (dBm) = output power + substitution Gain.


3.5.4 Test Setup





3.5.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	26~28°C
Test Mode :	GSPRS Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : HF-EIRP(080306) HORIZONTAL
 Model : FG 850905
 Mode : Mode 1
 Plane : F1

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-41.95	-13	-28.95	-49.7	-40.96	3.39	4.55	H	Pass
2509	-42.18	-13	-29.18	-49.16	-42.24	3.71	5.92	H	Pass
5850	-47.27	-13	-34.27	-65.67	-49.72	4.38	8.98	H	Pass
6690	-38.16	-13	-25.16	-59.97	-40.35	5.22	9.56	H	Pass
7530	-36.97	-13	-23.97	-61.09	-38.31	6.22	9.71	H	Pass
8370	-43.75	-13	-30.75	-65.57	-46.49	5.59	10.48	H	Pass



Band :	GSM850	Temperature :	26~28°C
Test Mode :	GPRS Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY
 Condition : HF-EIRP(080306) VERTICAL
 Model : FG 850905
 Mode : Mode 1
 Plane : E1

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-54.00	-13	-41.00	-61.92	-52.62	3.39	4.16	V	Pass
2509	-41.97	-13	-28.97	-52.6	-41.83	3.71	5.72	V	Pass
5850	-47.52	-13	-34.52	-65.64	-51.01	4.38	10.02	V	Pass
6690	-37.76	-13	-24.76	-58.98	-41.01	5.22	10.62	V	Pass
7530	-39.91	-13	-26.91	-63.81	-42.35	6.22	10.81	V	Pass



Band :	GSM850	Temperature :	26~28°C
Test Mode :	EDGE Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : HF-EIRP(080306) HORIZONTAL
 Model : FG 850905
 Mode : Mode 2
 Plane : E1

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-47.03	-13	-34.03	-53.92	-46.04	3.39	4.55	H	Pass
2509	-47.73	-13	-34.73	-54.81	-47.79	3.71	5.92	H	Pass
6690	-41.04	-13	-28.04	-62.85	-43.23	5.22	9.56	H	Pass



Band :	GSM850	Temperature :	26~28°C
Test Mode :	EDGE Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY
 Condition : HF-EIRP(080306) VERTICAL
 Model : FG 850905
 Mode : Mode 2
 Plane : E1

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
2509	-48.82	-13	-35.82	-59.41	-48.68	3.71	5.72	V	Pass
6690	-40.88	-13	-27.88	-62.1	-44.13	5.22	10.62	V	Pass



Band :	GSM1900	Temperature :	26~28°C
Test Mode :	GSM Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : HF-EIRP(080306) HORIZONTAL
 Model : FG 850905
 Mode : Mode 1
 Plane : E1

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
5636	-44.60	-13	-31.60	-63.52	-49.54	3.87	8.81	H	Pass
7520	-42.28	-13	-29.28	-63.9	-46.16	5.83	9.71	H	Pass
11280	-35.11	-13	-22.11	-66.62	-37.39	8.48	10.76	H	Pass



Band :	GSM1900	Temperature :	26~28°C
Test Mode :	GSM Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)
 Site : 09CH07-HY
 Condition : HF-EIRP(080306) VERTICAL
 Model : FG 850905
 Mode : Mode 1
 Plane : E1

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
5636	-42.79	-13	-29.79	-63.19	-48.69	3.87	9.77	V	Pass
7520	-40.50	-13	-27.50	-62.98	-45.48	5.83	10.81	V	Pass



Band :	GSM1900	Temperature :	26~28°C
Test Mode :	EDGE Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : HF-EIRP(080306) HORIZONTAL
 Model : FG 850905
 Mode : Mode 2
 Plane : E1

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
5636	-45.27	-13	-32.27	-64.54	-50.21	3.87	8.81	H	Pass
7520	-43.80	-13	-30.80	-64.71	-47.68	5.83	9.71	H	Pass



Band :	GSM1900	Temperature :	26~28°C
Test Mode :	EDGE Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)
 Site : 09CH07-HY
 Condition : HF-EIRP(080306) VERTICAL
 Model : FG 850905
 Mode : Mode 2
 Plane : E1

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
5636	-39.01	-13	-26.01	-62.6	-44.91	3.87	9.77	V	Pass
7520	-40.56	-13	-27.56	-62.94	-45.54	5.83	10.81	V	Pass



Band :	WCDMA Band V	Temperature :	26~28°C
Test Mode :	WCDMA Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)
 Site : 09CH07-HY
 Condition : HF-EIRP(080306) HORIZONTAL
 Model : FG 850905
 Mode : Mode 3
 Plane : E1

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-52.37	-13	-39.37	-57.95	-51.38	3.39	4.55	H	Pass
2509	-51.24	-13	-38.24	-61.38	-51.3	3.71	5.92	H	Pass
3349	-50.00	-13	-37.00	-60.95	-51.93	3.13	7.21	H	Pass



Band :	WCDMA Band V	Temperature :	26~28°C
Test Mode :	WCDMA Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH07-HY
 Condition : HF-EIRP(080306) VERTICAL
 Model : FG 850905
 Mode : Mode 3
 Plane : E1

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3349	-47.09	-13	-34.09	-57.39	-49.29	3.13	7.48	V	Pass



Band :	WCDMA Band II	Temperature :	26~28°C
Test Mode :	WCDMA Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : HF-EIRP(080306) HORIZONTAL
 Model : FG 850905
 Mode : Mode 3
 Plane : E1

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-52.33	-13	-39.33	-66.69	-55.7	4.03	7.40	H	Pass



Band :	WCDMA Band II	Temperature :	26~28°C
Test Mode :	WCDMA Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : HF-EIRP(080306) VERTICAL
 Model : FG 850905
 Mode : Mode 3
 Plane : E1

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-50.43	-13	-37.43	-65.73	-54.31	4.03	7.91	V	Pass



Band :	GSM850	Temperature :	26~28°C
Test Mode :	GPRS + WLAN Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : HF-EIRP(080306) HORIZONTAL
 Model : FG 850905
 Mode : Mode 1
 Plane : E1

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-42.13	-13	-29.13	-49.88	-41.14	3.39	4.55	H	Pass
2509	-34.89	-13	-21.89	-43.19	-34.95	3.71	5.92	H	Pass
5850	-47.03	-13	-34.03	-65.43	-49.48	4.38	8.98	H	Pass
6690	-38.78	-13	-25.78	-60.59	-40.97	5.22	9.56	H	Pass
7530	-37.95	-13	-24.95	-62.07	-39.29	6.22	9.71	H	Pass



Band :	GSM850	Temperature :	26~28°C
Test Mode :	GPRS + WLAN Link	Relative Humidity :	41~43%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Trace: (Discrete)
 Site : 03CH07-HY
 Condition : HF-EIRP(080306) VERTICAL
 Model : FG 850905
 Mode : Mode 1
 Plane : E1

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1669	-56.82	-13	-43.82	-59.4	-55.44	3.39	4.16	V	Pass
2509	-42.71	-13	-29.71	-53.41	-42.57	3.71	5.72	V	Pass
6690	-38.63	-13	-25.63	-59.85	-41.88	5.22	10.62	V	Pass
7530	-38.31	-13	-25.31	-62.21	-40.75	6.22	10.81	V	Pass

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.6.2 Measuring Instruments

See list of measuring instruments of this test report.


3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT can not be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.6.5 Test Setup





3.6.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5		

Temperature (°C)	GPRS		EDGE		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-51	-0.06	46	0.05	PASS
-20	-54	-0.06	31	0.04	
-10	-58	-0.07	24	0.03	
0	25	0.03	26	0.03	
10	27	0.03	36	0.04	
20	21	0.02	46	0.05	
30	13	0.02	-15	-0.02	
40	15	0.02	26	0.03	
50	12	0.01	43	0.05	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5		

Temperature (°C)	GSM		EDGE		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	27	0.01	-57	-0.03	PASS
-20	43	0.02	-35	-0.02	
-10	41	0.02	-29	-0.02	
0	29	0.02	-14	-0.01	
10	37	0.02	-15	-0.01	
20	27	0.01	-27	-0.01	
30	16	0.01	-35	-0.02	
40	28	0.01	-52	-0.03	
50	34	0.02	-58	-0.03	



Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5		

Temperature (°C)	WCDMA		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	42	0.05	PASS
-20	23	0.03	
-10	28	0.03	
0	35	0.04	
10	39	0.05	
20	22	0.03	
30	34	0.04	
40	44	0.05	
50	-11	-0.01	

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5		

Temperature (°C)	WCDMA		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	15	0.01	PASS
-20	-8	0.00	
-10	-16	-0.01	
0	-24	-0.01	
10	-38	-0.02	
20	-21	-0.01	
30	-56	-0.03	
40	-34	-0.02	
50	-59	-0.03	



3.6.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS	3.7	21	0.02	2.5	PASS
		BEP	65	0.08		
		4.2	36	0.04		
	EDGE	3.7	46	0.05		
		BEP	63	0.07		
		4.2	18	0.02		
GSM 1900 CH661	GSM	3.7	27	0.01		
		BEP	-8	0.00		
		4.2	60	0.03		
	EDGE	3.7	-27	-0.01		
		BEP	38	0.02		
		4.2	66	0.03		
WCDMA Band V CH4182	WCDMA	3.7	22	0.03		
		BEP	-25	-0.03		
		4.2	34	0.04		
WCDMA Band II CH9400	WCDMA	3.7	-21	-0.01		
		BEP	39	0.02		
		4.2	-81	-0.04		

Remark:

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.3 V.



4 List of Measuring Equipments

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Base Station	R&S	CMU200	116456	N/A	Jun. 05, 2008	Jun. 04, 2009	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 26, 2008	Jun. 25, 2009	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D35P	TBN-930701	N/A	Aug. 01, 2008	Jul. 31, 2009	Conducted (TH02-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2726	30MHz ~ 1GHz	Dec. 01, 2007	Nov. 30, 2008	Radiation (03CH07-HY)
Spectrum Analyzer	R&S	FSP	101067	9kHz ~ 30GHz	Dec. 05, 2007	Dec. 04, 2008	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	75962	1G ~ 18GHz	Aug. 13, 2008	Aug. 12, 2009	Radiation (03CH07-HY)
Pre Amplifier	Agilent	8449B	3008A02362	1 ~ 26.5GHz	Dec. 22, 2007	Dec. 21, 2008	Radiation (03CH07-HY)
Pre Amplifier	COM-POWER	PA-103A	161241	10-1000MHz.32dB. GAIN	Mar. 31, 2008	Mar. 30, 2009	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	66584	1G ~ 18GHz	Aug. 06, 2008	Aug. 05, 2009	Radiation (03CH07-HY)
Base Station	R&S	CMU200	116456	NA	Jul. 05, 2008	Jul. 04, 2009	Radiation (03CH07-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of x_i		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.10	Normal(k=2)	0.05
Cable loss	0.10	Normal(k=2)	0.05
AMN insertion loss	2.50	Rectangular	0.63
Receiver Spec	1.50	Rectangular	0.43
Site imperfection	1.39	Rectangular	0.80
Mismatch	+0.34/-0.35	U-shape	0.24
Combined standard uncertainty Uc(y)	1.13		
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	2.26		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of x_i		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.41	Normal(k=2)	0.21
Antenna factor calibration	0.83	Normal(k=2)	0.42
Cable loss calibration	0.25	Normal(k=2)	0.13
Pre Amplifier Gain calibration	0.27	Normal(k=2)	0.14
RCV/SPA specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site imperfection	1.43	Rectangular	0.83
Mismatch	+0.39/-0.41	U-shaped	0.28
Combined standard uncertainty Uc(y)	1.27		
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	2.54		



Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of x_i		$u(x_i)$	C_i	$C_i * u(x_i)$
	dB	Probability Distribution			
Receiver reading	±0.10	Normal(k=1)	0.10	1	0.10
Antenna factor calibration	±1.70	Normal(k=2)	0.85	1	0.85
Cable loss calibration	±0.50	Normal(k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20 \log(1 - \Gamma_1 * \Gamma_2)$	+0.34/-0.35	U-shaped	0.244	1	0.244
Combined standard uncertainty Uc(y)	2.36				
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	4.72				

6 Certification of TAF Accreditation



Certificate No. : L1190-090417

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities

Jay-san Chen

Jay-San Chen
President, Taiwan Accreditation Foundation
Date : April 17, 2009

P1, total 20 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix



Appendix A. Photographs of EUT

Please refer to Sporton report number EP850905-03 as below.