

SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230500007002 Page: 1 of 10

# **RF EXPOSURE EVALUATION REPORT**

Application No.:	FYCR2305000070AT
Applicant:	ASUSTeK COMPUTER INC.
Address of Applicant:	1F., No. 15, Lide Rd., Beitou Dist., Taitei City 112 Taiwan
Manufacturer:	ASUSTeK COMPUTER INC.
Address of Manufacturer:	1F., No. 15, Lide Rd., Beitou Dist., Taitei City 112 Taiwan
Factory:	Dongguan Soai Electronic Technology Co., LTD
Address of Factory:	3 Huayu road, Changlong village, Huangjiang town, Dongguan city, Guangdong province
Equipment Under Test (EUT	):
EUT Name:	Dongle
Model No.:	CW101-D
Trade Mark:	ASUS
FCC ID:	MSQ-DG-CW101
Standard(s) :	FCC Rules 47 CFR §2.1093
	KDB 447498 D04 interim General RF Exposure Guidance v01
Date of Receipt:	2023-05-05
Date of Evaluation:	2023-05-06 to 2023-05-30
Date of Issue:	2023-05-30
Evaluation Result:	Pass*

\* In the configuration evaluated, the EUT complied with the standards specified above.

WinkeyWang

Winkey Wang EMC Technical Manager



y → - Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printeroverieaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.Terms-ot-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appears hown in this total moor wherein the anneal of the sample(s) tested and such sample(s) are related for the day of days only. The such sample is authering of the sample(s) tested and such sample(s) are related for 30 days only. The medicine, the submeticing of testing / inservice medicate, please contact us at telephone: (85-75) 8307 1443, or email: CM Doccheck?

Fuyong lab. Xinlong Technic Park, Fengtang Road, Fuyong Subdistrict, Bao'an, Shenzhen, China 518103 tt (86–755) 88663988 ft (86–755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 tt (86–755) 88663988 ft (86–755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230500007002 Page: 2 of 10

	Revision Record							
Version	Chapter	Date	Modifier	Remark				
01		2023-05-30		Original				

Authorized for issue by:		
	Tree Zhan	
	Tree Zhan/Project Engineer	
	WinkeyWarg	
	Winkey Wang/Reviewer	•



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-end-Conditions/T

Fuyong lab. Xiniong TechnoPark, Fenglang Road, Fuyong Subdistict, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国 ·深圳 ·宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230500007002 Page: 3 of 10

# 2 Contents

			Page
1	Cov	ver Page	1
2	Cor	ntents	3
3	Ger	neral Information	4
	3.1	General Description of E.U.T.	4
	3.2	Details of E.U.T.	
	3.3	Separation Distance	
	3.4	Test Location	
	3.5	Test Facility	5
	3.6	Deviation from Standards	
	3.7	Abnormalities from Standard Conditions	5
4	FC	C Radiofrequency radiation exposure limits	6
	4.1	Blanket 1 mW Blanket Exemption	6
	4.2	MPE-based Exemption	
	4.3	SAR-based Exemption	
5	Меа	asurement and Calculation	10
	5.1	Maximum transmit power	10
	5.2	RF Exposure Calculation	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-end-Conditions/T

Fuyong kab. Xiniong TechnoPark, Fengtang Road, Fuyong Subdistrict, Barian, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230500007002 Page: 4 of 10

### **3** General Information

#### 3.1 General Description of E.U.T.

	⊠ Portable device
Product Type:	Mobile device
	Fixed device

#### 3.2 Details of E.U.T.

Power supply:	Input 5Vdc via PC USB port
Operation Frequency:	2402-2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	Integral Antenna
Antenna Gain:	-5.92dBi

Remark: The information in this section is provided by the applicant or manufacturer, CCS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

#### 3.3 Separation Distance

 Minimum test separation distance:
 5mm

 Remark: This minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.Terms-end-Conditions.Terms-end-Conditions/T

Fuyong lab. Xiniong TechnoPark, Fenglang Road, Fuyong Subdistid, Bao'an, Shenzhen, China 518103 t (86–755) 88663988 f (86–755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86–755) 88663988 f (86–755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230500007002 Page: 5 of 10

#### 3.4 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc. Shenzhen branch.

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdistrict, Bao'an, Shenzhen, China Tel: +86 755 8866 3988 Fax: +86 755 2671 0594 No tests were sub-contracted.

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### A2LA (Certificate No. 6606.01)

Compliance Certification Services (Kunshan) Inc. Shenzhen branch is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6606.01.

#### • FCC –Designation Number: CN1322

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized as an accredited testing laboratory.

Designation Number: CN1322. Test Firm Registration Number: 718073

#### • Innovation, Science and Economic Development Canada

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0129.

IC#: 28189.

#### 3.6 Deviation from Standards

None

# 3.7 Abnormalities from Standard Conditions



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-an-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company have prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refor only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdishid, Bao'an, Shenzhen, China 518103 t (86–755) 88663988 f (86–755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86–755) 88663988 f (86–755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230500007002 Page: 6 of 10

# 4 FCC Radiofrequency radiation exposure limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

#### 4.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

#### 4.2 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

RF Source Frequency			Minimum Distance Th			Threshold ERP		
<i>f</i> ∟ MHz		<i>f</i> ⊦ MHz	λ∟ / 2π		λ <sub>Η</sub> / 2π	W		
0.3	_	1.34	159 m	_	35.6 m	1,920 R <sup>2</sup>		
1.34	_	30	35.6 m	_	1.6 m	3,450 R²/f ²		
30	_	300	1.6 m	_	159 mm	3.83 R <sup>2</sup>		
300	_	1,500	159 mm	_	31.8 mm	0.0128 R <sup>2</sup> f		
1,500	1,500 – 100,000 31.8 mm – 0.5 mm 19.2R <sup>2</sup>							
Subscripts L and H are low and high; λ is wavelength.								
From §1.1307(	b)(3)(i)(	C), modified by a	dding Minimum D	Distance	e columns.			

Table B.1—Thresholds For Single RF Sources Subject to Routine Environmental Evaluation

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least  $\lambda/2\pi$ . The thresholds are



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or results shown in this test report refer only to the sample(s) are related for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-75) 8307 1443, or email: Ch.Doccheck&ses.com

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdishid, Badan, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230500007002 Page: 7 of 10

based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of \$1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in \$1.1310 is necessary if the ERP of the device is greater than *ERP*<sub>20cm</sub> in Formula (B.1) [repeated from \$2.1091(c)(1); also in \$1.1307(b)(1)(i)(B)].

 $P_{\rm th} (\rm mW) = ERP_{20 \,\rm cm} (\rm mW) = \begin{cases} 2040f & 0.3 \,\rm GHz \le f < 1.5 \,\rm GHz \\ \\ 3060 & 1.5 \,\rm GHz \le f \le 6 \,\rm GHz \end{cases}$ (B.1)

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

Limit calculation							
Frequency range Frequency(MHz) R(λ/2π)(m) Threshold ERP(W)							
300~1500MHz	915	0.0522	0.032				
1500~100000MHz	2480	0.0193	0.007				

#### 4.3 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of  $\lambda/4$ .

As for devices with antennas of length greater than  $\lambda/4$  where the gain is not well defined, but always less than that of a half-wave dipole (length  $\lambda/2$ ), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excered the parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fulleet steint of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report accriticate, please contact us at telephone: (86-755) 8307 1443, or email: Ch.Doccheck@ses.com

Fuyong lab. Xiniong TechnoPark, Fengtang Road, Fuyong Subdistind, Bacian, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgs.group.com.cn 中国・深圳・宝安区福永街道凤塘大道嘉龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230500007002 Page: 8 of 10

The SAR-based exemption formula of \$1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold  $P_{th}$  (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{\text{th}}$  is given by Formula (B.2).

$$P_{\rm th} \,({\rm mW}) = \begin{cases} ERP_{20\,\rm cm} (d/20\,\rm cm)^x & d \le 20\,\rm cm \\ \\ ERP_{20\,\rm cm} & 20\,\rm cm < d \le 40\,\rm cm \end{cases}$$
(B.2)

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20}\operatorname{cm}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP<sub>20cm</sub> is per Formula (B.1).



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document cannot be reproduced except in full, without prior written approval of the Company, any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443, results. Howeheet the company is sole certificate, please contact us at telephone: (86-755) 83071443, results.

Fuyong kab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdistict, Bao'an, Shenzhen, China 518103 t (86–755) 88663988 f (86–755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86–755) 88663988 f (86–755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230500007002 Page: 9 of 10

Example values shown in Table B.2 are for illustration only.

Frequency					Distan	ce(mm)				
(MHz)	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Table B.2—Example Power Thresholds (mW)

Limit calculation						
Frequency range(GHz)	Frequency(GHz)	Х	Distance(cm)	Pth (mW)		
0.3~1.5	0.915	1.474	0.5	8.133		
1.5~6	2.48	1.905	0.5	2.717		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-an-Comterms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-an-Comterms-and-Conditions for the Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Cond

Fuyong kab. Xiniong TechnoPark, Fengtang Road, Fuyong Subdistrict, Barian, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR230500007002 Page: 10 of 10

# 5 Measurement and Calculation

#### 5.1 Maximum transmit power

Test Mode	Test Channel (MHz)	Maximum Field Strength (dBuV/m)	E.I.R.P (dBm)	Max ANT Gain (dBi)	Conducted Power (dBm)	Conducted Power (mW)
GFSK	2440	89.77*	-5.46	-5.92	0.46	1.11

(\*) Note:

The Maximum Field Strength is based on the RF Test Report FYCR230500007001.

E (dBuV/m) =EIRP(dBm)-20logD(m)+104.77

E=89.77dBuV/m(Refer to test report FYCR230500007001)

D=3m

EIRP=89.77-(-20log(3)+104.77)

EIRP=-5.46dBm

#### 5.2 RF Exposure Calculation

The Max conducted power is 1.11mW.

**Remark**: we used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

	Evaluation method	Exempt Limit(mW)	Verdict
	Blanket 1 mW Blanket Exemption	1mW	N/A
	MPE-based Exemption(ERP)	7mW(ERP)	N/A
$\boxtimes$	SAR-based Exemption( <i>P</i> th)	2.7mW	Yes

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report.

--End of the Report--



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document cannot be reproduced except in full, without prior written approval of the Company, any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) issues defined for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN Doccheck@ss.com

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdishid, Barlan, Shenzhen, China 518103 tt (86-755) 88663988 ft (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 tt (86-755) 88663988 ft (86-755) 26710594 sgs.china@sgs.com