

# FCC Test Report

Product Name	Smart Door Lock
Model No.	DL101
FCC ID	MSQ-DL101

Applicant	ASUSTeK COMPUTER INC.
Address	4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

Date of Receipt	June 16, 2015
Issued Date	Aug. 20, 2015
Report No.	1560454R-RFUSP17V00
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of Quietek Corporation.

# Test Report

Issued Date: Aug. 20, 2015

Report No.: 1560454R-RFUSP17V00



Product Name	Smart Door Lock
Applicant	ASUSTeK COMPUTER INC.
Address	4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan
Manufacturer	TONG LUNG METAL INDUSTRY CO., LTD.
Model No.	DL101
FCC ID.	MSQ-DL101
EUT Rated Voltage	DC 6V (Power by AA/1.5V*4 Battery)
EUT Test Voltage	DC 6V (Power by AA/1.5V*4 Battery)
Trade Name	ASUS
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2014 ANSI C63.4: 2014, ANSI C63.10: 2013 KDB 558074 D01 DTS Meas Guidance v03r03
Test Result	Complied

Documented By : Anita Chou  
( Senior Engineering Adm. Specialist /  
Anita Chou)

Tested By : Nova chu  
( Engineer / Nova Chu )

Approved By : Vincent Lin  
( Director / Vincent Lin)

## TABLE OF CONTENTS

Description	Page
<b>1. GENERAL INFORMATION.....</b>	<b>5</b>
1.1. EUT Description.....	5
1.2. Operational Description .....	6
1.3. Tested System Details.....	7
1.4. Configuration of tested System .....	7
1.5. EUT Exercise Software .....	7
1.6. Test Facility .....	8
<b>2. Conducted Emission.....</b>	<b>9</b>
2.1. Test Equipment.....	9
2.2. Test Setup .....	9
2.3. Limits .....	10
2.4. Test Procedure .....	10
2.5. Uncertainty .....	10
2.6. Test Result of Conducted Emission.....	11
<b>3. Radiated Emission.....</b>	<b>12</b>
3.1. Test Equipment.....	12
3.2. Test Setup .....	12
3.3. Limits .....	13
3.4. Test Procedure .....	14
3.5. Uncertainty .....	15
3.6. Test Result of Radiated Emission.....	16
<b>4. Band Edge .....</b>	<b>22</b>
4.1. Test Equipment.....	22
4.2. Test Setup .....	22
4.3. Limits .....	23
4.4. Test Procedure .....	23
4.5. Uncertainty .....	23
4.6. Test Result of Band Edge .....	24
<b>5. Frequency Tolerance .....</b>	<b>25</b>
5.1. Test Equipment.....	25
5.2. Test Setup .....	25
5.3. Limits .....	25
5.4. Test Procedure .....	25
5.5. Uncertainty .....	25
5.6. Test Result of Frequency Stability.....	26
<b>6. EMI Reduction Method During Compliance Testing .....</b>	<b>28</b>

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

## 1. GENERAL INFORMATION

### 1.1. EUT Description

Product Name	Smart Door Lock
Trade Name	ASUS
Model No.	DL101
FCC ID	MSQ-DL101
Frequency Range	13.56MHz
Modulation	ASK
Antenna Type	Loop Antenna
Main Chip	MCU Renesas/RL78/G13
Touch IC	MCU Renesas/RL78/G13Acypress/CY8C4014
NFC Module	NXP PN5331B3HN

Frequency of Each Channel:

Channel	Frequency
Channel 1:	13.56 MHz

Note:

1. This device is an Smart Door Lock with a built-in 13.56MHz transceiver.
2. This device includes NFC and Zigbee, transmit signals simultaneously in radiated emission measurement.
3. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.225

Test Mode	Mode 1: Transmit mode
-----------	-----------------------


### 1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
N/A				

Signal Cable Type	Signal cable Description
N/A	

### 1.4. Configuration of tested System



### 1.5. EUT Exercise Software

- (1) Setup the EUT as shown in Section 1.4
- (2) Provide the DC Power Source.
- (3) Start the continuous transmitter.
- (4) Verify that the EUT works properly.

**1.6. Test Facility**

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site: <http://www.quietek.com/chinese/about/certificates.aspx?bval=5>

The address and introduction of Quietek Corporation's laboratories can be founded in our Web site: <http://www.quietek.com/>

Site Description: File on  
Federal Communications Commission  
FCC Engineering Laboratory  
7435 Oakland Mills Road  
Columbia, MD 21046  
Registration Number: 92195

Site Name: Quietek Corporation  
Site Address: No.5-22, Ruishukeng,  
Linkou Dist. New Taipei City 24451,  
Taiwan, R.O.C.  
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789  
E-Mail : [service@quietek.com](mailto:service@quietek.com)

FCC Accreditation Number: TW1014

## 2. Conducted Emission


### 2.1. Test Equipment

	Equipment	Manufacturer	Model No. / Serial No.	Last Cal.	Remark
X	Test Receiver	R & S	ESCS 30 / 825442/018	Sep., 2014	
X	Artificial Mains Network	R & S	ENV4200 / 848411/10	Feb., 2015	Peripherals
X	LISN	R & S	ESH3-Z5 / 825562/002	Feb., 2015	EUT
	DC LISN	Schwarzbeck	8226 / 176	Mar, 2015	EUT
X	Pulse Limiter	R & S	ESH3-Z2 / 357.8810.52	Feb., 2015	
	No.1 Shielded Room				

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

### 2.2. Test Setup



### 2.3. Limits

<b>FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit</b>		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56 <sub>(註)</sub>	56-46 <sub>(註)</sub>
0.50-5.0	56	46
5.0 - 30	60	50

### 2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

### 2.5. Uncertainty

± 2.26 dB

## 2.6. Test Result of Conducted Emission

Product : Smart Door Lock  
Test Item : Conducted Emission Test

Owing to the EUT use battery supply voltage, this test item is not performed.

### 3. Radiated Emission

#### 3.1. Test Equipment


The following test equipments are used during the radiated emission test:

Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Site # 3	X Magnetic Loop Antenna	Teseq	HLA6121/ 37133	Sep, 2014
	X Bilog Antenna	Schaffner Chase	CBL6112B/ 2707	Jun, 2015
	X EMI Test Receiver	R&S	ESCS 30/838251/ 001	Jun, 2015
	X Coaxial Cable	QTK(Arnist)	RG 214/ LC003-RG	Jun, 2015
	X Coaxial signal switch	Arnist	MP59B/ 6200798682	Jun, 2015


- Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.  
2. The test instruments marked with "X" are used to measure the final test results.

#### 3.2. Test Setup

9kHz~30MHz



30MHz~1GHz



### 3.3. Limits

➤ Fundamental electric field strength Limit

FCC Part 15 Subpart C Paragraph 15.225 Limits				
Fundamental Frequency MHz	Field strength of fundamental			
	uV/m	Distance (meter)	dBuV/m	Distance (meter)
13.553 – 13.567	15848	30	124	3
13.410 – 13.553 and 13.567 – 13.710	334	30	90.47	3
13.110 – 13.410 and 13.710 – 14.010	106	30	80.50	3
Outside of the 13.110 – 14.010	See 15.209 Limits			

Remarks : 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)

2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

► Spurious electric field strength Limit

FCC Part 15 Subpart C Paragraph 15.209 Limits			
Frequency MHz	uV/m	dBuV/m	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	See Remark <sup>1</sup>	300
0.490-1.705	24000/F(kHz)	See Remark <sup>1</sup>	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

- Remarks :
1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
  2. In the Above Table, the tighter limit applies at the band edges.
  3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

### 3.4. Test Procedure

Fundamental electric field strength:

The EUT and its simulators are placed on a turn table which is 1 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum electric field strength.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna which is 1 meter above ground. All X-axis, Y-axis and Z-axis polarization of the antenna are set on measurement.

Spurious electric field strength:

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C6310: 2013 on radiated measurement.

On any frequency the radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission measurement are included emission measurement below 1000 MHz, there also is a limit on the radio frequency emissions, as

measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

The bandwidth below 30MHz setting on the field strength meter is 9kHz and above 30MHz is 120kHz.

The frequency range from 9kHz to 10th harmonics is checked.

### **3.5. Uncertainty**

± 2.6 dB below 30MHz

± 3.8 dB above 30MHz

**3.6. Test Result of Radiated Emission**

Product : Smart Door Lock  
Test Item : Fundamental Radiated Emission  
Test Site : No.3 OATS  
Test Mode : Mode 1: Transmit mode (simultaneous transmission)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>X-axis</b>					
<b>Quasi-Peak</b>					
<b>Horizontal</b>					
13.560	20.410	23.300	43.710	-80.290	124.000
<b>Vertical</b>					
13.560	20.410	23.300	43.710	-80.290	124.000

Note:

1.  $Limit = 84 \text{dBuV/m} + 40 * \text{Log} (30 \text{(m)} / 3 \text{(m)}) = 124 \text{dBuV/m}$
2. All Readings below 1GHz are Quasi-Peak, above are average value.
3. Measurement Level = Reading Level + Correct Factor.
4. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Smart Door Lock  
Test Item : General Radiated Emission Data (below 30MHz)  
Test Site : No.3 OATS  
Test Mode : Mode 1: Transmit mode (simultaneous transmission)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
27.120	19.950	2.900	22.850	-46.690	69.540
<b>Vertical</b>					
27.120	19.950	2.900	22.850	-46.690	69.540

Note:

1. Limit=29.54dBuV/m + 40\*Log (30(m)/3(m))=69.54dBuV/m
2. All Readings below 1GHz are Quasi-Peak, above are average value.
3. “█” means the worst emission level.
4. Measurement Level = Reading Level + Correct Factor.

Product : Smart Door Lock  
 Test Item : General Radiated Emission Data (above 30MHz)  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit mode (simultaneous transmission)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
<b>QP Detector</b>					
379.200	1.301	28.495	29.796	-16.204	46.000
460.680	4.030	23.252	27.282	-18.718	46.000
515.000	3.191	26.223	29.414	-16.586	46.000
542.160	3.925	25.766	29.691	-16.309	46.000
608.120	3.925	21.758	25.683	-20.317	46.000
823.460	7.241	22.281	29.522	-16.478	46.000
<b>Vertical</b>					
<b>QP Detector</b>					
352.040	-1.292	29.058	27.766	-18.234	46.000
386.960	-0.708	28.202	27.494	-18.506	46.000
515.000	0.081	27.644	27.725	-18.275	46.000
542.160	1.855	27.717	29.572	-16.428	46.000
615.880	1.473	23.439	24.912	-21.088	46.000
804.060	3.371	20.960	24.331	-21.669	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. "█" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : Smart Door Lock  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit mode (2405MHz) (simultaneous transmission)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4810.000	2.532	44.950	47.482	-26.518	74.000
7215.000	9.411	38.676	48.087	-25.913	74.000
9620.000	10.282	37.933	48.215	-25.785	74.000
<b>Average Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4810.000	2.927	45.601	48.528	-25.472	74.000
7215.000	9.895	38.171	48.066	-25.934	74.000
9620.000	10.760	38.013	48.773	-25.227	74.000
<b>Average Detector:</b>					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss –Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Smart Door Lock  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit mode (2440MHz) (simultaneous transmission)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4880.000	2.038	44.783	46.821	-27.179	74.000
7320.000	9.699	38.385	48.084	-25.916	74.000
9760.000	9.665	37.909	47.574	-26.426	74.000
<b>Average Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4880.000	2.499	45.568	48.067	-25.933	74.000
7320.000	10.303	38.025	48.328	-25.672	74.000
9760.000	10.299	37.236	47.536	-26.464	74.000
<b>Average Detector:</b>					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : Smart Door Lock  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit mode (2480MHz) (simultaneous transmission)

Frequency MHz	Correct Factor dB	Reading Level dBuV	Measurement Level dBuV/m	Margin dB	Limit dBuV/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4960.000	2.582	45.985	48.567	-25.433	74.000
7440.000	10.555	38.481	49.036	-24.964	74.000
9920.000	10.206	39.456	49.662	-24.338	74.000
<b>Average Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4960.000	3.398	46.254	49.653	-24.347	74.000
7440.000	11.214	38.488	49.702	-24.298	74.000
9920.000	11.245	38.698	49.943	-24.057	74.000
<b>Average Detector:</b>					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.


## 4. Band Edge

### 4.1. Test Equipment

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Site # 3	X	Magnetic Loop Antenna	Teseq	HLA6121/ 37133	Sep, 2014
	X	Bilog Antenna	Schaffner Chase	CBL6112B/ 2707	Jun, 2015
	X	EMI Test Receiver	R&S	ESCS 30/838251/ 001	Jun, 2015
	X	Coaxial Cable	QTK(Arnist)	RG 214/ LC003-RG	Jun, 2015
	X	Coaxial signal switch	Arnist	MP59B/ 6200798682	Jun, 2015

- Note:
1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
  2. The test instruments marked with "X" are used to measure the final test results.

### 4.2. Test Setup



### **4.3. Limits**

In any 9 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 50 dB below that in the 9 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### **4.4. Test Procedure**

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated measurement.

The bandwidth below 30MHz setting on the field strength meter is 9kHz and above 30MHz is 120kHz.

### **4.5. Uncertainty**

Radiated is  $\pm 2.6$  dB

#### 4.6. Test Result of Band Edge

Product : Smart Door Lock  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit mode (simultaneous transmission)

##### RF Radiated Measurement

Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	QP Limit (dBuV/m)	Result
<b>Horizontal</b>					
13.110	20.430	12.500	32.930	69.540	Pass
13.360	20.420	12.400	32.820	69.540	Pass
13.410	20.420	11.200	31.620	69.540	Pass
14.010	20.400	13.200	33.600	69.540	Pass

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. “█” means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Frequency (MHz)	Correct Factor (dB)	Reading Level (dBuV)	Emission Level (dBuV/m)	QP Limit (dBuV/m)	Result
<b>Vertical</b>					
13.110	20.430	3.800	24.230	69.540	Pass
13.360	20.420	3.900	24.320	69.540	Pass
13.410	20.420	3.800	24.220	69.540	Pass
14.010	20.400	3.800	24.200	69.540	Pass

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. “█” means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor


## 5. Frequency Tolerance

### 5.1. Test Equipment

Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2015
Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2015
X Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2015
X Temperature Chamber	TDE	CHM 150CT	March, 2015

Note: All equipments are calibrated every one year.

### 5.2. Test Setup



### 5.3. Limits

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency.

### 5.4. Test Procedure

The over operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### 5.5. Uncertainty

$\pm 150$  Hz

### 5.6. Test Result of Frequency Stability

Product : Smart Door Lock  
 Test Item : Frequency Tolerance  
 Test Site : Temperature Chamber  
 Test Mode : Mode 1: Transmit mode

Temperature (°C)	Voltage (V)	Observe Time	Declared Frequency (MHz)	Read Frequency (MHz)	Tolerance (%)	Limit (%)
20	6	start	13.56	13.56076	0.005605	± 0.01 %
		2mins	13.56	13.56076	0.005605	
		5mins	13.56	13.56076	0.005605	
		10mins	13.56	13.56076	0.005605	
20	6.9	start	13.56	13.56076	0.005605	± 0.01 %
		2mins	13.56	13.56076	0.005605	
		5mins	13.56	13.56076	0.005605	
		10mins	13.56	13.56076	0.005605	
20	5.1	start	13.56	13.56076	0.005605	± 0.01 %
		2mins	13.56	13.56076	0.005605	
		5mins	13.56	13.56076	0.005605	
		10mins	13.56	13.56076	0.005605	
50	6	start	13.56	13.56033	0.002434	± 0.01 %
		2mins	13.56	13.56033	0.002434	
		5mins	13.56	13.56033	0.002434	
		10mins	13.56	13.56033	0.002434	
40	6	start	13.56	13.56046	0.003392	± 0.01 %
		2mins	13.56	13.56046	0.003392	
		5mins	13.56	13.56046	0.003392	
		10mins	13.56	13.56046	0.003392	
30	6	start	13.56	13.56023	0.001696	± 0.01 %
		2mins	13.56	13.56023	0.001696	
		5mins	13.56	13.56023	0.001696	
		10mins	13.56	13.56023	0.001696	

10	6	start	13.56	13.56011	0.000811	± 0.01 %
		2mins	13.56	13.56011	0.000811	
		5mins	13.56	13.56011	0.000811	
		10mins	13.56	13.56011	0.000811	
0	6	start	13.56	13.56011	0.000811	± 0.01 %
		2mins	13.56	13.56011	0.000811	
		5mins	13.56	13.56011	0.000811	
		10mins	13.56	13.56011	0.000811	
-10	6	start	13.56	13.56092	0.006785	± 0.01 %
		2mins	13.56	13.56092	0.006785	
		5mins	13.56	13.56092	0.006785	
		10mins	13.56	13.56092	0.006785	
-20	6	start	13.56	13.56092	0.006785	± 0.01 %
		2mins	13.56	13.56092	0.006785	
		5mins	13.56	13.56092	0.006785	
		10mins	13.56	13.56092	0.006785	

**6. EMI Reduction Method During Compliance Testing**

No modification was made during testing.

## Attachment 1: EUT Test Photographs

## Attachment 2: EUT Detailed Photographs