

RF Exposure Evaluation Report

Product Name : Detachable Keyboard
Model No. : GZ700G Mobile Dock
FCC ID : MSQ-GZ700KB

Applicant : ASUSTeK Computer Inc

Address : 4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

Date of Receipt : Dec. 20, 2018
Date of Declaration : April 17, 2019
Report No. : 18C0278R-SAUSP03V00
Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

Issued Date: April 17, 2019

Report No.: 18C0278R-SAUSP03V00



Product Name	Detachable Keyboard
Applicant	ASUSTeK Computer Inc
Address	4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan
Manufacturer	ASUSTeK Computer Inc
Model No.	GZ700G Mobile Dock
FCC ID.	MSQ-GZ700KB
Trade Name	ASUS
Applicable Standard	FCC 47 CFR 1.1307 KDB 447498 D01 v06
Test Result	Complied

Documented By

:



(Senior Adm. Specialist / Rita Huang)

Tested By

:



(Senior Engineer / Wen Lee)

Approved By

:



(Director / Vincent Lin)

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Detachable Keyboard
Trade Name	ASUS
Model No.	GZ700G Mobile Dock
FCC ID.	MSQ-GZ700KB
Frequency Range	2402~2480MHz
Channel Control	Auto
Antenna Type	PIFA Antenna
Channel Number	40
Type of Modulation	GFSK

1.2. Antenna List

No.	Manufacturer	Part No.	ASUS No.	Antenna Type	Peak Gain
1	INPAQ	WAG-P-LA-00-012	14008-03420500	PIFA Antenna	-0.8 dBi for 2.4 GHz

2. RF Exposure Evaluation

2.1. Standard Applicable

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

2.2. Measurement Result:

According to KDB Publication 447498 D01, section 4.3.1, per the calculations of item 1 ($\text{Power(mW)}/\text{separation (mm)} \cdot \sqrt{f(\text{GHz})} \leq 3.0$), SAR is required as shown in the table below where calculated values are greater than 3.0:

1.)

Operation frequency = 2450MHz and antenna separation distance = 5mm,
SAR Test Exclusion Threshold = 10mW

Frequency Band (MHz)	Maximum H-Field power		SAR Test Exclusion Threshold	Calculated Threshold Value (≤ 3.0 SAR is not required)
	(dBuV/3m)	(mW)	(mW)	
2402 ~ 2480	87.353	0.16	10	0.051

Note1: The SAR/MPE measurement is not necessary.

Note2: The conducted output power is refer to report No.: 18C0278R-RFUSP15V00 from the DEKRA.