

# RF Exposure Evaluation Report

Product Name : ASUS VivoWatch BP

Model No. : HC-A04

FCC ID : MSQ-HC-A04

Applicant : ASUSTeK COMPUTER INC.

Address : 4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

Date of Receipt : May. 22, 2018

Date of Declaration : Jul. 27, 2018

Report No. : 1850291R-RFUSP02V00

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

Issued Date: Jul. 27, 2018

Report No.: 1850291R-RFUSP02V00



Product Name	ASUS VivoWatch BP
Applicant	ASUSTeK COMPUTER INC.
Address	4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan
Manufacturer	ASUSTeK COMPUTER INC.
Model No.	HC-A04
FCC ID.	MSQ-HC-A04
EUT Rated Voltage	DC 3.8 (Power by Battery)
EUT Test Voltage	DC 3.8( Power by Battery)
Trade Name	ASUS
Applicable Standard	FCC 47 CFR 1.1310
Test Result	Complied

Documented By

:



( Adm. Assistant / Vita Wang )

Tested By

:



( Engineer / Jason Tuan )

Approved By

:



( Director / Vincent Lin )

## 1. Standard Applicable

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

## 2. Measurement Result:

According to KDB 447498 D01 Mobile Portable RF Exposure v06,  
Operation frequency = 2480MHz and antenna separation distance = 5mm,  
SAR Test Exclusion Threshold = 10mW

Frequency Band	Maximum output power Peak Gain: 0.39dBi		SAR Test Exclusion Threshold (mW)
	Conductive (dBm)	EIRP (mW)	
2480MHz	2.13	1.79	10

The SAR measurement is not necessary.