

客戶名稱：
CUSTOMER **ASUSTEK**

Documnet No.: ENS000169150

Approval Sheet Rev.: A1

Spec. Rev. P1

承認書

APPROVAL SHEET

產品品名/Product Model No. : **WAG-F-LA-00-185**

客戶料號/Customer No. : **14008-05200000**

案名/Model Name: **AURORA**

發行日期/ Issue Date : **2022/08/16**

承認日期/ Approved Date : _____

Approved by customer: (signing or stamping here)

 佳邦科技股份有限公司
INPAQ TECHNOLOGY CO., LTD.

■ 350 苗栗縣竹南鎮公義里11鄰科義街11號 □ 428 台中市大雅區科雅路27號4樓

電話：037-585-555

傳真：037-585-511

No. 11, Ke-Yi St., Chunan, Miaoli 350,
Taiwan, R.O.C.

Tel. : +886-37-585-555

Fax : +886-37-585-511

電話：04-2560-6555

傳真：04-2560-5151


4F, No. 27, Keya Road, Daya Dist., Taichung City
428, Taiwan, R.O.C.

Tel. : +886-4-25606555

Fax : +886-4-25605151

Embedded Single-band BLE Antenna for WAG-F-LA-00-185

1. Explanation of part number :



- (1) Product Type : Wireless Antenna (PIFA)
- (2) Material : FPCB
- (3) Frequency : 2.4~2.5GHz
- (4) Coaxial Cable Type : NO
- (5) Suffix : 185

2. Electrical Specification :

Ant. Part Number (main & aux parts)	Type	Highest Peak Gain with Cable Loss (dBi)	Cable loss (dB)	Connector Type	Cable length	Laptop/ Host Model
INPAQ P/N: WAG-F-LA-00-185 ASUS P/N: 14008-05200000	PIFA	N/A	N/A	N/A	N/A	AURORA

Antenna Type	PIFA Antenna For BT
Connector Type	N/A
Cable Type	N/A
Impedance	50Ω
Polarization	Linear
Radiation Pattern	Omni-directional
Frequency Range	BT:2.4~2.5GHz
VSWR	≤ 2.0
Operation Temperature	-10°C ~ +55°C
Storage Temperature	-30°C ~ +75°C
Return Loss	≤ -10dB
Max Power	1W

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY: 周敬晨

CHECKED BY: 鄭榮謀

DESIGNED BY: 張建焜

APPROVED BY: 宋承翰

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


TITLE : Embedded Single-band BLE Antenna for
WAG-F-LA-00-185

DOCUMENT
NO.


ENS000169150

SPEC REV.
P1

3. Antenna Picture :



4. Antenna Drawing :



NOTE:
 1. 工程圖上*為重點尺寸標註指示
 Mark * are the key dimensions.
 2. 工程圖上#為Cpk量測尺寸標註指示
 Mark # are CPK dimensions.

Drawing Rev P3

ITEM	DESCRIPTION	MATERIAL SPECIFICATION	QUAN TITY	UNIT	SUPPLIER	UL File NO
1	FPCB	35.4x5X0.12mm	1	PCS	HA1079	E523295

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A UNIT : mm
 DRAWN BY: 周敬晨 CHECKED BY: 鄭榮謀
 DESIGNED BY: 張建焜 APPROVED BY: 宋承翰

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded Single-band BLE Antenna for WAG-F-LA-00-185

DOCUMENT NO.	ENS000169150	SPEC REV. P1
--------------	--------------	--------------

5. Electrical Specification :

Those specifications were specially defined for **AURORA** model, and all characteristics were measured under the model's handset testing jig.

5-1. Frequency Band :

Frequency Band	MHz
BT	2400~2500

5-2. Impedance :


50 ohm nominal


5-3. Matching circuit :

None

5-4.-1 Return loss/VSWR :

Frequency(MHz)	2400	2500
BT S11 (dB)	-15.76	-20.96



UNLESS OTHER SPECIFIED TOLERANCES ON :			INPAQ TECHNOLOGY CO., LTD.	
X=±	X.X=±			
ANGLES=±		HOLEDIA=±		
SCALE : N/A	UNIT : mm			
DRAWN BY: 周敬晨	CHECKED BY: 鄭榮謀			
DESIGNED BY: 張建焜	APPROVED BY: 宋承翰			
TITLE : Embedded Single-band BLE Antenna for WAG-F-LA-00-185		DOCUMENT NO.	ENS000169150	SPEC REV. P1


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

5-5 Gain and Radiation Pattern

5-5.1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

5-5.2 Chamber definition



1. An anechoic chamber (10mx3mx3m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quiet room region is 50cmx50cmx50cm at the center of rotator
3. The distance between DUT and standard antenna is 9.14m
4. Two measurement antennas is 3164-06 (300MHz - 6GHz) and 3164-05 (2 - 18GHz)

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY: 周敬晨

CHECKED BY: 鄭榮謀

DESIGNED BY: 張建焜

APPROVED BY: 宋承翰

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

**TITLE : Embedded Single-band BLE Antenna for
 WAG-F-LA-00-185**

**DOCUMENT
 NO.**




ENS000169150

SPEC REV.
P1

5-5.3 Gain data and radiation pattern

Antenna gain is marked (dBi) and is based on **STANDARD HORN** antenna. The data shows Peak-Gain and Average-Gain.

Freq. [unit: MHz]	Three-dimensional peak (dBi)	Average [dBi]	Efficiency [%]
2400	-4.22	-9.97	10
2412	-4.1	-9.75	11
2437	-3.7	-9.47	11
2440	-3.8	-9.48	11
2462	-3.7	-9.46	11
2484	-3.78	-9.54	11
2500	-3.6	-9.61	11



UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY: 周敬晨

CHECKED BY: 鄭榮謀

DESIGNED BY: 張建焜

APPROVED BY: 宋承翰

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded Single-band BLE Antenna for
 WAG-F-LA-00-185

DOCUMENT NO.

ENS000169150

SPEC REV.
P1



ZPK2.E523295 - Wiring, Printed - Flexible Material Constructions - Component

Wiring, Printed - Flexible Material Constructions - Component

Dongguan Boyongkai Electronic Technology Co., Ltd
 Fenghuang East Road, Shajiao Community, Humen Town
 Dongguan, Guangdong 523936 China

E523295

Type	Cond Width		Cond Thk	SS/DSO	Max Area		Max Solder		Max Assembly Solder		Oper Temp	Flame Class	Meets UL796F DSR	C T I
	Min mm(in)	Edge mm(in)			Diam mm(in)	Solder Limits °C sec	Process (IPC) °C Cycles							
Single layer flexible materials interconnect constructions, Flammability Recognition only														
BYK-D	-	-	-	DS	-	288	10	-	-	-	V-0	-	-	-

Marking: Company name, type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2021-08-11

在此資料庫中出現的公司名稱或產品，並不代表其產品本身的製造有經過UL 後續檢驗服務的把關。僅有附 UL 標誌的產品才可被視為取得認證，並涵蓋在UL 後續檢驗服務範疇裡。請務必確認產品上是否有此標誌。

UL 允許複製線上認證目錄中所包含的資料，但必須符合以下條件：1.指南資訊、零組件、構造、設計、系統和/或認證(檔案)必須以完整的方式呈現，且不得誤導、不得操弄這些資料(或圖繪)。2.「經 UL 許可自線上認證目錄轉載」的聲明，必須顯示在擷取的資料旁。此外，轉載的資料必須包含以下格式的版權聲明：“© 2022 UL LLC”

iq.ul.com

Wiring, Printed - Flexible Material Constructions

E523295

Guide Information

Dongguan Boyongkai Electronic Technology Co., Ltd

Fenghuang East Road, Shajiao Community, Humen Town, Dongguan Guangdong 523936 CN

Type dsq: BYK-D

Single layer flexible materials interconnect constructions, Flammability Recognition only

<u>Cond Width Min</u> (mm)	<u>Cond Width Edge</u> (mm)	<u>Cond Thk Min</u> (mic)	<u>Cond Thk Max Int</u> (mic)	<u>Cond Thk Max Ext</u> (mic)	<u>SS/DSO</u>	<u>Max Area Diam</u> (mm)	<u>Assembly Solder Process Temp(°C)</u>	<u>Assembly Solder Process Cycles</u>	<u>Solder Limits Temp</u> (°C)	<u>Solder Limits Time</u> (sec)	<u>Max Oper Temp</u> (°C)	<u>Flame Class</u>	<u>Meets UL796F DSR</u>	<u>CTI</u>
-	-	-	-	-	DS	-	-	-	288	10	-	V-0	-	-

Report Date: 2021-08-10

Last Revised: 2021-08-10

© 2022 UL LLC





UL Product iQ
UL'S NEXT GENERATION CERTIFICATIONS SEARCH
 The same trusted data in a modern search engine.

NOW AVAILABLE
 ▶ **LEARN MORE**

VZQC2.E350554
Subassemblies for High-technology Equipment - Component

[Page Bottom](#)

Subassemblies for High-technology Equipment - Component

[See General Information for Subassemblies for High-technology Equipment - Component](#)

INPAQ TECHNOLOGY (SUZHOU) CO LTD

E350554

No 5 Chunqiu Rd
 Panyang Industrial Park
 Huangdai Town Xiangcheng Zone
 Suzhou, Jiangsu 215001 CHINA

Subassemblies. Recognition based on the traceability of components and materials used in the subassembly. UL assigned code designation SBA006K.

Marking: Company name, subassembly identification, UL assigned code designation and the Recognized Component Mark



on the shipping container or specification sheet in the shipping container.

[Last Updated](#) on 2011-11-08

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".