

# FCC RADIO TEST REPORT

According to

47 CFR FCC Part 15 Subpart E § 15.407

**Equipment** : ASUS 300Mbps Wireless Dual-Band  
PCI-E Card  
**Brand Name** : ASUS  
**Model** : PCE-N53  
**Filing Type** : New Application  
**Applicant** : ASUSTeK Computer INC  
**Manufacturer** : No.15, Li-Te Rd., Peitou, Taipei,  
1259 Taiwan  
**FCC ID** : MSQ-PCEN53  
**Received Date** : Mar. 07, 2012  
**Final Test Date** : Mar. 24, 2012

## Statement

**Test result included is only for the 802.11a/n (5150~5250MHz) of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart E**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



***SPORTON International Inc.***

No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

**Table of Contents**

**1 SUMMARY OF THE TEST RESULT .....2**

**2 GENERAL INFORMATION.....3**

2.1 Product Details.....3

2.2 Table for Filed Antenna.....4

2.3 Table for Carrier Frequencies.....5

2.4 Table for Test Modes.....5

2.5 Table for Testing Locations.....5

2.6 Table for Supporting Units.....6

2.7 Table for Parameters of Test Software Setting.....6

2.8 EUT Operation during Test.....6

2.9 Test Configuration.....7

**3 TEST RESULT .....10**

3.1 AC Power Line Conducted Emissions Measurement .....10

3.2 99% Occupied Bandwidth Measurement.....14

3.3 Maximum Conducted Output Power Measurement.....32

3.4 Power Spectral Density Measurement.....35

3.5 Peak Excursion Measurement.....46

3.6 Radiated Emissions Measurement .....56

3.7 Band Edge and Fundamental Emissions Measurement.....78

3.8 Frequency Stability Measurement .....82

3.9 Antenna Requirements .....84

**4 LIST OF MEASURING EQUIPMENTS.....85**

**5 TEST LOCATION.....87**

**6 TAF CERTIFICATE OF ACCREDITATION.....88**

**APPENDIX A. RF EXPOSURE EVALUATION .....A3**

**APPENDIX B. TEST PHOTOS .....B6**

**APPENDIX C. PHOTOGRAPHS OF EUT .....C8**




# CERTIFICATE OF COMPLIANCE

According to

47 CFR FCC Part 15 Subpart E § 15.407

Equipment : ASUS 300Mbps Wireless Dual-Band  
PCI-E Card  
Brand Name : ASUS  
Model : PCE-N53  
Applicant : ASUSTeK Computer INC  
No.15, Li-Te Rd., Peitou, Taipei, 1259 Taiwan

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Mar. 07, 2012 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Wayne Hsu / Assistant Manager

**SPORTON International Inc.**

No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

**1 SUMMARY OF THE TEST RESULT**

<b>Applied Standard: 47 CFR FCC Part 15 Subpart E</b>				
<b>Part</b>	<b>Rule Section</b>	<b>Description of Test</b>	<b>Result</b>	<b>Under Limit</b>
3.1	15.207	AC Power Line Conducted Emissions	Complies	6.58 dB
3.2	15.407(a)	26dB Spectrum Bandwidth Measurement	Complies	-
3.3	15.407(a)	Maximum Conducted Output Power	Complies	0.32 dB
3.4	15.407(a)	Power Spectral Density	Complies	0.21 dB
3.5	15.407(a)	Peak Excursion	Complies	5.89 dB
3.6	15.407(b)	Radiated Emissions	Complies	3.03 dB
3.7	15.407(b)	Band Edge Emissions	Complies	1.14 dB
3.8	15.407(g)	Frequency Stability	Complies	-
3.9	15.203	Antenna Requirements	Complies	-

<b>Test Items</b>	<b>Uncertainty</b>	<b>Remark</b>
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.5dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
Peak Excursion	±0.5dB	Confidence levels of 95%
26dB Spectrum Bandwidth / Frequency Stability	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

## 2 GENERAL INFORMATION

### 2.1 Product Details

EUT may match the four antennas use. Only the radio detail of IEEE 802.11a/n is shown in this report. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

Items	Description
Power Type	From host
Data Modulation Data Rate (Mbps)	OFDM for IEEE 802.11a (BPSK / QPSK / 16QAM / 64QAM) (6/9/12/18/24/36/48/54) See the below table for IEEE 802.11n
Frequency Range	5150~5250MHz
Channel Band Width (99%)	802.11a : 16.80 MHz 802.11n : MCS 8 (20MHz) : 17.70 MHz ; MCS 8 (40MHz) : 36.20 MHz
Conducted Output Power	802.11a : 15.32 dBm 802.11n : MCS 8 (20MHz) : 14.85 dBm ; MCS 8 (40MHz) : 16.68 dBm

#### IEEE 802.11n Modulation Scheme

MCS	Spatial	Modulation	Coding Rate	Data rate(Mbps)	
				20 MHz channel	40 MHz channel
Index	Streams	Type	Type	800nsGI	800nsGI
0	1	BPSK	1/2	6.5	13.5
1	1	QPSK	1/2	13	27
2	1	QPSK	3/4	19.5	40.5
3	1	16-QAM	1/2	26	54
4	1	16-QAM	3/4	39	81
5	1	64-QAM	2/3	52	108
6	1	64-QAM	3/4	58.5	121.5
7	1	64-QAM	5/6	65	135
8	2	BPSK	1/2	13	27
9	2	QPSK	1/2	26	54
10	2	QPSK	3/4	39	81
11	2	16-QAM	1/2	52	108
12	2	16-QAM	3/4	78	162
13	2	64-QAM	2/3	104	216
14	2	64-QAM	3/4	117	243
15	2	64-QAM	5/6	130	270

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

2.2 Table for Filed Antenna

Antenna Category (Ant. Cat.)	
<input checked="" type="checkbox"/>	External antenna (dedicated antennas)
<input checked="" type="checkbox"/>	Single Power Level (PL) with corresponding antenna(s). Power Level (PL): 1
<input checked="" type="checkbox"/>	Unique antenna connector. (e.g., MMCX, U.FL, IPX, and RP-SMA, RP-N type...)

Transmitter Outputs & Receiver Inputs Information			
Modulation	Transmitter Outputs	Receiver Inputs	Transmitter Output Signals
802.11a	1	1	-
802.11n HT20	2	2	-
802.11n HT40	2	2	-

Antenna General Information									
Antenna Port (Total 2 Port)					1(TX/RX), 2(TX/RX)				
Maximum RF Output Power Level (PL)					1				
Transmit Chains Power Distribution					<input checked="" type="checkbox"/> symmetrical distribution <input type="checkbox"/> asymmetrical distribution				
Ant. No.	PL	Ant. Port [Ant No. X connect to Ant. Port Y]	Ant. Cat.	Ant. Type	Brand	Model	G <sub>ANT</sub> (dBi)	DG (dBi) [correlated] N <sub>TX</sub> = 1	DG (dBi) [uncorrelated] N <sub>TX</sub> = 2
1	1	1,2	External	Dipole	ARISTOTLE	RFA-25-C52M3-B70-25	3	N/A	3
2	1	1,2	External	Dipole	ARISTOTLE	RFA-25-L14M3-B70-25	2	N/A	2
3	1	1,2	External	Dipole	ARISTOTLE	RFA-25-C2M2-03	2	N/A	2
4	1	1,2	External	Dipole	ARISTOTLE	AIR-ANT2460WNP-R	2	N/A	2
<input checked="" type="checkbox"/>	EUT is consist of multiple antenna models assembly (multiple antenna models are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type. Then Ant. No. <u>1</u> shall be performed the radiated test.								
<input checked="" type="checkbox"/>	The equipment is normally installed and point-to-point or point-to-multipoint systems: Ant. No. <u>1~4</u>								
<p>Note 1: For all transmitter outputs with equal antenna gains, directional gain is to be computed as follows:                      Any transmit signals are correlated, Directional Gain (DG) = G<sub>ANT</sub> + 10 log(N) dBi                      All transmit signals are completely uncorrelated, Directional Gain (DG)= G<sub>ANT</sub></p> <p>Note 2: For all transmitter outputs with unequal antenna gains, directional gain is to be computed as follows:                      Any transmit signals are correlated, Directional Gain (DG) = 10 log[(10<sup>G<sub>1/20</sub></sup> + 10<sup>G<sub>2/20</sub></sup> + ... + 10<sup>G<sub>N/20</sub></sup>)<sup>2</sup> / N] dBi                      All transmit signals are completely uncorrelated, Directional Gain (DG) = 10 log[(10<sup>G<sub>1/10</sub></sup> + 10<sup>G<sub>2/10</sub></sup> + ... + 10<sup>G<sub>N/10</sub></sup>) / N] dBi</p>									

**2.3 Table for Carrier Frequencies**

Frequency Band	Channel No.	Frequency (20MHz)	Channel No.	Frequency (40MHz)
5150~5250 MHz Band 1	36	5180 MHz	38	5190 MHz
	40	5200 MHz	46	5230 MHz
	44	5220 MHz	-	-
	48	5240 MHz	-	-

**2.4 Table for Test Modes**

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on the entire possible Configuration for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
AC Power Conducted Emission Radiated Emission Below 1GHz	System Mode	-	-
26dB Spectrum Bandwidth 99% Occupied Bandwidth Measurement Peak Excursion	11a Band 1/BPSK	6Mbps	36/40/48
	11n Band 1/BPSK MCS 8 (20MHz)	13Mbps	36/40/48
	11n Band 1/BPSK MCS 8 (40MHz)	27Mbps	38/46
Max. Conducted Output Power Measurement Power Spectral Density	11a Band 1/BPSK	6Mbps	36/40/48
	11n Band 1/BPSK MCS 8 (20MHz)	13Mbps	36/40/48
	11n Band 1/BPSK MCS 8 (40MHz)	27Mbps	38/46
Radiated Emission Above 1GHz Fundamental Emissions	11a Band 1/BPSK	6Mbps	36/40/48
	11n Band 1/BPSK MCS 8 (20MHz)	13Mbps	36/40/48
	11n Band 1/BPSK MCS 8 (40MHz)	27Mbps	38/46
Band Edge Emission	11a Band 1/BPSK	6Mbps	36/48
	11n Band 1/BPSK MCS 8 (20MHz)	13Mbps	36/48
	11n Band 1/BPSK MCS 8 (40MHz)	27Mbps	38/46

**2.5 Table for Testing Locations**

Test Site No.	Site Category	Location
CO04-HY	Conduction	Hwa Ya
TH01-HY	OVEN Room	Hwa Ya
03CH02-HY	SAC	Hwa Ya

Semi Anechoic Chamber (SAC).

**2.6 Table for Supporting Units**

Support Unit	Brand	Model	FCC ID
Personal Computer	HP COMPAQ	dc7700	DoC
(PS/2) Keyboard	HP	KB-0133	DoC
(PS/2) Mouse	HP	M-S69	JNZ211443
Printer	HP	C2642A (DJ400)	B94C2642X
Modem	ACEEX	DM-1414	IFAXDM1414
LCD Monitor	DELL	U2410f	DoC
Wireless AP (Remote Workstation)	D-Link	DNS-G120	DoC

\*\*The EUT was embedded into PC during testing.

**2.7 Table for Parameters of Test Software Setting**

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

**For Single Chain:  
Power Parameters of IEEE 802.11a**

Test Software Version	RT5x9x QA		
Frequency	5180 MHz	5200 MHz	5240 MHz
IEEE 802.11a	14	14	16

**For Two Chains:  
Power Parameters of IEEE 802.11n**

Test Software Version	RT5x9x QA		
Frequency	5180 MHz	5200 MHz	5240 MHz
IEEE 802.11n (20MHz)	13/13	14/14	15/15
Frequency	5190 MHz	5230 MHz	-
IEEE 802.11n (40MHz)	14/14	19/19	-

**2.8 EUT Operation during Test**

An executive program, "EMCTEST.exe" under Win XP, which generates a complete line of continuously repeating "H" pattern was used as the test software.


The program was executed as follows:

- a. Turn on the power of all equipment.
- b. The PC reads the test program from the hard disk drive and runs it.
- c. The PC sends "H" messages to the monitor and displays "H" patterns on the screen.


At the same time, the following programs were executed:

- Executed "WiFi function" to link with the Wireless AP (remote workstation) to receive and transmit.
- Executed "RT5x9x QA" to keep transmitting signals at fixed frequency.


### 2.9 Test Configuration For Conducted Emissions



For Radiated Emissions 9kHz~1GHz



**For Radiated Emissions above 1GHz**



**3 TEST RESULT**

**3.1 AC Power Line Conducted Emissions Measurement**

**3.1.1 Limit**

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

**Class B**

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

**3.1.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

**3.1.3 Test Procedures**

1. The EUT was warmed up for 15 minutes before testing started.
2. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
5. The frequency range from 150 kHz to 30 MHz was searched.
6. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. The measurement has to be done between each power line and ground at the power terminal.

3.1.4 Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω. LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

3.1.5 Test Deviation

There is no deviation with the original standard.


3.1.6 EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.

3.1.7 Results of AC Power Line Conducted Emissions Measurement


Final Test Date	Mar. 23, 2012	Test Site No.	CO04-HY
Temperature	25°C	Humidity	48%
Test Engineer	Assen	Configuration	System Mode

Line



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1845550	50.40	-13.88	64.28	50.08	0.30	0.02	QP
2	0.1845550	46.77	-7.51	54.28	46.45	0.30	0.02	Average
3	0.5520430	33.71	-12.29	46.00	33.29	0.29	0.13	Average
4	0.5520430	35.70	-20.30	56.00	35.28	0.29	0.13	QP
5	1.953	28.92	-17.08	46.00	28.51	0.31	0.10	Average
6	1.953	38.39	-17.61	56.00	37.98	0.31	0.10	QP
7	2.310	30.73	-15.27	46.00	30.31	0.32	0.10	Average
8	2.310	42.45	-13.55	56.00	42.03	0.32	0.10	QP
9	8.157	49.73	-10.27	60.00	49.12	0.43	0.18	QP
10	8.157	41.02	-8.98	50.00	40.41	0.43	0.18	Average
11	13.129	41.01	-18.99	60.00	40.10	0.51	0.40	QP
12	13.129	38.85	-11.15	50.00	37.94	0.51	0.40	Average

Neutral



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.1854100	51.30	-12.94	64.24	51.02	0.26	0.02	QP
2	0.1854100	47.66	-6.58	54.24	47.38	0.26	0.02	Average
3	1.768	34.11	-11.89	46.00	33.76	0.27	0.08	Average
4	1.768	41.11	-14.89	56.00	40.76	0.27	0.08	QP
5	2.322	33.96	-12.04	46.00	33.59	0.27	0.10	Average
6	2.322	42.50	-13.50	56.00	42.13	0.27	0.10	QP
7	7.237	43.33	-16.67	60.00	42.82	0.35	0.16	QP
8	7.237	35.41	-14.59	50.00	34.90	0.35	0.16	Average
9	8.097	48.90	-11.10	60.00	48.35	0.37	0.18	QP
10	8.097	40.77	-9.23	50.00	40.22	0.37	0.18	Average
11	12.760	38.51	-11.49	50.00	37.71	0.42	0.38	Average
12	12.760	42.91	-17.09	60.00	42.11	0.42	0.38	QP

Note:  
Level = Read Level + LISN Factor + Cable Loss.

**3.2 99% Occupied Bandwidth Measurement**

**3.2.1 Limit**

No restriction limits. But resolution bandwidth within band edge measurement is 1% of the 99% occupied bandwidth.

**3.2.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RB	300 kHz
VB	1000 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

**3.2.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 300 kHz and the video bandwidth of 1000 kHz were used.
3. Measured the spectrum width with power higher than 26dB below carrier.
4. Measuring multiple antennas, the connectors are required to link with Spectrum Analyzer through a combiner. (Only for IEEE 802.11n test)

**3.2.4 Test Setup Layout**



**3.2.5 Test Deviation**

There is no deviation with the original standard.

**3.2.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

**3.2.7 Test Result of 99% Occupied Bandwidth**

<b>Final Test Date</b>	Mar. 24, 2012	<b>Test Site No.</b>	TH01-HY
<b>Temperature</b>	25.9°C	<b>Humidity</b>	23%
<b>Test Engineer</b>	Ian	<b>Configurations</b>	802.11a/n

**For Single Chain:**

**Configuration of IEEE 802.11a**

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	22.90	16.80
40	5200 MHz	20.50	16.80
48	5240 MHz	20.40	16.80

**For Two Chains:**

**Configuration of IEEE 802.11n (20MHz) Port 1**

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	20.50	17.70
40	5200 MHz	20.40	17.70
48	5240 MHz	20.40	17.70

**Configuration of IEEE 802.11n (20MHz) Port 2**

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	19.90	17.60
40	5200 MHz	19.90	17.60
48	5240 MHz	20.00	17.50


**Configuration of IEEE 802.11n (40MHz) Port 1**

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
38	5190 MHz	40.40	36.00
46	5230 MHz	40.40	36.20

**Configuration of IEEE 802.11n (40MHz) Port 2**


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
38	5190 MHz	39.60	36.20
46	5230 MHz	40.00	36.20

26 dB Bandwidth Plot  
Configuration IEEE 802.11a 5180 MHz




Date: 24.MAR.2012 00:38:45

Configuration IEEE 802.11a 5200 MHz




Date: 24.MAR.2012 00:41:29

Configuration IEEE 802.11a 5240 MHz




Date: 24.MAR.2012 00:43:43

Configuration IEEE 802.11n (20MHz) 5180 MHz Port 1




Date: 24.MAR.2012 00:05:24

Configuration IEEE 802.11n (20MHz) 5200 MHz Port 1




Date: 24.MAR.2012 01:08:11

Configuration IEEE 802.11n (20MHz) 5240 MHz Port 1




Date: 24.MAR.2012 01:10:52

Configuration IEEE 802.11n (20MHz) 5180 MHz Port 2




Date: 24.MAR.2012 01:43:34

Configuration IEEE 802.11n (20MHz) 5200 MHz Port 2




Date: 24.MAR.2012 01:45:57

Configuration IEEE 802.11n (20MHz) 5240 MHz Port 2




Date: 24.MAR.2012 01:47:58

Configuration IEEE 802.11n (40MHz) 5190 MHz Port 1




Date: 24.MAR.2012 02:15:46

Configuration IEEE 802.11n (40MHz) 5230 MHz Port 1




Date: 24.MAR.2012 02:18:09

Configuration IEEE 802.11n (40MHz) 5190 MHz Port 2




Date: 24.MAR.2012 02:51:20

Configuration IEEE 802.11n (40MHz) 5230 MHz Port 2




Date: 24.MAR.2012 02:53:38

99% Occupied Bandwidth Plot  
Configuration IEEE 802.11a 5180 MHz




Date: 24.MAR.2012 00:45:12

Configuration IEEE 802.11a 5200 MHz




Date: 24.MAR.2012 00:44:40

Configuration IEEE 802.11a 5240 MHz




Date: 24.MAR.2012 00:44:04

Configuration IEEE 802.11n (20MHz) 5180 MHz Port 1




Date: 24.MAR.2012 01:05:45

Configuration IEEE 802.11n (20MHz) 5200 MHz Port 1




Date: 24.MAR.2012 01:08:23

Configuration IEEE 802.11n (20MHz) 5240 MHz Port 1




Date: 24.MAR.2012 01:11:04

Configuration IEEE 802.11n (20MHz) 5180 MHz Port 2




Date: 24.MAR.2012 01:43:45

Configuration IEEE 802.11n (20MHz) 5200 MHz Port 2




Date: 24.MAR.2012 01:46:07

Configuration IEEE 802.11n (20MHz) 5240 MHz Port 2




Date: 24.MAR.2012 01:48:09

Configuration IEEE 802.11n (40MHz) 5190 MHz Port 1




Date: 24.MAR.2012 02:15:57

Configuration IEEE 802.11n (40MHz) 5230 MHz Port 1




Date: 24.MAR.2012 02:18:19

Configuration IEEE 802.11n (40MHz) 5190 MHz Port 2



Date: 24.MAR.2012 02:51:32

Configuration IEEE 802.11n (40MHz) 5230 MHz Port 2



Date: 24.MAR.2012 02:53:49

**3.3 Maximum Conducted Output Power Measurement**

**3.3.1 Limit**

For the band 5.15~5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW (17dBm) or 4 dBm + 10log B, where B is the 26 dB emissions bandwidth in MHz. If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power and power density from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Maximum Conducted Output Power mean that the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level

**3.3.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

<b>Power Meter Parameter</b>	<b>Setting</b>
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Sensor	MA2411B

**3.3.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the wideband power meter.
2. Turn on the EUT and power meter and then record the power value.
3. Repeat above procedures on all channels needed to be tested.
4. When measuring maximum conducted output power within multiple antenna systems, add every result of the values by mathematic formula. (Only for IEEE 802.11n test)

**3.3.4 Test Setup Layout**



**3.3.5 Test Deviation**

There is no deviation with the original standard.

**3.3.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

**3.3.7 Test Result of Maximum Conducted Output Power**

<b>Final Test Date</b>	Mar. 24, 2012	<b>Test Site No.</b>	TH01-HY
<b>Temperature</b>	25.9°C	<b>Humidity</b>	23%
<b>Test Engineer</b>	Ian	<b>Configurations</b>	802.11a/n

**For Single Chain:**  
**Configuration of IEEE 802.11a**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	15.32	17	<b>Complies</b>
40	5200 MHz	14.87	17	<b>Complies</b>
48	5240 MHz	14.85	17	<b>Complies</b>

**For Two Chains:**  
**Configuration IEEE 802.11n (20MHz) Port 1**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	12.56	17	<b>Complies</b>
40	5200 MHz	12.79	17	<b>Complies</b>
48	5240 MHz	12.51	17	<b>Complies</b>

**Configuration IEEE 802.11n (20MHz) Port 2**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	10.28	17	<b>Complies</b>
40	5200 MHz	10.62	17	<b>Complies</b>
48	5240 MHz	10.11	17	<b>Complies</b>

**Configuration IEEE 802.11n (20MHz) Port 1+Port 2**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	14.58	17	<b>Complies</b>
40	5200 MHz	14.85	17	<b>Complies</b>
48	5240 MHz	14.48	17	<b>Complies</b>

**Configuration IEEE 802.11n (40MHz) Port 1**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
38	5190 MHz	12.34	17	Complies
46	5230 MHz	14.75	17	Complies

**Configuration IEEE 802.11n (40MHz) Port 2**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
38	5190 MHz	10.47	17	Complies
46	5230 MHz	12.24	17	Complies

**Configuration IEEE 802.11n (40MHz) Port 1+Port 2**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
38	5190 MHz	14.52	17	Complies
46	5230 MHz	16.68	17	Complies

**3.4 Power Spectral Density Measurement**

**3.4.1 Limit**

The power spectral density is defined as the highest level of power in dBm per MHz generated by the transmitter within the power envelope. The following table is power spectral density limits and decrease power density limit rule refer to section 3.3.1.

Frequency Range	Power Spectral Density limit (dBm/MHz)
5.15~5.25 GHz	4

**3.4.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	RMS
Trace	Max Hold
Sweep Time	Auto

**3.4.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 1000kHz and VBW to 3000kHz. Set Detector to RMS, Trace to Max Hold. Mark the frequency with maximum peak power as the center of the display of the spectrum.
3. When measuring maximum conducted output power within multiple antenna systems, add every result of the values by mathematic formula. (Only for IEEE 802.11n test)

**3.4.4 Test Setup Layout**



**3.4.5 Test Deviation**

There is no deviation with the original standard.

**3.4.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

**3.4.7 Test Result of Power Spectral Density**

<b>Final Test Date</b>	Mar. 23, 2012	<b>Test Site No.</b>	TH01-HY
<b>Temperature</b>	25.9°C	<b>Humidity</b>	23%
<b>Test Engineer</b>	Ian	<b>Configurations</b>	802.11a/n

**For Single Chain:  
Configuration of IEEE 802.11a**

Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
5180 MHz	3.79	4	<b>Complies</b>
5200 MHz	3.78	4	<b>Complies</b>
5240 MHz	3.49	4	<b>Complies</b>

**For Two Chains:  
Configuration IEEE 802.11n (20MHz) Port 1**

Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
5180 MHz	1.76	4	<b>Complies</b>
5200 MHz	1.94	4	<b>Complies</b>
5240 MHz	1.94	4	<b>Complies</b>

**Configuration IEEE 802.11n (20MHz) Port 2**

Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
5180 MHz	-1.60	4	<b>Complies</b>
5200 MHz	-1.45	4	<b>Complies</b>
5240 MHz	-1.44	4	<b>Complies</b>

**Configuration IEEE 802.11n (20MHz) Port 1+Port 2**

Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
5180 MHz	3.41	4	<b>Complies</b>
5200 MHz	3.58	4	<b>Complies</b>
5240 MHz	3.58	4	<b>Complies</b>

**Configuration IEEE 802.11n Port 1 (40MHz)**

Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
5190 MHz	-1.61	4	<b>Complies</b>
5230 MHz	1.15	4	<b>Complies</b>


**Configuration IEEE 802.11n Port 2 (40MHz)**

Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
5190 MHz	-4.32	4	<b>Complies</b>
5230 MHz	-1.77	4	<b>Complies</b>

**Configuration IEEE 802.11n Port 1 + Port 2 (40MHz)**


Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
5190 MHz	0.25	4	<b>Complies</b>
5230 MHz	2.94	4	<b>Complies</b>

Power Density Plot  
Configuration IEEE 802.11a 5180 MHz




Date: 23.MAR.2012 19:34:30

Configuration IEEE 802.11a 5200 MHz




Date: 23.MAR.2012 19:29:21

Configuration IEEE 802.11a 5240 MHz




Date: 23.MAR.2012 19:33:29

Configuration IEEE 802.11n (20MHz) 5180 MHz Port 1




Date: 23.MAR.2012 19:44:42

Configuration IEEE 802.11n (20MHz) 5200 MHz Port 1




Date: 23.MAR.2012 19:46:50

Configuration IEEE 802.11n (20MHz) 5240 MHz Port 1




Date: 23.MAR.2012 19:49:32

Configuration IEEE 802.11n (20MHz) 5180 MHz Port 2




Date: 23.MAR.2012 19:45:22

Configuration IEEE 802.11n (20MHz) 5200 MHz Port 2




Date: 23.MAR.2012 19:47:39

Configuration IEEE 802.11n (20MHz) 5240 MHz Port 2




Date: 23.MAR.2012 19:50:16

Configuration IEEE 802.11n (40MHz) 5190 MHz Port 1




Date: 23.MAR.2012 22:18:34

Configuration IEEE 802.11n (40MHz) 5230 MHz Port 1




Date: 23.MAR.2012 22:26:01

Configuration IEEE 802.11n (40MHz) 5190 MHz Port 2



Date: 23.MAR.2012 22:19:26

Configuration IEEE 802.11n (40MHz) 5230 MHz Port 2



Date: 23.MAR.2012 22:26:36

**3.5 Peak Excursion Measurement**

**3.5.1 Limit**

The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum conducted output power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emissions bandwidth whichever is less.

**3.5.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz (Peak Trace) / 1000 kHz (Average Trace)
VB	3000 kHz (Peak Trace) / 300 kHz (Average Trace)
Detector	Peak (Peak Trace) / Sample (Average Trace)
Trace	Max Hold
Sweep Time	60s

**3.5.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set the spectrum analyzer span to view the entire emissions bandwidth. The largest difference between the following two traces (Peak Trace and Average Trace) must be  $\leq 13$  dB for all frequencies across the emissions bandwidth. Submit a plot.
3. Peak Trace: Set RBW = 1 MHz, VBW  $\geq 3$  MHz with peak detector and max-hold settings.
4. Average Trace: Method #3—video averaging with max hold—and sum power across the band. Set span to encompass the entire emissions bandwidth (EBW) of the signal. Set sweep trigger to “free run”. Set RBW = 1 MHz. Set VBW  $\geq 1/T$  (IEEE 802.11a VBW = 300kHz  $\geq 1/4\mu$ s). Use sample detector mode if bin width (i.e., span/number of points in spectrum)  $< 0.5$  RBW. Otherwise use peak detector mode. Set max hold. Allow max hold to run for 60 seconds.
5. Measuring multiple antennas, the connectors are required to link with Spectrum Analyzer through a combiner. (Only for IEEE 802.11n test)

**3.5.4 Test Setup Layout**



**3.5.5 Test Deviation**

There is no deviation with the original standard.

**3.5.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

**3.5.7 Test Result of Peak Excursion**

<b>Final Test Date</b>	Mar. 24, 2012	<b>Test Site No.</b>	TH01-HY
<b>Temperature</b>	25.9°C	<b>Humidity</b>	23%
<b>Test Engineer</b>	Bear	<b>Configurations</b>	802.11a/n

**For Single Chain:  
Configuration of IEEE 802.11a**

Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
5180 MHz	5.41	13	<b>Complies</b>
5200 MHz	5.29	13	<b>Complies</b>
5240 MHz	4.96	13	<b>Complies</b>

**For Two Chains:  
Configuration IEEE 802.11n (20MHz) Port 1**

Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
5180 MHz	5.95	13	<b>Complies</b>
5200 MHz	5.56	13	<b>Complies</b>
5240 MHz	5.38	13	<b>Complies</b>

**Configuration IEEE 802.11n (20MHz) Port 2**

Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
5180 MHz	7.11	13	<b>Complies</b>
5200 MHz	7.07	13	<b>Complies</b>
5240 MHz	6.86	13	<b>Complies</b>


**Configuration IEEE 802.11n (40MHz) Port 1**

Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
5190 MHz	6.81	13	<b>Complies</b>
5230 MHz	6.39	13	<b>Complies</b>

**Configuration IEEE 802.11n (40MHz) Port 2**


Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
5190 MHz	5.24	13	<b>Complies</b>
5230 MHz	7.04	13	<b>Complies</b>

Peak Excursion Plot  
Configuration IEEE 802.11a 5180 MHz




Date: 24.MAR.2012 00:37:22

Configuration IEEE 802.11a 5200 MHz




Date: 24.MAR.2012 00:39:46

Configuration IEEE 802.11a 5240 MHz




Date: 24.MAR.2012 00:42:23

Configuration IEEE 802.11n (20MHz) 5180 MHz Port 1




Date: 24.MAR.2012 00:01:26

Configuration IEEE 802.11n (20MHz) 5200 MHz Port 1




Date: 24.MAR.2012 01:06:46

Configuration IEEE 802.11n (20MHz) 5240 MHz Port 1




Date: 24.MAR.2012 01:09:30

Configuration IEEE 802.11n (20MHz) 5180 MHz Port 2




Date: 24.MAR.2012 01:42:11

Configuration IEEE 802.11n (20MHz) 5200 MHz Port 2




Date: 24.MAR.2012 01:44:44

Configuration IEEE 802.11n (20MHz) 5240 MHz Port 2




Date: 24.MAR.2012 01:46:54

Configuration IEEE 802.11n (40MHz) 5190 MHz Port 1




Date: 24.MAR.2012 02:14:22

Configuration IEEE 802.11n (40MHz) 5230 MHz Port 1




Date: 24.MAR.2012 02:16:50

Configuration IEEE 802.11n (40MHz) 5190 MHz Port 2



Date: 24.MAR.2012 02:50:17

Configuration IEEE 802.11n (40MHz) 5230 MHz Port 2



Date: 24.MAR.2012 02:52:19

**3.6 Radiated Emissions Measurement**

**3.6.1 Limit**

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.25 GHz band shall not exceed an EIRP of -27 dBm/MHz (68.3dBuV/m at 3m). For transmitters operating in the 5.47-5.725 GHz band: all emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz (68.3dBuV/m at 3m). In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

<b>Frequencies (MHz)</b>	<b>Field Strength (micorvolts/meter)</b>	<b>Measurement Distance (meters)</b>
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

**3.6.2 Measuring Instruments and Setting**

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

<b>Spectrum Parameter</b>	<b>Setting</b>
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz z for peak


<b>Receiver Parameter</b>	<b>Setting</b>
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

**3.6.3 Test Procedures**


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.6.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 5GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.  
 Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$  (dB);  
 Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.6.5 Test Deviation

There is no deviation with the original standard.

3.6.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

**3.6.7 Results of Radiated Emissions (9kHz~30MHz)**

<b>Final Test Date</b>	Mar. 09, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	22.6°C	<b>Humidity</b>	52%
<b>Test Engineer</b>	Streak		

<b>Freq. (MHz)</b>	<b>Level (dBuV)</b>	<b>Over Limit (dB)</b>	<b>Limit Line (dBuV)</b>	<b>Remark</b>
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.6.8 Results of Radiated Emissions (30MHz~1GHz)


Final Test Date	Mar. 09, 2012	Test Site No.	03CH02-HY
Temperature	22.6°C	Humidity	52%
Test Engineer	Streak	Configuration	System Mode

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	148.340	29.27	-14.23	43.50	43.99	10.90	2.02	27.64	Peak	---	---
2	230.790	34.23	-11.77	46.00	46.55	12.37	2.64	27.33	Peak	---	---
3	299.660	35.36	-10.64	46.00	45.86	13.70	2.96	27.16	Peak	---	---
4	350.100	36.98	-9.02	46.00	46.84	14.48	3.18	27.52	Peak	---	---
5	498.510	36.69	-9.31	46.00	43.97	17.26	3.82	28.36	Peak	---	---
6	929.190	40.13	-5.87	46.00	41.46	20.75	5.41	27.49	Peak	---	---

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	148.340	36.64	-6.86	43.50	51.36	10.90	2.02	27.64	Peak	---	---
2	198.780	36.84	-6.66	43.50	50.56	11.28	2.42	27.42	Peak	---	---
3	249.220	36.39	-9.61	46.00	47.94	12.97	2.77	27.29	Peak	---	---
4	350.100	39.37	-6.63	46.00	49.23	14.48	3.18	27.52	Peak	---	---
5	498.510	41.86	-4.14	46.00	49.14	17.26	3.82	28.36	Peak	---	---
6	933.070	37.34	-8.66	46.00	38.53	20.85	5.44	27.48	Peak	---	---

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.6.9 Results for Radiated Emissions (1GHz~40GHz)

For Single Chain:


Final Test Date	Mar. 08, 2012	Test Site No.	03CH02-HY
Temperature	22.6°C	Humidity	52%
Test Engineer	Streak	Configuration	802.11a Ch. 36

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	6898.000	46.10	-31.74	77.84	39.66	35.86	5.57	34.99	Peak	---	---
2	10360.000	48.07	-29.77	77.84	38.36	38.22	6.71	35.22	Peak	---	---
3	@15540.000	53.04	-10.50	63.54	38.81	40.81	8.45	35.03	PK	---	---


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	6898.000	51.40	-26.44	77.84	44.96	35.86	5.57	34.99	Peak	---	---
2	10360.000	48.47	-29.37	77.84	38.76	38.22	6.71	35.22	Peak	---	---
3	@15540.000	53.41	-10.13	63.54	39.18	40.81	8.45	35.03	PK	---	---


Final Test Date	Mar. 08, 2012	Test Site No.	03CH02-HY
Temperature	22.6°C	Humidity	52%
Test Engineer	Streak	Configuration	802.11a Ch. 40

Horizontal



Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	6911.000	47.92	-29.92	77.84	41.47	35.87	5.58	35.00 Peak	---	---
2	10400.000	51.83	-26.01	77.84	42.02	38.24	6.75	35.18 Peak	---	---
3	@15600.000	58.69	-4.85	63.54	44.50	40.84	8.45	35.10 PK	---	---


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	6911.000	53.97	-23.87	77.84	47.52	35.87	5.58	35.00	Peak	---	---
2	10400.000	51.80	-26.04	77.84	41.99	38.24	6.75	35.18	Peak	---	---
3	15600.000	62.15	-21.39	83.54	47.96	40.84	8.45	35.10	Peak	---	---
4	@15600.000	49.70	-13.84	63.54	35.51	40.84	8.45	35.10	Average	---	---


Final Test Date	Mar. 08, 2012	Test Site No.	03CH02-HY
Temperature	22.6°C	Humidity	52%
Test Engineer	Streak	Configuration	802.11a Ch. 48

Horizontal



Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	6963.000	53.16	-24.68	77.84	46.69	35.89	5.59	35.01 Peak	---	---
2	@10480.000	62.73	-15.11	77.84	52.74	38.29	6.82	35.12 Peak	---	---
3	15720.000	60.81	-22.73	83.54	46.66	40.89	8.46	35.20 Peak	---	---
4	@15720.000	51.99	-11.55	63.54	37.84	40.89	8.46	35.20 Average	---	---

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	@ 6963.000	59.07	-18.77	77.84	52.60	35.89	5.59	35.01	Peak	---	---
2	10480.000	55.30	-22.54	77.84	45.31	38.29	6.82	35.12	Peak	---	---
3	15720.000	63.96	-19.58	83.54	49.81	40.89	8.46	35.20	Peak	---	---
4	@15720.000	52.06	-11.48	63.54	37.91	40.89	8.46	35.20	Average	---	---

For Two Chains:


Final Test Date	Mar. 08, 2012	Test Site No.	03CH02-HY
Temperature	22.6°C	Humidity	52%
Test Engineer	Streak	Configuration	802.11n Ch. 36 (20MHz)

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	6898.000	51.40	-26.44	77.84	44.96	35.86	5.57	34.99	Peak	---	---
2	10360.000	48.50	-29.34	77.84	38.79	38.22	6.71	35.22	Peak	---	---
3	@15540.000	51.61	-11.93	63.54	37.38	40.81	8.45	35.03	PK	---	---


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	6898.000	57.72	-20.12	77.84	51.28	35.86	5.57	34.99	Peak	---	---
2	10360.000	47.97	-29.87	77.84	38.26	38.22	6.71	35.22	Peak	---	---
3	@15540.000	53.25	-10.29	63.54	39.02	40.81	8.45	35.03	PK	---	---


Final Test Date	Mar. 08, 2012	Test Site No.	03CH02-HY
Temperature	22.6°C	Humidity	52%
Test Engineer	Streak	Configuration	802.11n Ch. 40 (20 MHz)

Horizontal



Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 6911.000	53.63	-24.21	77.84	47.18	35.87	5.58	35.00	Peak	---	---
2 10400.000	48.51	-29.33	77.84	38.70	38.24	6.75	35.18	Peak	---	---
3 @15600.000	55.17	-8.37	63.54	40.98	40.84	8.45	35.10	PK	---	---


Vertical



Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 6911.000	62.05	-15.79	77.84	55.60	35.87	5.58	35.00	Peak	---	---
2 @ 10400.000	49.96	-27.88	77.84	40.15	38.24	6.75	35.18	Peak	---	---
3 @ 15600.000	60.04	-3.50	63.54	45.85	40.84	8.45	35.10	PK	---	---


<b>Final Test Date</b>	Mar. 08, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	22.6°C	<b>Humidity</b>	52%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11n Ch. 48 (20 MHz)

**Horizontal**



Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	6963.000	56.96	-20.88	77.84	50.49	35.89	5.59	35.01 Peak	---	---
2	@10480.000	60.15	-17.69	77.84	50.16	38.29	6.82	35.12 Peak	---	---
3	@15720.000	58.10	-5.44	63.54	43.95	40.89	8.46	35.20 PK	---	---


Vertical



Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 6963.000	63.56	-14.28	77.84	57.09	35.89	5.59	35.01	Peak	---	---
2 10480.000	58.79	-19.05	77.84	48.80	38.29	6.82	35.12	Peak	---	---
3 @15720.000	60.51	-3.03	63.54	46.36	40.89	8.46	35.20	PK	---	---


<b>Final Test Date</b>	Mar. 08, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	22.6°C	<b>Humidity</b>	52%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11n Ch. 38 (40MHz)

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	6911.000	48.04	-29.80	77.84	41.59	35.87	5.58	35.00	Peak	---	---
2	10380.000	45.05	-32.79	77.84	35.27	38.23	6.75	35.20	Peak	---	---
3	@15570.000	50.23	-13.31	63.54	36.00	40.83	8.45	35.05	PK	---	---


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	6911.000	55.75	-22.09	77.84	49.30	35.87	5.58	35.00	Peak	---	---
2	10380.000	45.01	-32.83	77.84	35.23	38.23	6.75	35.20	Peak	---	---
3	@15570.000	50.41	-13.13	63.54	36.18	40.83	8.45	35.05	PK	---	---


<b>Final Test Date</b>	Mar. 08, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	22.6°C	<b>Humidity</b>	52%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11n Ch. 46 (40MHz)

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	6963.000	53.72	-24.12	77.84	47.25	35.89	5.59	35.01	Peak	---	---
2	@10460.000	59.66	-18.18	77.84	49.71	38.27	6.82	35.14	Peak	---	---
3	@15690.000	55.66	-7.88	63.54	41.50	40.88	8.46	35.18	PK	---	---

Vertical



Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBUV/m	dB	dBUV/m	dBUV	dB/m	dB	dB		cm	deg
1 @ 6963.000	62.42	-15.42	77.84	55.95	35.89	5.59	35.01	Peak	---	---
2 10460.000	56.85	-20.99	77.84	46.90	38.27	6.82	35.14	Peak	---	---
3 @15690.000	58.69	-4.85	63.54	44.53	40.88	8.46	35.18	PK	---	---

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

The limits above 5GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = 20 log (specific distance [3m] / test distance [1m]) (dB);

Limit line = specific limits (dBUV) + distance extrapolation factor [9.54 dB].

**3.7 Band Edge and Fundamental Emissions Measurement**

**3.7.1 Limit**

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.25 GHz band shall not exceed an EIRP of -27 dBm/MHz (68.3dBuV/m at 3m). For transmitters operating in the 5.47-5.725 GHz band: all emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz (68.3dBuV/m at 3m). In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

<b>Frequencies (MHz)</b>	<b>Field Strength (microrvolts/meter)</b>	<b>Measurement Distance (meters)</b>
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

**3.7.2 Measuring Instruments and Setting**

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

<b>Spectrum Parameter</b>	<b>Setting</b>
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1 MHz /1 MHz for Peak

**3.7.3 Test Procedures**

1. The test procedure is the same as section 3.6.3; only the frequency range investigated is limited to 100MHz around band edges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

**3.7.4 Test Setup Layout**

This test setup layout is the same as that shown in section 3.6.4.

**3.7.5 Test Deviation**

There is no deviation with the original standard.

**3.7.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

3.7.7 Test Result of Band Edge and Fundamental Emissions

For Single Chain:

Final Test Date	Mar. 08, 2012	Test Site No.	03CH02-HY
Temperature	22.6°C	Humidity	52%
Test Engineer	Streak	Configuration	802.11a Ch. 36, 40, 48

Channel 36

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	5150.000	61.99	-1.55	63.54	22.32	34.89	4.78	0.00	Average	---	---
2 @	5178.200	109.19			69.48	34.91	4.80	0.00	Average	---	---
1	5149.900	76.46	-7.08	83.54	36.79	34.89	4.78	0.00	Peak	---	---
2 @	5176.200	117.80			78.09	34.91	4.80	0.00	Peak	---	---

The item 2 is fundamental emissions.

Channel 40

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	5147.400	62.25	-1.29	63.54	22.58	34.89	4.78	0.00	Average	---	---
2 @	5196.600	112.29			72.56	34.92	4.81	0.00	Average	---	---
3 @	5350.500	52.22	-11.32	63.54	12.34	35.01	4.87	0.00	Average	---	---
1 @	5147.700	74.95	-8.59	83.54	35.28	34.89	4.78	0.00	Peak	---	---
2 @	5196.600	121.99			82.26	34.92	4.81	0.00	Peak	---	---
3 @	5350.200	65.36	-18.18	83.54	25.48	35.01	4.87	0.00	Peak	---	---

The item 2 is fundamental emissions.

Channel 48

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	5127.300	56.38	-7.16	63.54	16.72	34.88	4.78	0.00	Average	---	---
2 @	5236.500	114.13			74.37	34.94	4.82	0.00	Average	---	---
3 @	5352.900	53.42	-10.12	63.54	13.54	35.01	4.87	0.00	Average	---	---
1 @	5133.300	69.40	-14.14	83.54	29.74	34.88	4.78	0.00	Peak	---	---
2 @	5236.500	124.06			84.30	34.94	4.82	0.00	Peak	---	---
3 @	5351.700	65.95	-17.59	83.54	26.07	35.01	4.87	0.00	Peak	---	---

The item 2 is fundamental emissions.

For Two Chains:

Final Test Date	Mar. 08, 2012	Test Site No.	03CH02-HY
Temperature	22.6°C	Humidity	52%
Test Engineer	Streak	Configuration	802.11n (20MHz) Ch. 36, 40, 48

Channel 36

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	5150.000	61.79	-1.75	63.54	22.12	34.89	4.78	0.00	Average	---	---
2 @	5178.200	108.99			69.28	34.91	4.80	0.00	Average	---	---
1 @	5147.800	77.99	-5.55	83.54	38.32	34.89	4.78	0.00	Peak	---	---
2 @	5175.900	119.65			79.94	34.91	4.80	0.00	Peak	---	---

The item 2 is fundamental emissions.

Channel 40

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	5147.700	62.03	-1.51	63.54	22.36	34.89	4.78	0.00	Average	---	---
2 @	5198.100	111.44			71.71	34.92	4.81	0.00	Average	---	---
3 @	5361.000	52.31	-11.23	63.54	12.42	35.02	4.87	0.00	Average	---	---
1 @	5147.700	75.11	-8.43	83.54	35.44	34.89	4.78	0.00	Peak	---	---
2 @	5195.400	121.95			82.22	34.92	4.81	0.00	Peak	---	---
3 @	5381.700	65.42	-18.12	83.54	25.52	35.03	4.87	0.00	Peak	---	---

The item 2 is fundamental emissions.

Channel 48

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @	5127.300	56.79	-6.75	63.54	17.13	34.88	4.78	0.00	Average	---	---
2 @	5237.700	113.04			73.28	34.94	4.82	0.00	Average	---	---
3 @	5361.300	53.29	-10.25	63.54	13.40	35.02	4.87	0.00	Average	---	---
1 @	5126.100	69.36	-14.18	83.54	29.70	34.88	4.78	0.00	Peak	---	---
2 @	5241.300	123.00			83.24	34.94	4.82	0.00	Peak	---	---
3 @	5359.800	67.14	-16.40	83.54	27.26	35.01	4.87	0.00	Peak	---	---

The item 2 is fundamental emissions.

<b>Final Test Date</b>	Mar. 08, 2012	<b>Test Site No.</b>	03CH02-HY
<b>Temperature</b>	22.6°C	<b>Humidity</b>	52%
<b>Test Engineer</b>	Streak	<b>Configuration</b>	802.11n (40MHz) Ch. 38, 46

**Channel 38**

	<b>Freq</b>	<b>Level</b>	<b>Over Limit</b>	<b>Limit Line</b>	<b>ReadAntenna Level</b>	<b>Antenna Factor</b>	<b>Cable Loss</b>	<b>Preamp Factor</b>	<b>Remark</b>	<b>Ant Pos</b>	<b>Table Pos</b>
	<b>MHz</b>	<b>dBuV/m</b>	<b>dB</b>	<b>dBuV/m</b>	<b>dBuV</b>	<b>dB/m</b>	<b>dB</b>	<b>dB</b>		<b>cm</b>	<b>deg</b>
1 @	5150.000	62.40	-1.14	63.54	22.73	34.89	4.78	0.00	Average	---	---
2 @	5179.100	100.91			61.20	34.91	4.80	0.00	Average	---	---
1 @	5149.900	79.16	-4.38	83.54	39.49	34.89	4.78	0.00	Peak	---	---
2 @	5185.400	111.45			71.74	34.91	4.80	0.00	Peak	---	---

The item 2 is fundamental emissions.

**Channel 46**

	<b>Freq</b>	<b>Level</b>	<b>Over Limit</b>	<b>Limit Line</b>	<b>ReadAntenna Level</b>	<b>Antenna Factor</b>	<b>Cable Loss</b>	<b>Preamp Factor</b>	<b>Remark</b>	<b>Ant Pos</b>	<b>Table Pos</b>
	<b>MHz</b>	<b>dBuV/m</b>	<b>dB</b>	<b>dBuV/m</b>	<b>dBuV</b>	<b>dB/m</b>	<b>dB</b>	<b>dB</b>		<b>cm</b>	<b>deg</b>
1 @	5149.750	62.20	-1.34	63.54	22.53	34.89	4.78	0.00	Average	---	---
2 @	5223.750	108.79			69.05	34.93	4.81	0.00	Average	---	---
3 @	5352.500	53.78	-9.76	63.54	13.90	35.01	4.87	0.00	Average	---	---
1 @	5150.000	76.28	-1.56	77.84	36.61	34.89	4.78	0.00	Peak	---	---
2 @	5218.750	119.79			80.05	34.93	4.81	0.00	Peak	---	---
3 @	5357.500	66.84	-16.70	83.54	26.96	35.01	4.87	0.00	Peak	---	---

The item 2 is fundamental emissions.

**3.8 Frequency Stability Measurement**

**3.8.1 Limit**

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emissions is maintained within the band of operation under all conditions of normal operation as specified in the user’s manual or ±20ppm (IEEE 802.11a specification).

**3.8.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RB	10 kHz
VB	10 kHz
Sweep Time	Auto

**3.8.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5.  $f_c$  is declaring of channel frequency. Then the frequency error formula is  $(f_c-f)/f_c \times 10^6$  ppm and the limit is less than ±20ppm (IEEE 802.11a specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature rule is -20°C~50°C.
8. Measuring multiple antennas, the connectors are required to link with Spectrum Analyzer through a combiner.

**3.8.4 Test Setup Layout**



**3.8.5 Test Deviation**

There is no deviation with the original standard.

**3.8.6 EUT Operation during Test**

The EUT was programmed to be in continuously un-modulation transmitting mode.

**3.8.7 Test Result of Frequency Stability**

**Voltage vs. Frequency Stability**

<b>Voltage</b>	<b>Measurement Frequency (MHz)</b>
<b>(V)</b>	<b>5200 MHz</b>
<b>126.5</b>	5199.950800
<b>110</b>	5199.975600
<b>93.5</b>	5199.975400
<b>Max. Deviation (MHz)</b>	<b>0.049200</b>
<b>Max. Deviation (ppm)</b>	<b>9.46</b>

**Temperature vs. Frequency Stability**

<b>Temperature</b>	<b>Measurement Frequency (MHz)</b>
<b>(°C)</b>	<b>5200 MHz</b>
<b>-20</b>	5200.018600
<b>-10</b>	5200.012600
<b>0</b>	5200.005400
<b>10</b>	5199.993400
<b>20</b>	5199.975400
<b>30</b>	5199.962800
<b>40</b>	5199.954400
<b>50</b>	5199.950800
<b>Max. Deviation (MHz)</b>	<b>0.049200</b>
<b>Max. Deviation (ppm)</b>	<b>9.46</b>

### **3.9 Antenna Requirements**

#### **3.9.1 Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

#### **3.9.2 Antenna Connector Construction**

Please refer to section 2.2 in this test report; antenna connector complied with the requirements.

**4 LIST OF MEASURING EQUIPMENTS**

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9 kHz ~ 2.75 GHz	Mar. 23, 2012	Conduction (CO04-HY)
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz – 30MHz	Feb. 08, 2012	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9 kHz ~ 30 MHz	May 04, 2011	Conduction (CO04-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	CB049	9 kHz ~ 30 MHz	Apr. 21, 2011	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP 40	100305	9 KHz ~ 40 GHz	Feb. 21, 2012	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Jun. 03, 2011	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-SP-SD	MAA1112-007	-20~100°C	Dec. 07, 2011	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10 MHz ~ 40 GHz	Jun. 07, 2011	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	1027452	300 MHz ~ 40 GHz	Jun. 16, 2011	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	1124009	300 MHz ~ 40 GHz	Jun. 20, 2011	Conducted (TH01-HY)
RF Cable-1m	Jye Bao	RG142	CB034-1m	20 MHz ~ 7 GHz	Dec. 03, 2011	Conducted (TH01-HY)
RF Cable-2m	Jye Bao	RG142	CB035-2m	20 MHz ~ 1 GHz	Dec. 03, 2011	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP40	100593	9 kHz ~ 40 GHz	Aug. 08, 2011	Radiation (03CH02-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30 MHz ~ 1 GHz 3m	May 11, 2011	Radiation (03CH02-HY)
Amplifier	Agilent	8447D	2944A11146	100 kHz ~ 1.3 GHz	Jul. 25, 2011	Radiation (03CH02-HY)
Amplifier	Agilent	8449B	3008A02373	1 GHz ~ 26.5 GHz	Jul. 25, 2011	Radiation (03CH02-HY)
Horn Antenna	ETS-LINDGREN	3117	00091920	1 GHz ~ 18 GHz	Nov. 15, 2011	Radiation (03CH02-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz ~ 1 GHz	Nov. 11, 2011	Radiation (03CH02-HY)
RF Cable-high	SUHNER	SUCOFLEX106	03CH02-HY	1 GHz ~ 40 GHz	Mar. 06, 2012	Radiation (03CH02-HY)
Bilog Antenna	SCHAFFNER	CBL61128	2723	30 MHz ~ 2 GHz	Oct. 22, 2011	Radiation (03CH02-HY)
Turn Table	HD	DS 420	420/649/00	0 - 360 degree	N/A	Radiation (03CH02-HY)
Antenna Mast	HD	MA 240	240/559/00	1 m - 4 m	N/A	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 29, 2010*	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is two year.

**5 TEST LOCATION**

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei 221, Taiwan, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Vil., Linkou Dist., New Taipei City 244, Taiwan, R.O.C. TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei 114, Taiwan, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei 235, Taiwan, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6 TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-111208

財團法人全國認證基金會  
Taiwan Accreditation Foundation

## Certificate of Accreditation

This is to certify that

**Sporton International Inc.**  
**EMC & Wireless Communications Laboratory**  
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

**is accredited in respect of laboratory**

<b>Accreditation Criteria</b>	: ISO/IEC 17025:2005
<b>Accreditation Number</b>	: 1190
<b>Originally Accredited</b>	: December 15, 2003
<b>Effective Period</b>	: January 10, 2010 to January 09, 2013
<b>Accredited Scope</b>	: Testing Field, see described in the Appendix
<b>Specific Accreditation Program</b>	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities



Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : December 08, 2011

P1, total 24 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix