



Test report No.: 2380887R-RFUSV01S-B

TEST REPORT

Product Name	Wireless headphone
Trademark	ASUS
Model and /or type reference	R55ES(L), R55ES(R)
FCC ID	MSQ-RCTWSNEL MSQ-RCTWSNER
Applicant's name / address	ASUSTeK COMPUTER INC. 1F., No. 15, Lide Rd., Beitou Dist., Taipei City 112, Taiwan
Manufacturer's name	ASUSTeK COMPUTER INC.
Test method requested, standard	FCC CFR Title 47 Part 15 Subpart C ANSI C63.4: 2014, ANSI C63.10: 2013
Verdict Summary	IN COMPLIANCE
Documented By (Senior Project Specialist / Genie Chang)	Genie Chang
Tested By (Senior Engineer / Ivan Chuang)	Ivan Chuang
Approved By (Senior Engineer / Jack Hsu)	Jack Hsu
Date of Receipt	2023/08/29
Date of Issue	2023/12/15
Report Version	V1.0

INDEX

	Page
1. General Information.....	6
1.1. EUT Description.....	6
1.2. Tested System Details.....	8
1.3. Configuration of Tested System	9
1.4. EUT Exercise Software	9
1.5. Test Facility	10
1.6. List of Test Equipment.....	11
1.7. Uncertainty	12
2. Conducted Emission	13
2.1. Test Setup	13
2.2. Limits.....	13
2.3. Test Procedure	14
2.4. Test Result of Conducted Emission.....	15
3. Peak Power Output.....	16
3.1. Test Setup	16
3.2. Limit	16
3.3. Test Procedure	16
3.4. Test Result of Peak Power Output.....	17
4. Radiated Emission	21
4.1. Test Setup	21
4.2. Limits.....	22
4.3. Test Procedure	23
4.4. Test Result of Radiated Emission.....	25
5. RF Antenna Conducted Test	33
5.1. Test Setup	33
5.2. Limits.....	33
5.3. Test Procedure	33
5.4. Test Result of RF Antenna Conducted Test.....	34
6. Band Edge	38
6.1. Test Setup	38
6.2. Limit	39
6.3. Test Procedure	39
6.4. Test Result of Band Edge	41

7. 6dB Bandwidth	53
7.1. Test Setup	53
7.2. Limits.....	53
7.3. Test Procedure	53
7.4. Test Result of 6dB Bandwidth.....	54
8. Power Density.....	58
8.1. Test Setup	58
8.2. Limits.....	58
8.3. Test Procedure	58
8.4. Test Result of Power Density	59
9. Duty Cycle	63
9.1. Test Setup	63
9.2. Test Procedure	63
9.3. Test Result of Duty Cycle.....	64

Appendix 1: EUT Test Photographs

Appendix 2: Product Photos-Please refer to the file: 2380887R -Product Photos

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Report No.	Version	Description	Issued Date
2380887R-RFUSV01S-B	V1.0	Initial issue of report.	2023/12/15

1. General Information

1.1. EUT Description

Product Name	Wireless headphone
Trademark	ASUS
Model and /or type reference	R55ES(L), R55ES(R)
EUT Rated Voltage	DC 3.85V by Battery
EUT Test Voltage	DC 3.85V by Battery
Frequency Range	2402 - 2480 MHz
Channel Number	40
Type of Modulation	GFSK(1 Mbps, 2 Mbps)
Channel Control	Auto
Wireless headphone	ASUS / R55ES(L)
Wireless headphone	ASUS / R55ES(R)
Wireless Charge Case	ASUS / R55ES
USB Cable	ASUS / R55ES, Shielded, 0.6m
USB-C Wireless Dongle	ASUS / R55ES-D
USB-C to USB-A adaptor dongle	ASUS / R55ES
Battery	Hynetech / CH1154AA

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	Cicent (Right)	102BK3F1421	Monopole	-1.2 dBi for 2400 MHz
2	Cicent (Left)	102BK3F1420	Monopole	-0.2 dBi for 2400 MHz

Note: 1. The antenna of EUT is conforming to FCC 15.203.

2. The antenna gain as by the manufacturer provided.

Center Frequency of Each Channel:

Channel	Frequency (MHz)						
00	2402	01	2404	02	2406	03	2408
04	2410	05	2412	06	2414	07	2416
08	2418	09	2420	10	2422	11	2424
12	2426	13	2428	14	2430	15	2432
16	2434	17	2436	18	2438	19	2440
20	2442	21	2444	22	2446	23	2448
24	2450	25	2452	26	2454	27	2456
28	2458	29	2460	30	2462	31	2464
32	2466	33	2468	34	2470	35	2472
36	2474	37	2476	38	2478	39	2480

Note:

1. The EUT is a Wireless headphone with built-in 2.4G wireless and Bluetooth transceiver, this report for Bluetooth LE.
2. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report
3. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
4. The spectrum plot against conducted item only shows the worst case.
5. DEKRA has evaluated each test mode. Only the worst case is shown in the report.
6. These tests were conducted on a sample for the purpose of demonstrating compliance of transmitter with Part 15 Subpart C Paragraph 15.247 for spread spectrum devices.

Test Mode	Mode 1	Transmit - 1 Mbps
		Transmit - 2 Mbps
	Mode 2	Charger mode

1.2. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook PC	DELL	Latitude 5580	2HRD7H2	N/A
2	Test Fixture	Mercury Electronics	FT232RL USB To UART	N/A	N/A


Cable Type	Cable Description
A	USB Cable
B	Signal Cable

Charger mode


Product		Manufacturer	Model No.	Serial No.	Power Cord
1	Power Adapter	Apple	A1385	N/A	N/A
2	Wireless Charge Case	ASUS	R55ES	N/A	N/A

Cable Type	Cable Description
A	USB Cable
B	USB Cable

1.3. Configuration of Tested System



Charger mode



1.4. EUT Exercise Software

1	Setup the EUT as shown in Section 1.3.
2	Execute software ‘Airoha Tool Kit Version 3.5.6’ on the Notebook PC.
3	Configure the test mode, the test channel, and the data rate.
4	Verify that the EUT works properly.

1.5. Test Facility

Ambient conditions in the laboratory:

Performed Item	Items	Required	Actual
Conducted Emission	Temperature (°C)	10~40 °C	26.7 °C
	Humidity (%RH)	10~90 %	58.0 %
Radiated Emission	Temperature (°C)	10~40 °C	21.6 °C
	Humidity (%RH)	10~90 %	63.8 %
Conductive	Temperature (°C)	10~40 °C	23.9 °C
	Humidity (%RH)	10~90 %	56.2 %

USA	FCC Registration Number: TW0033
Canada	CAB Identifier Number: TW3023 / Company Number: 26930

Site Description	Accredited by TAF Accredited Number: 3023
------------------	--

Test Laboratory	DEKRA Testing and Certification Co., Ltd. Linkou Laboratory
Address	No.5-22, Ruishukeng Linkou District, New Taipei City, 24451, Taiwan, R.O.C.
Performed Location	No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.
Phone Number	+886-3-275-7255
Fax Number	+886-3-327-8031

1.6. List of Test Equipment

For Conduction Measurements /HY-SR01

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	EMI Test Receiver	R&S	ESR7	101601	2023/06/20	2024/06/19
V	Two-Line V-Network	R&S	ENV216	101306	2023/03/16	2024/03/15
V	Two-Line V-Network	R&S	ENV216	101307	2023/08/17	2024/08/16
V	Coaxial Cable	SUHNER	RG400_BNC	RF001	2023/01/10	2024/01/09

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “V” are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

For Conducted Measurements /HY-SR02

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Spectrum Analyzer	R&S	FSV30	103466	2022/12/22	2023/12/21
V	Peak Power Analyzer	KEYSIGHT	8990B	MY51000539	2023/05/15	2024/05/14
V	Power Sensor	KEYSIGHT	N1923A	MY59240002	2023/05/18	2024/05/17
V	Power Sensor	KEYSIGHT	N1923A	MY59240003	2023/05/18	2024/05/17

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “V” are used to measure the final test results.
3. Test Software Version: RF Conducted Test Tools R3 V3.0.1.14.

For Radiated Measurements / HY-CB02

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
	Loop Antenna	AMETEK	HLA6121	49611	2023/02/21	2024/02/20
V	Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-0678	2021/09/23	2023/09/22
V	Horn Antenna	RF SPIN	DRH18-E	210503A18ES	2023/02/24	2024/02/23
V	Horn Antenna	Com-Power	AH-840	101101	2021/11/30	2023/11/29
V	Pre-Amplifier	SGH	EM330	60736	2023/01/10	2024/01/09
V	Pre-Amplifier	SGH	PRAMP118	20200203	2023/01/10	2024/01/09
V	Pre-Amplifier	EMCI	EMC05820SE	980285	2023/01/10	2024/01/09
V	Pre-Amplifier	EMCI	EMC184045SE	980369	2023/01/10	2024/01/09
	Coaxial Cable	EMCI	EMC102-KM-KM-600	1160314		
V	Coaxial Cable	EMCI	EMC102-KM-KM-7000	170242		
	V	Filter	MICRO TRONICS	BRM50702	G249	2023/01/05
V	Filter	MICRO TRONICS	BRM50716	G187	2023/01/05	2024/01/04
V	EMI Test Receiver	R&S	ESR7	101601	2023/06/20	2024/06/19
V	Spectrum Analyzer	R&S	FSV3044	101113	2023/02/04	2024/02/03
V	Coaxial Cable	SGH	HA800	GD20110223-2	2023/01/10	2024/01/09
	Coaxial Cable	SGH	HA800	GD20110222-4		
	Coaxial Cable	SGH	SGH18	2021005-2		
	Coaxial Cable	SGH	SGH18	202108-5		

Note:

1. Bi-Log Antenna and Horn Antenna(AH-840) is calibrated every two years, the other equipments are calibrated every one year.
2. The test instruments marked with “V” are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

1.7. Uncertainty

Uncertainties have been calculated according to the DEKRA internal document.


The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system but are based on the results of the compliance measurement.

Test item	Uncertainty
Conducted Emission	± 3.50 dB
Peak Power Output	Spectrum Analyzer: ± 2.14 dB Power Meter: ± 1.05 dB
Radiated Emission	9 kHz~30 MHz: ± 3.88 dB 30 MHz~1 GHz: ± 4.42 dB 1 GHz~18 GHz: ± 4.28 dB 18 GHz~40 GHz: ± 3.90 dB
RF Antenna Conducted Test	± 2.14 dB
Band Edge	For Radiated: 9 kHz~30 MHz: ± 3.88 dB 30 MHz~1 GHz: ± 4.42 dB 1 GHz~18 GHz: ± 4.28 dB 18 GHz~40 GHz: ± 3.90 dB For Conducted: ± 2.14 dB
6dB Bandwidth	± 1580.61 Hz
Power Density	± 2.14 dB
Duty Cycle	± 0.53 %

2. Conducted Emission

2.1. Test Setup



2.2. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dB μ V) Limit		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

Remarks: In the above table, the tighter limit applies at the band edges.

2.3. Test Procedure


The EUT and Peripherals are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.

Conducted emissions were invested over the frequency range from 0.15 MHz to 30 MHz using a receiver bandwidth of 9 kHz.


The EUT was setup to ANSI C63.4, 2014; tested to DTS test procedure of FCC KDB-558074 for compliance to FCC 47CFR Subpart C requirements.

2.4. Test Result of Conducted Emission



3. Peak Power Output

3.1. Test Setup



3.2. Limit

The maximum peak power shall be less 1Watt.

3.3. Test Procedure

The EUT was tested according to C63.10:2013 for compliance to FCC 47CFR 15.247 requirements. The maximum peak conducted output power using C63.10:2013 Section 11.9.1.3 PKPM1 Peak power meter method.

3.4. Test Result of Peak Power Output

Product : Wireless headphone
Test Item : Peak Power Output
Test Mode : Transmit - 1 Mbps_Right
Test Date : 2023/09/04

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
00	2402	9.27	1 Watt= 30 dBm	Pass
19	2440	9.35	1 Watt= 30 dBm	Pass
39	2480	9.41	1 Watt= 30 dBm	Pass

Product : Wireless headphone
Test Item : Peak Power Output
Test Mode : Transmit - 2 Mbps _Right
Test Date : 2023/09/04

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
00	2402	9.27	1 Watt= 30 dBm	Pass
19	2440	9.35	1 Watt= 30 dBm	Pass
39	2480	9.39	1 Watt= 30 dBm	Pass

Product : Wireless headphone
Test Item : Peak Power Output
Test Mode : Transmit - 1 Mbps_Left
Test Date : 2023/09/04

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
00	2402	9.32	1 Watt= 30 dBm	Pass
19	2440	9.48	1 Watt= 30 dBm	Pass
39	2480	9.57	1 Watt= 30 dBm	Pass


Product : Wireless headphone
Test Item : Peak Power Output
Test Mode : Transmit - 2 Mbps_Left
Test Date : 2023/09/04

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
00	2402	9.30	1 Watt= 30 dBm	Pass
19	2440	9.43	1 Watt= 30 dBm	Pass
39	2480	9.55	1 Watt= 30 dBm	Pass


4. Radiated Emission

4.1. Test Setup


Radiated Emission Under 30 MHz



Radiated Emission Below 1 GHz



Radiated Emission Above 1 GHz



4.2. Limits

➤ General Radiated Emission Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209 Limits		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remarks:

1. RF Voltage (dB μ V) = 20 log RF Voltage (uV)
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

4.3. Test Procedure

The EUT was setup according to ANSI C63.10: 2013 and tested according to C63.10:2013 Section 11.12.1 for compliance to FCC 47CFR 15.247 requirements.

Measuring the frequency range below 1 GHz, the EUT is placed on a turn table which is 0.8 meter above ground, when measuring the frequency range above 1 GHz, the EUT is placed on a turn table which is 1.5 meter above ground.

The turn table is rotated 360 degrees to determine the position of the maximum emission level.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2013 on radiated measurement.

The resolution bandwidth below 30 MHz setting on the field strength meter is 9 kHz and 30 MHz~1 GHz is 120 kHz and above 1 GHz is 1 MHz.

Radiated emission measurements below 30 MHz are made using Loop Antenna and 30 MHz~1 GHz are made using broadband Bilog antenna and above 1 GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The measurement frequency range form 9 kHz - 10th Harmonic of fundamental was investigated.

RBW and VBW Parameter setting:

According to C63.10 Section 11.12.2.4 Peak measurement procedure.

RBW = as specified in Table 1.

$\text{VBW} \geq 3 \times \text{RBW}$.

Table 1 —RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

According to C63.10 Section 11.12.2.5 Average measurement procedure.

RBW = 1 MHz.

$\text{VBW} = 10 \text{ Hz}$, when duty cycle $\geq 98\%$

$\text{VBW} \geq 1/T$, when duty cycle $< 98\%$


(T refers to the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.)


2.4 GHz band (Right)	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
BLE (1 Mbps)	84.00	2.100	476	500
BLE (2 Mbps)	42.06	1.060	943	1000
2.4 GHz band (Left)	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
BLE (1 Mbps)	84.00	2.100	476	500
BLE (2 Mbps)	41.60	1.040	962	1000


Note: Duty Cycle Refer to Section 9.


4.4. Test Result of Radiated Emission

Right













Left










5. RF Antenna Conducted Test

5.1. Test Setup



5.2. Limits

According to FCC Section 15.247(d). In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.


5.3. Test Procedure

The EUT was tested according to C63.10:2013 Section 11.11 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.


5.4. Test Result of RF Antenna Conducted Test

Product : Wireless headphone
Test Item : RF Antenna Conducted Test
Test Mode : Transmit - 1 Mbps_Right
Test Date : 2023/09/04



Product : Wireless headphone
Test Item : RF Antenna Conducted Test
Test Mode : Transmit - 2 Mbps_Right
Test Date : 2023/09/04


Channel 39



Date: 4.SEP.2023 12:07:37


Product : Wireless headphone
Test Item : RF Antenna Conducted Test
Test Mode : Transmit - 1 Mbps_Left
Test Date : 2023/09/04

Figure Channel 39



Product : Wireless headphone
Test Item : RF Antenna Conducted Test
Test Mode : Transmit - 2 Mbps_Left
Test Date : 2023/09/04

Figure Channel 39




Date: 4.SEP.2023 11:23:25


6. Band Edge

6.1. Test Setup

RF Conducted Measurement



RF Radiated Measurement:



6.2. Limit

According to FCC Section 15.247(d). In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

6.3. Test Procedure

The EUT was setup according to ANSI C63.10, 2013 and tested according to C63.10:2013 Section 11.12.1 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.

RBW and VBW Parameter setting:

According to C63.10 Section 11.12.2.4 Peak measurement procedure.

RBW = as specified in Table 1.

$\text{VBW} \geq 3 \times \text{RBW}$.

Table 1 —RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

According to C63.10 Section 11.12.2.5 Average measurement procedure.

RBW = 1 MHz.

$\text{VBW} = 10 \text{ Hz}$, when duty cycle $\geq 98\%$

$\text{VBW} \geq 1/T$, when duty cycle $< 98\%$


(T refers to the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.)

2.4 GHz band (Right)	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
BLE (1 Mbps)	84.00	2.100	476	500
BLE (2 Mbps)	42.06	1.060	943	1000
2.4 GHz band (Left)	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
BLE (1 Mbps)	84.00	2.100	476	500
BLE (2 Mbps)	41.60	1.040	962	1000


Note: Duty Cycle Refer to Section 9.


6.4. Test Result of Band Edge

Right












Left











Product : Wireless headphone
 Test Item : Band Edge
 Test Mode : Transmit - 1 Mbps_Right
 Test Date : 2023/09/04

Channel 00




Channel 39




Product : Wireless headphone
 Test Item : Band Edge
 Test Mode : Transmit - 2 Mbps_Right
 Test Date : 2023/09/04

Channel 00




Channel 39




Product : Wireless headphone
 Test Item : Band Edge
 Test Mode : Transmit - 1 Mbps_Left
 Test Date : 2023/09/04

Channel 00




Channel 39




Product : Wireless headphone
 Test Item : Band Edge
 Test Mode : Transmit - 2 Mbps_Left
 Test Date : 2023/09/04

Channel 00




Channel 39



7. 6dB Bandwidth

7.1. Test Setup



7.2. Limits

The minimum bandwidth shall be at least 500 kHz.


7.3. Test Procedure

The EUT was tested according to ANSI C63.10 Section 11.8 for compliance to FCC 47CFR 15.247 requirements.

7.4. Test Result of 6dB Bandwidth

Product : Wireless headphone
 Test Item : 6dB Bandwidth Data
 Test Mode : Transmit - 1 Mbps_Right
 Test Date : 2023/09/04


Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
00	2402	659	>500	Pass
19	2440	664	>500	Pass
39	2480	664	>500	Pass



Product : Wireless headphone
 Test Item : 6dB Bandwidth Data
 Test Mode : Transmit - 2 Mbps_Right
 Test Date : 2023/09/04

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
00	2402	1234	>500	Pass
19	2440	1229	>500	Pass
39	2480	1234	>500	Pass

Channel 19




Date: 4.SEP.2023 12:04:37

Product : Wireless headphone
 Test Item : 6dB Bandwidth Data
 Test Mode : Transmit - 1 Mbps_Left
 Test Date : 2023/09/04

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
00	2402	664	>500	Pass
19	2440	664	>500	Pass
39	2480	664	>500	Pass

Figure Channel 00




Date: 4.SEP.2023 11:08:59

Product : Wireless headphone
 Test Item : 6dB Bandwidth Data
 Test Mode : Transmit - 2 Mbps _Left
 Test Date : 2023/09/04

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
00	2402	1234	>500	Pass
19	2440	1234	>500	Pass
39	2480	1234	>500	Pass


Figure Channel 00



Date: 4.SEP.2023 11:16:25

8. Power Density

8.1. Test Setup



8.2. Limits

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3 kHz bandwidth.

8.3. Test Procedure


The EUT was setup according to ANSI C63.10, 2013; tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

The maximum power spectral density using C63.10 Section 11.10.2 Method PKPSD (peak PSD)

8.4. Test Result of Power Density


Product : Wireless headphone
 Test Item : Power Spectral Density
 Test Mode : Transmit - 1 Mbps_Right
 Test Date : 2023/09/04

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
00	2402	-8.22	≤8dBm	Pass
19	2440	-8.20	≤8dBm	Pass
39	2480	-8.04	≤8dBm	Pass



Product : Wireless headphone
 Test Item : Power Spectral Density
 Test Mode : Transmit - 2 Mbps_Right
 Test Date : 2023/09/04


Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
00	2402	-10.89	≤8dBm	Pass
19	2440	-10.84	≤8dBm	Pass
39	2480	-10.70	≤8dBm	Pass



Date: 4.SEP.2023 12:06:42

Product : Wireless headphone
 Test Item : Power Spectral Density
 Test Mode : Transmit - 1 Mbps_Left
 Test Date : 2023/09/04


Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
00	2402	-8.02	≤8dBm	Pass
19	2440	-7.97	≤8dBm	Pass
39	2480	-7.79	≤8dBm	Pass



Date: 4.SEP.2023 11:14:34


Product : Wireless headphone
 Test Item : Power Spectral Density
 Test Mode : Transmit - 2 Mbps_Left
 Test Date : 2023/09/04

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
00	2402	-10.73	≤8dBm	Pass
19	2440	-10.64	≤8dBm	Pass
39	2480	-10.49	≤8dBm	Pass



9. Duty Cycle

9.1. Test Setup



9.2. Test Procedure

The EUT was setup according to ANSI C63.10 2013; tested according to ANSI C63.10 2013 for compliance to FCC 47CFR 15.247 requirements.

9.3. Test Result of Duty Cycle

Product : Wireless headphone
 Test Item : Duty Cycle
 Test Mode : Transmit - 1 Mbps_Right


Formula:

$$\text{Duty Cycle} = \text{Ton} / (\text{Ton} + \text{Toff})$$


$$\text{Duty Factor} = 10 \log (1/\text{Duty Cycle})$$

2.4GHz Band	Ton (ms)	Ton + Toff (ms)	Duty Cycle (%)	Duty Factor (dB)
BLE (1 Mbps)	2.100	2.500	84.00	0.76
BLE (2 Mbps)	1.060	2.520	42.06	3.76

BLE 1 Mbps



BLE 2 Mbps



Product : Wireless headphone
 Test Item : Duty Cycle
 Test Mode : Transmit - 2 Mbps_ Left


Formula:

$$\text{Duty Cycle} = \text{Ton} / (\text{Ton} + \text{Toff})$$

$$\text{Duty Factor} = 10 \log (1/\text{Duty Cycle})$$


2.4GHz Band	Ton (ms)	Ton + Toff (ms)	Duty Cycle (%)	Duty Factor (dB)
BLE (1 Mbps)	2.100	2.500	84.00	0.76
BLE (2 Mbps)	1.040	2.500	41.60	3.81

BLE 1 Mbps



Date: 4.SEP.2023 11:08:32

BLE 2 Mbps



Date: 4.SEP.2023 11:16:00