FCC RADIO EXPOSURE TEST REPORT

FCC ID	:	MSQ-RT0M00
Equipment	:	Wireless-AC3200 Tri-band Gigabit Router
Brand Name	:	ASUS
Model Name	:	RT-AC3200, RT-AC3200R, RT-AC3200W
Applicant	:	ASUSTeK COMPUTER INC. 4F, No. 150, Li-Te Rd., Peitou, Taipei 112, Taiwan
Manufacturer (1)	:	ASKEY TECHNOLOGH(JIANGSU)LTD. N0.1388, JiaoTong Road, WuKiang Economic-Technological Development Area,Jangus Province,P.R.C
Manufacturer (2)	:	Compal Networking (KunShan) Co., LTD. No. 520, Nabbang Rd., Economic & Technical Development Zone Kunshan, Jiangsu Province China
Standard	:	47 CFR Part 2.1091

The product was received on Oct. 22, 2019, and testing was started from Dec. 05, 2019 and completed on Dec. 13, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Sam Chen

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 EUT General Information 5
1.2 Table for Multiple Listing 5
1.3 Table for SKU List 5
1.4 Table for Housing List 5
1.5 Table for Class II Change 6
1.6 Testing Location 8
2 Maximum Permissible Exposure **9**
2.1 Limit of Maximum Permissible Exposure 9
2.2 MPE Calculation Method 9
2.3 Calculated Result and Limit 10
Photographs of EUT v01

History of this test report

Report No.	Version	Description	Issued Date
FA471703-12	01	Initial issue of report	Dec. 18, 2019

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sam Chen

Report Producer: Cindy Peng

1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	**Frequency Range (MHz)**	**Operating Frequency (MHz)**	**Modulation Type**
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)

The EUT supports Master (AP Router) and Slave without radar detection (Bridge) functions.

1.2 Table for Multiple Listing

The EUT has three model names which are identical to each other in all aspects except for the following table:

Model Name	Description
RT-AC3200	All the models are identical, the difference model for difference brand served as marketing strategy.
RT-AC3200R	
RT-AC3200W	

From the above models, model: RT-AC3200 was selected as representative model for the test and its data was recorded in this report.

1.3 Table for SKU List

The EUT has two SKU which are identical to each other in all aspects except for the following table:

SKU	Description
1	The difference between SKU 1 and SKU 2 is LAN transformer
2	

1.4 Table for Housing List

The EUT has two housing and which are identical to each other in all aspects except for the following table:

Housing	With Hole	Without Hole
1	V	X
2	X	V

From the above models, housing 2 was selected as representative model for the test and its data was recorded in

this report.

1.5 Table for Class II Change

This product is an extension of original one reported under Sporton project number: 471703

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
1. Updating the test rule of 5GHz band 4 to “15.407 (b)(4)(i)” from “15.407 (b)(4)(ii)”.	Maximum Permissible Exposure.
2. Adding two adapters (Brand: Delta, Model: ADP-45BW B / Brand: PI, Model: AD883J20).	It does not affect the Maximum Permissible Exposure.
Note: Maximum Permissible Exposure of 2.4GHz and 5GHz band 1 are based on original test report	

a. Changing the adapter (model: AD883J20). The difference between adapter 1 and adapter 4 as below:

Adapter 1	Adapter 4
Type: 010KLF BAH	Type: 010K-3LF

b. Changing the adapter (model: ADP-45BW B). The difference between adapter 2 and adapter 3 as below:

Adapter 2			
Design No	**MFG TITLE**	**MFG PART**	**DESCRIPTION**
Q1	AUK	SMK0760F	FET 600V 7A 1.2ohm TO-220F-3P
Q1	ST	STP6NK60ZFP	FET 600V 6A 1.2ohm TO-220FP-3P
Q1	TOSHIBA	TK10A60DR(STA4,X)	FET 600V 10A 750mohm TO-220SIS-3P
D101	ST	STPS20S100CT	DIO SBD 20A 100V TO-220AB-3P C.C.
D101	ST	STPS20SM100ST	DIO SBD 20A 100V TO-220AB-3P
D101	ST	STPS30SM100ST	DIO SBD 30A 100V TO-220AB-3P
IC31	ON	DAP022ASN65T1G	IC ASIC PWM CURRENT MODE TSOP-6P SMD
IC131	TI	TL432BIDBZR	IC VOL REF ADJ 2.495V 100mA 0.5%
IC131	NXP	TL431BMFDT	IC VOL REF ADJ 2.495V 100mA 0.5%
IC131	DIODES	AS431ANTR-G1	IC VOL REF ADJ 2.5V 100mA 0.5% SOT-23-3P
IC32	EVERLIGHT	EL816M(Y)(D)-VG	PHOTO TR 50mA 80V DIP-4P 150%-300%
IC32	SHARP	PC123Y92FZ0F	PHOTO TR 50mA 70V DIP-4P 160%-300%
IC32	Renesas	PS2561DL1-1Y-V-A(G)	EOL PHOTO TR 40mA 80V DIP-4P 150%-300%
CX1	EUROPTRONIC	MPX2224K30B15LXD20	CAP X2 MP PC 305VAC 0.22uF K S15
CX1	OKAYA	LE224-MX-30-C3.2	CAP X2 MP PC 300VAC 0.22uF K S15
CX1	HUA	MKP-224K0275AB115S-G	CAP X2 MP PC 275VAC 0.22uF K S15
FL1	DELTA	HFV-MP13202	LINE FILTER T14 14mH MIN

FL101	DELTA	LFV-MP13303	LINE FILTER T10 17uH MIN
T1	DELTA	MV-MP13167	TRANSFORMER MAIN RM10 1mH +/-5%
C1	NICHICON	UPT2G680MHD3	CAP AL 400V 68uF M 16*25 P7.5
C1	NCC	EKMG401ELL680ML25S	CAP AL 400V 68uF M 16*25 P7.5
C1	L-Tec	TYJ2GM680K25O	CAP AL 400V 68uF M 16*25 P7.5
CY1	MURATA	DE1B3KX221KNHAN99F	CAP Y1/X1 CD 250VAC 220pF K B TP VI10
CY1	TDK	CD70-B2GA221KYVK	CAP Y1/X1 CD 250VAC 220pF K B TP VI10
CY1	WALSIN	YP0AH221K061DASDAB	CAP Y1/X1 CD 250VAC 220pF K B TP VI10
Adapter 3			
Design No	**MFG TITLE**	**MFG PART**	**DESCRIPTION**
Q1	TOSHIBA	TK10A60DR(STA4,X)	FET 600V 10A 750mohm TO-220SIS-3P
Q1	FUJI	FMV11N60ES	FET 600V 11A 750mohm TO-220F-3P
D101	ST	STPS20S100CT	DIO SBD 20A 100V TO-220AB-3P C.C.
D101	ST	STPS20H100CT	DIO SBD 20A 100V TO-220AB-3P C.C.
D101	ST	STPS30H100CT	DIO SBD 30A 100V TO-220AB-3P C.C.
IC31	NeoEnergy	DAP022AT	IC ASIC PWM CURRENT MODE SOT-26-6P SMD
IC131	LITE-ON	LA431OCRPA	IC REGU ADJ 2.495V 100mA 0.4% SOT-23R-3P
IC131	TI	TL432BIDBZR	IC VOL REF ADJ 2.495V 100mA 0.5%
IC131	NXP	TL431BMFDT	IC VOL REF ADJ 2.495V 100mA 0.5%
IC32	EVERLIGHT	EL816M(Y)(D)-VG	PHOTO TR 50mA 80V DIP-4P 150%-300%
IC32	SHARP	PC123Y92FZ0F	PHOTO TR 50mA 70V DIP-4P 160%-300%
IC32	TOSHIBA	TLP785F(D4-GRH,F	PHOTO TR 60mA 80V DIP-4P 150%-300%
CX1	HUA	MKP-334K0275AB115S-G	CAP X2 MP PC 275VAC 0.33uF K S15
CX1	HUA	MKP-334K0275AB115S-P	CAP X2 MP PC 275VAC 0.33uF K S15
CX1	EUROPTRONIC	MPX2334K30B15LXD31	CAP X2 MP PC 305VAC 0.33uF K S15
FL1	DELTA	HFV-MP15027	LINE FILTER T16 12.7mH MIN
FL101	DELTA	LFV-MP13171	LINE FILTER T6 1.55uH MIN
T1	DELTA	MV-MP15037	TRANSFORMER MAIN RM10 1000uH +/-5%
C1	NCC	EKMG401ELL680ML25S	CAP AL 400V 68uF M 16*25 P7.5
CY1	MURATA	DE1B3KX221KNHAN99F	CAP Y1/X1 CD 250VAC 220pF K B TP VI10
CY1	WALSIN	YP0AH221K061DASDAB	CAP Y1/X1 CD 250VAC 220pF K B TP VI10

1.6 Testing Location

Testing Location			
☐	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973	
☒	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085	

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086D with Industry Canada.

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time |E|²,|H|² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time |E|²,|H|² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 31 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

E (V/m) = $\frac{\sqrt{30 \times P \times G}}{d}$ Power Density: *Pd* (W/m²) = $\frac{E^2}{377}$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

Pd = $\frac{30 \times P \times G}{377 \times d^2}$

2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm^2)	S Limit (mW/cm^2)
2.4G	7.37	28.51	35.88	0.11	35.99	3.97192	31	0.32889	1
5G B1	8.14	27.73	35.87	0.12	35.99	3.97192	31	0.32889	1
5G B4	8.24	27.72	35.96	0.03	35.99	3.97192	31	0.32889	1

Simultaneous Transmission Analysis Mode: WLAN 2.4GHz + WLAN 5GHz band 1 + WLAN 5GHz band 4

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm^2)	S Limit (mW/cm^2)	Ratio (S/Limit)
2.4G	7.37	28.51	35.88	0.11	35.99	3.97192	31	0.32889	1	0.32889
5G B1	8.14	27.73	35.87	0.12	35.99	3.97192	31	0.32889	1	0.32889
5G B4	8.24	27.72	35.96	0.03	35.99	3.97192	31	0.32889	1	0.32889
									Sum Ratio	0.98667
									Ratio Limit	1

Note: The above antenna gain was declared by manufacturer.

———THE END———