



Antenna Composite Gain Test Report

FCC ID	MSQ-RTAX6P00
Equipment	ZenWiFi Hybrid MoCA Mesh Router
Brand Name	ASUS
Model Name	XC5
Applicant	ASUSTeK COMPUTER INC. 1F., No. 15, Lide Rd., Beitou, Taipei 112, Taiwan
Sample Received	Apr. 24, 2023
Start Test Date	May 11, 2023
Final Test Date	May 11, 2023

Approved by: **Sam Chen**

Sporton International Inc. Hsinchu Laboratory

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
1. Operation Mode and Antenna Information	4
2. Test Frequency	4
3. Testing Location.....	4
4. Test Facility and Configuration.....	5
5. Reference Calibration	6
6. Test Method	7
7. Measured Values and Calculation of Maximum Gain Positions.....	8
8. Summary of Test Result	9
9. Test Setup	10
10. Test Equipment and Calibration Data	11
11. Test Results	12



History of this test report

Report No.	Version	Description	Issued Date
AP143018-04	01	Initial issue of report	Jun. 28, 2023



1. Operation Mode and Antenna Information

Antenna Position	RF Port	Brand Name	Model Name	Ant. Type	Connector	Modes of Operation
Ant1	1	Airgain	N03ASAFc-PK1-LB1X85BUI	PCB	I-PEX	2.4GHz, 5GHz UNII 1~3
Ant2	2	Airgain	N03ASAFc- PK1-LG1X120BUI	PCB	I-PEX	2.4GHz, 5GHz UNII 1~3

Note:

2.4GHz and 5GHz Operation Mode (2TX/2RX)

2G 5G Ant1~2 can be used as transmitting/receiving antenna.

2G 5G Ant1~2 could transmit/receive simultaneously.

2. Test Frequency

The listed frequency of each bands are selected to represent each frequency bands

Band [MHz]	Test Frequency [MHz]
2400-2483.5	2450
5150-5250	5200
5250-5350	5300
5470-5725	5600
5725-5850	5785

3. Testing Location

Testing Location		
Sporton International Inc. Hsinhua Laboratory		
<input checked="" type="checkbox"/>	HWA YA	ADD : No.13-1 & 14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333, Taiwan R.O.C.

Test Condition	Test Site No.	Test Engineer	Test Environment (°C / %)	Test Date
Radiated	05CH03-HY	Rex Liao	23.5-24.5 / 50-55	May 11, 2023

Note:

Testing Site Information

Brand Name: TDK

Dimension: 11m*6m*6m

Characteristic: Fully Anechoic Chamber

4. Test Facility and Configuration


Test configuration: Reference to CITA OTA distributed-axes system configuration.

Chamber: Fully Anechoic Chamber.

Measurement antenna: Dual Polarization Horn antenna

Turntable: Multi-axis positioner (Theta and Phi angle).


#Reference to CTIA “ctia-test-plan-for-wireless-device-over-the-air-performance-ver-3-7-1”



5. Reference Calibration

Connected cables to VNA calibration kit and use network analyzer internal function to do calibration. Do short, open and load to each side. Then connect through to both side and calibrate G values. The cable loss is calibrated and set inside the network analyzer.

Measurement Antenna is connected to port1 of Network analyzer and reference antenna connected to port 2 of Network Analyzer. Record G values and used with reference antenna gain to calculate gain factor.



Frequency (MHz)	2400	2450	2500	5150	5200	5300	5600	5750	5800	5900	6000	6500	7000	7200
G(theta) reading (dB)	-33.55	-33.27	-32.92	-32.91	-32.73	-32.02	-32.67	-32.82	-32.98	-33.18	-32.8	-33.92	-34.62	-35.57
G(phi) reading (dB)	-33.15	-32.7	-32.41	-32.61	-32.43	-31.72	-32.37	-32.51	-32.52	-32.66	-32.5	-33.62	-34.32	-35.48
Reference gain (dBi)	10.1	10.4	10.7	12.5	12.7	13.5	13.4	13.3	13.3	13.2	13.4	12.5	12.1	11.4
Factor(theta) (dB)	43.65	43.67	43.62	45.41	45.43	45.52	46.07	46.12	46.28	46.38	46.2	46.42	46.72	46.97
Factor(phi) (dB)	43.25	43.1	43.11	45.11	45.13	45.22	45.77	45.81	45.82	45.86	45.9	46.12	46.42	46.88

Note:

$$G \text{ reading (dB)} = 20 \cdot \log(V2/V1) = 10 \cdot \log(P2/P1)$$

V2 is the voltage of VNA port2 is measured, V1 is the voltage of VNA port1 is the reference source.

P2 is the power of VNA port2 is measured, P1 is the power of VNA port1 is the reference source.

$$\text{Factor} = \text{gain factor} + \text{power gain conversion} = (\text{Reference antenna gain}) - (G \text{ reading})$$



6. Test Method

EUT set on multi-axis positioner and adjust EUT's physical center to measurement reference center. Measurement antenna set at phi polarization and 1.5 meter height. Port 1 of Network analyzer connect to antenna 1 of EUT. Record G value every 7.5 degree from 0 to 352.5 degree on Phi angle and 0 to 180 on theta angle of multi-axis positioner. Then set measurement antenna to theta polarization and repeat process. Repeat process to each antenna of EUT.

DG steps:

1. Each Phi and Theta polarization antenna gain are measured for all test angles.
2. Composite Phi and Theta antenna gain are computed, using formula in KDB662911 D01 d) (i) and e) (ii), for all angles.
3. Composite antenna gain are examined for all angles to determine max gain and Phi/Theta position. Max gain and phi/theta position are listed in section 7 tables.

Note: Antenna gain = G reading + factor, The factor of chapter five includes reference antenna gain factor and power gain conversion.

7. Measured Values and Calculation of Maximum Gain Positions

DG_1SS max value position

Frequency (Hz)	2.45G	5.2G	5.3G	5.6G	5.785G
Ant. 1 (dBi)	-0.41	1.21	1.54	0.06	-0.69
Ant. 2 (dBi)	3.33	1.93	0	2.04	2.56
DG [1SS] (dBi)	4.67	4.59	3.81	4.12	4.1
Polarization	Theta	Theta	Theta	Theta	Theta
$\Theta(^{\circ})$	97.5	82.5	82.5	82.5	82.5
$\Phi(^{\circ})$	172.5	255	307.5	285	292.5

Note: The DG 1SS max value position is the maximum value of section 11 table DG 1SS Result.

DG_1SS max value position calculation

Frequency (Hz)	2.45G	5.2G	5.3G	5.6G	5.785G
Ant. 1 [$10^{(G/20)}$]	$10^{(-0.41/20)}$	$10^{(1.21/20)}$	$10^{(1.54/20)}$	$10^{(0.06/20)}$	$10^{(-0.69/20)}$
Ant. 2 [$10^{(G/20)}$]	$10^{(3.33/20)}$	$10^{(1.93/20)}$	$10^{(0/20)}$	$10^{(2.04/20)}$	$10^{(2.56/20)}$
Ant. 1 [$10^{(G/20)}$] value	0.954	1.149	1.194	1.007	0.924
Ant. 2 [$10^{(G/20)}$] value	1.467	1.249	1	1.265	1.343
Sum All Antenna [Amax]	2.421	2.398	2.194	2.272	2.266
DG [$10 \cdot \log(A_{max}^2/N_{ant})$]	4.67	4.59	3.81	4.12	4.1

Note:

Directional Gain (1SS) is the max value of every look angle. Each position value is calculated by KDB662911 D01 d) (i).

Directional gain (1SS) = $10 \cdot \log(10^{(G_{ant1}/20)} + 10^{(G_{ant2}/20)} + 10^{(G_{ant3}/20)} + 10^{(G_{ant4}/20)} + \dots)^2 / N_{ant}$


8. Summary of Test Result

Freq(Hz)	2.45G	5.2G	5.3G	5.6G	5.785G
Ant. 1 Max Gain (dBi)	2.01	2.51	2.39	2.78	3.09
Ant. 2 Max Gain (dBi)	3.33	2.12	2.96	2.58	3.35
Ant. 1 Polarization/ $\Theta(^{\circ})/\Phi(^{\circ})$	Theta/82.5/105	Theta/52.5/150	Theta/75/105	Theta/45/150	Theta/75/120
Ant. 2 Polarization/ $\Theta(^{\circ})/\Phi(^{\circ})$	Theta/97.5/172.5	Theta/45/315	Theta/45/315	Theta/45/307.5	Theta/45/315
Max Gain (dBi)	3.33	2.51	2.96	2.78	3.35
DG [1SS] (dBi)	4.67	4.59	3.81	4.12	4.10
DG [2SS] (dBi)	3.33	2.51	2.96	2.78	3.35

Note:

1. Directional Gain (2SS) = Directional Gain (1SS) – 3dB. If directional gain is less than max gain, use max gain as directional gain.
2. Each antenna max gain is the max value of measurement G of theta and phi through all measurement angles.
3. The max gain is the max value of all antennas.

9. Test Setup



Note:

Photos of Test Position: Please refer to the test photos in the appendix.



10. Test Equipment and Calibration Data

Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date
Horn Antenna	SCHWARZBECK	BBHA9120D	BBHA 9120D-1543	1GHz~18GHz	May 31, 2022	May 30, 2023
Dual Polarization Horn Antenna	Sporton	S0209DP	S0209DP-001	2GHz~9GHz	N.C.R.	N.C.R.
ENA Series Network Analyzer	AGILENT	E5071C	MY46419477	100kHz~8.5GHz	Jul. 20, 2022	Jul. 19, 2023
VNA Calibration Kit	TS RF	TS85033E-F	-	DC~9GHz	N.C.R.	N.C.R.
Multi-axis positioner	Sporton	MAPS01	MAPS01-001	Theta / Phi axis	N.C.R.	N.C.R.
Test Software	SPORTON	SENSE-RDG	V1.0.8	-	N.C.R.	N.C.R.

Note: Calibration Interval of instruments listed above is one year.

NCR means Non-Calibration required.



11. Test Results

Please refer to the appendix.

Appendix A – Radiated Composite Gain.....	Page 13
Appendix B – Antenna Pattern.....	Page 22
Appendix C – Test Photos.....	Page 26



Freq(Hz)	2.45G	5.2G	5.3G	5.6G	5.785G
Ant. 1 Max Gain (dBi)	2.01	2.51	2.39	2.78	3.09
Ant. 2 Max Gain (dBi)	3.33	2.12	2.96	2.58	3.35
Ant. 1 Polarization/ Θ (°)/ Φ (°)	Theta/82.5/105	Theta/52.5/150	Theta/75/105	Theta/45/150	Theta/75/120
Ant. 2 Polarization/ Θ (°)/ Φ (°)	Theta/97.5/172.5	Theta/45/315	Theta/45/315	Theta/45/307.5	Theta/45/315
Max Gain (dBi)	3.33	2.51	2.96	2.78	3.35
DG [1SS] (dBi)	4.67	4.59	3.81	4.12	4.1
DG [2SS] (dBi)	3.33	2.51	2.96	2.78	3.35



Radiated Composite Gain Data

Appendix A

DG 1SS Result

Table with columns for Frequency (MHz), Gain (dB), and various polarization/tilt settings. It contains multiple rows of numerical data for different frequencies and orientations.



Radiated Composite Gain Data

Appendix A

Table with columns for Frequency (MHz), Power (dBm), and Gain (dB) for various polarization and frequency combinations. It contains a large matrix of numerical data.



Radiated Composite Gain Data

Appendix A

Table with 24 columns (Theta 0 to Theta 172.5) and 100 rows (Theta 0 to Theta 172.5). Each cell contains numerical gain data for various frequencies and polarizations.

E1(XY plane) – $\Theta(90)\Phi(0-360)$
 E2(XZ plane) – $\Theta(0-180)\Phi(0)$ and $\Theta(0-180)\Phi(180)$
 E3(YZ plane) – $\Theta(0-180)\Phi(90)$ and $\Theta(0-180)\Phi(270)$

