



RADIO EXPOSURE TEST REPORT

FCC ID : MSQ-RTBE6J00
Equipment : ROG Rapture GT-BE19000 WiFi 7 Tri-band Gaming Router
Brand Name : ASUS
Model Name : GT-BE19000
Applicant : ASUSTeK COMPUTER INC.
1F., No. 15, Lide Rd., Beitou, Taipei City 112, Taiwan
Standard : 47 CFR Part 2.1091

The product was received on Mar. 04, 2024, and testing was started from Mar. 05, 2024 and completed on May 15, 2024. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Sam Chen

Sporton International Inc. Hsinchu Laboratory

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....3

Summary of Test Result.....4

1 General Description5

1.1 EUT General Information5

1.2 Antenna Information6

1.3 Table for Multiple Listing7

1.4 Table for EUT Supports Functions7

1.5 Table for Radio Function8

1.6 Accessories8

1.7 Applicable Standards8

1.8 Testing Location8

2 Maximum Permissible Exposure9

2.1 Limit of Maximum Permissible Exposure9

2.2 MPE Calculation Method9

2.3 MPE Exemption10

2.4 Calculated Result and Limit11

Photographs of EUT v01



History of this test report

Report No.	Version	Description	Issued Date
FA422102	01	Initial issue of report	May 17, 2024
FA422102	02	Modify the MPE distance.	Jun. 28, 2024
FA422102	03	Update the typo for WWAN Band on page 12.	Aug. 16, 2024



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the chapter "Measurement Uncertainty".

Disclaimer:

1. The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.
2. The test configuration, test mode and test software were written in this test report are declared by the manufacturer.

Reviewed by: Sam Chen

Report Producer: Vicky Huang



1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5250 5260-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
6GHz WLAN (LPI Access Point)	5925-7125	5955-7095	802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
6GHz WLAN (Standard Power Access Point)	5925-6425 6525-6875	5955-6415 6535-6855	802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) 802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)



1.2 Antenna Information

For EUT 1:

Ant.	Port			Brand	Model Name	Antenna Type	Connector	Gain (dBi)
	WLAN 6GHz	WLAN 2.4GHz	WLAN 5GHz					
1	1	-	-	WHA Yu	C660-510587-A	Dipole Antenna	I-PEX	Note 1
2	2	-	-	WHA Yu	C660-510588-A	Dipole Antenna	I-PEX	
3	3	-	-	WHA Yu	C660-510589-A	Dipole Antenna	I-PEX	
4	4	-	-	WHA Yu	C660-510590-A	Dipole Antenna	I-PEX	
5	-	1	1	WHA Yu	C660-510591-A	Dipole Antenna	I-PEX	
6	-	4	4	WHA Yu	C660-510592-A	Dipole Antenna	I-PEX	
7	-	3	3	WHA Yu	C660-510593-A	Dipole Antenna	I-PEX	
8	-	2	2	WHA Yu	C660-510594-A	Dipole Antenna	I-PEX	

For EUT 2:

Ant.	Port			Brand	Model Name	Antenna Type	Connector	Gain (dBi)
	WLAN 6GHz	WLAN 2.4GHz	WLAN 5GHz					
1	1	-	-	WHA Yu	C660-510587-AW1	Dipole Antenna	I-PEX	Note 1
2	2	-	-	WHA Yu	C660-510588-AW1	Dipole Antenna	I-PEX	
3	3	-	-	WHA Yu	C660-510589-AW1	Dipole Antenna	I-PEX	
4	4	-	-	WHA Yu	C660-510590-AW1	Dipole Antenna	I-PEX	
5	-	1	1	WHA Yu	C660-510591-AW1	Dipole Antenna	I-PEX	
6	-	4	4	WHA Yu	C660-510592-AW1	Dipole Antenna	I-PEX	
7	-	3	3	WHA Yu	C660-510593-AW1	Dipole Antenna	I-PEX	
8	-	2	2	WHA Yu	C660-510594-AW1	Dipole Antenna	I-PEX	

Note 1

Ant.	Antenna Gain (dBi)								
	WLAN 2.4GHz	WLAN 5GHz UNII 1	WLAN 5GHz UNII 2A	WLAN 5GHz UNII 2C	WLAN 5GHz UNII 3	WLAN 6GHz UNII 5	WLAN 6GHz UNII 6	WLAN 6GHz UNII 7	WLAN 6GHz UNII 8
1	-	-	-	-	-	1.75	1.52	2.13	2.17
2	-	-	-	-	-	1.95	2.41	2.19	1.64
3	-	-	-	-	-	1.61	1.96	1.51	1.93
4	-	-	-	-	-	1.98	1.44	1.47	2.21
5	2.09	1.52	1.17	1.98	1.08	-	-	-	-
6	1.84	2.29	2.9	3.09	2.51	-	-	-	-
7	2.91	2.7	3.04	2.48	3.39	-	-	-	-
8	2.14	1.21	1.19	3.23	1.87	-	-	-	-



Item	Directional gain (dBi)								
	WLAN 2.4GHz	WLAN 5GHz UNII 1	WLAN 5GHz UNII 2A	WLAN 5GHz UNII 2C	WLAN 5GHz UNII 3	WLAN 6GHz UNII 5	WLAN 6GHz UNII 6	WLAN 6GHz UNII 7	WLAN 6GHz UNII 8
4T1S	5.99	4.72	5.97	5.72	5.64	5.99	5.46	5.38	5.5
4T2S	2.99	2.7	3.04	3.23	3.39	2.99	2.46	2.38	2.5

Note 2: The above information(excepting antenna gain and directional gain) was declared by manufacturer.
 Note 3: The antenna gain and directional gain are measured which follow the procedure of KDB 662911 D03.
 Note 4: **For 2.4GHz function:**

- For IEEE 802.11 b/g/n/VHT/ax/be (4TX/4RX):**
 Port 1, Port 2, Port 3 and Port 4 can be used as transmitting/receiving antenna.
 Port 1, Port 2, Port 3 and Port 4 could transmit/receive simultaneously.
- For 5GHz function:**
For IEEE 802.11a/n/ac/ax/be (4TX/4RX):
 Port 1, Port 2, Port 3 and Port 4 can be used as transmitting/receiving antenna.
 Port 1, Port 2, Port 3 and Port 4 could transmit/receive simultaneously.
- For 6GHz function:**
For IEEE 802.11ax/be mode (4TX/4RX):
 Port 1, Port 2, Port 3 and Port 4 can be used as transmitting/receiving antenna.
 Port 1, Port 2, Port 3 and Port 4 could transmit/receive simultaneously.

1.3 Table for Multiple Listing

The difference for each EUT is shown as below:

EUT	Enclosure/Antenna Color	Heatsink Color on the Back of the EUT
1	Black	Red
2	White	Black

Note 1: The difference between EUT 1 and EUT 2 is only color, there is only EUT 1 tested and recorded in this report.
 Note 2: The above information was declared by manufacturer.

1.4 Table for EUT Supports Functions

Function	Support Type
AP Router	Master
Bridge	Slave without radar detection
Extender	Master
Mesh	Master

Note: The above information was declared by manufacturer.



1.5 Table for Radio Function

Radio 1	Radio 2	Radio 3
WLAN 2.4GHz	WLAN 5GHz UNII 1~3	WLAN 6GHz UNII 5~8

Note: The above information was declared by manufacturer.

1.6 Accessories

Power	Brand	Model	Rating	Remark
Adapter 1	AcBel	ADD011	INPUT: 100-240V~ 1.7A, 50-60Hz OUTPUT: +19.5V, 3.33A, 65.0W MAX.	With the DC cable: Non-shielded, 1.5m
Adapter 2	AcBel	ADD011	INPUT: 100-240V~ 1.7A, 50-60Hz OUTPUT: +19.5V, 3.33A, 65.0W MAX.	With the DC cable: Non-shielded, 1.5m
Adapter 3	LEI	MU60B3120500-A1	INPUT: 100-240V~50/60Hz, 1.5A OUTPUT: 12.0V, 5.0A	-
Others				
RJ-45 cable*1: Shielded, 1.5m				
Power cord*1: Non-shielded, 0.9m for Adapter 1 and Adapter 2 use				

Note1: Adapter 1 & Adapter 2 is identical.

Note2: Refer to photographs of EUT for the detail information of difference between Adapter 1 & Adapter 2.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1091
 - ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01
- The following reference test guidance is not within the scope of accreditation of TAF.
- ♦ 47 CFR Part 1.1307
 - ♦ 47 CFR Part 1.1310

1.8 Testing Location

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)
(TAF: 3787)	TEL: 886-3-656-9065 FAX: 886-3-656-9085
	Test site Designation No. TW3787 with FCC.
	Conformity Assessment Body Identifier (CABID) TW3787 with ISED.



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500	-	-	f/300	<6
1500-100,000	-	-	5	<6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500	-	-	f/1500	<30
1500-100,000	-	-	1.0	<30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 61 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 MPE Exemption

Option (A): 1.1307(b)(3)(i)(A): Available maximum time-averaged power is < 1 mW

Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <= Pth.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option (C): 1.1307(b)(3)(i)(C): ERP is below a threshold calculated based on the distance R between the person and the antenna / radiating structure, where $R > \lambda / 2 \pi$.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R ² .
1.34-30	3,450 R ² /f ² .
30-300	3.83 R ² .
300-1,500	0.0128 R ² f.
1,500-100,000	19.2R ² .

Note: R is in meters, f is in MHz.



2.4 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode 1: EUT 1-WLAN 2.4GHz + WLAN 5GHz + WLAN 6GHz

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	5.99	28.34	32.18	0.50	1853.532	61	C	7144.4	0.2595
5.2G;D1D	4.72	29.98	32.55	0.50	2018.366	61	C	7144.4	0.2921
5.3G;D1D	5.97	23.95	27.77	0.07	608.135	61	C	7144.4	0.0880
5.6G;D1D	5.72	23.93	27.50	0.34	608.135	61	C	7144.4	0.0880
5.8G;D1D	5.64	29.97	33.46	0.38	2421.029	61	C	7144.4	0.3504
6.2G;D1D	5.99	29.98	33.82	0.02	2421.029	61	C	7144.4	0.3390
6.4G;D1D	8.45	-	24.70	0.50	331.131	61	C	7144.32	0.0463
6.7G;D1D	5.38	30.6	33.83	0.01	2421.029	61	C	7144.4	0.3390
7.0G;D1D	5.44	-	23.22	0.50	235.505	61	C	7144.32	0.0330

Simultaneous Transmission Analysis

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	5.99	28.34	32.18	0.50	1853.532	61	C	7144.4	0.2595
5.8G;D1D	5.64	29.97	33.46	0.38	2421.029	61	C	7144.4	0.3390
6.7G;D1D	5.38	30.6	33.83	0.01	2421.029	61	C	7144.4	0.3390
Sum TL Ratio_C	0.9375								
Ratio Limit	1								



Mode 2: EUT 1-WLAN 2.4GHz + WLAN 5GHz + WLAN 6GHz + WWAN

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	5.99	28.34	32.18	0.50	1853.532	61	C	7144.4	0.2595
5.2G;D1D	4.72	29.98	32.55	0.50	2018.366	61	C	7144.4	0.2921
5.3G;D1D	5.97	23.95	27.77	0.07	608.135	61	C	7144.4	0.0880
5.6G;D1D	5.72	23.93	27.50	0.34	608.135	61	C	7144.4	0.0880
5.8G;D1D	5.64	29.97	33.46	0.38	2421.029	61	C	7144.4	0.3504
6.2G;D1D	5.99	29.98	33.82	0.02	2421.029	61	C	7144.4	0.3390
6.4G;D1D	8.45	-	24.70	0.50	331.131	61	C	7144.32	0.0463
6.7G;D1D	5.38	30.6	33.83	0.01	2421.029	61	C	7144.4	0.3390
7.0G;D1D	5.44	-	23.22	0.50	235.505	61	C	7144.32	0.0330
Band12;G7D	0.00	24.00	21.85	0.50	171.791	61	C	3880.4	0.0443

Simultaneous Transmission Analysis

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	5.99	28.34	32.18	0.50	1853.532	61	C	7144.4	0.2595
5.8G;D1D	5.64	29.97	33.46	0.38	2421.029	61	C	7144.4	0.3390
6.7G;D1D	5.38	30.6	33.83	0.01	2421.029	61	C	7144.4	0.3390
Band12;G7D	0.00	24.00	21.85	0.50	171.791	61	C	3880.4	0.0443
Sum TL Ratio_C	0.9818								
Ratio Limit	1								

————THE END————