

## RF Exposure Evaluation declaration

Product Name : High Power Wireless N Router  
Model No. : RT-N12HP  
FCC ID. : MSQ-RTN12HP

Applicant : ASUSTeK COMPUTER INC.

Address : 4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

Date of Receipt : 2012/10/25  
Date of Declaration : 2012/11/05  
Report No. : 12A425R-RF-US-Exp  
Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product	High Power Wireless N Router
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 7dBi or 5.01 in linear scale.

#### Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	162.93	0.047
6	2437	148.94	0.043
11	2462	132.13	0.038

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	118.58	0.034
6	2437	260.62	0.075
11	2462	102.10	0.029

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	High Power Wireless N Router
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 7dBi or 5.01 in linear scale.

### Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (20MHz) ANT 0+1			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	149.97	0.043
6	2437	205.02	0.059
11	2462	116.47	0.034

IEEE 802.11n (40MHz) ANT 0+1			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
3	2422	47.973	0.013
6	2437	90.991	0.026
9	2452	33.497	0.010

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.