

RF Exposure Evaluation Declaration

Product Name : ASUS SRT-AC1900 Wireless Smart Router
Model No. : SRT-AC1900
FCC ID. : MSQ-SRTAC1900

Applicant : ASUSTeK COMPUTER INC.

Address : 4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

Date of Receipt : 2015/05/04

Date of Declaration : 2015/05/20

Report No. : 1550110R-RF-US-Exp-A

Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (Minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational/ Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100,000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/ Uncontrolled Exposures | | | | |
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100,000 | -- | -- | 1 | 30 |

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

| | |
|----------------|---------------------------------------|
| Product | ASUS SRT-AC1900 Wireless Smart Router |
| Test Mode | Transmit |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.61dBi or 2.3 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| GFSK | | | |
|--------------------|-------------------------|------------------------------|--|
| Bluetooth Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 00 | 2402 | 11.6413 | 0.00533 |
| 39 | 2441 | 14.8252 | 0.00678 |
| 78 | 2480 | 16.3456 | 0.00748 |

| $\pi/4$ DQPSK | | | |
|--------------------|-------------------------|------------------------------|--|
| Bluetooth Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 00 | 2402 | 10.5536 | 0.00483 |
| 39 | 2441 | 13.2923 | 0.00608 |
| 78 | 2480 | 14.5479 | 0.00666 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|---------------------------------------|
| Product | ASUS SRT-AC1900 Wireless Smart Router |
| Test Mode | Transmit |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.61dBi or 2.3 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| 8DQPSK | | | |
|--------------------|-------------------------|------------------------------|--|
| Bluetooth Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 00 | 2402 | 6.6865 | 0.00306 |
| 39 | 2441 | 8.7237 | 0.00399 |
| 78 | 2480 | 9.5345 | 0.00436 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².