


RF Exposure Evaluation Report

APPLICANT : ASUSTeK COMPUTER INC.
EQUIPMENT : ASUS Mobile Dock
BRAND NAME : ASUS
MODEL NAME : T90 Chi Mobile Dock
FCC ID : MSQ-T90CHIDOCK
STANDARD : 47 CFR Part 2.1093
FCC KDB 447498 D01 v05r02

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1093, and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



Table of Contents

1. Administration Data 3

2. General Information 3

2.1 Description of Device Under Test (DUT) 3

3. Maximum RF output power among production units 4

4. RF Exposure Evaluation 4

Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA4N2528	Rev. 01	Initial issue of report	Dec. 31, 2014



1. Administration Data

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	ASUSTeK COMPUTER INC.
Address	4F, No. 150, LI-TE RD., PEITOU, TAIPEI, TAIWAN

Manufacturer	
Company Name	ASUSTeK COMPUTER INC.
Address	4F, No. 150, LI-TE RD., PEITOU, TAIPEI, TAIWAN

2. General Information

2.1 Description of Device Under Test (DUT)

Product Feature & Specification	
DUT Type	ASUS Mobile Dock
Brand Name	ASUS
Model Name	T90 Chi Mobile Dock
FCC ID	MSQ-T90CHIDOCK
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz
Mode	• Bluetooth v3.0+EDR
Antenna Type	PIFA Antenna
DUT Stage	Identical Prototype
Remark:	
1. The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.	

3. Maximum RF output power among production units

Band / Mode	Average Power (dBm)
	v3.0+EDR
Bluetooth	2.0

4. RF Exposure Evaluation

Bluetooth Max Power (dBm)	mW	Separation Distance (mm)	Frequency (GHz)	Exclusion Thresholds
2.0	2.00	< 5	2.48	0.63

Note:

1. Per KDB 447498 D01v05r02, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(max. \text{ power of channel, including tune-up tolerance, mW}) / (min. \text{ test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Conclusion: Per KDB 447498 D01v05r02, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.63 which is ≤ 3, SAR testing is not required.