

Test Report

Industry Canada RSS-Gen Issue 2/RSS-210 Issue 7
FCC Part15 Subpart C

Product Name : Eee PC
Model No. : Eee PC 1015PN
FCC ID : MSQ15PNNE047
IC : 3568A-15PNNE047

Applicant : ASUSTEK COMPUTER INC.

Address : NO.150, Li-Te Rd., Peitou, Taipei, Taiwan, R. O. C

Date of Receipt : Jul. 22, 2010
Test Date : Jul. 23, 2010 ~ Aug. 03, 2010
Issued Date : Aug. 04, 2010
Report No. : 107S051R-RF-US-P06V01
Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, NVLAP or any agency of the Government.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

Test Report Certification

Issued Date : Aug. 04, 2010

Report No. : 107S051R-RF-US-P06V01



Product Name : Eee PC

Applicant : ASUSTEK COMPUTER INC.

Address : NO.150, Li-Te Rd., Peitou, Taipei, Taiwan, R. O. C

Manufacturer : PROTEK (Shanghai) Limited

Address : NO.3768 Xiu Yan Rd.Kang Qiao Town, PuDong Dist, Shang
Hai

Model No. : Eee PC 1015PN

FCC ID : MSQ15PNNE047

IC : 3568A-15 PNNE047

EUT Voltage : 19Vdc

Trade Name : ASUS

Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2008
ANSI C63.4: 2009
RSS-Gen Issue 2/RSS-210 Issue 7

Test Result : Complied

Performed Location : SuZhou EMC laboratory
No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech
Development Zone., SuZhou, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Registration Number: 800392, IC Lab Code: 4075B

Documented By : Alice Ni
(Engineering ADM: Alice Ni)

Reviewed By : Marlin Chen
(Engineering Supervisor: Marlin Chen)

Approved By : Dream Cao
(Engineering Manager: Dream Cao)

Laboratory Information

We, **Quietek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

Taiwan R.O.C.	: BSMI, NCC, TAF
Germany	: TUV Rheinland
Norway	: Nemko, DNV
USA	: FCC, NVLAP
Japan	: VCCI

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site : <http://www.quietek.com/tw/emc/accreditations/accreditations.htm>
 The address and introduction of Quietek Corporation's laboratories can be founded in our Web site : <http://www.quietek.com/>
 If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

HsinChu Testing Laboratory :

No.75-2, 3rd Lin, Wangye Keng, Yonghxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.
 TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : service@quietek.com



LinKou Testing Laboratory :

No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen, Lin-Kou Shiang, Taipei, Taiwan, R.O.C.
 TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : service@quietek.com



Suzhou (China) Testing Laboratory :

No. 99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., Suzhou,China.
 TEL : +86-512-6251-5088 / FAX : +86-512-6251-5098 E-Mail : service@quietek.com



TABLE OF CONTENTS

Description	Page
1. General Information.....	7
1.1. EUT Description	7
1.2. Mode of Operation	9
1.3. Tested System Details.....	10
1.4. Configuration of Tested System	11
1.5. EUT Exercise Software	12
2. Technical Test.....	13
2.1. Summary of Test Result	13
2.2. Test Environment	14
3. Conducted Emission	15
3.1. Test Equipment	15
3.2. Test Setup	15
3.3. Limit.....	16
3.4. Test Procedure	16
3.5. Uncertainty	16
3.6. Test Result	17
4. Radiated Emission	19
4.1. Test Equipment	19
4.2. Test Setup	19
4.3. Limit.....	21
4.4. Test Procedure	21
4.5. Uncertainty	21
4.6. Test Result	22
5. 20dB Bandwidth	24
5.1. Test Equipment	24
5.2. Test Setup	24
5.3. Limit.....	24
5.4. Test Procedure	25
5.5. Uncertainty	25
5.6. Test Result	26
6. Carrier Frequency Separation	30
6.1. Test Equipment	30
6.2. Test Setup	30
6.3. Limit.....	30
6.4. Test Procedure	31
6.5. Uncertainty	31
6.6. Test Result	32

7.	Number of Hopping Frequencies	36
7.1.	Test Equipment	36
7.2.	Test Setup	36
7.3.	Limit.....	36
7.4.	Test Procedure	37
7.5.	Uncertainty	37
7.6.	Test Result	38
8.	Time of Occupancy (Dwell Time).....	44
8.1.	Test Equipment	44
8.2.	Test Setup	44
8.3.	Limit.....	44
8.4.	Test Procedure	45
8.5.	Uncertainty	45
8.6.	Test Result	46
9.	Peak Output Power	52
9.1.	Test Equipment	52
9.2.	Test Setup	52
9.3.	Limit.....	52
9.4.	Test Procedure	53
9.5.	Uncertainty	53
9.6.	Test Result	54
10.	Band-edge Compliance of RF Conducted Emissions	55
10.1.	Test Equipment	55
10.2.	Test Setup	55
10.3.	Limit.....	55
10.4.	Test Procedure	56
10.5.	Uncertainty	56
10.6.	Test Result	57
11.	Spurious RF Conducted Emissions.....	60
11.1.	Test Equipment	60
11.2.	Test Setup	60
11.3.	Limit.....	60
11.4.	Test Procedure	61
11.5.	Uncertainty	61
11.6.	Test Result	62
12.	Radiated Emission Band Edge.....	66
12.1.	Test Equipment	66
12.2.	Test Setup	66

12.3. Limit.....	66
12.4. Test Procedure	66
12.5. Uncertainty	67
12.6. Test Result	68
13. Receiver Spurious Emission for RSS-GEN	84
13.1. Test Specification	84
13.2. Test Setup	84
13.3. Limit.....	85
13.4. Test Procedure	85
13.5. Deviation from Test Standard	86
13.6. Test Result	87

1. General Information**1.1. EUT Description**

Product Name	Eee PC
Trade Name	ASUS
Model No.	Eee PC 1015PN
Wireless Module	AW-NB047H
Working Voltage	19Vdc
Frequency Range	2402 - 2480 MHz
Channel Number	79
Type of Modulation	FHSS
Data Rate	1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK)
Channel Control	Auto
Antenna Type	PIFA Antenna
Peak Antenna Gain	1.41dBi for 2.4G

Bluetooth Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz	03	2405 MHz
04	2406 MHz	05	2407 MHz	06	2408 MHz	07	2409 MHz
08	2410 MHz	09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz	15	2417 MHz
16	2418 MHz	17	2419 MHz	18	2420 MHz	19	2421 MHz
20	2422 MHz	21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz	27	2429 MHz
28	2430 MHz	29	2431 MHz	30	2432 MHz	31	2433 MHz
32	2434 MHz	33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz	39	2441 MHz
40	2442 MHz	41	2443 MHz	42	2444 MHz	43	2445 MHz
44	2446 MHz	45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz	51	2453 MHz
52	2454 MHz	53	2455 MHz	54	2456 MHz	55	2457 MHz
56	2458 MHz	57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz	63	2465 MHz
64	2466 MHz	65	2467 MHz	66	2468 MHz	67	2469 MHz
68	2470 MHz	69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz	75	2477 MHz
76	2478 MHz	77	2479 MHz	78	2480 MHz	N/A	N/A

1.2. Mode of Operation

Quietek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmit (DH5)
Mode 2: Transmit (3DH5)
Mode 3: Receive (DH5)
Mode 4: Receive (3DH5)

Note:


1. DH5 is for GFSK modulation, and 3DH5 is for 8DPSK.
2. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.

1.3. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 LCD Monitor	Lenovo	L2240pwD	9M0337992301042	Non-Shielded, 1.8m
2 Microphone & Earphone	SOMIC	CD-2688M.V	N/A	N/A
3 iPod	Apple	A1199	6U715UPHVQ5	Power by PC
4 iPod	Apple	A1199	6U715UPHVQ5	Power by PC
5 USB Mouse	DELL	MO56UOA	F1B03EZZ	Power by PC

1.4. Configuration of Tested System



1.5. EUT Exercise Software

1	Setup the EUT and simulators as shown on above
2	Turn on the power of equipment.
3	Run control software "Broadcom Bluetool Version 1.2.0.8" provided by applicant.
4	Select test channel and test mode for test.

2. Technical Test

2.1. Summary of Test Result

No deviations from the test standards

Deviations from the test standards as below description:

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.207 RSS-Gen Issue 2 June 2007 Section 7.2.2	Yes	No
Radiated Emission	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.209 RSS-210 Issue 7 June 2007 Section 2.7 Table 2 and Table 3	Yes	No
20dB Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1) RSS-210 Issue 7 June 2007 Section A8.1	Yes	No
99% Occupied Bandwidth	RSS-Gen Issue 2 June 2007 Section 4.6.1	Yes	No
Carrier Frequency Separation	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1) RSS-210 Issue 7 June 2007 Section A8.1	Yes	No
Number of Hopping Frequencies	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)(iii) RSS-210 Issue 7 June 2007 Section A8.1	Yes	No
Time of Occupancy (Dwell Time)	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)(iii) RSS-210 Issue 7 June 2007 Section A8.1	Yes	No
Peak Output Power	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(b)(1) RSS-210 Issue 7 June 2007 Section A8.4	Yes	No
Band-edge Compliance of RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.215(c), 15.247(d)	Yes	No
Spurious RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2008 15.247(d) RSS-210 Issue 7 June 2007 Section A8.5	Yes	No
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2008 15.247(d) RSS-210 Issue 7 June 2007 Section A8.5	Yes	No

2.2. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

3. Conducted Emission


3.1. Test Equipment

Conducted Emission / TR-1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
EMI Test Receiver	R&S	ESCI	100726	2010.04.23
Two-Line V-Network	R&S	ENV216	100043	2009.09.07
Two-Line V-Network	R&S	ENV216	100044	2009.09.07
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2010.05.25
50ohm Termination	SHX	TF2	07081401	2009.09.29
Temperature/Humidity Meter	zhicheng	ZC1-2	TR1-TH	2010.01.14

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

3.2. Test Setup



3.3. Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

3.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)

Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.


Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

3.5. Uncertainty

The measurement uncertainty is defined as ± 2.02 dB


3.6. Test Result

Profile: 107S051R	Page No.: 2
Engineer: Jame	
Site: TR1	Time: 2010/07/31 - 12:41
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101043(0.009-30MHz)	Polarity: Line
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1	*	0.191	50.260	40.605	-13.742	64.003	9.655	QP
2		0.191	33.719	24.063	-20.284	54.003	9.655	AV
3		0.238	44.187	34.507	-17.978	62.166	9.680	QP
4		0.238	28.869	19.189	-23.297	52.166	9.680	AV
5		0.314	35.382	25.702	-24.482	59.864	9.680	QP
6		0.314	21.687	12.007	-28.177	49.864	9.680	AV
7		0.358	34.783	25.103	-23.992	58.775	9.680	QP
8		0.358	21.935	12.255	-26.840	48.775	9.680	AV
9		0.654	41.171	31.481	-14.829	56.000	9.690	QP
10		0.654	28.678	18.988	-17.322	46.000	9.690	AV
11		0.842	30.272	20.592	-25.728	56.000	9.681	QP
12		0.842	15.376	5.695	-30.624	46.000	9.681	AV

Profile: 107S051R	Page No.: 1
Engineer: Jame	
Site: TR1	Time: 2010/07/31 - 12:36
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101043(0.009-30MHz)	Polarity: Neutral
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1	*	0.191	51.109	41.454	-12.894	64.003	9.655	QP
2		0.191	34.696	25.041	-19.307	54.003	9.655	AV
3		0.238	45.160	35.480	-17.005	62.166	9.680	QP
4		0.238	29.675	19.995	-22.491	52.166	9.680	AV
5		0.310	36.846	27.166	-23.124	59.970	9.680	QP
6		0.310	25.884	16.204	-24.087	49.970	9.680	AV
7		0.350	34.587	24.907	-24.375	58.962	9.680	QP
8		0.350	20.876	11.196	-28.086	48.962	9.680	AV
9		0.662	41.098	31.408	-14.902	56.000	9.690	QP
10		0.662	28.216	18.526	-17.784	46.000	9.690	AV
11		25.266	28.688	18.286	-31.312	60.000	10.401	QP
12		25.266	23.786	13.385	-26.214	50.000	10.401	AV

4. Radiated Emission

4.1. Test Equipment

Radiated Emission / AC-2


Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
EMI Test Receiver	R&S	ESCI	100573	2010/04/23
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2009/11/12
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2010/05/05
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC2-TH	2010/01/14

Radiated Emission / AC-5


Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2010.04.23
EMI Test Receiver	R&S	ESCI	100573	2010.04.23
Preamplifier	Quietek	AP-025C	CHM-0511006	2010.05.05
Preamplifier	Quietek	AP-180C	CHM-0602013	2010.05.05
Bilog Type Antenna	Schaffner	CBL6112B	2932	2009.11.21
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2010.06.11
High-Pass Filter	Wainwright	WHKX2.8/18G-12SS	SN1	2010.03.03
Band Reject Filter	Wainwright	WRCG2400/2485-2375 /2510-60/11SS	SN9	2010.03.03
High-Pass Filter	Wainwright	WHKX7.0/18G-8SS	SN16	2010.03.03
Low-Pass Filter	Wainwright	WLKS4500-9SS	SN2	2010.03.03
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2010.05.05
Temperature/Humidity Meter	zhicheng	ZC1-2	AC5-TH	2010.01.14

4.2. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



4.3. Limit

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Distance (m)	Level (dBuV/m)
30 - 88	3	40
88 - 216	3	43.5
216 - 960	3	46
Above 960	3	54

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) = 20 log E field strength (uV/m)

4.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2009 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.

Note: When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna has the narrow beamwidth) in order to keeping the antenna in the "cone of radiation" of EUT. The 3dB beamwidth is 60~10 degrees for H-plane and 90~10 degrees for E-plane.

4.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB
 below 1G is defined as ± 3.8 dB

4.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;

Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Measure Level = Reading Level + Cable Loss + Antenna Factor – Preamplifier Gain

DH5

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	2401.7	62.7	30.6	93.3	Fundamental	/	PK
	V	415.0	33.8	-4.5	29.3	46	-16.7	QP
	V	699.0	30.0	-1.0	29.0	46	-17.0	QP
	V	2997.5	60.2	-17.8	42.4	54(note)	-11.6	PK
	H	4804.0	54.9	-14.3	40.6	54(note)	-13.4	PK
	H	7206.0	52.9	-6.2	46.7	54(note)	-7.3	PK
	H	24000.0	59.1	-8.9	50.2	54(note)	-3.8	PK
39	H	2440.9	63.2	30.8	94.0	Fundamental	/	PK
	V	415.0	33.8	-4.5	29.3	46	-16.7	QP
	V	699.0	29.8	-1.0	28.8	46	-17.2	QP
	V	2997.5	60.3	-17.8	42.5	54(note)	-11.5	PK
	H	4882.0	54.5	-14.0	40.5	54(note)	-13.5	PK
	H	7323.0	52.7	-6.0	46.7	54(note)	-7.3	PK
	H	24000.0	59.1	-8.9	50.2	54(note)	-3.8	PK
78	H	2480.0	63.8	30.3	94.1	Fundamental	/	PK
	V	415.0	30.7	-4.5	26.2	46	-19.8	QP
	V	699.0	29.7	-1.0	28.7	46	-17.3	QP
	V	2997.5	59.6	-17.8	41.8	54(note)	-12.2	PK
	H	4960.0	54.4	-13.8	40.6	54(note)	-13.4	PK
	H	7440.0	52.8	-5.3	47.5	54(note)	-6.5	PK
	H	24000.0	59.1	-8.9	50.2	54(note)	-3.8	PK

3DH5

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	2402.0	65.2	30.6	95.8	Fundamental	/	PK
	V	415.0	33.6	-4.5	29.1	46	-16.9	QP
	V	699.0	29.5	-1.0	28.5	46	-17.5	QP
	V	2997.5	60.3	-17.8	42.5	54(note)	-11.5	PK
	H	4804.0	54.3	-14.3	40.0	54(note)	-14.0	PK
	H	7206.0	52.3	-6.2	46.1	54(note)	-7.9	PK
	H	24000.0	59.1	-8.9	50.2	54(note)	-3.8	PK
39	H	2441.0	65.7	30.6	96.3	Fundamental	/	PK
	V	415.0	34.0	-4.5	29.5	46	-16.5	QP
	V	699.0	29.3	-1.0	28.3	46	-17.7	QP
	V	2997.5	59.8	-17.8	42.0	54(note)	-12.0	PK
	H	4882.0	54.0	-14.0	40.0	54(note)	-14.0	PK
	H	7323.0	52.6	-6.0	46.6	54(note)	-7.4	PK
	H	24000.0	59.1	-8.9	50.2	54(note)	-3.8	PK
78	H	2480.0	63.6	30.3	93.9	Fundamental	/	PK
	V	415.0	34.2	-4.5	29.7	46	-16.3	QP
	V	699.0	29.1	-1.0	28.1	46	-17.9	QP
	V	2997.5	59.0	-17.8	41.2	54(note)	-12.8	PK
	H	4960.0	54.3	-13.8	40.5	54(note)	-13.5	PK
	H	7440.0	53.5	-5.3	48.2	54(note)	-5.8	PK
	H	24000.0	59.1	-8.9	50.2	54(note)	-3.8	PK

Note: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

5. 20dB Bandwidth


5.1. Test Equipment

20dB Bandwidth / AC-6

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2010.04.30
Temperature/Humidity Meter	zhicheng	ZC1-2	AC6-TH	2010.01.14

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

5.2. Test Setup



5.3. Limit

- For frequency hopping systems operating in 2400-2483.5 MHz band, no limitation.
- For frequency hopping systems operating in 902-928 MHz band, the maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- For frequency hopping systems operating in 5725-5850 MHz band, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

5.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel

RBW \geq 1% of the 20dB bandwidth

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize.

Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

5.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

5.6. Test Result


Product	:	Eee PC
Test Item	:	Occupied Bandwidth
Test Site	:	AC-6
Test Mode	:	Mode 1: Transmit (DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	919.26	866.99
39	2441	920.35	866.89
78	2480	918.46	867.74


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	Eee PC
Test Item	:	Occupied Bandwidth
Test Site	:	AC-6
Test Mode	:	Mode 2: Transmit (3DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1345	1199.4
39	2441	1343	1199.0
78	2480	1345	1198.6


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



6. Carrier Frequency Separation


6.1. Test Equipment

Carrier Frequency Separation / AC-6

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2010.04.30
Temperature/Humidity Meter	zhicheng	ZC1-2	AC6-TH	2010.01.14

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

6.2. Test Setup



6.3. Limit

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping

channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

6.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) \geq 1% of the span

Video (or Average) Bandwidth VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

6.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

6.6. Test Result


Product	:	Eee PC
Test Item	:	Carrier Frequency Separation
Test Site	:	AC-6
Test Mode	:	Mode 1: Transmit (DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	Eee PC
Test Item	:	Carrier Frequency Separation
Test Site	:	AC-6
Test Mode	:	Mode 2: Transmit (3DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



7. Number of Hopping Frequencies


7.1. Test Equipment

Number of Hopping Frequencies / AC-6

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2010.04.30
Temperature/Humidity Meter	zhicheng	ZC1-2	AC6-TH	2010.01.14

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

7.2. Test Setup



7.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.
- For frequency hopping systems operating in 902-928 MHz band shall use at least 50 hopping frequencies.
- For frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.

7.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW \geq 1% of the span

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to bread the span up to sections, in order to clearly show all of the hopping frequencies.

7.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

7.6. Test Result


Product	:	Eee PC
Test Item	:	Number of Hopping Frequencies
Test Site	:	AC-6
Test Mode	:	Mode 1: Transmit (DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz




2462 - 2480 MHz




Product	:	Eee PC
Test Item	:	Number of Hopping Frequencies
Test Site	:	AC-6
Test Mode	:	Mode 2: Transmit (3DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz



2462 - 2480 MHz



8. Time of Occupancy (Dwell Time)


8.1. Test Equipment

Time of Occupancy (Dwell Time) / AC-6

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2010.04.30
Temperature/Humidity Meter	zhicheng	ZC1-2	AC6-TH	2010.01.14

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

8.2. Test Setup



8.3. Limit

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75

hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

- Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1MHz

VBW \geq RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

8.5. Uncertainty

The measurement uncertainty is defined as ± 0.1 us

8.6. Test Result


Product	:	Eee PC
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	AC-6
Test Mode	:	Transmit (3DH1)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	112.0	< 400	Pass

Test Time Period: $0.4 * 79 = 31.6 \text{sec}$, Hopping Times Within 1sec: $40/50 \text{msec} = 800 \text{hops/sec}$.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(350.0 \mu \text{s} * 800) / 79] * 31.6 = 112.0 \text{msec}$

Channel 39 (2441MHz)-(3DH1)






Product	:	Eee PC
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	AC-6
Test Mode	:	Transmit (3DH3)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	264.0	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6 \text{sec}$, Hopping Times Within 1sec: $20/50 \text{msec} = 400 \text{hops/sec}$.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(1.65 \text{ ms} \times 400) / 79] \times 31.6 = 264.0 \text{msec}$

Channel 39 (2441MHz) - (3DH3)






Product	:	Eee PC
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	AC-6
Test Mode	:	Transmit (3DH5)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	322.5	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6 \text{sec}$, Hopping Times Within 1sec: $14/50 \text{msec} = 280 \text{hops/sec}$.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(2.88 \text{ ms} \times 280) / 79] \times 31.6 = 322.5 \text{msec}$

Channel 39 (2441MHz) - (3DH5)





9. Peak Output Power


9.1. Test Equipment

Peak Output Power / AC-6

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2010.04.30
Temperature/Humidity Meter	zhicheng	ZC1-2	AC6-TH	2010.01.14

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

9.2. Test Setup



9.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
- For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels.

Note: the conducted output power limit specified above is based on the use the antennas with

directional gains that do not exceed 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values above, as appropriate, by the amount in dB that the directional gain of antenna exceeds 6 dBi.

9.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured.

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (don't forget added the external attenuation and cable loss).

9.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB

9.6. Test Result

Product	:	Eee PC
Test Item	:	Power Output
Test Mode	:	Mode 1: Transmit by DH5

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	-0.74	30.00	Pass
39	2441	-0.26	30.00	Pass
78	2480	-0.01	30.00	Pass

Product	:	Eee PC
Test Item	:	Power Output
Test Mode	:	Mode 2: Transmit by 3DH5

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	1.18	30.00	Pass
39	2441	1.66	30.00	Pass
78	2480	1.92	30.00	Pass

10. Band-edge Compliance of RF Conducted Emissions


10.1. Test Equipment

Band-edge Compliance of RF Conducted Emissions / AC-6

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2010.04.30
Temperature/Humidity Meter	zhicheng	ZC1-2	AC6-TH	2010.01.14

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

10.2. Test Setup



10.3. Limit

- Intentional radiators operating under the alternative provisions to the general emission limits as contained in 15.217 through 15.257 and in Subpart E of FCC part 15, must be designed to ensure that 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz

bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) of FCC part 15 is not required.

10.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation.

RBW \geq 1% of the span

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge.

Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.


10.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB


10.6. Test Result

Product	:	Eee PC
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 1: Transmit (DH5)

Channel 00 (2402MHz)




Channel 78 (2480MHz)




Product	:	Eee PC
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 2: Transmit (3DH5)



Channel 00 (2402MHz)



Channel 78 (2480MHz)



Hopping Mode



11. Spurious RF Conducted Emissions


11.1. Test Equipment

Spurious RF Conducted Emissions / AC-6

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2010.04.30
Temperature/Humidity Meter	zhicheng	ZC1-2	AC6-TH	2010.01.14

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

11.2. Test Setup



11.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in

Section 15.209(a) of FCC part 15 is not required.

11.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.


11.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB


11.6. Test Result

Product	:	Eee PC
Test Item	:	Spurious RF Conducted Emissions
Test Site	:	AC-6
Test Mode	:	Mode 1: Transmit (DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	Eee PC
Test Item	:	Spurious RF Conducted Emissions
Test Site	:	AC-6
Test Mode	:	Mode 2: Transmit (3DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)




12. Radiated Emission Band Edge

12.1. Test Equipment

☒ Radiated Emission Band Edge / AC-5

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2010.04.23
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2010.06.11
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC5-TH	2010.01.14

12.2. Test Setup



12.3. Limit

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) of FCC part 15.

12.4. Test Procedure

According to FCC Public Notice DA 00-705, March 30, 2000.

This test is required for any spurious emission or modulation product that falls in a Restricted Band, as defined in Section 15.205 of FCC part 15. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer

settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b) of FCC part 15.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209 of FCC Part 15. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit of FCC part 15.

If the emission on which a radiated measurement must be made is located at the edge of the authorized band of operation, then the alternative "marker-delta" method may be employed.

12.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB

below 1G is defined as ± 3.8 dB


12.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;


Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Profile: 107S051R	Page No.: 98
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 12:53
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 1: Transmit at channel 2402MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	54.942	24.387	-19.058	74.000	30.555	PK
2	*	2401.791	93.303	62.743	N/A	N/A	30.560	PK

Profile: 107S051R	Page No.: 99
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 12:57
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 1: Transmit at channel 2402MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	41.790	11.235	-12.210	54.000	30.555	AV
2	*	2401.884	82.041	51.481	N/A	N/A	30.561	AV

Profile: 107S051R	Page No.: 96
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 12:48
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 1: Transmit at channel 2402MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	54.522	23.967	-19.478	74.000	30.555	PK
2	*	2401.930	91.805	61.245	N/A	N/A	30.561	PK

Profile: 107S051R	Page No.: 97
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 12:51
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 1: Transmit at channel 2402MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	41.705	11.150	-12.295	54.000	30.555	AV
2	*	2402.070	81.275	50.715	N/A	N/A	30.561	AV

Profile: 107S051R	Page No.: 100
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 12:58
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 1: Transmit at channel 2480MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.040	94.119	63.783	N/A	N/A	30.336	PK
2		2483.500	54.759	24.437	-19.241	74.000	30.321	PK

Profile: 107S051R	Page No.: 101
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 13:01
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 1: Transmit at channel 2480MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.103	83.220	52.885	N/A	N/A	30.335	AV
2		2483.500	42.021	11.699	-11.979	54.000	30.321	AV

Profile: 107S051R	Page No.: 102
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 13:01
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 1: Transmit at channel 2480MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.008	92.581	62.245	N/A	N/A	30.336	PK
2		2483.500	54.613	24.291	-19.387	74.000	30.321	PK

Profile: 107S051R	Page No.: 103
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 13:04
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 1: Transmit at channel 2480MHz By DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.071	81.624	51.288	N/A	N/A	30.336	AV
2		2483.500	41.920	11.598	-12.080	54.000	30.321	AV

Profile: 107S051R	Page No.: 108
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 13:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 2: Transmit at channel 2402MHz By 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	54.497	23.942	-19.503	74.000	30.555	PK
2	*	2402.070	95.728	65.168	N/A	N/A	30.561	PK

Profile: 107S051R	Page No.: 109
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 13:13
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 2: Transmit at channel 2402MHz By 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	41.780	11.225	-12.220	54.000	30.555	AV
2	*	2401.930	81.747	51.187	N/A	N/A	30.561	AV

Profile: 107S051R	Page No.: 110
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 13:14
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 2: Transmit at channel 2402MHz By 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	54.031	23.476	-19.969	74.000	30.555	PK
2	*	2401.977	94.098	63.538	N/A	N/A	30.561	PK

Profile: 107S051R	Page No.: 111
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 13:15
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 2: Transmit at channel 2402MHz By 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	41.740	11.185	-12.260	54.000	30.555	AV
2	*	2401.977	80.116	49.556	N/A	N/A	30.561	AV

Profile: 107S051R	Page No.: 104
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 13:06
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 2: Transmit at channel 2480MHz By 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.008	93.901	63.565	N/A	N/A	30.336	PK
2		2483.500	54.965	24.643	-19.035	74.000	30.321	PK

Profile: 107S051R	Page No.: 105
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 13:08
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Horizontal
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 2: Transmit at channel 2480MHz By 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.113	79.823	49.488	N/A	N/A	30.335	AV
2		2483.500	41.927	11.605	-12.073	54.000	30.321	AV

Profile: 107S051R	Page No.: 106
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 13:08
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 2: Transmit at channel 2480MHz By 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.050	94.831	64.495	N/A	N/A	30.336	PK
2		2483.500	54.332	24.010	-19.668	74.000	30.321	PK

Profile: 107S051R	Page No.: 107
Engineer: Jame	
Site: AC5	Time: 2010/07/31 - 13:10
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D-499(1-18GHz)	Polarity: Vertical
EUT: Eee PC	Power: AC 120V/60Hz
Note: Mode 2: Transmit at channel 2480MHz By 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.050	80.775	50.439	N/A	N/A	30.336	AV
2		2483.500	41.947	11.625	-12.053	54.000	30.321	AV


13. Receiver Spurious Emission for RSS-GEN

13.1. Test Specification


According to EMC Standard: FCC Part 15 Subpart B Class B, ANSI C63.4 or RSS-GEN

13.2. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



13.3. Limit

FCC Part 15 Subpart B Paragraph 15.109 & RSS-GEN		
Frequency (MHz)	Distance (m)	Level (dBuV/m)
30 - 88	3	40
88 - 216	3	43.5
216 - 960	3	46
Above 960	3	54

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) = 20 log E field strength (uV/m)

13.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated on radiated measurement.

For an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 - 108	1000
108 - 500	2000

500 - 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

On any frequency or frequencies below or equal to 1000 MHz, the radiated limits shown are based on measuring equipment employing a quasi-peak detector function and above 1000 MHz, the radiated limits shown are based measuring equipment employing an average detector function.

When average radiated emission measurement are included emission measurement Above 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

For class A, the measurement distance between the EUT and antenna is 3 meters for under 1GHz and above 1GHz.

For class B, the measurement distance between the EUT and antenna is 3 meters for under 1GHz and 3 meters for above 1GHz.

The bandwidth below 1GHz setting on the field strength meter (R&S Test Receiver ESCI) is 120 kHz and above 1GHz is 1MHz.

Note: When measurement above 1GHz, the horn antenna will bend down a little (as horn antenna have the narrow beamwidth) in order to find the maximum emission of EUT.

13.5. Deviation from Test Standard

No deviation.

13.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;

Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Measure Level = Reading Level + Cable Loss + Antenna Factor - Preamplifier Gain

DH5

CH	Antenna	Frequen cy (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
00	H	322.9	38.3	-7.4	30.9	46	-15.1	QP
	V	322.9	39.6	-7.4	32.2	46	-13.8	QP
	H	415.0	33.8	-4.5	29.3	46	-16.7	QP
	V	415.0	34.6	-4.5	30.1	46	-15.9	QP
	H	1221.5	61.7	-23.5	38.2	54(note)	-15.8	PK
	V	1221.5	59.1	-23.4	35.7	54(note)	-18.3	PK
	H	2496.0	57.9	-18.8	39.1	54(note)	-14.9	PK
	V	2496.0	59.7	-18.8	40.9	54(note)	-13.1	PK
39	H	322.9	38.2	-7.4	30.8	46	-15.2	QP
	V	322.9	39.5	-7.4	32.1	46	-13.9	QP
	H	415.0	33.8	-4.5	29.3	46	-16.7	QP
	V	415.0	34.6	-4.5	30.1	46	-15.9	QP
	H	1221.5	61.5	-23.5	38.0	54(note)	-16.0	PK
	V	1221.5	59.1	-23.4	35.7	54(note)	-18.3	PK
	H	2496.0	57.8	-18.8	39.0	54(note)	-15.0	PK
	V	2496.0	59.7	-18.8	40.9	54(note)	-13.1	PK
78	H	322.9	38.2	-7.4	30.8	46	-15.2	QP
	V	322.9	39.5	-7.4	32.1	46	-13.9	QP
	H	415.0	33.8	-4.5	29.3	46	-16.7	QP
	V	415.0	34.6	-4.5	30.1	46	-15.9	QP
	H	1221.5	61.7	-23.5	38.2	54(note)	-15.8	PK
	V	1221.5	59.1	-23.4	35.7	54(note)	-18.3	PK
	H	2496.0	57.9	-18.8	39.1	54(note)	-14.9	PK
	V	2496.0	58.9	-18.8	40.1	54(note)	-13.9	PK

3DH5

CH	Antenna	Frequen cy (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
00	H	322.9	38.2	-7.4	30.8	46	-15.2	QP
	V	322.9	39.5	-7.4	32.1	46	-13.9	QP
	H	415.0	33.8	-4.5	29.3	46	-16.7	QP
	V	415.0	34.6	-4.5	30.1	46	-15.9	QP
	H	1221.5	61.7	-23.5	38.2	54(note)	-15.8	PK
	V	1221.5	59.1	-23.4	35.7	54(note)	-18.3	PK
	H	2496.0	57.9	-18.8	39.1	54(note)	-14.9	PK
	V	2496.0	59.7	-18.8	40.9	54(note)	-13.1	PK
39	H	322.9	38.2	-7.4	30.8	46	-15.2	QP
	V	322.9	39.5	-7.4	32.1	46	-13.9	QP
	H	415.0	33.8	-4.5	29.3	46	-16.7	QP
	V	415.0	34.6	-4.5	30.1	46	-15.9	QP
	H	1221.5	61.7	-23.5	38.2	54(note)	-15.8	PK
	V	1221.5	59.1	-23.4	35.7	54(note)	-18.3	PK
	H	2496.0	57.9	-18.8	39.1	54(note)	-14.9	PK
	V	2496.0	59.7	-18.8	40.9	54(note)	-13.1	PK
78	H	322.9	38.2	-7.4	30.8	46	-15.2	QP
	V	322.9	39.5	-7.4	32.1	46	-13.9	QP
	H	415.0	33.8	-4.5	29.3	46	-16.7	QP
	V	415.0	34.6	-4.5	30.1	46	-15.9	QP
	H	1221.5	61.7	-23.5	38.2	54(note)	-15.8	PK
	V	1221.5	59.2	-23.4	35.8	54(note)	-18.2	PK
	H	2496.0	57.9	-18.8	39.1	54(note)	-14.9	PK
	V	2496.0	59.7	-18.8	40.9	54(note)	-13.1	PK

Note: This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.