



4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan 112

September 8, 2017

Declaration – MIF for HAC RF Interference Evaluation

To Whom It May Concern,

This device, with FCC ID: **MSQA009**, Hearing Aid Compatibility Requirement is going to be certified under **ANSI C63.19-2011 version per Part 20.19**.

The M rating was determined by measuring the maximum steady state average E-field values in dB (V/m) as documented in the HAC report and adding the MIF value in dB (V/m) using pre-determined values provided by Speag under **UID 10021 DAC (16.11.2016) / UID 10011 CAB (16.01.2014) / UID 10170 CAC (16.11.2016) / UID 10061 CAB (26.11.2014) / UID 10077 CAB (26.11.2014)**.

The Speag-reference documentation for supporting the pre-determined MIF value is Schmid & Partner Engineering AG, **UID SUMMARY (Communication Systems for Calibration, Issued Date 2016/07/08)**.

We confirm that the Speag simulation provided represents all the air interface modes applicable for a HAC rating for this handset.

Sincerely Yours,

Jackson Yen / Associate Vice President

ASUSTeK Computer Inc

Tel: +886-2-28943447

Fax: +886-2-28987364

E-mail: jackson_yen@asus.com