

Test Report

Applicant : ASUSTeK COMPUTER INC.

Applicant Address : 1F., No. 15, Lide Rd., Beitou Dist., Taipei City 112, Taiwan

Product Type : Intel® Wi-Fi 6E AX210

Trade Name : Intel

Model Number : AX210NGW

Applicable Standard : 47 CFR Part §2.1093

Received Date : Oct. 13, 2021

Test Period : Oct. 24 ~ Nov. 17, 2021

Issued Date : Nov. 29, 2021

Issued by

Approved By	:		
	:	(Kris Pan)	

A Test Lab Techno Corp.

No. 140-1, Changan Street, Bade District, Taoyuan City 33465, Taiwan (R.O.C.)

Tel: +886-3-2710188 / Fax: +886-3-2710190





Taiwan Accreditation Foundation accreditation number: 1330

Test Firm MRA designation number: TW0010

Note:

- 1. The test results are valid only for samples provided by customers and under the test conditions described in this report.
- 2. This report shall not be reproduced except in full, without the written approval of A Test Lab Technology Corporation.
- 3. The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.



Revision History

Rev.	Issue Date	Revisions	Revised By
00	Nov. 29, 2021	Initial Issue	Nicole Chu



Contents

1.	General Information	4
	1.1 Reference Testing Standards	4
2. 3. 4.	Description of Device Under Test (DUT) Summary of Maximum Value Introduction	7
	4.1 SAR Definition	
	4.2 Power Density Definition	8
	4.3 RF Exposure Limits	9
5.	System Describtion	10
	5.1 SAR Measurement System	10
	5.2 Test Site Environment	13
	5.3 Tissue Simulating Liquids (TSL)	14
	5.4 Power Density Measurement System	19
6.	System Verification	23
	6.1 SAR System Verification	23
	6.2 Power Density System Verification	24
7.	Test Equipment List	
8.	Measurement Procedure	
•	8.2 Power Density Measurement Procedure	
9.	9.1 SAR Measurement Uncertainty	
	9.2 Power Density Measurement Uncertainty	
10.	·	
	10.1 Positioning of the DUT in Relation to the Phantom	
	10.2 SAR Testing with RF Transmitter	37
	10.3 Conducted Power Measurements	39
	10.4 Antenna location	39
	10.5 Test Results	40
	10.6 SAR Measurement Variability	47
	10.7 Simultaneous Transmission Evaluation	48
	10.8 Requirements on the Uncertainty Evaluation	53
11.	. Conclusion	53

Appendix A - Conducted Power Measurements

Appendix B - System Performance Check Plots

Appendix C - Highest Measurement Plots

Appendix D - Calibration Certificates

Appendix E - Test Setup Photographs



1. General Information

1.1 Reference Testing Standards

Standard	Description	Version
IEC/IEEE 62209-1528	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)	2020
IEC TR 63170	Measurement procedure for the evaluation of power density related to human exposure to radio frequency fields from wireless communication devices operating between 6 GHz and 100 GHz	2018
IEEE 1528	Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques	2013
IEEE C95.1	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz	1992
47 CFR Part §2.1093	Radiofrequency radiation exposure evaluation: portable devices	-
KDB 248227 D01	SAR guidance for IEEE 802.11 (Wi-Fi) transmitters	v02r02
KDB 447498 D01	RF exposure procedures and equipment authorization policies for mobile and portable devices	v06
KDB 616217 D04	SAR evaluation considerations for laptop, notebook and tablet computers	v01r02
KDB 865664 D01	SAR measurement requirement for 100 MHz to 6 GHz	v01r04
KDB 865664 D02	RF exposure compliance reporting and documentation considerations	v01r02



2. Description of Device Under Test (DUT)

Applicant Manufacture Product Type	ASUSTEK COMPUTER INC. 1F., No. 15, Lide Rd., Beitou Dist., Taipei City 112, Taiwan ASUSTEK COMPUTER INC. 1F., No. 15, Lide Rd., Beitou Dist., Taipei City 112, Taiwan
Product Type	
	Intel® Wi-Fi 6E AX210
Trade Name	Intel
Model Number	AX210NGW
SN No.	7194630400003
FCC ID	MSQAX210NG
Host Information	Product Type: Notebook PC Trade Name: ASUS Model Name: B5402CE, B5402CEA, B5402FE, B5408FE, B5402FEA, B5408CEA, B5408CEA, B5408CEA, B5402CEAW, B5402FEAW, B5400FE, B5400CE, B5400FEA, B5400CEA All models are electrically identical, different model names are for marketing purpose and the flip angle of panel, as below. B5402FE \cdot B5402FEA \cdot B5402FEAW \cdot B5400FE \cdot B5400FEA \cdot B5408FEA is for 360 degree; B5402CE \cdot B5402CEA \cdot B5402CEAW \cdot B5400CE \cdot B5400CEA \cdot B5408CEA is for 180 degree
Frequency Range	WLAN 2.4 GHz Band: 2412 - 2472 MHz WLAN 5.2 GHz Band: 5180 - 5240 MHz WLAN 5.3 GHz Band: 5260 - 5320 MHz WLAN 5.6 GHz Band: 5500 - 5720 MHz WLAN 5.8 GHz Band: 5745 - 5825 MHz WLAN 6.2 GHz Band: 5955 - 6415 MHz WLAN 6.5 GHz Band: 6435 - 6515 MHz WLAN 6.7 GHz Band: 6535 - 6855 MHz WLAN 7.0 GHz Band: 6875 - 7115 MHz Bluetooth: 2402 - 2480 MHz
Supported Modulations	WLAN 2.4 GHz: 802.11b/g/n/ax HT20 / HT40 / HE20 / HE40 WLAN 5 GHz: 802.11a /n / ac / ax HT20 / HT40 / VHT20 / VHT40 / VHT80 / VHT160 / HE20 / HE40 / HE80 / HE160 WLAN 6 GHz: 802.11a / n / ac / ax HT20 / HT40 / VHT20 / VHT40 / VHT80 / VHT160 / HE20 / HE40 / HE80 / HE160 Bluetooth: BR / EDR / LE
Device Category	Portable Device
Application Type	Certification
<u> </u>	

Note:

 The above information of DUT was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



Antenna list:

Antenna	ANIT	Manufacture	Dont No (Mandan)	Time	Type Frequency		ain(dBi)
Source	ANT	Manufacturer	Part No.(Vendor)	Type	Frequency	NB	PAD
					2402 - 2480	1.93	1.25
					5150 - 5250	3.26	3.12
	Chain B	High-Tek	DC33002NB00	PIFA Antenna	5250 - 5350	3.26	3.39
					5470 - 5725	4.09	4.19
1					5725 - 5850	4.25	4.19
'					2402 - 2480	2.77	1.91
					5150 - 5250	3.08	2.67
	Chain A	High-Tek	DC33002NB10	PIFA Antenna	5250 - 5350	3.13	3.40
					5470 - 5725	4.24	4.42
					5725 - 5850	4.36	4.50
		Chain B MAG.LAYERS	DC33002N900	PIFA Antenna	2402 - 2480	0.90	0.73
	Chain B MA				5150 - 5250	2.98	2.73
					5250 - 5350	2.98	3.17
					5470 - 5725	3.79	3.68
2					5725 - 5850	3.80	3.68
2				PIFA Antenna	2402 - 2480	2.68	1.38
					5150 - 5250	3.00	2.31
	Chain A	MAG.LAYERS	DC33002N910		5250 - 5350	3.05	2.89
					5470 - 5725	3.95	4.23
					5725 - 5850	3.95	4.41

Note:

- 1. Antenna Source 1 (High-Tek) gain is higher. Hence, it is regarded as the initial configuration, and then tested and recorded in this report.
- 2. Antenna Source 1 (High-Tek) and Antenna Source 2 (MAG.LAYERS) are the same type of antenna, only different in manufacturer.
- 3. The Chain A is connected to AUX port / Chain B is connected to Main port of module.



3. Summary of Maximum Value

		Highest Reported 1g SAR (W/kg)		Highest Reported 1g SAR (W/kg)	
		Tablet/SKU1		Notebook/SKU2	
Equipment Class	Mode	Body standalone SAR 1 g(W/kg)	Highest Simultaneous Transmission SAR	Body standalone SAR 1 g(W/kg)	Highest Simultaneous Transmission SAR
DTS	WLAN2.4GHz Ant Main	1.03	1 20	0.74	1.08
DIS	WLAN2.4GHz Ant Aux	2.4GHz Ant Aux 1.18 1.08	1.08	1.06	
NII	WLAN5GHz Ant Main	1.05	1.30	1.19	1.41
INII	WLAN5GHz Ant Aux	1.08	1.30	0.82	1.41
6VD	WLAN6GHz Ant Main	1.02	1.38	0.47	1.12
6XD	WLAN6GHz Ant Aux	1.02	1.30	0.43	1.12
DSS / DTS	Bluetooth Ant Aux	0.36	1.38	0.22	1.41

Equipment Class	Mode	Highest Standalone Transmission	Highest Simultaneous Transmission
Equipment Class	Wode	Averaging Area [4 cm²] Total PD [mW/cm²]	Total Exposure Rate
6XD	WLAN6GHz	0.39	0.97

Note:

- 1. The SAR limit for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (§2.1093) and ANSI/IEEE C95.1-1992.
- 2. The test procedures, as described in American National Standards, Institute ANSI/IEEE C95.1 were employed and they specify the maximum exposure limit of tissue for portable devices being used within 20 cm between user and EUT in the uncontrolled environment. A description of the product and operating configuration, detailed summary of the test results, methodology and procedures used in the equipment used are included within this test report.
- 3. The evaluation requirements, as described in 47 CFR Part §1.310 were employed and they specify the maximum exposure limit for general population / uncontrolled exposure is 1.0 mW/cm² (equal to 10 W/m²) for 1.5 GHz to 100 GHz.
- 4. According to the TCB Worshop Oct. 2018 notes, the average power density results are presented using averaging areas of 4 cm².
- 5. Total exposure ratio (TER) calculated by taking ratio of reported SAR divided by SAR limit and adding it to measured power density divided by power density limit. Numerical sum of the two ratios should be less than 1.
- 6. This device has two kinds of SKU, SKU 1 is 360 convertible laptop computer, SKU 2 is laptop only. All circuit designs, circuit board and other related designs are electrically identical.



4. Introduction

4.1 SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dw) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\mathbf{SAR} = \frac{d}{dt} \left(\frac{dw}{dm} \right) = \frac{d}{dt} \left(\frac{dw}{\rho dv} \right)$$

SAR measurement can be related to the electrical field in the tissue by

$$\mathsf{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where:

 σ = conductivity of the tissue (S/m)

 ρ = mass density of the tissue (kg/m³)

E = RMS electric field strength (V/m)

SAR is expressed in units of Watts per kilogram (W/kg).

4.2 Power Density Definition

Power density (PD) is defined as the rates of energy transfer per area for an electromagnetic filed. According to the IEC TR 63170, the following formula is used to determine the local power density:

$$S = \frac{1}{2}\Re(E \times H) \cdot \widehat{n}$$

And the spatial-average power denity distribution on the evaluate surface is determined as the following equation:

$$S_{av} = \frac{1}{2A} \Re \cdot \left(\int E \times H \cdot \widehat{n} \, dA \right)$$

Where:

E is the complex electric field peak phasor and H is the complex conjugate magnetic field peak phasor, respectively. A is the spatial averae area spefied by the applicable exposure or regulatory requirement.

Power density is expressed in unit of watt per square meter (W/m²).



4.3 RF Exposure Limits

Table 1 Safety Limits for Controlled / Uncontrolled Environment Exposure

SAR Exposure Limit			
	General Population / Uncontrolled Exposure ¹ (W/kg)	Occupational / Controlled Exposure ² (W/kg)	
Spatial Peak SAR ³ (head or Body)	1.60	8.00	
Spatial Peak SAR ⁴ (Whole Body)	0.08	0.40	
Spatial Peak SAR ⁵ (Hands / Feet / Ankle / Wrist)	4.00	20.00	
Pov	wer Density Exposure Limit (1,500 - 100,000 MHz)		
	General Population / Uncontrolled Exposure (mW/cm²) ⁶	Occupational / Controlled Exposure (mW/cm²)	
Power Density (S)	1.0	5.0	

Notes:


- 1. **General Population / Uncontrolled Environments** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.
- 2. **Occupational / Controlled Environments** are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).
- 3. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
- 4. The Spatial Average value of the SAR averaged over the whole body.
- 5. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
- 6. $1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$.



5. System Describtion

5.1 SAR Measurement System

The DASY6 system in cDASY6/DASY5 V5.2 SAR Configuration is shown below:



The system for performing compliance tests consists of the following items:

- 1. A standard high precision 6-axis robot (Stäubli TX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- 2. An isotropic field probe optimized and calibrated for the targeted measurements.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset
 measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or
 rechargeable batteries. The signal is optically transmitted to the EOC.
- 4. The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- 5. The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- 6. The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- 7. A computer running Win7/Win8/Win10 professional operating system and the cDASY6 and DASY5 V5.2 software.
- 8. Remote controls with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- 9. The phantom, the device holder and other accessories according to the targeted measurement.
- 10. Tissue simulating liquid mixed according to the given recipes.
- 11. The validation dipole has been calibrated within and the system performance check has been successful.




<DASY E-Field Probe System>

The SAR measurements were conducted with the dosimetric probe (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probes is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting. The approach is stopped when reaching the maximum.

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Frequency	4 MHz to 10 GHz Linearity: ± 0.2 dB (30 MHz to 10 GHz)
Directivity	±0.1 dB in TSL (rotation around probe axis) ±0.3 dB in TSL (rotation normal to probe axis)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Calibration	ISO/IEC 17025 calibration service available





EX3DV4 E-Field Probe

Probe setup on robot



<Data Acquisition Electronic (DAE) System>

Model	DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4 mV, 400 mV)	li di di di
Input Offset Voltage	< 5 μV (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	


<Robot>

1		
Positioner	Stäubli Unimation Corp.	
Robot Model	TX90XL	
Number of Axes	6	
Nominal Load	5 kg	
Reach	1450 mm	
Repeatability	<u>+</u> 0.035 mm	



<Device Holder>

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity ε =3 and loss tangent δ =0.02. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.





<Oval Flat Phantom - ELI>

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (Oval Flat) phantom defined in IEEE 1528, IEC 62209-2 and IEC/IEEE 62209-1528. It enables the dosimetric evaluation of wireless portable device usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

Shell Thickness	2 ±0.2 mm	S D O B G
Filling Volume	Approx. 30 liters	
Dimensions	190×600×400 mm (H × L × W)	₽ p3

<SAM Phantom>

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528, IEC 62209-1 and IEC/IEEE 62209-1528. It enables the dosimetric evaluation of left and right hand phone usage as well as body-mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

Shell Thickness	2 ±0.2 mm	© 2q 020 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	. p3

5.2 Test Site Environment

Temperature (°C)	l 21_23
icinperature (0)	21-25



5.3 Tissue Simulating Liquids (TSL)

<Tissue Dielectric Parameters in IEEE 1528-2013 and IEC/IEEE 62209-1528>

The following table incorporates the tissue dielectric parameters of head recommended by IEEE 1528-2013 and IEC/IEEE 62209-1528. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in human head. Other head and body tissue parameters that have not been specified are derived from the tissue dielectric parameters which computed by the 4-Cole-Cole equation according to the above-mentioned standards.


Table 2 Dielectric properties of the tissue-equivalent liquid material

Frequency (MHz)	Relative Permittivity (ϵ_r)	Conductivity (σ)
30	55.0	0.75
150	52.3	0.76
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1800	40.0	1.40
1900	40.0	1.40
1950	40.0	1.40
2000	40.0	1.40
2100	39.8	1.49
2450	39.2	1.80
2600	39.0	1.98
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27
6000	35.1	5.48
6500	34.5	6.07
7000	33.9	6.65
7500	33.3	7.24
8000	32.7	7.84
8500	32.1	8.46
9000	31.6	9.08
9500	31.0	9.71
10000	30.4	10.4



<Liquid Depth>

The depth of tissue-equivalent liquid in a phantom must be \geq 15.0 cm to ensure that the probe is immersed sufficiently in the tissue medium.



<Liquid Check>

- 1. The dielectric parameters of the liquids were verified prior to the SAR evaluation using a DAKS 3.5 Probe Kit.
- 2. The SAR testing with IEC tissue parameters as an alternative option to Head and body parameters. The head TSL were applied to body SAR tests with restrictions below:

The mixing and matching of head TSL and body TSL for body SAR testing in a single application are not permitted. For example, testing body SAR with head TSL and then switch to Body TSL for body SAR test is not allowed. The consistency of TSL is required.



Tissue Temp	Head /	Frequency	Cond.	Perm.	target Cond.	target Perm.	σ (Dolto)(%)	εr (Delta)(%)	Limit (%)	Date	
(°C)	Body		σ	٤r	σ	٤r	(Delta)(%)				
22.5	Head	2412 MHz	1.75	39.50	1.77	39.27	-0.69	0.59	±5	Oct. 28, 2021	
22.5	Head	2422 MHz	1.77	39.45	1.78	39.25	-0.57	0.51	±5	Oct. 28, 2021	
22.5	Head	2437 MHz	1.78	39.41	1.79	39.22	-0.39	0.47	±5	Oct. 28, 2021	
22.5	Head	2452 MHz	1.80	39.35	1.80	39.20	-0.33	0.38	±5	Oct. 28, 2021	
22.5	Head	2462 MHz	1.81	39.31	1.81	39.18	-0.36	0.33	±5	Oct. 28, 2021	
22.5	Head	2467 MHz	1.81	39.29	1.82	39.18	-0.33	0.28	±5	Oct. 28, 2021	
22.5	Head	2472 MHz	1.82	39.27	1.82	39.17	-0.30	0.26	±5	Oct. 28, 2021	
21.6	Head	2412 MHz	1.75	39.89	1.77	39.27	-0.80	1.58	±5	Nov. 03, 2021	
21.6	Head	2422 MHz	1.76	39.85	1.78	39.25	-0.64	1.53	±5	Nov. 03, 2021	
21.6	Head	2437 MHz	1.78	39.82	1.79	39.22	-0.45	1.53	±5	Nov. 03, 2021	
21.6	Head	2452 MHz	1.80	39.78	1.80	39.20	-0.17	1.48	±5	Nov. 03, 2021	
21.6	Head	2462 MHz	1.81	39.75	1.81	39.18	-0.10	1.46	±5	Nov. 03, 2021	
21.6	Head	2467 MHz	1.82	39.74	1.82	39.18	0.11	1.43	±5	Nov. 03, 2021	
21.6	Head	2472 MHz	1.82	39.72	1.82	39.17	0.02	1.41	±5	Nov. 03, 2021	
22.8	Head	5180 MHz	4.50	37.05	4.64	36.02	-3.09	2.85	±5	Oct. 26, 2021	
22.8	Head	5190 MHz	4.52	37.01	4.65	36.01	-2.89	2.78	±5	Oct. 26, 2021	
22.8	Head	5200 MHz	4.53	36.97	4.66	36.00	-2.78	2.70	±5	Oct. 26, 2021	
22.8	Head	5220 MHz	4.56	36.94	4.68	35.98	-2.58	2.66	±5	Oct. 26, 2021	
22.8	Head	5230 MHz	4.57	36.91	4.69	35.97	-2.48	2.61	±5	Oct. 26, 2021	
22.8	Head	5240 MHz	4.58	36.90	4.70	35.96	-2.48	2.61	±5	Oct. 26, 2021	
22.8	Head	5250 MHz	4.60	36.89	4.71	35.95	-2.39	2.62	±5	Oct. 26, 2021	
22.8	Head	5260 MHz	4.61	36.85	4.72	35.94	-2.39	2.54	±5	Oct. 26, 2021	
22.8	Head	5270 MHz	4.61	36.85	4.73	35.93	-2.54	2.56	±5	Oct. 26, 2021	
22.8	Head	5280 MHz	4.62	36.86	4.74	35.92	-2.55	2.61	±5	Oct. 26, 2021	
22.8	Head	5290 MHz	4.62	36.88	4.75	35.91	-2.72	2.69	±5	Oct. 26, 2021	
22.8	Head	5300 MHz	4.63	36.88	4.76	35.90	-2.77	2.74	±5	Oct. 26, 2021	
22.8	Head	5310 MHz	4.65	36.90	4.77	35.89	-2.61	2.80	±5	Oct. 26, 2021	
22.8	Head	5320 MHz	4.66	36.91	4.78	35.88	-2.44	2.86	±5	Oct. 26, 2021	
22.8	Head	5500 MHz	4.86	36.65	4.97	35.65	-2.09	2.79	±5	Oct. 26, 2021	
22.8	Head	5510 MHz	4.87	36.62	4.98	35.64	-2.22	2.76	±5	Oct. 26, 2021	
22.8	Head	5530 MHz	4.88	36.58	5.00	35.61	-2.40	2.73	±5	Oct. 26, 2021	
22.8	Head	5550 MHz	4.89	36.50	5.02	35.58	-2.59	2.59	±5	Oct. 26, 2021	
22.8	Head	5570 MHz	4.89	36.44	5.04			±5	Oct. 26, 2021		
22.8	Head	5580 MHz	4.90	36.41	5.05	35.53	-2.99	2.49	±5	Oct. 26, 2021	
22.8	Head	5610 MHz	4.91	36.30	5.08	35.49	-3.30	2.28	±5	Oct. 26, 2021	
22.8	Head	5620 MHz	4.93	36.27	5.09	35.48	-3.20	2.22	±5	Oct. 26, 2021	
22.8	Head	5630 MHz	4.94	36.24	5.10	35.47	-3.07	2.18	±5	Oct. 26, 2021	



Tissue Temp	Head /	Frequency	Cond.	Perm.	target Cond.	target Perm.	σ (Dalta)(0/)	13 (Doldato)	Limit (%)	Date	
(°C)	Body		σ	٤r	σ	εr	(Delta)(%)	(Delta)(%)	()		
22.8	Head	5660 MHz	5.03	36.11	5.13	35.44	-2.03	1.89	±5	Oct. 26, 2021	
22.8	Head	5670 MHz	5.06	36.06	5.14	35.43	-1.60	1.78	±5	Oct. 26, 2021	
22.8	Head	5690 MHz	5.12	35.95	5.16	35.41	-0.69	1.52	±5	Oct. 26, 2021	
22.8	Head	5700 MHz	5.15	35.92	5.17	35.40	-0.30	1.47	±5	Oct. 26, 2021	
22.8	Head	5710 MHz	5.18	35.92	5.18	35.39	-0.09	1.49	±5	Oct. 26, 2021	
22.8	Head	5720 MHz	5.19	35.92	5.19	35.38	-0.08	1.52	±5	Oct. 26, 2021	
22.8	Head	5500 MHz	4.95	36.18	4.97	35.65	-0.26	1.50	±5	Nov. 03, 2021	
22.8	Head	5510 MHz	4.96	36.17	4.98	35.64	-0.28	1.49	±5	Nov. 03, 2021	
22.8	Head	5530 MHz	4.97	36.12	5.00	35.61	-0.45	1.42	±5	Nov. 03, 2021	
22.8	Head	5550 MHz	4.99	36.07	5.02	35.58	-0.47	1.37	±5	Nov. 03, 2021	
22.8	Head	5570 MHz	5.01	36.00	5.04	35.55	-0.59	1.26	±5	Nov. 03, 2021	
22.8	Head	5580 MHz	5.02	35.97	5.05	35.53	-0.62	1.24	±5	Nov. 03, 2021	
22.8	Head	5610 MHz	5.05	35.85	5.08	35.49	-0.55	1.02	±5	Nov. 03, 2021	
22.8	Head	5620 MHz	5.07	35.83	5.09	35.48	-0.33	0.99	±5	Nov. 03, 2021	
22.8	Head	5630 MHz	5.09	35.78	5.10	35.47	-0.19	0.88	±5	Nov. 03, 2021	
22.8	Head	5660 MHz	5.18	35.66	5.13	35.44	0.92	0.62	±5	Nov. 03, 2021	
22.8	Head	5670 MHz	5.21	35.62	5.14	35.43	1.32	0.55	±5	Nov. 03, 2021	
22.8	Head	5690 MHz	5.26	35.56	5.16	35.41	1.90	0.43	±5	Nov. 03, 2021	
22.8	Head	5700 MHz	5.28	35.54	5.17	35.40	2.15	0.39	±5	Nov. 03, 2021	
22.8	Head	5710 MHz	5.30	35.52	5.18	35.39	2.22	0.38	±5	Nov. 03, 2021	
22.8	Head	5720 MHz	5.31	35.52	5.19	35.38	2.21	0.41	±5	Nov. 03, 2021	
22.6	Head	5745 MHz	5.19	35.95	5.22	35.36	-0.44	1.68	±5	Oct. 27, 2021	
22.6	Head	5755 MHz	5.19	35.96	5.23	35.35	-0.77	1.73	±5	Oct. 27, 2021	
22.6	Head	5775 MHz	5.18	35.99	5.25	35.33	-1.33	1.87	±5	Oct. 27, 2021	
22.6	Head	5785 MHz	5.17	35.98	5.26	35.32	-1.65	1.86	±5	Oct. 27, 2021	
22.6	Head	5795 MHz	5.16	35.96	5.27	35.31	-1.98	1.84	±5	Oct. 27, 2021	
22.6	Head	5825 MHz	5.13	35.89	5.30	35.28	-3.20	1.74	±5	Oct. 27, 2021	
22.5	Head	5745 MHz	5.31	35.55	5.22	35.36	1.88	0.55	±5	Nov. 03, 2021	
22.5	Head	5755 MHz	5.31	35.57	5.23	35.35	1.57	0.63	±5	Nov. 03, 2021	
22.5	Head	5775 MHz	5.29	35.59	5.25	35.33	0.76	0.74	±5	Nov. 03, 2021	
22.5	Head	5785 MHz	5.27	35.58	5.26	35.32	0.20	0.73	±5	Nov. 03, 2021	
22.5	Head	5795 MHz	5.26	35.56	5.27	35.31	-0.15	0.71	±5	Nov. 03, 2021	
22.5	Head	5825 MHz	5.25	35.45	5.30	35.28	-0.81	0.48	±5	Nov. 03, 2021	
22.5	Head	6025 MHz	5.64	35.17	5.51	35.07	2.41	0.29	±5	Oct. 24, 2021	
22.5	Head	6185 MHz	5.76	35.18	5.70	34.88	1.02	0.86	±5	Oct. 24, 2021	
22.5	Head	6345 MHz	6.10	34.57	5.89	34.69	3.58	-0.35	±5	Oct. 24, 2021	
22.5	Head	6465 MHz	6.22	34.54	6.03	34.54	3.09	-0.02	±5	Oct. 24, 2021	




Tissue Temp	Head / Body	Frequency	Cond.	Perm.	target Cond.	target Perm.	σ (Delta)(%)	εr (Delta)(%)	Limit (%)	Date
(°C)	Body		σ	٤r	σ	٤r	(Bolla)(70)	(Boila)(70)		
22.5	Head	6505 MHz	6.23	34.39	6.08	34.49	2.58	-0.29	±5	Oct. 24, 2021
22.5	Head	6665 MHz	6.44	33.89	6.26	34.30	2.89	-1.18	±5	Oct. 24, 2021
22.5	Head	6825 MHz	6.66	33.84	6.45	34.11	3.26	-0.78	±5	Oct. 24, 2021
22.5	Head	6525 MHz	6.26	34.27	6.10	34.47	2.69	-0.58	±5	Oct. 24, 2021
22.5	Head	6985 MHz	6.79	33.36	6.63	33.92	2.35	-1.66	±5	Oct. 24, 2021
22.5	Head	7025 MHz	6.83	33.34	6.68	33.87	2.27	-1.58	±5	Oct. 24, 2021
22.5	Head	7115 MHz	6.91	33.50	6.79	33.76	1.88	-0.78	±5	Oct. 24, 2021
22.5	Head	6025 MHz	5.62	35.06	5.51	35.07	1.96	-0.02	±5	Oct. 25, 2021
22.5	Head	6185 MHz	5.73	35.07	5.70	34.88	0.57	0.57 0.55		Oct. 25, 2021
22.5	Head	6345 MHz	6.07	34.46	5.89	34.69	3.14	-0.67	±5	Oct. 25, 2021
22.5	Head	6465 MHz	6.19	34.43	6.03	34.54	2.65	-0.33	±5	Oct. 25, 2021
22.5	Head	6505 MHz	6.21	34.28	6.08	34.49	2.14	-0.61	±5	Oct. 25, 2021
22.5	Head	6665 MHz	6.41	33.79	6.26	34.30	2.45	-1.50	±5	Oct. 25, 2021
22.5	Head	6825 MHz	6.63	33.73	6.45	34.11	2.83	-1.10	±5	Oct. 25, 2021
22.5	Head	6525 MHz	6.24	34.16	6.10	34.47	2.25	-0.89	±5	Oct. 25, 2021
22.5	Head	6985 MHz	6.76	33.25	6.63	33.92	1.92	-1.98	±5	Oct. 25, 2021
22.5	Head	7025 MHz	6.80	33.23	6.68	33.87	1.84	-1.90	±5	Oct. 25, 2021
22.5	Head	7115 MHz	6.88	33.39	6.79	33.76	1.44	-1.11	±5	Oct. 25, 2021
22.6	Head	2402 MHz	1.75	39.60	1.76	39.28	-0.65	0.81	±5	Nov. 17, 2021
22.6	Head	2441 MHz	1.79	39.44	1.79	39.22	-0.24	0.56	±5	Nov. 17, 2021
22.6	Head	2480 MHz	1.83	39.29	1.83	39.16	-0.15	0.33	±5	Nov. 17, 2021
22.6	Head	2402 MHz	1.75	39.60	1.76	39.28	-0.65	0.81	±5	Nov. 17, 2021
22.6	Head	2440 MHz	1.79	39.44	1.79	39.22	-0.24	0.57	±5	Nov. 17, 2021
22.6	Head	2480 MHz	1.83	39.29	1.83	39.16	-0.15	0.33	±5	Nov. 17, 2021



5.4 Power Density Measurement System

The DASY6 system in cDASY6 SAR Configuration is shown below:



The DASY6 system for performing compliance tests consists of the following items:

- 1. A standard high precision 6-axis robot (Stäubli TX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated. The probe is equipped with an optical surface detector system.
- 3. A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- 4. The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- 5. A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- 6. A computer running Win7/Win8/Win10 professional operating system and the cDASY6 and DASY5 V5.2 software.
- 7. Remote controls with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- 8. The mmWave phantom.
- 9. Validation dipole kits allowing validating the proper functioning of the system.



<DASY E-Field Probe System>

The EUmmWV3 probe is based on the pseudo-vector probe design, which not only measures the field magnitude but also derives its polarization ellipse. This probe concept also has the advantage that the sensor angle errors or distortions of the field by the substrate can be largely nullified by calibration. This is particularly important as, at these very high frequencies, field distortions by the substrate are dependent on the wavelength. It has two dipoles optimally arranged to obtain pseudo-vector information. It has minimum 3 measurements/point, 120° rotated around probe axis. Sensors (0.8 mm length) printed on glass substrate protected by high density foam. Low perturbation of the measured field. Requires positioner which can do accurate probe rotation.

Frequency Range	750 MHz - 110 GHz							
Dynamic Range	< 20 V/m - 10'000 V/m with	< 20 V/m - 10'000 V/m with PRE-10 (min < 50 V/m - 3000 V/m)						
Position Precision	< 0.2 mm	< 0.2 mm						
Dimensions	Distance from probe tip to d	8 mm (internal sensor < 1mm)						
Applications	operating above 10 GHz in Power density, magnetic field	ctric field measurements of 5G devices and other mm-wave transmitters rating above 10 GHz in <2 mm distance from device (free-space) ver density, magnetic field, and far-field analysis using total field reconstruction ASY6 5G or ICEy-mmW module required)						
compatibility	cDASY6 + 5G-Module SW1	cDASY6 + 5G-Module SW1.0 and higher						
		sensor————————————————————————————————————						
E-Field n	nm-Wave Probe	Sensor to DUT Surface						



<mmWave phantom>

The mmWave phantom approximates free-space conditions, allowing to evaluate not only the antenna side of the device but also the front (screen) or any opposite-radiating side of wireless devices operating above 10 GHz without distorting the radiofrequency (RF) field. It consists of a 40 mm thick Rohacell plate used as a test bed which has a loss tangent (tan δ) \leq 0.05 and a relative permittivity (ϵ r) \leq 1.2. The high-performance RF absorbers are placed below the foam.



<Data Acquisition Electronic (DAE)>

The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preampli er with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter, and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The input impedance of DAE box is 200MOhm; the inputs are symmetric and oating. Common mode rejection is above 80 dB.



Model	DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4 mV, 400 mV)	and the state of t
Input Offset Voltage	< 5 μV (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

<Robot>

Positioner	Stäubli Unimation Corp.	
Robot Model	TX90XL	
Number of Axes	6	
Nominal Load	5 kg	
Reach	1450 mm	
Repeatability	<u>+</u> 0.035 mm	



6. System Verification

6.1 SAR System Verification

<Symmetric Dipoles for SAR System Verification>

Construction	Symmetrical dipole with λ/4 balun enables measurement of feed point impedance with NWA matched for use near flat phantoms filled with head simulating solutions Includes distance holder and tripod adaptor Calibration Calibrated SAR value for specified position and input power at the flat phantom in head simulating solutions.								
Return Loss Options		> 20 dB at specified verification position. Dipoles for other frequencies or solutions and other calibration conditions are available upon request							
Signal Generator Amp	Tuning element 3D Probe positioner Field probe Field Phantom Dipole Pass Att3 Att2 PM2 PM2								
	System Verification Setup Diagram	Validation Kit							



6.1.1 SAR Verification Summary

Prior to the assessment, the validation data compared to the original value provided by SPEAG should be within its specifications of $\pm 10\%$. The measured SAR will be normalized to 1 W input power. The result indicates the system check can meet the variation criterion and plots can be referred to Appendix B of this report.

Mixture			Probe	Dipole	SAR _{1 g}	Normalize to 1 Watt	1 W Target	SAR _{10 g}	Normalize to 1 Watt	1 W Target	Difference	Difference percentage	Date
Туре	(MHz)	rowei	Model / Serial No.	Model / Serial No.	(W/Kg)	1 g (W/Kg)	SAR _{1 g} (W/Kg)	(W/Kg)	10 g (W/Kg)	SAR _{10 g} (W/Kg)	1 g	10 g	Date
Head	2450	250 mW	EX3DV4-SN 3977	D2450V2 – SN712	12.4	49.6	51.00	5.74	22.96	23.20	-2.7%	-1.0%	Oct. 28, 2021
Head	2450	250 mW	EX3DV4-SN 3977	D2450V2 – SN712	13.1	52.4	51.00	6.13	24.52	23.20	2.7%	5.7%	Nov. 03, 2021
Head	2450	250 mW	EX3DV4-SN 3977	D2450V2 – SN712	12.9	51.6	51.00	5.96	23.84	23.20	1.2%	2.8%	Nov. 17, 2021
Head	5250	100 mW	EX3DV4-SN 3977	D5250V2 – SN1021	8.41	84.1	78.40	2.34	23.4	22.20	7.3%	5.4%	Oct. 26, 2021
Head	5600	100 mW	EX3DV4-SN 3977	D5600V2 – SN1021	8.75	87.5	82.20	2.39	23.9	23.50	6.4%	1.7%	Oct. 26, 2021
Head	5600	100 mW	EX3DV4-SN 3977	D5600V2 – SN1021	8.73	87.3	82.20	2.37	23.7	23.50	6.2%	0.9%	Nov. 03, 2021
Head	5750	100 mW	EX3DV4-SN 3977	D5750V2 – SN1021	7.95	79.5	77.30	2.21	22.1	21.70	2.8%	1.8%	Oct. 27, 2021
Head	5750	100 mW	EX3DV4-SN 3977	D5750V2 – SN1021	8.38	83.8	77.30	2.28	22.8	21.70	8.4%	5.1%	Nov. 03, 2021
Head	6500	100 mW	EX3DV4-SN 3847	D6500V2 – SN1016	28.1	281	292.00	5.26	52.6	53.60	-3.8%	-1.9%	Oct. 24, 2021
Head	6500	100 mW	EX3DV4-SN 3847	D6500V2 – SN1016	27.9	279	292.00	5.22	52.2	53.60	-4.5%	-2.6%	Oct. 25, 2021

6.2 Power Density System Verification

The system performance check verifies that the system operates within its specifications.

The system check is successful if the difference between the normalized measured local power density and the numerically validated target value is within the reported expanded uncertainty of the measurement system.

The recommended settings for measurement of verification sources are listed in the following:

Settings for Measurement of Verification Sources								
Frequency[GHz]	Grid step	Grid extent X/Y [mm]	Measurement points					
10	0.25 (λ/4)	120 / 120	18 × 18					
30	0.25 (λ/4)	60 / 60	26 × 26					
45	0.25 (λ/4)	42 / 42	28 × 28					
60	0.25 (λ/4)	32.5 / 32.5	28 × 28					
90	0.25 (λ/4)	30 / 30	38 × 38					



<System Varification Souce>

The verification sources apply to system check or verification at specific mmWave frequencies. The sources comprise horn-antennas and very stable signal generators.

Frequency accuracy	10 GHz at 10 mm from the antenna	
E-field polarization	Linear	
Input Power	Max. 20 W	
Conector	SMA	
Weight	700 g	
Operation	requires a stable source with known forward power to perform system performance check or validation	

Calibrated Frequency	30 GHz at 10mm from the antenna (5.55 mm from the case surface)
Frequency accuracy	± 100 MHz
E-field polarization	Linear
Harmonics	-20 dBc
Total radiated power	14 dBm
Power stability	0.05 dB
Power consumption	5 W
Size	100 × 100 × 100 mm
Weight	1 kg




Calibrated Frequency	60 GHz at 10mm from the antenna (5.55 mm from the case surface)
Frequency accuracy	± 100 MHz
E-field polarization	± 100 MHz
Harmonics	Linear
Total radiated power	-20 dBc
Harmonics	14 dBm
Power stability	0.1 dB
Power consumption	5 W
Size	100 × 100 × 100 mm
Weight	1 kg





6.2.1 Power Density Verification Summary



Prior to the assessment, the validation data compared to the original value provided by SPEAG should be within its specifications of \pm 0.66 dB. The \pm 0.66 dB deviation threshold represents the expanded uncertainty for system performance checks using SPEAG's mmWave verification sources. The power density distribution was verified through visual inspection as per Nov. 2017 TCB Workshop Notes, both spatially (shape) and numerically (level) have no noticeable differences. The following result indicates the system check can meet the variation criterion and plots can be referred to Appendix B of this report.

Frequency (MHz)	Probe Model / Serial No.	Dipole Model / Serial No.	Averaging Area [4 cm²] Measured Total PD [W/m²]	Averaging Area [4 cm²] Target Total PD [W/m²]	Difference percentage (%)	Date
10G	EUmmWV3-SN9403	5G Verification Source 10 GHz-2003	147.00	149.00	-1.3%	Oct. 29, 2021

Note:

The measured total PD was the average of psPDn+, psPDtot+ and psPDmod+, which refers to the demonstration from calibration certificate.



7. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibr	ation
Manufacturer	Name of Equipment	i ype/iviodei	Serial Number	Cal. Date	Cal.Period
SPEAG	2450MHz System Validation Kit	D2450V2	712	2021/04/14	1 year
SPEAG	5GHz System Validation Kit	D5GHzV2	1021	2021/04/16	1 year
SPEAG	6.5GHz System Validation Kit	D6.5GHzV2	1016	2021/08/26	1 year
SPEAG	5G Verification Source	10 GHz	2003	2021/02/17	1 year
SPEAG	Dosimetric E-Field Probe	EUmmWV3	9403	2021/09/20	1 year
SPEAG	Dosimetric E-Field Probe	EX3DV4	3977	2021/07/26	1 year
SPEAG	Dosimetric E-Field Probe	EX3DV4	3847	2021/03/26	1 year
SPEAG	Data Acquisition Electronics	DAE4	779	2021/07/30	1 year
SPEAG	Data Acquisition Electronics	DAE4	541	2021/03/22	1 year
SPEAG	Measurement Server	SE UMS 028 BB	1488	NC	R
SPEAG	Measurement Server	SE UMS 011 BB	1241	NC	R
SPEAG	Device Holder	N/A	N/A	NC	R
SPEAG	Phantom	ELI V4.0	1036	NC	R
SPEAG	Phantom	ELI V5.0	1175	NC	R
SPEAG	5G Phantom	5G	OX-030	NC	R
SPEAG	Robot	Staubli TX90XL	F16/54FTA1/A/01	NC	R
SPEAG	Robot	Staubli TX90XL	F11/5G9EA1/A/01	NC	R
00540	0.5	cDASY6	N1/A	NG	\D
SPEAG	Software	V16.0.0.116	N/A	NC	K
ODEAO	0-6	DASY52	N1/A	NG	\D
SPEAG	Software	V52.10.4.1535	N/A	NC	,K
ODEAO	0-4	SEMCAD X	N1/A	NG	\D
SPEAG	Software	V14.6.14(7501)	N/A	NC	,K
R&S	Bluetooth Tester	CBT	100350	2021/03/17	2 year
SPEAG	Network Analyzer	DAKS_VNA R140	0010318	2021/05/26	1 year
SPEAG	Dielectric Probe Kit	DAKS-3.5	1101	2021/05/26	1 year
HILA	Digital Thermometer	TM-906A	1500033	2021/10/28	1 year
Agilent	Power Sensor	8481H	3318A20779	2021/05/26	1 year
Agilent	Power Meter	EDM Series E4418B	GB40206143	2021/05/26	1 year
Agilent	Power Sensor	N1921A	MY45241957	2020/12/09	1 year
Agilent	Power Meter	N1911A	MY45101619	2020/12/09	1 year
Agilent	Signal Generator	E8257D	MY44320425	2021/02/18	1 year
Agilent	Spectrum Analyzer	N9030A	MT-112	2021/01/08	1 year
Mini-Circuits	Dual Directional Coupler	ZCDC20-5R263-S+	E69806	NC	R
Mini-Circuits	Power Amplifier	EMC014225P	980292	NC	R
Mini-Circuits	Power Amplifier	EMC2830P	980293	NC	R
EMCI	Power Amplifier	EMC0618-P	980833	NC	R
Aisi	Attenuator	IEAT 3dB	N/A	NC	R

Testing Engineer: Jason Tsao / Ted Hsieh / Rocky Wang



8. Measurement Procedure

8.1 SAR Measurement Procedure

The measurement procedures are as follows:

- 1. The DUT is installed engineering testing software that provides continuous transmitting signal.
- 2. Measure output power through RF cable and power meter
- 3. Set scan area, grid size and other setting on the DASY software
- 4. Find out the largest SAR result on these testing positions of each band
- Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- 1. Power reference measurement
- 2. Area scan
- 3. Zoom scan
- 4. Power drift measurement



8.1.1 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures points and step size follow as below. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution.

The measure settings are referred to KDB 865664 D01v01r04:

			≤ 3 GHz	> 3 GHz	
Maximum distance from closest	measureme	ent point (geometric	E 1. 4	½·δ·ln(2) mm ± 0.5	
center of probe sensors) to phar	itom surfac	е	5 mm ± 1 mm	mm	
Maximum probe angle from probat the measurement location	e axis to pl	nantom surface normal	30° ± 1°	20° ± 1°	
			≤ 2 GHz: ≤ 15 mm	3 – 4 GHz: ≤ 12 mm	
			2 – 3 GHz: ≤ 12 mm	4 – 6 GHz: ≤ 10 mm	
			When the x or y dimension of	of the test device, in the	
Maximum area agen english read	lution, Av.	measurement plane orientat	ion, is smaller than the		
Maximum area scan spatial reso	iulion. ΔΧΑr	above, the measurement res	solution must be ≤ the		
			corresponding x or y dimens	ion of the test device	
		with at least one measurement point on the test			
		device.			
Maximum zoom agan anatial roo	Maximum zoom scan spatial resolution: Δx _{Area} , Δy _{Area}			3 – 4 GHz: ≤ 5 mm*	
waxiinum 200m scan spatiai res	Olution. Ax	Area, Δ y Area	2 – 3 GHz: ≤ 5 mm*	4 – 6 GHz: ≤ 4 mm*	
				3 – 4 GHz: ≤ 4 mm	
	uniform o	ırid: Δz _{Zoom} (n)	≤ 5 mm	4 – 5 GHz: ≤ 3 mm	
		Πα. <u>Δε</u> 200Π(Π)	2 3 111111	5 – 6 GHz: ≤ 2 mm	
				0 00112. = 2111111	
Maximum zoom scan spatial		$\Delta z_{Zoom}(1)$:		3 – 4 GHz: ≤ 3 mm	
resolution, normal to phantom		between 1st two	≤ 4 mm	4 – 5 GHz: ≤ 2.5 mm	
surface	Graded	points closest to		5 – 6 GHz: ≤ 2 mm	
	grid	phantom surface		0 001121 = 2111111	
	giid	$\Delta z_{Zoom}(n>1)$:			
		between subsequent	≤ 1.5·Δz _{Zoom} (ι	n-1) mm	
		points		T	
				3 – 4 GHz: ≥ 28 mm	
Minimum zoom scan volume		x, y, z	≥ 30 mm	4 – 5 GHz: ≥ 25 mm	
				5 – 6 GHz: ≥ 22 mm	

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.

^{*} When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB Publication 447498 is \leq 1.4 W/kg, \leq 8 mm, \leq 7 mm and \leq 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.



8.1.2 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1 g aggregate SAR, the DUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.1.3 Power Drift Monitoring

All SAR testing is under the DUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of DUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5 %, the SAR will be retested.

8.1.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1 g and 10 g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1 g and 10 g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1 g and 10 g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- 1. Extraction of the measured data (grid and values) from the Zoom Scan
- 2. Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- 3. Generation of a high-resolution mesh within the measured volume
- 4. Interpolation of all measured values form the measurement grid to the high-resolution grid
- 5. Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- 6. Calculation of the averaged SAR within masses of 1 g and 10 g



8.2 Power Density Measurement Procedure

8.2.1 Power Density Assessment Based on E-field

According to the IEC TR 63170, within a short distance from the transmitting source, power density is determined based on both electric and magnetic fields. Generally, the magnitude and phase of two components of either the E-field or H-field are needed on a sufficiently large surface to fully characterize the total E-field and H-field distributions. The measurement points are chosen according to the requirements of the methodology used. The following procedure was used:

- (1) Measure the E-field on the measurement surface at a reference location where the field is well above the noise level. This reference level will be used at the end of this procedure to assess output power drift of the DUT during the measurement.
- (2) Scan the electric field on the measurement surface. The requirements of measurement surface dimensions and spatial resolution are dependent on the measurement system and assessment methodology applied. Measurements are therefore conducted according to the instructions provided by SPEAG user's mannual.
- (3) Measurement spatial resolution can depend on the measured field characteristic and measurement methodology used by the system. Planar scanners typically require a step size of less than λ /2.
- (4) Calculated H-field from measured field by using reconstruction algorithm since only E-field is directly measured on the evaluation surface. Reconstruction algorithms can also be used to obtain field information from the measured data. In substance, reconstruction algorithms are the set of algorithms, mathematical techniques and procedures that are applied to the measured field on the measurement surface to determine E- and H-field (amplitude and phase) on the evaluation surface.
- (5) Determine the spatial-average power density distribution on the evaluation surface by the following formula. The spatial averaging area, A, is specified by the applicable exposure limits or regulatory requirements. The circular shape recommended in IEC TR 63170 was applied.

$$S_{av} = \frac{1}{2A} \Re \cdot \left(\int E \times H + \widehat{n} \, dA \right)$$

- (6) The maximum spatial-average and/or local power density on the evaluation surface is the final quantity to determine compliance against applicable limits. The spatial averaging area, 4cm², is specified by the TCB Workshop notes requirements.
- (7) Measure the E-field on the measurement surface position at the reference location chosen in step A). The power drift of the DUT is estimated as the difference between the squared amplitude of the field values taken in steps a) and g). When the drift is smaller than ± 5 %, this term should be considered in the uncertainty budget. Drifts larger than 5 % due to the design and operating characteristics of the device should be accounted for or addressed according to regulatory requirements to determine compliance.

8.2.2 Total Field and Power Density Reconstruction

Computation of the power density in general requires knowledge of the electric (E-) and magnetic (H-) field amplitudes and phases in the plane of incidence. Reconstruction of these quantities from pseudo-vector E-field measurements is feasible, as they are constrained by Maxwell's equations. The manufacturer SPEAG have developed a reconstruction approach based on the Gerchberg-Saxton algorithm, which benefits from the availability of the E-field polarization ellipse information obtained with the EUmmWV3 probe. This reconstruction algorithm, together with the ability of the probe to measure extremely close to the source without perturbing the field, permits reconstruction of the E- and H-fields, as well as of the power density, on measurement planes located as near as λ 5 away.



9. Measurement Uncertainty

9.1 SAR Measurement Uncertainty

Measurement Uncertainty (0.3-6 GHz)								
Uncertainty Component	Tol.	Prob. Dist.	Div.	Ci - 1g	Ci - 10g	ui - 1g (%)	ui - 10g (%)	vi
Measurement System								
Probe calibration	12.0	N	2	1	1	6.0	6.0	8
Probe Calibration Drift	1.7	R	1.732	1	1	1.0	1.0	8
Data acquisition	0.3	N	1	1	1	0.3	0.3	8
Probe Linearity	4.7	R	1.732	1	1	2.7	2.7	∞
Broadband Signal	3.0	R	1.732	1	1	1.7	1.7	∞
Probe Isotropy	7.6	R	1.732	1	1	4.4	4.4	8
RF Ambient	1.8	N	1	1	1	1.8	1.8	∞
Probe Positioning	0.2	N	1	0.14	0.14	0.0	0.0	8
Data Processing	1.2	N	1	1	1	1.2	1.2	∞
Phantom and Device Errors								
Conductivity (meas.)DAK	2.5	N	1	0.78	0.71	2.0	1.8	∞
Conductivity (temp.)	3.3	R	1.732	0.78	0.71	1.5	1.4	8
Phantom Shell Permittivity	14	R	1.732	0	0	0.0	0.0	8
Distance DUT - TSL	2	N	1	2	2	4.0	4.0	8
Device Positioning	1	N	1	1	1	1.0	1.0	8
Device Holder	3.6	N	1	1	1	3.6	3.6	∞
DUT Modulation	2.4	R	1.732	1	1	1.4	1.4	∞
Time-average SAR	1.7	R	1.732	1	1	1.0	1.0	∞
DUT Drift	2.5	N	1	1	1	2.5	2.5	∞
Correction to the SAR Result	ts							
Deviation to Target	1.9	N	1	1	0.84	1.9	1.6	∞
SAR scaling	0.0	R	1.732	1	1	0.0	0.0	∞
Combined Standard Uncertainty					RSS	11.0	10.9	
Expanded Uncertainty (95% confidence interval)				k =2	21.9	21.7		



	Measurement Uncertainty (3-6 GHz)								
Uncertainty Component	Tol.	Prob. Dist.	Div.	Ci - 1g	Ci - 10g	ui - 1g (%)	ui - 10g (%)	vi	
Measurement System									
Probe Calibration	13.1	N	2	1	1	6.55	6.55	∞	
Probe Calibration Drift	1.7	R	1.732	1	1	1.0	1.0	∞	
Data Acquisition	0.3	N	1	1	1	0.3	0.3	∞	
Probe Linearity	4.7	R	1.732	1	1	2.7	2.7	∞	
Broadband Signal	2.6	R	1.732	1	1	1.5	1.5	∞	
Probe Isotropy	7.6	R	1.732	1	1	4.4	4.4	∞	
RF Ambient	1.8	N	1	1	1	1.8	1.8	∞	
Probe Positioning	0.2	N	1	0.33	0.33	0.1	0.1	∞	
Data Processing	2.3	N	1	1	1	2.3	2.3	∞	
Phantom and Device Errors	•		•						
Conductivity (meas.)DAK	2.5	N	1	0.78	0.71	2.0	1.8	∞	
Conductivity (temp.)	3.4	R	1.732	0.78	0.71	1.5	1.4	∞	
Phantom Shell Permittivity	14	R	1.732	0.25	0.25	2.0	2.0	∞	
Distance DUT - TSL	2	N	1	2	2	4.0	4.0	∞	
Device Positioning	1	N	1	1	1	1.0	1.0	∞	
Device Holder	3.6	N	1	1	1	3.6	3.6	∞	
DUT Modulation	2.4	R	1.732	1	1	1.4	1.4	∞	
Time-average SAR	1.7	R	1.732	1	1	1.0	1.0	∞	
DUT Drift	2.5	N	1	1	1	2.5	2.5	∞	
Correction to the SAR Result	ts								
Deviation to Target	1.9	N	1	1	0.84	1.9	1.6	∞	
SAR scaling	0.0	R	1.732	1	1	0.0	0.0	∞	
Combined Standard Uncerta	inty				RSS	11.6	11.5		
Expanded Uncertainty (95%	Expanded Uncertainty (95% confidence interval)				k =2	23.2	23.0		



	Measurement Uncertainty (6-10 GHz)								
Uncertainty Component	Tol.	Prob. Dist.	Div.	Ci - 1g	Ci - 10g	ui - 1g (%)	ui - 10g (%)	vi	
Measurement System	Measurement System								
Probe calibration	18.6	N	2	1	1	9.3	9.3	8	
Probe Calibration Drift	1.7	R	1.732	1	1	1.0	1.0	8	
Data Acquisition	0.3	N	1	1	1	0.3	0.3	∞	
Probe Linearity	4.7	R	1.732	1	1	2.7	2.7	∞	
Broadband Signal	2.8	R	1.732	1	1	1.6	1.6	∞	
Probe Isotropy	7.6	R	1.732	1	1	4.4	4.4	∞	
RF Ambient Condition	1.8	N	1	1	1	1.8	1.8	∞	
Probe Positioning	0.2	N	1	0.67	0.67	0.1	0.1	∞	
Data Processing	3.5	N	1	1	1	3.5	3.5	∞	
Phantom and Device Errors								•	
Conductivity (meas.)DAK	2.5	N	1	0.78	0.71	2.0	1.8	∞	
Conductivity (temp.)	2.4	R	1.732	0.78	0.71	1.1	1.0	∞	
Phantom Shell Permittivity	14.0	R	1.732	0.5	0.5	4.0	4.0	∞	
Distance DUT - TSL	2	N	1	2	2	4.0	4.0	∞	
Device Positioning	1	N	1	1	1	1.0	1.0	∞	
Device Holder	3.6	N	1	1	1	3.6	3.6	∞	
DUT Modulation	2.4	R	1.732	1	1	1.4	1.4	∞	
Time-average SAR	1.7	R	1.732	1	1	1.0	1.0	∞	
DUT Drift	2.5	N	1	1	1	2.5	2.5	∞	
Correction to the SAR Resul	ts								
Deviation to Target	1.9	N	1	1	0.84	1.9	1.6	∞	
SAR scaling	0.0	R	1.732	1	1	0.0	0.0	∞	
Combined Standard Uncerta	inty				RSS	14.0	13.9		
Expanded Uncertainty (95%	confide	nce interval)			k =2	28.0	27.9		



9.2 Power Density Measurement Uncertainty

	Measurement Und	certainty for PD				
Error Description	Uncertainty Value (<u>+</u> dB)	Prob Dist.	Div.	(C _i)	Standard Uncertainty (± dB)	Vif
Measurement System				<u> </u>		-
Probe calibration	0.49	N	1	1	0.98	∞
Isotropy	0.50	R	1.732	1	0.29	∞
System Linearity	0.20	R	1.732	1	0.12	∞
System Detectection Limit	0.04	R	1.732	1	0.02	∞
Amplitude and phase noise	0.04	R	1.732	1	0.02	∞
Data Acquisition	0.03	N	1	1	0.03	∞
Probe Positioning Repeatability	0.04	R	1.732	1	0.02	∞
Probe Positioning Offset	0.30	R	1.732	1	0.17	∞
Field Reconstruction	0.60	R	1.732	1	0.35	∞
Test Sample Related						
Power Drift of Measurement	0.20	R	1.732	1	0.12	∞
Modulation Response	0.40	R	1.732	1	0.23	∞
Integration Time	0	R	1.732	1	0	∞
Response Time	0	R	1.732	1	0	∞
RF Ambient Noise	0.04	R	1.732	1	0.02	∞
RF Ambient Reflection	0.04	R	1.732	1	0.02	∞
Combined Std. Uncertainty			·		0.76	∞
Expanded Std. Uncertainty (K=2)					1.52	-



10. Measurement Evaluation

10.1 Positioning of the DUT in Relation to the Phantom

The following measurement procedure shall be according to RSS-102 Supplementary procedures (SPR-001):

Unless the side(s)/edge(s) of the laptop type computer (laptop mode/tablet mode) containing the built-in antenna(s) was already tested against the flat phantom.

Industry Canada requires SAR measurements to be performed with the side(s)/edge(s) of the display screen containing the built-in antenna(s) pointing towards the flat phantom.

- 1. If the integrated antenna(s) are located in the back side of the display screen, the back side shall be facing towards the flat phantom at a distance not exceeding 25 mm.
- 2. If the integrated antenna(s) are installed along the edge(s) of the display screen, the edge(s) shall be facing towards the flat phantom at a distance not exceeding 25 mm.

According to KDB 616217 D04:

- When antennas are incorporated in the keyboard section of a laptop computer, SAR is required for the bottom surface
 of the keyboard. Provided tablet use conditions are not supported by the laptop computer, SAR tests for bystander
 exposure from the edges of the keyboard.
- 2. Some 2-in-1 tablets may operate with the display folded on top of the keyboard. Most recent tablets are designed with an interactive display that may not require a physical keyboard. Both configurations are used in similar manners and require SAR evaluation for the back surface and edges of the tablet. For keyboards that can be unfolded like a laptop, the procedures for laptop platform should also be applied.



10.2 SAR Testing with RF Transmitter

10.2.1 SAR Testing with WLAN

A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actualchannel frequencies.

For WLAN SAR testing, the DUT has installed WLAN engineering testing software which can provide continuous transmitting RF signal. And the RF signal utilized in SAR measurement has almost 100 % duty cycle and crest factor is 1.

• The cards was operated utilizing proprietary software (DRTU) and each channel was measured using a broadband power meter to determine the maximum average power.

SAR test reduction for 802.11 Wi-Fi transmission mode configurations are considered separately for DSSS and OFDM. An initial test position is determined to reduce the number of tests required for certain exposure configurations with multiple test positions. An initial test configuration is determined for each frequency band and aggregated band according to maximum output power, channel bandwidth, wireless mode configurations and other operating parameters to streamline the measurement requirements. For 2.4 GHz DSSS, either the initial test position or DSSS procedure is applied to reduce the number of SAR tests; these are mutually exclusive. For OFDM, an initial test position is only applicable to next to the ear, UMPC mini-tablet and hotspot mode configurations, which is tested using the initial test configuration to facilitate test reduction. For other exposure conditions with a fixed test position, SAR test reduction is determined using only the initial test configuration.

The multiple test positions require SAR measurements in head, hotspot mode or UMPC mini-tablet configurations may be reduced according to the highest reported SAR determined using the initial test position(s) by applying the DSSS or OFDM SAR measurement procedures in the required wireless mode test configuration(s). The initial test position(s) is measured using the highest measured maximum output power channel in the required wireless mode test configuration(s). When the reported SAR for the initial test position is:

- ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and wireless mode combination within the frequency band or aggregated band. DSSS and OFDM configurations are considered separately according to the required SAR procedures.
- > 0.4 W/kg, SAR is repeated using the same wireless mode test configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions are tested.
- X For subsequent test positions with equivalent test separation distance or when exposure is dominated by coupling conditions, the position for maximum coupling condition should be tested.
- X When it is unclear, all equivalent conditions must be tested.
- For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, measure the SAR for these positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required test channels are considered.
- X The additional power measurements required for this step should be limited to those necessary for identifying subsequent highest output power channels to apply the test reduction.
- When the specified maximum output power is the same for both UNII 1 and UNII 2A, begin SAR measurements in UNII 2A with the channel with the highest measured output power. If the reported SAR for UNII 2A is ≤ 1.2 W/kg, SAR is not required for UNII 1; otherwise treat the remaining bands separately and test them independently for SAR.



When the specified maximum output power is different between UNII 1 and UNII 2A, begin SAR with the band that
has the higher specified maximum output. If the highest reported SAR for the band with the highest specified power is
≤ 1.2 W/kg, testing for the band with the lower specified output power is not required; otherwise test the remaining
bands independently for SAR.

To determine the initial test position, Area Scans were performed to determine the position with the Maximum Value of SAR (measured). The position that produced the highest Maximum Value of SAR is considered as the worst case position; thus used as the initial test position.

- After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following:
 - (1) The channel closest to mid-band frequency is selected for SAR measurement.
 - (2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

 These channel selection procedures apply to both the initial test configuration and subsequent test configuration(s) selection.

WIFI6E SAR and Power Density measurements were implemented according to the U-NII 6-7 GHz Interim Procedures described in Oct. 2020 TCB workshop.

• The SAR evaluations using 6-7 GHz parameters were perfomed per IEC/IEEE 62209-1528, and the Absorbed Power Density (APD) were reported based on SAR measurements. According to DASY Application Note, the APD is evaluated numerically using the FDTD method of Sim4Life V5.2. For comparison with the basic restrictions, the APD is averaged over square surface areas of 1 cm² and 4 cm² in the lowermost voxel layer of a flat phantom at a frequency of 6.5 GHz. The phantom consists of a dielectric shell of 2 mm thickness and a relative permittivity $\epsilon_r = 3.7$. It is filled with a tissue-simulating liquid with $\epsilon_r = 34.5$ and $\sigma = 6.07$ S/m.



10.2.2 Gravity Sener (G-sensor) Consideration

This device has built-in G-sensor which triggers power reduction in specified modes. The mechanism operation was verificated according to the guidance in TCB workshop Oct.2021. The results shows as follows.

Laptop Mode

- <A> From close mode 0 degrees, open the screen in 10 degree step until laptop mode is obtained.
- Move back by 5 degree, until close mode is obtained again.
- <C> Open the screen in 1 degree steps until laptop mode is obtained again and continue opening the screen in 1 degree steps at least 5 degrees.
- <D> Then continue opening the screen in 10 degree steps until tablet mode is obtained.

Degree	0	10	20	30	40	50	180	181	182	183	184	185	186	187	188	189	190	191	192
Trigger	X	X	Х	Х	Х	Х	X	X	X	X	X	X	X	X	X	Х	0	0	0
Degree	190	191	192	193	194	195	196	197	198	199	200	210	220	230	240	250	260	270	360
Trigger	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Tablet Mode

- <A> From tablet mode 360 degrees, open the screen in 10 degree step until laptop mode is obtained again.
- Move back by 5 degree, until open mode is obtained.
- <C> Close the screen in 1 degree steps until laptop mode is obtained and continue closing the screen in 1 degree steps at least 5 degrees.
- <D> Then continue closing the screen in 10 degree steps until laptop mode is obtained.

Degree	360	350	340	330	320	310	200	199	198	197	196	195	194	193	192	191	190	189	188
Trigger	X	X	X	X	X	Х	X	X	X	X	X	X	X	X	X	X	X	0	0
Degree	187	186	185	184	183	182	181	180	170	160	150	140	130	120	110	100	90	80	0
Trigger	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Note:

- 1. This table were summarized the results of the step <A> to <D> in each mode.
- 2. "X" denotes that the present mode is carried on; "O" denotes switching to another mode.
- 3. When the hinge angles = 0°~ 189°, DUT will read the laptop mode power table; when the hinge angles = 190°~ 360°, DUT will read the tablet mode power table.

10.3 Conducted Power Measurements

Refer to Appendix A.

10.4 Antenna location

Refer to Appendix E.



10.5 Test Results

10.5.1 SAR Test Result

			Frequ	uency	Test	Spacing	SAR _{1g}	Burst	Max	Duty	Donorto d		Antenna
Index.	Band	Modulation	Ch.	MHz	Position	(mm)	(W/Kg)	Avg Power (dBm)	Tune-up (dBm)	Cycle (%)	Reported SAR 1 g	Antenna	Manufacturer
1*	WLAN2.4GHz	802.11b	1	2412	Bottom of laptop	0	0.728	15.98	16	99.13	0.74	Ant Main	High-tek
	WLAN2.4GHz	802.11b	6	2437	Bottom of laptop	0	0.686	15.93	16	99.13	0.70	Ant Main	High-tek
	WLAN2.4GHz	802.11b	11	2462	Bottom of laptop	0	0.655	15.82	16	99.13	0.69	Ant Main	High-tek
	WLAN2.4GHz	802.11b	12	2467	Bottom of laptop	0	0.627	15.81	16	99.13	0.66	Ant Main	High-tek
	WLAN2.4GHz	802.11b	13	2472	Bottom of laptop	0	0.606	15.84	16	99.13	0.63	Ant Main	High-tek
11	WLAN2.4GHz	802.11b	6	2437	Bottom Face	0	0.987	12.35	12.5	99.13	1.03	Ant Main	High-tek
	WLAN2.4GHz	802.11b	6	2437	Bottom Face	0	0.819	12.35	12.5	99.13	0.86	Ant Main	MAG.LAYERS
	WLAN2.4GHz	802.11b	1	2412	Bottom Face	0	0.933	12.33	12.5	99.13	0.98	Ant Main	High-tek
	WLAN2.4GHz	802.11b	11	2462	Bottom Face	0	0.909	12.3	12.5	99.13	0.96	Ant Main	High-tek
	WLAN2.4GHz	802.11b	12	2467	Bottom Face	0	0.902	12.28	12.5	99.13	0.96	Ant Main	High-tek
	WLAN2.4GHz	802.11b	13	2472	Bottom Face	0	0.871	12.26	12.5	99.13	0.93	Ant Main	High-tek
	WLAN2.4GHz	802.11b	6	2437	Side 1	0	0.191	12.35	12.5	99.13	0.20	Ant Main	High-tek
	WLAN2.4GHz	802.11b	6	2437	Side 2	0	0.01	12.35	12.5	99.13	0.01	Ant Main	High-tek
	WLAN2.4GHz	802.11b	6	2437	Side 3	0	0.01	12.35	12.5	99.13	0.01	Ant Main	High-tek
	WLAN2.4GHz	802.11b	6	2437	Side 4	0	0.01	12.35	12.5	99.13	0.01	Ant Main	High-tek
2*	WLAN2.4GHz	802.11b	6	2437	Bottom of laptop	0	1.05	15.41	15.5	99.07	1.08	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	1	2412	Bottom of laptop	0	1.03	15.4	15.5	99.07	1.06	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	11	2462	Bottom of laptop	0	1.02	15.38	15.5	99.07	1.06	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	12	2467	Bottom of laptop	0	0.994	15.37	15.5	99.07	1.03	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	13	2472	Bottom of laptop	0	0.989	15.4	15.5	99.07	1.02	Ant Aux	High-tek
12	WLAN2.4GHz	802.11b	6	2437	Bottom Face	0	1.11	12.78	13	99.07	1.18	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	6	2437	Bottom Face	0	1.01	12.78	13	99.07	1.07	Ant Aux	MAG.LAYERS
	WLAN2.4GHz	802.11b	1	2412	Bottom Face	0	1.04	12.75	13	99.07	1.11	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	11	2462	Bottom Face	0	1.02	12.76	13	99.07	1.09	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	12	2467	Bottom Face	0	1.01	12.71	13	99.07	1.09	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	13	2472	Bottom Face	0	0.977	12.73	13	99.07	1.05	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	6	2437	Side 1	0	0.83	12.78	13	99.07	0.88	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	1	2412	Side 1	0	0.816	12.75	13	99.07	0.87	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	11	2462	Side 1	0	0.821	12.76	13	99.07	0.88	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	12	2467	Side 1	0	0.813	12.71	13	99.07	0.88	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	13	2472	Side 1	0	0.811	12.73	13	99.07	0.87	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	6	2437	Side 2	0	0.01	12.78	13	99.07	0.01	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	6	2437	Side 3	0	0.01	12.78	13	99.07	0.01	Ant Aux	High-tek
	WLAN2.4GHz	802.11b	6	2437	Side 4	0	0.01	12.78	13	99.07	0.01	Ant Aux	High-tek

Note:



Index.	Band	Modulation		uency	Test Position	Spacing		Burst Avg Power (dBm)	Max Tune-up (dBm)	Duty Cycle (%)	Reported SAR 1 g	Antenna	Antenna Manufacturer
	Bluetooth		78	2480	Bottom of laptop	0	0.15	6.95	7.5	77.33	0.22	Ant Aux	High-tek
	Bluetooth		0	2402	Bottom of laptop	0	0.115	6.72	7.5	77.33	0.18	Ant Aux	High-tek
	Bluetooth		39	2441	Bottom of laptop	0	0.111	6.74	7.5	77.33	0.17	Ant Aux	High-tek
1119	Bluetooth		78	2480	Bottom Face	0	0.248	6.95	7.5	77.33	0.36	Ant Aux	High-tek
	Bluetooth		78	2480	Bottom Face	0	0.231	6.95	7.5	77.33	0.34	Ant Aux	MAG.LAYERS
	Bluetooth		0	2402	Bottom Face	0	0.21	6.72	7.5	77.33	0.32	Ant Aux	High-tek
	Bluetooth		39	2441	Bottom Face	0	0.212	6.74	7.5	77.33	0.33	Ant Aux	High-tek
	Bluetooth		78	2480	Side 1	0	0.157	6.95	7.5	77.33	0.23	Ant Aux	High-tek
	Bluetooth		78	2480	Side 2	0	0.01	6.95	7.5	77.33	0.01	Ant Aux	High-tek
	Bluetooth		78	2480	Side 3	0	0.01	6.95	7.5	77.33	0.01	Ant Aux	High-tek
	Bluetooth		78	2480	Side 4	0	0.01	6.95	7.5	77.33	0.01	Ant Aux	High-tek
3	WLAN5GHz	802.11ac 160 MHz	50	5250	Bottom of laptop	0	1.08	14.48	14.5	95.98	1.13	Ant Main	High-tek
	WLAN5GHz	802.11ac 160 MHz	50	5250	Bottom of laptop	0	1.07	14.48	14.5	95.98	1.12	Ant Main	MAG.LAYERS
	WLAN5GHz	802.11ac 80 MHz	58	5290	Bottom of laptop	0	0.954	14.42	14.5	96.10	1.01	Ant Main	High-tek
	WLAN5GHz	802.11ac 160 MHz	50	5250	Bottom Face	0	0.595	9.61	10	95.98	0.68	Ant Main	High-tek
13*	WLAN5GHz	802.11ac 160 MHz	50	5250	Side 1	0	0.917	9.61	10	95.98	1.05	Ant Main	High-tek
	WLAN5GHz	802.11ac 80 MHz	58	5290	Side 1	0	0.844	9.92	10	96.10	0.89	Ant Main	High-tek
	WLAN5GHz	802.11ac 160 MHz	50	5250	Side 2	0	0.01	9.61	10	95.98	0.01	Ant Main	High-tek
	WLAN5GHz	802.11ac 160 MHz	50	5250	Side 3	0	0.01	9.61	10	95.98	0.01	Ant Main	High-tek
	WLAN5GHz	802.11ac 160 MHz	50	5250	Side 4	0	0.01	9.61	10	95.98	0.01	Ant Main	High-tek
	WLAN5GHz	802.11n 40 MHz	54	5270	Bottom of laptop	0	0.627	17.38	17.5	98.76	0.65	Ant Aux	High-tek
	WLAN5GHz	802.11n 40 MHz	62	5310	Bottom of laptop	0	0.555	16.16	16.25	98.76	0.57	Ant Aux	High-tek
14	WLAN5GHz	802.11ac 160 MHz	50	5250	Bottom Face	0	0.893	10.43	10.5	95.62	0.95	Ant Aux	High-tek
	WLAN5GHz	802.11ac 160 MHz	50	5250	Bottom Face	0	0.775	10.43	10.5	95.62	0.82	Ant Aux	MAG.LAYERS
	WLAN5GHz	802.11ac 80 MHz	58	5290	Bottom Face	0	0.874	10.4	10.5	96.37	0.93	Ant Aux	High-tek
	WLAN5GHz	802.11ac 160 MHz	50	5250	Side 1	0	0.358	10.43	10.5	95.62	0.38	Ant Aux	High-tek
	WLAN5GHz	802.11ac 160 MHz	50	5250	Side 2	0	0.01	10.43	10.5	95.62	0.01	Ant Aux	High-tek
	WLAN5GHz	802.11ac 160 MHz	50	5250	Side 3	0	0.01	10.43	10.5	95.62	0.01	Ant Aux	High-tek
	WLAN5GHz	802.11ac 160 MHz	50	5250	Side 4	0	0.01	10.43	10.5	95.62	0.01	Ant Aux	High-tek
	WLAN5GHz	802.11ac 160 MHz	114	5570	Bottom of laptop	0	0.926	14.44	15	95.98	1.10	Ant Main	High-tek
		802.11ac 160 MHz	114	5570	Bottom of laptop		0.808	14.44	15	95.98	0.96		MAG.LAYERS
5	WLAN5GHz	802.11ac 80 MHz	106	5530	Bottom of laptop		1	14.42	15	96.10	1.19	Ant Main	High-tek
		802.11ac 160 MHz	114	5570	Bottom Face	0	0.806	9.41	9.5	95.98	0.86	Ant Main	High-tek
88*		802.11ac 160 MHz	106	5530	Bottom Face	0	0.869	9.34	9.5	95.98	0.94	Ant Main	High-tek
	WLAN5GHz	802.11ac 160 MHz	114	5570	Side 1	0	0.967	9.41	9.5	95.98	1.03	Ant Main	High-tek
	WLAN5GHz	802.11ac 80 MHz	106	5530	Side 1	0	0.919	9.34	9.5	96.10	0.99	Ant Main	High-tek
	WLAN5GHz	802.11ac 160 MHz	114	5570	Side 2	0	0.01	9.41	9.5	95.98	0.01	Ant Main	High-tek
	WLAN5GHz	802.11ac 160 MHz	114	5570	Side 3	0	0.01	9.41	9.5	95.98	0.01	Ant Main	High-tek
	WLAN5GHz	802.11ac 160 MHz	114	5570	Side 4	0	0.01	9.41	9.5	95.98	0.01	Ant Main	High-tek



Index.	Band	Modulation	Frequ	uency	Test Position	Spacing	SAR 1g	Burst Avg Power (dBm)	Max Tune-up (dBm)	Duty Cycle (%)	Reported SAR 1 g	Antenna	Antenna Manufacturer
	WLAN5GHz	802.11ac 80 MHz	138	5690	Bottom of laptop	0	0.716	17.14	17.25	96.37	0.76	Ant Aux	High-tek
	WLAN5GHz	802.11ac 80 MHz	106	5530	Bottom of laptop	0	0.665	17.12	17.25	96.37	0.71	Ant Aux	High-tek
	WLAN5GHz	802.11ac 80 MHz	122	5610	Bottom of laptop	0	0.663	17.09	17.25	96.37	0.71	Ant Aux	High-tek
16	WLAN5GHz	802.11ac 160 MHz	114	5570	Bottom Face	0	0.992	9.94	10	95.62	1.05	Ant Aux	High-tek
	WLAN5GHz	802.11ac 160 MHz	114	5570	Bottom Face	0	0.81	9.94	10	95.62	0.86	Ant Aux	MAG.LAYERS
	WLAN5GHz	802.11ac 80 MHz	106	5530	Bottom Face	0	0.966	9.95	10	96.37	1.01	Ant Aux	High-tek
	WLAN5GHz	802.11ac 160 MHz	114	5570	Side 1	0	0.505	9.94	10	95.62	0.54	Ant Aux	High-tek
	WLAN5GHz	802.11ac 160 MHz	114	5570	Side 2	0	0.01	9.94	10	95.62	0.01	Ant Aux	High-tek
	WLAN5GHz	802.11ac 160 MHz	114	5570	Side 3	0	0.01	9.94	10	95.62	0.01	Ant Aux	High-tek
	WLAN5GHz	802.11ac 160 MHz	114	5570	Side 4	0	0.01	9.94	10	95.62	0.01	Ant Aux	High-tek
7	WLAN5GHz	802.11ac 80 MHz	155	5775	Bottom of laptop	0	1.02	16.13	16.5	96.10	1.16	Ant Main	High-tek
	WLAN5GHz	802.11ac 80 MHz	155	5775	Bottom of laptop	0	0.988	16.13	16.5	96.10	1.12	Ant Main	MAG.LAYERS
	WLAN5GHz	802.11n 40 MHz	159	5795	Bottom of laptop	0	0.976	16.29	16.5	98.23	1.04	Ant Main	High-tek
	WLAN5GHz	802.11ac 80 MHz	155	5775	Bottom Face	0	0.511	8.86	9	96.10	0.55	Ant Main	High-tek
	WLAN5GHz	802.11ac 80 MHz	155	5775	Side 1	0	0.77	8.86	9	96.10	0.83	Ant Main	High-tek
	WLAN5GHz	802.11n 40 MHz	159	5795	Side 1	0	0.715	8.95	9	98.23	0.74	Ant Main	High-tek
	WLAN5GHz	802.11ac 80 MHz	155	5775	Side 2	0	0.01	8.86	9	96.10	0.01	Ant Main	High-tek
	WLAN5GHz	802.11ac 80 MHz	155	5775	Side 3	0	0.01	8.86	9	96.10	0.01	Ant Main	High-tek
	WLAN5GHz	802.11ac 80 MHz	155	5775	Side 4	0	0.01	8.86	9	96.10	0.01	Ant Main	High-tek
10*	WLAN5GHz	802.11ac 80 MHz	155	5775	Bottom of laptop	0	0.773	17.39	17.5	96.37	0.82	Ant Aux	High-tek
	WLAN5GHz	802.11n 40 MHz	159	5795	Bottom of laptop	0	0.731	17.43	17.5	98.76	0.75	Ant Aux	High-tek
18	WLAN5GHz	802.11ac 80 MHz	155	5775	Bottom Face	0	0.999	9.84	10	96.37	1.08	Ant Aux	High-tek
	WLAN5GHz	802.11ac 80 MHz	155	5775	Bottom Face	0	0.912	9.84	10	96.37	0.98	Ant Aux	MAG.LAYERS
	WLAN5GHz	802.11n 40 MHz	159	5795	Bottom Face	0	0.969	9.98	10	98.76	0.99	Ant Aux	High-tek
99*	WLAN5GHz	802.11ac 80 MHz	155	5775	Side 1	0	0.656	9.84	10	96.37	0.71	Ant Aux	High-tek
	WLAN5GHz	802.11ac 80 MHz	155	5775	Side 2	0	0.01	9.84	10	96.37	0.01	Ant Aux	High-tek
	WLAN5GHz	802.11ac 80 MHz	155	5775	Side 3	0	0.01	9.84	10	96.37	0.01	Ant Aux	High-tek
	WLAN5GHz	802.11ac 80 MHz	155	5775	Side 4	0	0.01	9.84	10	96.37	0.01	Ant Aux	High-tek



			Frequ	uency	Tool	Spacing	SAR 1g	Burst	Max	Duty	Danastad		Antonno	APD
Index.	Band	Modulation	Ch.	MHz	Test Position	(mm)	(W/Kg)	Avg Power (dBm)	Tune-up (dBm)	Cycle (%)	Reported SAR 1 g	Antenna	Antenna Manufacturer	W/m ² (4cm ²)
	WLAN6GHz	802.11ax 160 MHz	15	6025	Bottom of laptop	0	0.3	13.47	13.5	99.24	0.30	Ant Main	High-tek	2.48
	WLAN6GHz	802.11ax 160 MHz	47	6185	Bottom of laptop	0	0.456	13.44	13.5	99.24	0.47	Ant Main	High-tek	2.75
	WLAN6GHz	802.11ax 160 MHz	79	6345	Bottom of laptop	0	0.357	13.46	13.5	99.24	0.36	Ant Main	High-tek	2.13
	WLAN6GHz	802.11ax 160 MHz	15	6025	Bottom Face	0	0.899	10.48	10.5	99.24	0.91	Ant Main	High-tek	4.31
	WLAN6GHz	802.11ax 160 MHz	47	6185	Bottom Face	0	0.896	10.47	10.5	99.24	0.91	Ant Main	High-tek	4.76
	WLAN6GHz	802.11ax 160 MHz	79	6345	Bottom Face	0	0.651	10.45	10.5	99.24	0.66	Ant Main	High-tek	3.54
207	WLAN6GHz	802.11ax 160 MHz	15	6025	Side 1	0	0.952	10.48	10.5	99.24	0.96	Ant Main	High-tek	4.81
	WLAN6GHz	802.11ax 160 MHz	15	6025	Side 1	0	0.849	10.48	10.5	99.24	0.86	Ant Main	MAG.LAYERS	4.27
	WLAN6GHz	802.11ax 160 MHz	47	6185	Side 1	0	0.728	10.47	10.5	99.24	0.74	Ant Main	High-tek	3.72
	WLAN6GHz	802.11ax 160 MHz	79	6345	Side 1	0	0.696	10.45	10.5	99.24	0.71	Ant Main	High-tek	3.93
	WLAN6GHz	802.11ax 160 MHz	15	6025	Side 2	0	0.01	10.48	10.5	99.24	0.01	Ant Main	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	15	6025	Side 3	0	0.01	10.48	10.5	99.24	0.01	Ant Main	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	15	6025	Side 4	0	0.01	10.48	10.5	99.24	0.01	Ant Main	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	15	6025	Bottom of laptop	0	0.293	13.46	13.5	99.21	0.30	Ant Aux	High-tek	2.17
	WLAN6GHz	802.11ax 160 MHz	47	6185	Bottom of laptop	0	0.182	13.45	13.5	99.21	0.19	Ant Aux	High-tek	1.7
	WLAN6GHz	802.11ax 160 MHz	79	6345	Bottom of laptop	0	0.203	13.43	13.5	99.21	0.21	Ant Aux	High-tek	1.95
201	WLAN6GHz	802.11ax 160 MHz	15	6025	Bottom Face	0	1	10.46	10.5	99.21	1.02	Ant Aux	High-tek	6.96
	WLAN6GHz	802.11ax 160 MHz	15	6025	Bottom Face	0	0.962	10.46	10.5	99.21	0.98	Ant Aux	MAG.LAYERS	5.96
	WLAN6GHz	802.11ax 160 MHz	47	6185	Bottom Face	0	0.781	10.45	10.5	99.21	0.80	Ant Aux	High-tek	5.43
	WLAN6GHz	802.11ax 160 MHz	79	6345	Bottom Face	0	0.747	10.42	10.5	99.21	0.77	Ant Aux	High-tek	4.92
217*	WLAN6GHz	802.11ax 160 MHz	15	6025	Side 1	0	0.658	10.46	10.5	99.21	0.67	Ant Aux	High-tek	4.26
	WLAN6GHz	802.11ax 160 MHz	15	6025	Side 2	0	0.01	10.46	10.5	99.21	0.01	Ant Aux	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	15	6025	Side 3	0	0.01	10.46	10.5	99.21	0.01	Ant Aux	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	15	6025	Side 4	0	0.01	10.46	10.5	99.21	0.01	Ant Aux	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	111	6505	Bottom of laptop	0	0.44	13.48	13.5	99.24	0.45	Ant Main	High-tek	2.56
	WLAN6GHz	802.11ax 80 MHz	103	6465	Bottom of laptop	0	0.211	10.7	10.75	99.47	0.21	Ant Main	High-tek	1.34
	WLAN6GHz	802.11ax 160 MHz	111	6505	Bottom Face	0	0.903	11.48	11.5	99.24	0.91	Ant Main	High-tek	4.41
	WLAN6GHz	802.11ax 80 MHz	103	6465	Bottom Face	0	0.827	10.7	10.75	99.47	0.84	Ant Main	High-tek	4.07
	WLAN6GHz	802.11ax 160 MHz	111	6505	Side 1	0	0.834	11.48	11.5	99.24	0.84	Ant Main	High-tek	4.06
		802.11ax 160 MHz	111	6505	Side 1	0	0.715	11.48	11.5	99.24	0.72		MAG.LAYERS	3.8
		802.11ax 80 MHz	103	6465	Side 1	0	0.99	10.7	10.75	99.47	1.01	Ant Main		4.9
		802.11ax 160 MHz	111	6505	Side 2	0	0.01	11.48	11.5	99.24	0.01	Ant Main	High-tek	0.01
		802.11ax 160 MHz	111	6505	Side 3	0	0.01	11.48	11.5	99.24	0.01	Ant Main	High-tek	0.01
		802.11ax 160 MHz	111	6505	Side 4	0	0.01	11.48	11.5	99.24	0.01	Ant Main	High-tek	0.01



			Frequ	iency	Tool	Spacing	SAR 1g	Burst	Max	Duty	Danadad		A	APD
Index.	Band	Modulation	Ch.	MHz	Test Position	(mm)	(W/Kg)	Avg Power (dBm)	Tune-up (dBm)	Cycle (%)	Reported SAR 1 g	Antenna	Antenna Manufacturer	W/m ² (4cm ²)
	WLAN6GHz	802.11ax 160 MHz	111	6505	Bottom of laptop	0	0.424	13.48	13.5	99.21	0.43	Ant Aux	High-tek	3.18
	WLAN6GHz	802.11ax 80 MHz	103	6465	Bottom of laptop	0	0.128	10.68	10.75	99.49	0.13	Ant Aux	High-tek	0.993
202	WLAN6GHz	802.11ax 160 MHz	111	6505	Bottom Face	0	0.998	10.48	10.5	99.21	1.01	Ant Aux	High-tek	6.97
	WLAN6GHz	802.11ax 160 MHz	111	6505	Bottom Face	0	0.78	10.48	10.5	99.21	0.79	Ant Aux	MAG.LAYERS	4.9
	WLAN6GHz	802.11ax 80 MHz	103	6465	Bottom Face	0	0.973	10.42	10.5	99.49	1.00	Ant Aux	High-tek	6.78
	WLAN6GHz	802.11ax 160 MHz	111	6505	Side 1	0	0.591	10.48	10.5	99.21	0.60	Ant Aux	High-tek	3.27
	WLAN6GHz	802.11ax 160 MHz	111	6505	Side 2	0	0.01	10.48	10.5	99.21	0.01	Ant Aux	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	111	6505	Side 3	0	0.01	10.48	10.5	99.21	0.01	Ant Aux	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	111	6505	Side 4	0	0.01	10.48	10.5	99.21	0.01	Ant Aux	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	143	6665	Bottom of laptop	0	0.456	13.47	13.5	99.24	0.46	Ant Main	High-tek	2.81
	WLAN6GHz	802.11ax 160 MHz	175	6825	Bottom of laptop	0	0.145	13.43	13.5	99.24	0.15	Ant Main	High-tek	0.969
	WLAN6GHz	802.11ax 160 MHz	143	6665	Bottom Face	0	0.701	10.43	10.5	99.24	0.72	Ant Main	High-tek	3.96
206	WLAN6GHz	802.11ax 160 MHz	143	6665	Side 1	0	0.979	10.43	10.5	99.24	1.00	Ant Main	High-tek	4.76
	WLAN6GHz	802.11ax 160 MHz	143	6665	Side 1	0	0.847	10.43	10.5	99.24	0.87	Ant Main	MAG.LAYERS	3.65
	WLAN6GHz	802.11ax 160 MHz	175	6825	Side 1	0	0.76	10.41	10.5	99.24	0.78	Ant Main	High-tek	3.73
	WLAN6GHz	802.11ax 160 MHz	143	6665	Side 2	0	0.01	10.43	10.5	99.24	0.01	Ant Main	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	143	6665	Side 3	0	0.01	10.43	10.5	99.24	0.01	Ant Main	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	143	6665	Side 4	0	0.01	10.43	10.5	99.24	0.01	Ant Main	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	143	6665	Bottom of laptop	0	0.359	13.46	13.5	99.21	0.37	Ant Aux	High-tek	2.74
	WLAN6GHz	802.11ax 160 MHz	175	6825	Bottom of laptop	0	0.101	13.44	13.5	99.21	0.10	Ant Aux	High-tek	0.68
203	WLAN6GHz	802.11ax 160 MHz	143	6665	Bottom Face	0	0.92	9.94	10	99.21	0.94	Ant Aux	High-tek	6.43
	WLAN6GHz	802.11ax 160 MHz	143	6665	Bottom Face	0	0.647	9.94	10	99.21	0.66	Ant Aux	MAG.LAYERS	4.17
	WLAN6GHz	802.11ax 160 MHz	175	6825	Bottom Face	0	0.907	9.92	10	99.21	0.93	Ant Aux	High-tek	5.23
	WLAN6GHz	802.11ax 160 MHz	143	6665	Side 1	0	0.165	9.94	10	99.21	0.17	Ant Aux	High-tek	2.56
	WLAN6GHz	802.11ax 160 MHz	143	6665	Side 2	0	0.01	9.94	10	99.21	0.01	Ant Aux	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	143	6665	Side 3	0	0.01	9.94	10	99.21	0.01	Ant Aux	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	143	6665	Side 4	0	0.01	9.94	10	99.21	0.01	Ant Aux	High-tek	0.01



			Frequ	iency	Test	Spacing	SAR 1g	Burst	Max	Duty	Donortod		Antenna	APD
Index.	Band	Modulation	Ch.	MHz	Position	(mm)	(W/Kg)	Avg Power (dBm)	Tune-up (dBm)	Cycle (%)	Reported SAR 1 g	Antenna	Manufacturer	W/m ² (4cm ²)
	WLAN6GHz	802.11ax 160 MHz	207	6985	Bottom of laptop	0	0.263	13.43	13.5	99.24	0.27	Ant Main	High-tek	1.67
	WLAN6GHz	802.11ax 80 MHz	215	7025	Bottom of laptop	0	0.109	9.9	10	99.47	0.11	Ant Main	High-tek	0.741
205	WLAN6GHz	802.11ax 160 MHz	207	6985	Bottom Face	0	1	12.45	12.5	99.24	1.02	Ant Main	High-tek	6.54
	WLAN6GHz	802.11ax 160 MHz	207	6985	Bottom Face	0	0.981	12.45	12.5	99.24	1.00	Ant Main	MAG.LAYERS	6.23
	WLAN6GHz	802.11ax 80 MHz	215	7025	Bottom Face	0	0.493	9.9	10	99.47	0.51	Ant Main	High-tek	3.64
	WLAN6GHz	802.11ax 160 MHz	207	6985	Side 1	0	0.762	12.45	12.5	99.24	0.78	Ant Main	High-tek	3.98
	WLAN6GHz	802.11ax 160 MHz	207	6985	Side 2	0	0.01	12.45	12.5	99.24	0.01	Ant Main	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	207	6985	Side 3	0	0.01	12.45	12.5	99.24	0.01	Ant Main	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	207	6985	Side 4	0	0.01	12.45	12.5	99.24	0.01	Ant Main	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	207	6985	Bottom of laptop	0	0.301	13.46	13.5	99.21	0.31	Ant Aux	High-tek	2.05
	WLAN6GHz	802.11ax 80 MHz	215	7025	Bottom of laptop	0	0.122	9.93	10	99.49	0.12	Ant Aux	High-tek	0.843
204	WLAN6GHz	802.11ax 160 MHz	207	6985	Bottom Face	0	0.92	10.43	10.5	99.21	0.94	Ant Aux	High-tek	5.92
	WLAN6GHz	802.11ax 160 MHz	207	6985	Bottom Face	0	0.892	10.43	10.5	99.21	0.91	Ant Aux	MAG.LAYERS	4.81
	WLAN6GHz	802.11ax 80 MHz	215	7025	Bottom Face	0	0.819	9.93	10	99.49	0.84	Ant Aux	High-tek	5.58
	WLAN6GHz	802.11ax 160 MHz	207	6985	Side 1	0	0.4	10.43	10.5	99.21	0.41	Ant Aux	High-tek	2.81
	WLAN6GHz	802.11ax 160 MHz	207	6985	Side 2	0	0.01	10.43	10.5	99.21	0.01	Ant Aux	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	207	6985	Side 3	0	0.01	10.43	10.5	99.21	0.01	Ant Aux	High-tek	0.01
	WLAN6GHz	802.11ax 160 MHz	207	6985	Side 4	0	0.01	10.43	10.5	99.21	0.01	Ant Aux	High-tek	0.01



10.5.2 Power Density Test Result

Index.	Band	Modulation	Frequ	uency	Test Position	Spacing	Averaging Area [4 cm²]	Averaging Area [4 cm²]	Burst Avg	Max tune-up	Duty Cycle	Scaling Averaging Area [4 cm²]	Scaling Averaging Area [4 cm²]	Ant
			Ch.	MHz		(mm)	Normal PD [W/m²]	Total PD [W/m²]	Power (dBm)	(dBm)	(%)	Normal PD [W/m²]	Total PD [W/m²]	
250	WLAN6GHz	802.11ax 160 MHz	15	6025	Side 1	2	3.27	3.86	10.48	10.5	99.24	3.31	3.91	Ant Main
251	WLAN6GHz	802.11ax 160 MHz	15	6025	Bottom Face	2	2.64	2.89	10.46	10.5	99.21	2.69	2.94	Ant Aux
253	WLAN6GHz	802.11ax 80 MHz	103	6465	Side 1	2	1.22	1.96	10.7	10.75	99.24	1.24	2.00	Ant Main
255	WLAN6GHz	802.11ax 80 MHz	103	6505	Bottom Face	2	1.55	1.89	10.42	10.5	99.49	1.59	1.93	Ant Aux
252	WLAN6GHz	802.11ax 160 MHz	111	6505	Bottom Face	2	1.92	2.11	11.48	11.5	99.47	1.94	2.13	Ant Main
254	WLAN6GHz	802.11ax 160 MHz	111	6505	Bottom Face	2	1.9	2.22	10.48	10.5	99.21	1.92	2.25	Ant Aux
256	WLAN6GHz	802.11ax 160 MHz	143	6665	Side 1	2	3.34	3.66	10.43	10.5	99.24	3.42	3.75	Ant Main
257	WLAN6GHz	802.11ax 160 MHz	143	6665	Bottom Face	2	3.25	3.5	9.94	10	99.21	3.32	3.58	Ant Aux
258	WLAN6GHz	802.11ax 160 MHz	207	6985	Bottom Face	2	2.82	3.09	12.45	12.5	99.24	2.88	3.15	Ant Main
259	WLAN6GHz	802.11ax 160 MHz	207	6985	Bottom Face	2	2.23	2.69	10.43	10.5	99.21	2.28	2.76	Ant Aux

Note:

- 1. The test spacing is the distance between probe sensor and DUT surface.
- 2. The test duty cycle was approached 100 % to facilitate test measurements only. It was confirmed by the manufacturer that the device was not over driven at this test duty cycle, to facilitate linear scaling in the test report.
- 3. $1.0 \text{ W/m}^2 = 0.1 \text{ mW/cm}^2$.



10.6 SAR Measurement Variability

Dand	Madulation	Fre	quency	Test	Nete	Original SAR 1 g	First SAR 1 g	First Ratio	A-4
Band	Modulation	Ch.	MHz	Position	Note	(W/kg)	(W/kg)	SAR 1 g	Antenna
WLAN2.4GHz	802.11b	6	2437	Bottom Face	original #11_once	0.987	0.966	2.13%	Ant Main
WLAN2.4GHz	802.11b	6	2437	Bottom Face	original #12_once	1.11	1.09	1.80%	Ant Aux
WLAN5GHz	802.11ac 160 MHz	50	5250	Bottom of laptop	original #3_once	1.08	1.05	2.78%	Ant Main
WLAN5GHz	802.11ac 160 MHz	50	5250	Bottom of laptop	original #14_once	0.893	0.885	0.90%	Ant Aux
WLAN5GHz	802.11ac 80 MHz	106	5530	Bottom of laptop	original #5_once	1	0.998	0.20%	Ant Main
WLAN5GHz	802.11ac 80 MHz	114	5570	Bottom Face	original #16_once	0.992	0.974	1.81%	Ant Aux
WLAN5GHz	802.11ac 80 MHz	155	5775	Bottom of laptop	original #7_once	1.02	1	1.96%	Ant Main
WLAN5GHz	802.11ac 80 MHz	155	5775	Bottom Face	original #18_once	0.999	0.987	1.20%	Ant Aux
WLAN6GHz	802.11ax 160 MHz	15	6025	Side 1	original #207_once	0.952	0.938	1.47%	Ant Main
WLAN6GHz	802.11ax 160 MHz	15	6025	Bottom Face	original #201_once	1	0.983	1.70%	Ant Aux
WLAN6GHz	802.11ax 160 MHz	103	6465	Side 1	original #208_once	0.99	0.977	1.31%	Ant Main
WLAN6GHz	802.11ax 160 MHz	111	6505	Bottom Face	original #202_once	0.998	0.974	2.40%	Ant Aux
WLAN6GHz	802.11ax 160 MHz	143	6665	Side 1	original #206_once	0.979	0.959	2.04%	Ant Main
WLAN6GHz	802.11ax 160 MHz	143	6665	Bottom Face	original #203_once	0.92	0.914	0.65%	Ant Aux
WLAN6GHz	802.11ax 160 MHz	207	6985	Bottom Face	original #205_once	1	0.973	2.70%	Ant Main
WLAN6GHz	802.11ax 160 MHz	207	6985	Bottom Face	original #204_once	0.92	0.893	2.93%	Ant Aux

According to KDB 865664 D01v01r04, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium.

The following procedures are applied to determine if repeated measurements are required:

- 1. The original highest measured Reported SAR 1-g is \geq 0.80 W/kg, repeated that measurement once.
- Perform a second repeated measurement the ratio of the largest to the smallest SAR for the original and first repeated measurements is <1.2 W/kg, or when the original or repeated measurement is ≥ 1.45 W/kg (~10% from the 1-g SAR limit).



10.7 Simultaneous Transmission Evaluation

10.7.1 Simultaneous Transmission Configurations

			J				
				Band			
Condition(s)	WLAN 2.4GHz Ant Main	WLAN 2.4GHz Ant Aux	WLAN 5GHz Ant Main	WLAN 5GHz Ant Aux	WLAN 6GHz Ant Main	WLAN 6GHz Ant Aux	Bluetooth
1	V						٧
2	V	V					
3			V				٧
4			V	V			
5			V	V			V
6					V		V
7					V	V	
8					V	V	V

<Total Exposure Ratio (TER)>

According to IEC TR 63170 and TCBC workshop, total Exposure Ratio (TER) is calculated by taking ratio of reported SAR divided by SAR limit and adding it to measured power density divided by power density limit.

$$\mathsf{TER} = \sum_{n=1}^{\mathsf{N}} \frac{\mathit{SAR}_n}{\mathit{SAR}_n} \, , \, \, \mathit{limit} \, + \, \sum_{m=1}^{\mathsf{M}} \frac{\mathit{S}_{m,avg}}{\mathit{S}_{lim}} \, , \, \, \mathit{limit} \, < 1$$

Numerical sum of the two ratios should be less than 1.

The worst-case power density results for each test configuration among all antenna arrays were considered for Total Exposure Ratio (TER) analysis. The sum of TER were listed in the following subclause.



10.7.2 Simultaneous Transmission Result

When the sum of 1-g SAR of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit, SAR test exclusion applies to that simultaneous transmission configuration.

The sum of 1-g SAR results and TER results are shown as below.

	1	2	3	4	5	6	7	4 7 5	4 0 5	2.7.	2.4.	2 4 7	T		5.0.7
Exposure Position	WLAN 2.4GHz Ant Main	WLAN 2.4GHz Ant Aux	WLAN 5GHz Ant Main	WLAN 5GHz Ant Aux	WLAN 6GHz Ant Main	WLAN 6GHz Ant Aux	Bluetooth Ant Aux	1+7 ∑ 1g SAR	1g SAR	1g SAR	3+4 ∑ 1g SAR	∑1g SAR	1g SAR	1g SAR	∑ 1g SAR (W/kg)
	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	(vv/kg)	(vv/kg)	(vv/kg)	(vv/kg)	(vv/kg)	(vv/kg)	(vv/kg)	(vv/kg)
Bottom Face at 0mm -	1.03	1.18	0.94	1.08	1.02	1.02	0.36	1.39	2.21	1.30	2.02	2.38	1.38	2.04	2.40
side 1 at 0mm -	0.20	0.88	1.05	0.71	1.01	0.67	0.23	0.43	1.08	1.28	1.76	1.99	1.24	1.68	1.91
side 2 at 0mm -	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.03	0.02	0.02	0.03
side 3 at 0mm -	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.03	0.02	0.02	0.03
side 4 at 0mm -	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.03	0.02	0.02	0.03

	1	2	3	4	5	6	7	4.75	1.05	2.75	2.45	2.4.7	r.75	F. C T	F.C.7
Exposure Position	WLAN 2.4GHz Ant Main	WLAN 2.4GHz Ant Aux	WLAN 5GHz Ant Main	WLAN 5GHz Ant Aux	WLAN 6GHz Ant Main	WLAN 6GHz Ant Aux	Bluetooth Ant Aux	1g SAR	1g SAR	1g SAR	3+4 ∑ 1g SAR	∑1g SAR	1g SAR	1g SAR	∑1g SAR
	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	(vv/kg)	(vv/kg)	(vv/kg)	(W/kg)	(vv/kg)	(vv/kg)	(vv/kg)	(vv/kg)
Bottom of laptop at 0mm -	0.74	1.08	1.19	0.82	0.47	0.43	0.22	0.96	1.82	1.41	2.01	2.23	0.69	0.90	1.12

Total Exposure Ratio (TER) Results

1	2	3	1+3	1+2	1+2+3
WLAN6GHz Ant Main	WLAN6GHz Ant Aux	Bluetooth Ant Aux	Total Exposure	Total Exposure	Total Exposure
Total PD (W/m²)	Total PD (W/m²)	1g SAR (W/kg)	Ratio	Ratio	Ratio
3.91	3.58	0.36	0.62	0.75	0.97

Note: $1.0 \text{ W/m}^2 = 0.1 \text{ mW/cm}^2$.



10.7.3 SAR to peak location separation (SPLSR)

According to KDB 447498, when the sum of SAR is greater than the limit, SAR test exclusion is determined by the SAR to peak location separation ratio (SPLSR), and the simultaneously transmitting antennas must be considered one pair at a time. The ratio is determined by (SAR1+SAR2)^{1.5} / (separation distance between the peak SAR locations for the antenna pair, mm), round to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

	#1_WLAN2.4GHz Main + WLAN2.4GHz Aux							
	Antenna	Index	Frequency (GHz)	Reported SAR1g (W/Kg)	∑ Reported SAR1g (W/Kg)	Antenna pair (mm)	Peak location separation ratio	
W	/LAN2.4GHz Main	11	2.437	1.03	2.21	196.00	0.02	
٧	VLAN2.4GHz Aux	12	2.437	1.18	2.21		0.02	
=	☐ Maxima and position w.r.t. Grid Reference Point associated 1g averages							
	☐ Zoom Scan (C:\Users\SAR3-PC\Desktop\SPLSR\#2\11_WLAN2.4GHz_802.11b_CH 6_Bottom Face_0mm_Ant							
	Max. 1 at (102.6	0, -85.60, 1.0	4) mm	1.03 W	/kg (Power Scale Fa	ctor: 1.04445844	6)	
	☐ Zoom Scan (C:\	Users\SAR3	-PC\Desktop\	\SPLSR\#2\12_WLA	N2.4GHz_802.11b	_CH 6_Bottom F	ace_0mm_Ant	
	Max. 2 at (102.4	0, 110.40, 0.7	7) mm	1.18 W	/kg (Power Scale Fa	ctor: 1.06142953	1)	
⊟	Distances and Sepa	aration Ratio	os					
	Max. 1 - Max. 2			Distan	ce [mm]: 196.00 / S	eparation ratio [\	N/kg/mm]: 0.02	

			#2 WLA	AN5GHz Main + WL	AN5GHz Aux			
	Antenna	Index	Frequency (GHz)	Reported SAR1g (W/Kg)	∑ Reported Antenna pai SAR1g (W/Kg) (mm)		Peak location separation ratio	
V	VLAN5GHz Main	88*	5.530	0.94	0.00	200	0.04	
V	VLAN5GHz Aux	18	5.775	1.08	2.02		0.01	
	Maxima and position ☐ Zoom Scan (C:\			oint assoc 1467_SPLSR\#2\88	iated 1g averages WLAN5GHz_802.1	11ac VHT80_CH	106_Bottom Fa	
	Max. 1 at (109.66	0, -81.00, 1.1	3) mm	0.94 W	/kg (Power Scale Fa	ctor: 1.08110460	9)	
	☐ Zoom Scan (C:\	Users\dasy\	Desktop\21-1	1467_SPLSR\#2\18_	WLAN5GHz_802.1	1ac VHT80_CH	155_Bottom Fa	
	Max. 2 at (100.60, 118.80, 0.79) mm		1.08 W	1.08 W/kg (Power Scale Factor: 1.076954496)				
	Distances and Sepa	aration Ratio	os					
					Distance [mm]: 200.00 / Separation ratio [W/kg/mm]: 0.01			



		#	#3_WLA	N6GH	z Main + WL	AN6	GHz Aux			
Antenna	Index		quency GHz)		Reported R1g (W/Kg)		∑ Reported AR1g (W/Kg)	Antenna pair (mm)	Peak location separation ratio	
WLAN6GHz Main	205	6.	6.985		85 1.02		2.04	404.45	0.02	
WLAN6GHz Aux	201	6.	.025		1.02		191.15			
205_WLAN6GHz_Ch207_Bottom Face_Main x(mm)					y(mm)		z(mm)	SAR	Power Scale Factor	
Max. 1 at			106.	23	-73.53		-157.60	1.02	1.01967209	
201_WLAN6GHz_Ch15_Bo	ottom Face_Au	Х	x(mi	m)	y(mm)		z(mm)	SAR	Power Scale Factor	
Max. 2 at			99.2	27	116.50		-177.01	1.02	1.017326909	
Distance and separation R	atios						Σ Reported SAR1g (W/Kg)	Distance(mm)	Separation ratio	
Max. 1 - Max . 2						2.04	191.15	0.02		

			#4_WLA	N5GHz Main + WL	AN5GHz Aux		
	Antenna	Index	Frequency (GHz)	Reported SAR1g (W/Kg)	∑ Reported SAR1g (W/Kg)	Antenna pair (mm)	Peak location separation ratio
٧	VLAN5GHz Main	13*	5.250	1.05	1.76	191.61	0.01
٧	VLAN5GHz Aux	99*	5.775	0.71	1.76		0.01
☐ Maxima and position w.r.t. Grid Reference Point associated 1g averages							
	☐ Zoom Scan (C:\	Users\SAR3	-PC\Desktop\	\SPLSR\#8\13_WLA	N5GHz_802.11ac	VHT160_CH 50_	Side 1_0 mm_A
	Max. 1 at (-3.40,	-84.00, -0.39	9) mm	1.05 W	/kg (Power Scale Fa	actor: 1.13990253	4)
	☐ Zoom Scan (C:\	Users\SAR3	-PC\Desktop\	\SPLSR\#8\99_WLA	N5GHz_802.11ac	VHT80_CH 155_	Side 1_0 mm_A
	Max. 2 at (-4.80,	107.60, -0.53	3) mm	0.71 W	/kg (Power Scale Fa	actor: 1.07695449	6)
	Distances and Sepa	aration Ratio	os				
	Max. 1 - Max. 2			Distan	ce [mm]: 191.61 / S	eparation ratio [\	N/kg/mm]: 0.01

		#	‡5 WLA	N6GH	Iz Main + WL	AN6	GHz Aux		
Antenna	Index	Fred	uency SHz)	F	Reported R1g (W/Kg)	·		Peak location separation ratio	
WLAN6GHz Main	208	6.	465		1.01 0.67 1.68 164.53		0.04		
WLAN6GHz Aux	217*	6.	025				1.68	164.53	0.01
208_WLAN6GHz_Ch103_5	Side1_Main		x(mm)		y(mm)		z(mm)	SAR	Power Scale Factor
Max. 1 at			-8.8	88	-82.62		-177.04	1.01	1.016637352
217_WLAN6GHz_Ch15_Si	ide1_Aux		x(mm)		y(mm)		z(mm)	SAR	Power Scale Factor
Max. 2 at			-8.8	32	82.29		-175.62	0.67	1.017326909
Distance and separation Ratios							Σ Reported SAR1g (W/Kg)	Distance(mm)	Separation ratio
Max. 1 - Max . 2							1.68	164.92	0.01
1					1			1	



			#6_WLAN	2.4GHz Main + WL	AN2.4GHz Aux		
	Antenna	Index	Frequency (GHz)	Reported SAR1g (W/Kg)	∑ Reported SAR1g (W/Kg)	Antenna pair (mm)	Peak location separation ratio
WL	AN2.4GHz Main	1*	2.412	0.74	1.82	199.22	0.01
W	LAN2.4GHz Aux	2*	2.437	1.08			0.01
	☐ Maxima and position w.r.t. Grid Reference Point associated 1g averages						
	☐ Zoom Scan (C:\\	Users\SAR3-	PC\Desktop\	SPLSR\#11\1_WLA	N2.4GHz_802.11b	_CH 1_Bottom o	of laptop_0mm
	Max. 1 at (-109.8	30, -84.00, 0.8	5) mm	0.74 W	/kg (Power Scale Fa	ctor: 1.01365733	2)
	☐ Zoom Scan (C:\	Users\SAR3-	PC\Desktop\	SPLSR\#11\2_WLA	N2.4GHz_802.11b	_CH 6_Bottom o	of laptop_0mm
	Max. 2 at (-107.0	00, 115.20, 0.6	7) mm	1.08 W	/kg (Power Scale Fa	ctor: 1.03012793	9)
⊟	Distances and Sepa	ration Ratio	s				
	Max. 1 - Max. 2			Distanc	ce [mm]: 199.22 / Se	eparation ratio [V	V/kg/mm]: 0.01

		#7_WLA	N5GHz Main + WL	AN5GHz Aux		
Antenna	Index	Frequency (GHz)	Reported SAR1g (W/Kg)	∑ Reported SAR1g (W/Kg)	Antenna pair (mm)	Peak location separation ratio
WLAN5GHz Main	5	5.530	1.19	2.01	400.0	0.01
WLAN5GHz Aux	VLAN5GHz Aux 10* 5.775		0.82	2.01	192.8	0.01
☐ Maxima and posit ☐ Zoom Scan (C:		Desktop\21-1	1467_SPLSR\#7\05			
		Max. 1 at (-111.60, -76.80, 1.49) mm 1.19 W/kg (Power Scale Factor: 1.189736347)				
Max. 1 at (-111				Commence of the Commence of th		
Max. 1 at (-111			1.19 W 1467_SPLSR\#7\08	Commence of the Commence of th		
Max. 1 at (-111	\Users\dasy\	Desktop\21-	1467_SPLSR\#7\08	Commence of the Commence of th	11ac VHT80_CH	155_Bottom of .
Max. 1 at (-111 ☐ Zoom Scan (C:	\Users\dasy\ .20, 116.00, 1.	Desktop\21-1 34) mm	1467_SPLSR\#7\08	WLAN5GHz_802.	11ac VHT80_CH	155_Bottom of



10.8 Requirements on the Uncertainty Evaluation

10.8.1 SAR Uncertainty Evaluation
Decision Rule
■ Uncertainty is not included.
☐ Uncertainty is included.
The highest measured 1-g SAR is less than 1.5 W/kg and the highest measured 10-g SAR is less than 3.75 W/kg.
Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis described in IEEE
1528-2013 and IEC/IEEE 62209-1528 is not required.
10.8.2 Power Density Uncertainty Evaluation
Decision Rule
■ Uncertainty is not included.
☐ Uncertainty is included.
According to IEC/IEEE 63195, if the total uncertainty exceeds 2 dB, the measurement results must be adjusted according
to IEC 62479. Since the total measurement uncertainty for DASY system is 1.52 dB, the adjustment is not required.
11. Conclusion
The SAR test values and PD test values found for the device are separately below the maximum limit of 1.6 W/kg and 1.0 mW/cm^2 .
END